Manual Chapter : Configuring Content Adaptation for HTTP Requests

Applies To:

Show Versions

Configuring a Simple Intranet

Configuring ISP Load Balancing

Routing Based on XML Content

Configuring nPath Routing

Configuring Layer 3 nPath Routing

Creating a Basic Web Site and E-commerce Configuration

Installing a BIG-IP System Without Changing the IP Network

Enabling IP Address Intelligence

Configuring Content Adaptation for HTTP Requests

Configuring Content Adaptation for HTTP Requests and Responses

Configuring HTTP Load Balancing with Source Address Affinity Persistence

Configuring HTTP Load Balancing with Cookie Persistence

Compressing HTTP Responses

Using Via Headers to Acquire Information About Intermediate Routers

Configuring the BIG-IP System as a Reverse Proxy Server

Load Balancing Passive Mode FTP Traffic

Load Balancing Passive Mode FTP Traffic with Data Channel Optimization

Configuring the BIG-IP System as a DHCP Relay Agent

Configuring the BIG-IP System for DHCP Renewal

Configuring a One-IP Network Topology

Configuring the BIG-IP System to Auto-Populate Pools

Implementing Health and Performance Monitoring

Preventing TCP Connection Requests From Being Dropped

Setting Connection Limits

Load Balancing to IPv6 Nodes

Mitigating Denial of Service Attacks

Implementing APM System Authentication

Configuring an SSL Intercept Explicit Proxy Mode

Configuring an Explicit HTTP Proxy Chain

Manipulating HTTPS Traffic by Using a Third-Party Device

Legal Notices

Configuring Content Adaptation for HTTP Requests

Overview: Configuring HTTP Request Adaptation

This implementation describes how to configure the BIG-IP content adaptation feature for adapting HTTP requests. With this feature, a BIG-IP virtual server can conditionally forward HTTP requests to a pool of Internet Content Adaptation Protocol (ICAP) servers for modification, before sending the request to a web server.

In this implementation, you create a standard HTTP virtual server and pool of web servers for processing client requests. The HTTP virtual server accepts each client request in the normal way, but before load balancing the request to the pool of web servers, the virtual server forwards the HTTP request to a special internal virtual server.

The ***internal virtual server*** receives the HTTP request from the standard virtual server, and load balances the request to a pool of ICAP servers for modification. After the ICAP server modifies the request, the BIG-IP system sends the request to the appropriate web server for processing.

Content adaptation configuration for modifying HTTP requests



The internal virtual server references the pool of content adaptation servers, including the load balancing method to use for those servers. The internal virtual server also references an ICAP profile, which includes specific instructions for how the BIG-IP system should wrap the HTTP request in an ICAP message for adaptation.

Optionally, the internal virtual server can reference:

- Any persistence method that you would like the BIG-IP system to use when load balancing traffic to the ICAP pool.
- Any health or performance monitor that you would like the BIG-IP system to use when load balancing traffic to the ICAP pool.
- Any iRules® related to the content adaptation.

Task summary for content adaptation for HTTP requests and responses

Complete the tasks in this implementation to create a BIG-IP configuration that performs content adaptation for HTTP requests and responses.

Creating a custom client-side ICAP profile

You create this ICAP profile when you want to use an ICAP server to wrap an HTTP request in an ICAP message before the BIG-IP system sends the request to a pool of web servers. The profile specifies the HTTP request-header values that the ICAP server uses for the ICAP message.

You can use macro expansion for all ICAP header values. For example, if an ICAP header value contains ${SERVER_IP}, the BIG-IP system replaces the macro with the IP address of the ICAP server selected from the pool assigned to the internal virtual server. If an ICAP header value contains ${SERVER_PORT}, the BIG-IP system replaces the macro with the port of the ICAP server selected from the pool assigned to the internal virtual server. For example, you can set the **URI** value in an ICAP profile to icap://${SERVER_IP}:${SERVER_PORT}/virusScan.

1. On the Main tab, click **Local Traffic › Profiles › Services › ICAP** .
2. Click **Create.**
3. In the **Name** field, type a unique name for the profile.
4. For the **Parent Profile** setting, retain the default value, `icap`.
5. On the right side of the screen, select the **Custom** check box.
6. In the **URI** field, type a URI in this format: `icap://hostname:port/path`.
   For example, using macro expansion, you can set the **URI** value to:

   ```
   icap://${SERVER_IP}:${SERVER_PORT}/virusScan
   ```

   .
7. In the **Preview Length** field, type a length or retain the default value `0`.

   This value defines the amount of the HTTP request or response that the BIG-IP system offers to the ICAP server when sending the request or response to the server for adaptation. This value should not exceed the length of the preview that the ICAP server has indicated it will accept.
8. In the **Header From** field, type a value for the From: ICAP header.
9. In the **Host** field, type a value for the Host: ICAP header.
10. In the **Referer** field, type a value for the Referer: ICAP header.
11. In the **User Agent** field, type a value for the User-Agent: ICAP header.
12. Click **Finished.**

After you create the ICAP profile, you can assign it to an internal virtual server so that the HTTP request that the BIG-IP system sends to an ICAP server is wrapped in an ICAP message, according to the settings you specified in the ICAP profile.

Creating a pool of ICAP servers

You perform this task to create a pool of ICAP servers that perform content adaptation on HTTP requests.

1. On the Main tab, click **Local Traffic › Pools** .
   The Pool List screen opens.
2. Click **Create.**
   The New Pool screen opens.
3. In the **Name** field, type a unique name for the pool.
4. For the **Health Monitors** setting, from the **Available** list, select the **http** monitor and move the monitor to the **Active** list.
5. From the **Load Balancing Method** list, select how the system distributes traffic to members of this pool.

   The default is **Round Robin.**
6. For the **Priority Group Activation** setting, specify how to handle priority groups:
   - Select **Disabled** to disable priority groups. This is the default option.

- Select **Less than**, and in the **Available Members** field type the minimum number of members that must remain available in each priority group in order for traffic to remain confined to that group.

7. Using the **New Members** setting, add each resource that you want to include in the pool:
   a. (Optional) In the **Node Name** field, type a name for the node portion of the pool member.
   b. In the **Address** field, type an IP address.
   c. In the **Service Port** field, type a port number, or select a service name from the list.
   d. (Optional) In the **Priority** field, type a priority number.
   e. Click **Add**.
8. Click **Finished**.

The pool of ICAP load balancing servers appears in the Pools list.

Creating an internal virtual server for forwarding requests to an ICAP server

A virtual server of type **internal** provides a destination that a **standard** type of virtual server can use when forwarding HTTP requests slated for ICAP-based content adaptation.

1. On the Main tab, click **Local Traffic › Virtual Servers** .
   The Virtual Server List screen opens.
2. Click **Create**.
   The New Virtual Server screen opens.
3. In the **Name** field, type a unique name for the virtual server.
4. In the **Description** field, type a description of the virtual server.
   For example: `This virtual server ensures HTTP request modification through the use of the` ***`service_name`*** `ICAP service.`.
5. From the **Type** list, select **Internal**.
6. For the **State** setting, verify that the value is set to **Enabled**.
7. From the **Configuration** list, select **Advanced**.
8. From the **ICAP Profile** list, select the ICAP profile that you previously created for handling HTTP requests.
9. From the **Default Pool** list, select the pool of ICAP servers that you previously created.
10. Click **Finished**.

After you perform this task, a standard type of virtual server can forward HTTP requests to an internal type of virtual server. The internal virtual server then sends the request to a pool of ICAP servers, before sending the request back to the standard virtual server for forwarding to the pool of web servers.

Creating a custom Request Adapt profile

You create a Request Adapt type of profile when you want a standard HTTP virtual server to forward HTTP requests to an internal virtual server that references a pool of ICAP servers. A Request Adapt type of profile instructs the HTTP virtual server to send an HTTP request to a named internal virtual server for possible request modification.

1. On the Main tab, click **Local Traffic › Profiles › Services › Request Adapt** .
2. Click **Create**.
3. In the **Name** field, type a unique name for the profile.
4. For the **Parent Profile** setting, retain the default value, `requestadapt`.
5. On the right-side of the screen, clear the **Custom** check box.

6. For the **Enabled** setting, retain the default value, `Enabled`.
   When you set this value to **Enabled**, the BIG-IP system forwards HTTP requests to the specified internal virtual server for adaptation.
7. From the **Internal Virtual Name** list, select the name of the internal virtual server that you previously created for forwarding HTTP requests to the pool of iCAP servers.
8. In the **Preview Size** field, type a numeric value.

   This specifies the maximum size of the preview buffer. This buffer holds a copy of the HTTP request header and the data sent to the internal virtual server, in case the adaptation server reports that no adaptation is needed. Setting the preview size to `0` disables buffering of the request and should only be done if the adaptation server always returns a modified HTTP request or the original HTTP request.
9. In the **Timeout** field, type a numeric value, in seconds.
   If the internal virtual server does not return a result within the specified time, a timeout error occurs. To disable the timeout, use the value `0`.
10. From the **Service Down Action** list, select an action for the BIG-IP system to take if the internal virtual server returns an error:
    - Select **Ignore** to instruct the BIG-IP system to ignore the error and send the unmodified HTTP request to an HTTP server in the HTTP server pool.
    - Select **Drop** to instruct the BIG-IP system to drop the connection.
    - Select **Reset** to instruct the BIG-IP system to reset the connection.
11. Click **Finished.**

After you perform this task, the BIG-IP system contains a Request Adapt profile that a standard HTTP virtual server can use to forward an HTTP request to an internal virtual server for ICAP traffic.

Creating a custom HTTP profile

An HTTP profile defines the way that you want the BIG-IPsystem to manage HTTP traffic.

Other HTTP profile types (HTTP Compression and Web Acceleration) enable you to configure compression and cache settings, as required. Use of these profile types is optional.

1. On the Main tab, click **Local Traffic › Profiles › Services › HTTP .**
   The HTTP profile list screen opens.
2. Click **Create.**
   The New HTTP Profile screen opens.
3. In the **Name** field, type a unique name for the profile.
4. From the **Parent Profile** list, select **http.**
5. Select the **Custom** check box.
6. Modify the settings, as required.
7. Click **Finished.**

The custom HTTP profile now appears in the HTTP profile list screen.

Creating a pool to process HTTP traffic

You can create a pool of web servers to process HTTP requests.

1. On the Main tab, click **Local Traffic › Pools .**
   The Pool List screen opens.
2. Click **Create.**
   The New Pool screen opens.
3. In the **Name** field, type a unique name for the pool.

4. For the **Health Monitors** setting, from the **Available** list, select the **http** monitor and move the monitor to the **Active** list.
5. From the **Load Balancing Method** list, select how the system distributes traffic to members of this pool.

   The default is **Round Robin**.
6. For the **Priority Group Activation** setting, specify how to handle priority groups:
   - Select **Disabled** to disable priority groups. This is the default option.
   - Select **Less than**, and in the **Available Members** field type the minimum number of members that must remain available in each priority group in order for traffic to remain confined to that group.
7. Using the **New Members** setting, add each resource that you want to include in the pool:
   a. Type an IP address in the **Address** field.
   b. Type `80` in the **Service Port** field, or select **HTTP** from the list.
   c. (Optional) Type a priority number in the **Priority** field.
   d. Click **Add**.
8. Click **Finished**.

The new pool appears in the Pools list.

Creating an HTTP virtual server for enabling request adaptation

You perform this task to create a standard virtual server that can forward an HTTP request to an internal virtual server. The internal virtual server then sends the request to a pool of ICAP servers before the BIG-IP system sends the request to the web server.

1. On the Main tab, click **Local Traffic › Virtual Servers** .
   The Virtual Server List screen opens.
2. Click **Create**.
   The New Virtual Server screen opens.
3. In the **Name** field, type a unique name for the virtual server.
4. In the **Destination Address** field, type the IP address that you want to use as a destination for client traffic destined for a pool of HTTP web servers.

   The supported format is address/prefix, where the prefix length is in bits. For example, an IPv4 address/prefix is `10.0.0.1` or `10.0.0.0/24`, and an IPv6 address/prefix is `ffe1::0020/64` or `2001:ed8:77b5:2:10:10:100:42/64`. When you use an IPv4 address without specifying a prefix, the BIG-IP system automatically uses a `/32` prefix.

   The IP address you type must be available and not in the loopback network.
5. In the **Service Port** field, type `443` or select **HTTPS** from the list.

   *If traffic is on a secure internal network, you can use `80`/**HTTP**.*
6. From the **Configuration** list, select **Advanced**.
7. From the **HTTP Profile** list, select the name of the HTTP profile that you created previously.
8. From the **Request Adapt Profile** list, select the name of the Request Adapt profile that you previously created.
9. From the **Source Address Translation** list, select **Auto Map**.
10. From the **Default Pool** list, select the name of the HTTP server pool that you previously created.
11. Click **Finished**.

After you create the virtual server, the BIG-IP system can forward an HTTP request to a pool of ICAP servers before sending the request to the web server.

Implementation result

After you complete the tasks in this implementation, the BIG-IP system can perform content adaptation on HTTP requests as they pass through the BIG-IP system during normal HTTP processing. The new objects that this implementation creates are:

- A custom ICAP profile
- A pool of ICAP content adaptation servers
- An internal virtual server that load balances HTTP requests to the ICAP pool
- A custom Request Adapt profile that references the internal virtual server
- A custom HTTP profile
- A standard HTTP pool of web servers
- A standard HTTP virtual server that sends HTTP requests to an internal virtual server for content adaptation and load balances HTTP requests to the web pool

Contact Support

HAVE A QUESTION?
Support and Sales >

FOLLOW US

ABOUT F5
Corporate Information
Newsroom

EDUCATION
Training
Certification

F5 SITES
F5.com
DevCentral

SUPPORT TASKS
Read Support Policies

Investor Relations
Careers
About AskF5
F5 University
Free Online Training
Support Portal
Partner Central
F5 Labs
Create Service Request
Leave feedback [+]

©2023 F5, Inc. All rights reserved.

Trademarks Policies Privacy California Privacy Do Not Sell My Personal Information Cookie Preferences