

DoseLab CT Imaging QA Results

Summary: All tests passed

DoseLab version: 6.80

Date: January 08, 2020

Machine: Unit 1, #:3951

Phantom: Catphan 504

Magnification: 100.06%

Energy: 125 kV

Expected slice width: 2.0 mm

Matrix size: 512x512

Performed by: Amy Frederick


Tolerance set: Unit:1,6,7,8 Large FOV

Scaling discrepancy: 0.2 mm (Pass)

Geometric distortion: 0.1 mm (Pass)

Spatial resolution (50% MTF): 0.46 lp/mm (Pass)

Minimum uniformity (ROI 21): 97.9% (Pass)



CTP404 module results

Contrast ROI details

Measured HU

1: 351

2: 89

HU constancy ROI details

Reference / Measured / Difference

3 (Acrylic): 120 / 119 / -1

4 (Air): -1000 / -998 / 2


5 (Polystyrene): -35 / -44 / -9

6 (LDPE): -100 / -99 / 1

7 (PMP): -200 / -195 / 5

8 (Teflon): 990 / 965 / -25

9 (CTP404): 100 / 133 / 33



CTP528 module results

Spatial resolution ROI details

Phantom lp/mm / Normalized MTF

11: 0.1 / 1.00

12: 0.2 / 0.94

13: 0.3 / 0.79


14: 0.4 / 0.62

15: 0.5 / 0.43

16: 0.6 / 0.31

17: 0.7 / 0.23

18: 0.8 / 0.13



CTP486 module results

Uniformity ROI details

Measured HU / Uniformity

19: 36 / 98.2%

20: 14 / 98.0%

21: 13 / 97.9%

22: 11 / 98.1%

23: 10 / 98.0%

