

Practices for Lesson 5: Using SQL Statements within a PL/SQL Block

Chapter 5

Practice 5: Using SQL Statements Within a PL/SQL

Note: If you have executed the code examples for this lesson, make sure that you execute the following code before starting this practice:

```
DROP table employees2;  
DROP table copy_emp;
```

In this practice, you use PL/SQL code to interact with the Oracle Server.

1. Create a PL/SQL block that selects the maximum department ID in the `departments` table and stores it in the `v_max_deptno` variable. Display the maximum department ID.
 - a. Declare a variable `v_max_deptno` of type `NUMBER` in the declarative section.
 - b. Start the executable section with the `BEGIN` keyword and include a `SELECT` statement to retrieve the maximum `department_id` from the `departments` table.
 - c. Display `v_max_deptno` and end the executable block.
 - d. Execute and save your script as `lab_05_01_soln.sql`. The sample output is as follows:

```
PL/SQL procedure successfully completed.  
  
The maximum department_id is : 270  
|
```

2. Modify the PL/SQL block that you created in step 1 to insert a new department into the `departments` table.
 - a. Load the `lab_05_01_soln.sql` script. Declare two variables:
`v_dept_name` of type `departments.department_name` and
`v_dept_id` of type `NUMBER`.
Assign 'Education' to `v_dept_name` in the declarative section.
 - b. You have already retrieved the current maximum department number from the `departments` table. Add 10 to it and assign the result to `v_dept_id`.
 - c. Include an `INSERT` statement to insert data into the `department_name`, `department_id`, and `location_id` columns of the `departments` table.
Use the values in `v_dept_name` and `v_dept_id` for `department_name` and `department_id`, respectively, and use `NULL` for `location_id`.
 - d. Use the SQL attribute `SQL%ROWCOUNT` to display the number of rows that are affected.
 - e. Execute a `SELECT` statement to check whether the new department is inserted. You can terminate the PL/SQL block with `/` and include the `SELECT` statement in your script.
 - f. Execute and save your script as `lab_05_02_soln.sql`. The sample output is as follows:

```
PL/SQL procedure successfully completed.  
  
The maximum department_id is : 270  
SQL%ROWCOUNT gives 1
```

Query Result x			
SQL All Rows Fetched: 1 in 0.004 seconds			
DEPARTMENT_ID	DEPARTMENT_NAME	MANAGER_ID	LOCATION_ID
1	280 Education	(null)	(null)

3. In step 2, you set `location_id` to NULL. Create a PL/SQL block that updates `location_id` to 3000 for the new department.

Note: If you successfully completed step 2, continue with step 3a. If not, first execute the solution script `/soln/sol_05.sql`. (Task 2 in `sol_05.sql`)

- Start the executable block with the `BEGIN` keyword. Include the `UPDATE` statement to set `location_id` to 3000 for the new department (`v_dept_id = 280`).
- End the executable block with the `END` keyword. Terminate the PL/SQL block with `/` and include a `SELECT` statement to display the department that you updated.
- Include a `DELETE` statement to delete the department that you added.
- Execute and save your script as `lab_05_03_soln.sql`. The sample output is as follows:

Script Output x Query Result x

Task completed in 0.425 seconds

PL/SQL procedure successfully completed.

>>Query Run In:Query Result

1 row deleted.

Script Output x Query Result x			
SQL All Rows Fetched: 1 in 0.172 seconds			
DEPARTMENT_ID	DEPARTMENT_NAME	MANAGER_ID	LOCATION_ID
1	280 Education	(null)	3000

Solution 5: Using SQL Statements Within a PL/SQL

In this practice, you use PL/SQL code to interact with the Oracle Server.

1. Create a PL/SQL block that selects the maximum department ID in the `departments` table and stores it in the `v_max_deptno` variable. Display the maximum department ID.
 - a. Declare a variable `v_max_deptno` of type `NUMBER` in the declarative section.

```
DECLARE
    v_max_deptno NUMBER;
```

- b. Start the executable section with the `BEGIN` keyword and include a `SELECT` statement to retrieve the maximum `department_id` from the `departments` table.

```
BEGIN
    SELECT MAX(department_id) INTO v_max_deptno FROM
        departments;
```

- c. Display `v_max_deptno` and end the executable block.

```
DBMS_OUTPUT.PUT_LINE('The maximum department_id is : ' ||
    v_max_deptno);
END;
```

- d. Execute and save your script as `lab_05_01_soln.sql`. The sample output is as follows:

```
PL/SQL procedure successfully completed.

The maximum department_id is : 270

|
```

2. Modify the PL/SQL block that you created in step 1 to insert a new department into the `departments` table.
 - a. Load the `lab_05_01_soln.sql` script. Declare two variables:
`v_dept_name` of type `departments.department_name` and
`v_dept_id` of type `NUMBER`.
Assign 'Education' to `v_dept_name` in the declarative section.

```
v_dept_name departments.department_name%TYPE:= 'Education';
v_dept_id NUMBER;
```

- b. You have already retrieved the current maximum department number from the `departments` table. Add 10 to it and assign the result to `v_dept_id`.

```
v_dept_id := 10 + v_max_deptno;
```

- c. Include an `INSERT` statement to insert data into the `department_name`, `department_id`, and `location_id` columns of the `departments` table. Use the values in `v_dept_name` and `v_dept_id` for `department_name` and `department_id`, respectively, and use `NULL` for `location_id`.

```
...  
INSERT INTO departments (department_id, department_name,  
location_id)  
VALUES (v_dept_id, v_dept_name, NULL);
```


- d. Use the SQL attribute `SQL%ROWCOUNT` to display the number of rows that are affected.

```
DBMS_OUTPUT.PUT_LINE (' SQL%ROWCOUNT gives ' || SQL%ROWCOUNT);  
...
```

- e. Execute a `SELECT` statement to check whether the new department is inserted. You can terminate the PL/SQL block with `/` and include the `SELECT` statement in your script.

```
...  
/  
SELECT * FROM departments WHERE department_id= 280;
```

- f. Execute and save your script as `lab_05_02_soln.sql`. The sample output is as follows:



The screenshot displays the output of a PL/SQL script in SQL Developer. The top window shows the message "PL/SQL procedure successfully completed." followed by "The maximum department_id is : 270" and "SQL%ROWCOUNT gives 1". Below this, a "Query Result" window shows a table with one row of data.

	DEPARTMENT_ID	DEPARTMENT_NAME	MANAGER_ID	LOCATION_ID
1	280	Education	(null)	(null)

3. In step 2, you set `location_id` to `NULL`. Create a PL/SQL block that updates the `location_id` to 3000 for the new department.
Note: If you successfully completed step 2, continue with step 3a. If not, first execute the solution script `/soln/sol_05.sql`. (Task 2 in `sol_05.sql`)
- a. Start the executable block with the `BEGIN` keyword. Include the `UPDATE` statement to set `location_id` to 3000 for the new department (`v_dept_id =280`).

```
BEGIN
```

```
UPDATE departments SET location_id=3000 WHERE
department_id=280;
```


- b. End the executable block with the `END` keyword. Terminate the PL/SQL block with `/` and include a `SELECT` statement to display the department that you updated.

```
END;
/
SELECT * FROM departments WHERE department_id=280;
```

- c. Include a `DELETE` statement to delete the department that you added.


```
DELETE FROM departments WHERE department_id=280;
```

- d. Execute and save your script as `lab_05_03_soln.sql`. The sample output is as follows:



The screenshot shows the 'Query Result' window in SQL Developer. It displays a table with 4 columns: DEPARTMENT_ID, DEPARTMENT_NAME, MANAGER_ID, and LOCATION_ID. There is one row of data with values 1, Education, (null), and 3000. The status bar indicates 'All Rows Fetched: 1 in 0.172 seconds'.

DEPARTMENT_ID	DEPARTMENT_NAME	MANAGER_ID	LOCATION_ID
1	Education	(null)	3000



The screenshot shows the 'Script Output' window in SQL Developer. It displays the text 'PL/SQL procedure successfully completed.' followed by a prompt '>>Query Run In:Query Result' and the message '1 row deleted.' The status bar indicates 'Task completed in 0.425 seconds'.

```
PL/SQL procedure successfully completed.

>>Query Run In:Query Result

1 row deleted.
```