
UNIVERSIDAD DE GRANADA

MASTER PROFESIONAL EN INGENIERÍA INFORMÁTICA

PRÁCTICA 2

Hadoop

Autor:

Manuel Jesús García Manday
(nickter@correo.ugr.es)

Master en Ingeniería Informática

19 de mayo de 2017

Índice

| | |
|--|---|
| 1. Objetivo. | 3 |
| 2. Introducción. | 3 |
| 3. Calcula el valor mínimo de la variable (columna) 5. | 4 |
| 4. Calcula el valor máximo de la variable (columna) 5. | 4 |
| 5. Calcula al mismo tiempo los valores máximo y mínimo de la variable 5. | 4 |
| 6. Calcula los valores máximo y mínimo de todas las variables (salvo la última, que es la etiqueta de la clase). | 4 |
| 7. Realizar la media de la variable 5. | 4 |
| 8. Obtener la media de todas las variables (salvo la clase). | 4 |
| 9. Comprobar si el conjunto de datos ECBDL es balanceado o no balanceado, es decir, que el ratio entre clases sea menor o mayor que 1.5 respectivamente. | 4 |
| 10.Cálculo del coeficiente de correlación entre todas las parejas de variables. | 4 |


1. Objetivo.

El objetivo de esta práctica es realizar programas escalables para mejorar la eficiencia en entornos Big Data.

2. Introducción.


Para comenzar a realizar las tareas que se piden en esta práctica, es necesario en primer lugar realizar una serie de pasos iniciales que se describen a continuación.

Realizamos una conexión remota hacia el servidor **hadoop.ugr.es** y una vez dentro creamos una carpeta nueva donde descargaremos el código Java de los programas. Comprobamos también que los datos de entrada se encuentran disponibles.




```
jesusgarciamanday — mcc48893432@hadoop-master:~ — ssh mcc48893432@hadoop.ugr.es
[MacBook-Pro-de-Jesus:~ jesusgarciamanday$ ssh mcc48893432@hadoop.ugr.es
[Password:
Last login: Tue May  9 18:48:58 2017 from cvi063087.ugr.es
```

Figura 1: Conexión remota a **hadoop.ugr.es**.



```
jesusgarciamanday — mcc48893432@hadoop-master:~ — ssh mcc48893432@hadoop.ugr.es
[mcc48893432@hadoop-master ~]$ mkdir stat
[mcc48893432@hadoop-master ~]$ cp /tmp/Min* ./stat/
[mcc48893432@hadoop-master ~]$ ls stat
Min.java  MinMapper.java  MinReducer.java
```


Figura 2: Copiando los ficheros Java.



```
jesusgarciamanday — mcc48893432@hadoop-master:~ — ssh mcc48893432@hadoop.ugr.es — 116x3
[mcc48893432@hadoop-master ~]$ hdfs dfs -ls /tmp/BDCC/datasets/ECBDL14
Found 1 items
-rw-r--r--  2 root supergroup _102747144 2017-03-16 11:06 /tmp/BDCC/datasets/ECBDL14/ECBDL14_10tst.data
```

Figura 3: Datos de entrada.

Viendo que están disponibles, ahora nos creamos un directorio local para las clases de java.




```
jesusgarciamanday — mcc48893432@hadoop-master:~/stat — ssh mcc48893432@hadoop.ugr.es
[mcc48893432@hadoop-master ~]$ cd stat/
[mcc48893432@hadoop-master stat]$ mkdir java_classes
```

Figura 4: Directorio local.

Con la preconfiguración realizada pasamos a realizar las diferentes tareas que se exponen en la práctica.

3. Calcula el valor mínimo de la variable (columna) 5.

La primera de ellas es calcular el mínimo sobre el conjunto de valores del dataset, por lo que una vez que tenemos los ficheros java ahora toca compilarlos para crear el fichero **.jar** a continuación y ejecutarlo en **hadoop**.




```

jesusgarciamanday — mcc48893432@hadoop-master:~/stat — ssh mcc48893432@hadoop.ugr.es — 116x32
[mcc48893432@hadoop-master stat]$ javac -cp /usr/lib/hadoop/*:/usr/lib/hadoop-mapreduce/* -d java_classes Min*
[mcc48893432@hadoop-master stat]$ /usr/java/jdk1.8.0_25/bin/jar -cvf stat.jar -C java_classes / .
added manifest
adding: oldapi/(in = 0) (out= 0)(stored 0%)
adding: oldapi/Min.class(in = 1420) (out= 782)(deflated 44%)
adding: oldapi/MinMapper.class(in = 1801) (out= 706)(deflated 60%)
adding: oldapi/MinReducer.class(in = 1717) (out= 709)(deflated 58%)
adding: MinMapper.java(in = 916) (out= 367)(deflated 59%)
adding: java_classes/(in = 0) (out= 0)(stored 0%)
adding: java_classes/oldapi/(in = 0) (out= 0)(stored 0%)
adding: java_classes/oldapi/Min.class(in = 1420) (out= 782)(deflated 44%)
adding: java_classes/oldapi/MinMapper.class(in = 1801) (out= 706)(deflated 60%)
adding: java_classes/oldapi/MinReducer.class(in = 1717) (out= 709)(deflated 58%)
adding: Min.java(in = 982) (out= 396)(deflated 59%)
adding: MinReducer.java(in = 816) (out= 334)(deflated 59%)

```

Figura 5: Compilamos y ejecutamos (I).



```

jesusgarciamanday — mcc48893432@hadoop-master:~/stat — ssh mcc48893432@hadoop.ugr.es — 132x35
[mcc48893432@hadoop-master stat]$ javac -cp /usr/lib/hadoop/*:/usr/lib/hadoop-mapreduce/* -d java_classes Min*
[mcc48893432@hadoop-master stat]$ /usr/java/jdk1.8.0_25/bin/jar -cvf stat.jar -C java_classes / .
added manifest
adding: oldapi/(in = 0) (out= 0)(stored 0%)
adding: oldapi/Min.class(in = 1420) (out= 782)(deflated 44%)
adding: oldapi/MinMapper.class(in = 1801) (out= 706)(deflated 60%)
adding: oldapi/MinReducer.class(in = 1717) (out= 709)(deflated 58%)
adding: MinMapper.java(in = 916) (out= 367)(deflated 59%)
adding: java_classes/(in = 0) (out= 0)(stored 0%)
adding: java_classes/oldapi/(in = 0) (out= 0)(stored 0%)
[mcc48893432@hadoop-master stat]$ hadoop jar stat.jar oldapi.Min /tmp/BDCC/datasets/ECBDL14/ECBDL14_10tst.data ./stat/output/
17/05/19 17:29:17 INFO client.RMPProxy: Connecting to ResourceManager at hadoop-master/192.168.10.1:8032
17/05/19 17:29:17 INFO client.RMPProxy: Connecting to ResourceManager at hadoop-master/192.168.10.1:8032
17/05/19 17:29:17 WARN mapreduce.JobResourceUploader: Hadoop command-line option parsing not performed. Implement the Tool interface
and execute your application with ToolRunner to remedy this.
17/05/19 17:29:18 INFO mapred.FileInputFormat: Total input paths to process : 1
17/05/19 17:29:18 INFO mapreduce.JobSubmitter: number of splits:2
17/05/19 17:29:18 INFO mapreduce.JobSubmitter: Submitting tokens for job: job_1494408081774_0178
17/05/19 17:29:18 INFO impl.YarnClientImpl: Submitted application application_1494408081774_0178
17/05/19 17:29:18 INFO mapreduce.Job: The url to track the job: http://hadoop.ugr.es:8088/proxy/application_1494408081774_0178/
17/05/19 17:29:18 INFO mapreduce.Job: Running job: job_1494408081774_0178
17/05/19 17:29:22 INFO mapreduce.Job: Job job_1494408081774_0178 running in uber mode : false
17/05/19 17:29:22 INFO mapreduce.Job: map 0% reduce 0%
17/05/19 17:29:32 INFO mapreduce.Job: map 100% reduce 0%
17/05/19 17:29:38 INFO mapreduce.Job: map 100% reduce 75%
17/05/19 17:29:39 INFO mapreduce.Job: map 100% reduce 81%
17/05/19 17:29:41 INFO mapreduce.Job: map 100% reduce 88%
17/05/19 17:29:42 INFO mapreduce.Job: map 100% reduce 100%
17/05/19 17:29:43 INFO mapreduce.Job: Job job_1494408081774_0178 completed successfully
17/05/19 17:29:43 INFO mapreduce.Job: Counters: 49

```

Figura 6: Compilamos y ejecutamos (II).

```

File System Counters
  FILE: Number of bytes read=2142847
  FILE: Number of bytes written=6470142
  FILE: Number of read operations=0
  FILE: Number of large read operations=0
  FILE: Number of write operations=0
  HDFS: Number of bytes read=102749934
  HDFS: Number of bytes written=8
  HDFS: Number of read operations=54
  HDFS: Number of large read operations=0
  HDFS: Number of write operations=32
Job Counters
  Launched map tasks=2
  Launched reduce tasks=16
  Rack-local map tasks=2
  Total time spent by all maps in occupied slots (ms)=112574
  Total time spent by all reduces in occupied slots (ms)=1894977
  Total time spent by all map tasks (ms)=16082
  Total time spent by all reduce tasks (ms)=38673
  Total vcore-seconds taken by all map tasks=16082
  Total vcore-seconds taken by all reduce tasks=38673
  Total megabyte-seconds taken by all map tasks=112574000
  Total megabyte-seconds taken by all reduce tasks=1933650000

```

Figura 7: Compilamos y ejecutamos (III).

```

Map-Reduce Framework
  Map input records=2897917
  Map output records=2897917
  Map output bytes=28979170
  Map output materialized bytes=2143005
  Input split bytes=234
  Combine input records=0
  Combine output records=0
  Reduce input groups=1
  Reduce shuffle bytes=2143005
  Reduce input records=2897917
  Reduce output records=1
  Spilled Records=5795834
  Shuffled Maps =32
  Failed Shuffles=0
  Merged Map outputs=32
  GC time elapsed (ms)=347
  CPU time spent (ms)=37010
  Physical memory (bytes) snapshot=7926947840
  Virtual memory (bytes) snapshot=984134000640
  Total committed heap usage (bytes)=19421724672
Shuffle Errors
  BAD_ID=0
  CONNECTION=0
  IO_ERROR=0
  WRONG_LENGTH=0
  WRONG_MAP=0
  WRONG_REDUCE=0
File Input Format Counters
  Bytes Read=102749700
File Output Format Counters
  Bytes Written=8

```

Figura 8: Compilamos y ejecutamos (IV).

Por último comprobamos el resultado para ver si se ha realizado correctamente.



```

jesusgarciamanday — mcc48893432@hadoop-master:~/stat — ssh mcc48893432@hadoop.ugr.es
[mcc48893432@hadoop-master stat]$ hdfs dfs -cat stat/output/*
1          -11.0

```

Figura 9: Comprobando resultado.

4. Calcula el valor máximo de la variable (columna) 5.
5. Calcula al mismo tiempo los valores máximo y mínimo de la variable 5.
6. Calcula los valores máximo y mínimo de todas las variables (salvo la última, que es la etiqueta de la clase).
7. Realizar la media de la variable 5.
8. Obtener la media de todas las variables (salvo la clase).
9. Comprobar si el conjunto de datos ECBDL es balanceado o no balanceado, es decir, que el ratio entre clases sea menor o mayor que 1.5 respectivamente.
10. Cálculo del coeficiente de correlación entre todas las parejas de variables.