

# COMP3141

## Software System Design and Implementation

### Induction, Data Types and Type Classes

Liam O'Connor  
CSE, UNSW (and Data61)  
Term 2 2019

## Recap: Induction

Suppose we want to prove that a property  $P(n)$  holds for **all** natural numbers  $n$ .

Remember that the set of natural numbers  $\mathbb{N}$  can be defined as follows:

### Definition of Natural Numbers

- 1 0 is a natural number.
- 2 For any natural number  $n$ ,  $n + 1$  is also a natural number.

## Recap: Induction

Therefore, to show  $P(n)$  for all  $n$ , it suffices to show:

- 1  $P(0)$  (the *base case*), and
- 2 assuming  $P(k)$  (the *inductive hypothesis*),  
 $\Rightarrow P(k+1)$  (the *inductive case*).

### Example

Show that  $f(n) = n^2$  for all  $n \in \mathbb{N}$ , where:

$$f(n) = \begin{cases} 0 & \text{if } n = 0 \\ 2n - 1 + f(n-1) & \text{if } n > 0 \end{cases}$$

(done on iPad)

# Induction on Lists

Haskell lists can be defined similarly to natural numbers.

## Definition of Haskell Lists

- 1 `[]` is a list.
- 2 For any list `xs`, `x:xs` is also a list (for any item `x`).

## Induction on Lists

Haskell lists can be defined similarly to natural numbers.

### Definition of Haskell Lists

- 1  $[]$  is a list.
- 2 For any list  $xs$ ,  $x:xs$  is also a list (for any item  $x$ ).

This means, if we want to prove that a property  $P(ls)$  holds for all lists  $ls$ , it suffices to show:

- 1  $P([])$  (the base case)
- 2  $P(x:xs)$  for all items  $x$ , assuming the inductive hypothesis  $P(xs)$ .

## Induction on Lists: Example

```
sum :: [Int] -> Int
```

```
sum [] = 0 -- 1
```

```
sum (x:xs) = x + sum xs -- 2
```

```
foldr :: (a -> b -> b) -> b -> [a] -> b
```

```
foldr f z [] = z -- A
```

```
foldr f z (x:xs) = x `f` foldr f z xs -- B
```

### Example

**Prove** for all `ls`:

$$\text{sum } ls == \text{foldr } (+) 0 \text{ } ls$$

(done on iPad)

## Custom Data Types

So far, we have seen **type synonyms** using the `type` keyword. For a graphics library, we might define:


```
type Point    = (Float, Float)
type Vector   = (Float, Float)
type Line     = (Point, Point)
type Colour   = (Int, Int, Int, Int) -- RGBA
```

```
movePoint :: Point -> Vector -> Point
movePoint (x,y) (dx,dy) = (x + dx, y + dy)
```

But these definitions allow `Points` and `Vectors` to be used interchangeably, increasing the **likelihood of errors**.

## Product Types

We can define our own compound types using the data keyword:



```
data Point = Point Float Float
           deriving (Show, Eq)
```

```
data Vector = Vector Float Float
            deriving (Show, Eq)
```

```
movePoint :: Point -> Vector -> Point
movePoint (Point x y) (Vector dx dy)
    = Point (x + dx) (y + dy)
```



# Records

We could define Colour similarly:

```
data Colour = Colour Int Int Int Int
```

But this has so many parameters, it's hard to tell which is which.

# Records

We could define Colour similarly:

```
data Colour = Colour Int Int Int Int
```

But this has so many parameters, it's hard to tell which is which. Haskell lets us declare these types as *records*, which is identical to the declaration style on the previous slide, but also gives us projection functions and record syntax:

```
data Colour = Colour { redC      :: Int
                      , greenC   :: Int
                      , blueC    :: Int
                      , opacityC :: Int
                      } deriving (Show, Eq)
```

Here, the code `redC (Colour 255 128 0 255)` gives 255.

## Enumeration Types

Similar to `enums` in C and Java, we can define types to have one of a set of predefined values:

```
data LineStyle = Solid
               | Dashed
               | Dotted
               deriving (Show, Eq)

data FillStyle = SolidFill | NoFill
               deriving (Show, Eq)
```

Types with more than one constructor are called *sum types*.

# Algebraic Data Types



Just as the `Point` constructor took two `Float` arguments, constructors for sum types can take parameters too, allowing us to model different kinds of shape:

```
data PictureObject
  = Path      [Point]      Colour LineStyle
  | Circle    Point Float   Colour LineStyle FillStyle
  | Polygon   [Point]      Colour LineStyle FillStyle
  | Ellipse   Point Float   Float Float
                  Colour LineStyle FillStyle
deriving (Show, Eq)

type Picture = [PictureObject]
```

# Live Coding: Cool Graphics

## Example (Ellipses and Curves)



# Recursive and Parametric Types

Data types can also be defined with **parameters**, such as the well known Maybe type, defined in the standard library:

```
data Maybe a = Just a | Nothing
```

## Recursive and Parametric Types

Data types can also be defined with **parameters**, such as the well known Maybe type, defined in the standard library:

```
data Maybe a = Just a | Nothing
```

Types can also be **recursive**. If lists weren't already defined in the standard library, we could define them ourselves:

```
data List a = Nil | Cons a (List a)
```

## Recursive and Parametric Types

Data types can also be defined with **parameters**, such as the well known Maybe type, defined in the standard library:

```
data Maybe a = Just a | Nothing
```

Types can also be **recursive**. If lists weren't already defined in the standard library, we could define them ourselves:

```
data List a = Nil | Cons a (List a)
```

We can even define natural numbers, where 2 is encoded as Succ(Succ Zero):

```
data Natural = Zero | Succ Natural
```



## Types in Design

### Sage Advice

An old adage due to Yaron Minsky (of Jane Street) is:

*Make illegal states **unrepresentable**.*

Choose types that *constrain* your implementation as much as possible. Then failure scenarios are eliminated automatically.

# Types in Design

## Sage Advice

An old adage due to Yaron Minsky (of Jane Street) is:

*Make illegal states **unrepresentable**.*

Choose types that *constrain* your implementation as much as possible. Then failure scenarios are eliminated automatically.

## Example (Contact Details)

```
data Contact = C Name (Maybe Address) (Maybe Email)
```

is changed to:

```
data ContactDetails = EmailOnly Email
                   | PostOnly Address
                   | Both Address Email

data Contact = C Name ContactDetails
```

What failure state is eliminated here? Liam: also talk about other famous screwups

## Partial Functions

Failure to follow Yaron's excellent advice leads to **partial functions**.

### Definition

A **partial function** is a function not defined for all possible inputs.

Examples: `head`, `tail`, `(!!)`, `division`

Partial functions are to be avoided, because they cause your program to crash if undefined cases are encountered.

## Partial Functions

Failure to follow Yaron's excellent advice leads to **partial functions**.

### Definition

A **partial function** is a function not defined for all possible inputs.

Examples: `head`, `tail`, `(!!)`, `division`

Partial functions are to be avoided, because they cause your program to crash if undefined cases are encountered.

To eliminate partiality, we must either:

- **enlarge** the codomain, usually with a `Maybe` type:

```
safeHead :: [a] -> Maybe a -- Q: How is this safer?  
safeHead (x:xs) = Just x  
safeHead []     = Nothing
```

## Partial Functions

Failure to follow Yaron's excellent advice leads to **partial functions**.

### Definition

A **partial function** is a function not defined for all possible inputs.

Examples: `head`, `tail`, `(!!)`, `division`

Partial functions are to be avoided, because they cause your program to crash if undefined cases are encountered.

To eliminate partiality, we must either:

- **enlarge** the codomain, usually with a `Maybe` type:

```
safeHead :: [a] -> Maybe a -- Q: How is this safer?
```

```
safeHead (x:xs) = Just x
```

```
safeHead []      = Nothing
```

- Or we must **constrain** the domain to be more specific:

```
safeHead' :: NonEmpty a -> a -- Q: How to define?
```

# Type Classes

You have already seen functions such as:

- compare
- (==)
- (+)
- show

that work on **multiple types**, and their corresponding constraints on type variables Ord, Eq, Num and Show.

# Type Classes

You have already seen functions such as:

- compare
- (==)
- (+)
- show

that work on **multiple types**, and their corresponding constraints on type variables Ord, Eq, Num and Show.

These constraints are called **type classes**, and can be thought of as a **set of types** for which certain operations are implemented.

## Show

The Show type class is a set of types that can be converted to strings. It is defined like:

```
class Show a where -- nothing to do with OOP
  show :: a -> String
```



## Show

The Show type class is a set of types that can be converted to strings. It is defined like:

```
class Show a where -- nothing to do with OOP
  show :: a -> String
```

Types are added to the type class as an *instance* like so:

```
instance Show Bool where
  show True  = "True"
  show False = "False"
```

## Show

The Show type class is a set of types that can be converted to strings. It is defined like:

```
class Show a where -- nothing to do with OOP
  show :: a -> String
```

Types are added to the type class as an *instance* like so:

```
instance Show Bool where
  show True  = "True"
  show False = "False"
```

We can also define instances that depend on other instances:

```
instance Show a => Show (Maybe a) where
  show (Just x) = "Just " ++ show x
  show Nothing  = "Nothing"
```

Fortunately for us, Haskell supports automatically deriving instances for some classes, including Show.

# Read

Type classes can also overload based on the type **returned**, unlike similar features like Java's interfaces:

```
class Read a where  
  read :: String -> a
```

Some examples:

```
● read "34" :: Int
```

# Read

Type classes can also overload based on the type **returned**, unlike similar features like Java's interfaces:

```
class Read a where  
  read :: String -> a
```

Some examples:

- `read "34" :: Int`
- `read "22" :: Char`

# Read

Type classes can also overload based on the type **returned**, unlike similar features like Java's interfaces:

```
class Read a where  
  read :: String -> a
```

Some examples:

- `read "34" :: Int`
- `read "22" :: Char` **Runtime error!**
- `show (read "34") :: String`

# Read

Type classes can also overload based on the type **returned**, unlike similar features like Java's interfaces:

```
class Read a where  
  read :: String -> a
```

Some examples:

- `read "34" :: Int`
- `read "22" :: Char` **Runtime error!**
- `show (read "34") :: String` **Type error!**

# Semigroup

## Semigroups

A *semigroup* is a pair of a set  $S$  and an operation  $\bullet : S \rightarrow S \rightarrow S$  where the operation  $\bullet$  is *associative*.

# Semigroup

## Semigroups

A *semigroup* is a pair of a set  $S$  and an operation  $\bullet : S \rightarrow S \rightarrow S$  where the operation  $\bullet$  is *associative*.

Associativity is defined as, for all  $a, b, c$ :

$$(a \bullet (b \bullet c)) = ((a \bullet b) \bullet c)$$

Haskell has a type class for semigroups! The associativity law is enforced only by programmer discipline:

```
class Semigroup s where
  (<>) :: s -> s -> s
  -- Law: (<>) must be associative.
```

What instances can you think of?



# Semigroup

Lets implement additive colour mixing:

```
instance Semigroup Colour where
  Colour r1 g1 b1 a1 <> Colour r2 g2 b2 a2
    = Colour (mix r1 r2)
              (mix g1 g2)
              (mix b1 b2)
              (mix a1 a2)
  where
    mix x1 x2 = min 255 (x1 + x2)
```

Observe that associativity is satisfied.

# Monoid

## Monoids

A *monoid* is a semigroup  $(S, \bullet)$  equipped with a special *identity element*  $z : S$  such that  $x \bullet z = x$  and  $z \bullet y = y$  for all  $x, y$ .

# Monoid

## Monoids

A *monoid* is a semigroup  $(S, \bullet)$  equipped with a special *identity element*  $z : S$  such that  $x \bullet z = x$  and  $z \bullet y = y$  for all  $x, y$ .

```
class (Semigroup a) => Monoid a where  
  mempty :: a
```

# Monoid

## Monoids

A *monoid* is a semigroup  $(S, \bullet)$  equipped with a special *identity element*  $z : S$  such that  $x \bullet z = x$  and  $z \bullet y = y$  for all  $x, y$ .

```
class (Semigroup a) => Monoid a where  
  mempty :: a
```

For colours, the identity element is transparent black:

```
instance Monoid Colour where  
  mempty = Colour 0 0 0 0
```

For each of the semigroups discussed previously:

- Are they monoids?
- If so, what is the identity element?

# Monoid

## Monoids

A *monoid* is a semigroup  $(S, \bullet)$  equipped with a special *identity element*  $z : S$  such that  $x \bullet z = x$  and  $z \bullet y = y$  for all  $x, y$ .

```
class (Semigroup a) => Monoid a where  
  mempty :: a
```

For colours, the identity element is transparent black:

```
instance Monoid Colour where  
  mempty = Colour 0 0 0 0
```

For each of the semigroups discussed previously:

- Are they monoids?
- If so, what is the identity element?

Are there any semigroups that are *not* monoids?

# Monoid

## Monoids

A *monoid* is a semigroup  $(S, \bullet)$  equipped with a special *identity element*  $z : S$  such that  $x \bullet z = x$  and  $z \bullet y = y$  for all  $x, y$ .

```
class (Semigroup a) => Monoid a where  
  mempty :: a
```

For colours, the identity element is transparent black:

```
instance Monoid Colour where  
  mempty = Colour 0 0 0 0
```

For each of the semigroups discussed previously:

- Are they monoids?
- If so, what is the identity element?

Are there any semigroups that are *not* monoids?

Non-empty lists, maximum

# Newtypes

There are multiple possible monoid instances for numeric types like Integer:

- The operation (+) is associative, with identity element 0
- The operation (\*) is associative, with identity element 1

## Newtypes

There are multiple possible monoid instances for numeric types like Integer:

- The operation (+) is associative, with identity element 0
- The operation (\*) is associative, with identity element 1

Haskell doesn't use any of these, because there can be only **one** instance per type per class in the **entire program** (including all dependencies and libraries used).

A common technique is to define a **separate type** that is represented identically to the original type, but can have its own, different type class instances.



# Newtypes

There are multiple possible monoid instances for numeric types like Integer:

- The operation (+) is associative, with identity element 0
- The operation (\*) is associative, with identity element 1

Haskell doesn't use any of these, because there can be only **one** instance per type per class in the **entire program** (including all dependencies and libraries used).

A common technique is to define a **separate type** that is represented identically to the original type, but can have its own, different type class instances.

In Haskell, this is done with the `newtype` keyword.

## Newtypes

A newtype declaration is much like a data declaration except that there can be only one constructor and it must take exactly one argument:

```
newtype Score = S Integer
```

```
instance Semigroup Score where  
  S x <> S y = S (x + y)
```

```
instance Monoid Score where  
  mempty = S 0
```

Here, `Score` is represented identically to `Integer`, and thus no performance penalty is incurred to convert between them.

In general, newtypes are a great way to prevent mistakes. Use them frequently!

# Ord

Ord is a type class for inequality comparison:

```
class Ord a where  
  (<=) :: a -> a -> Bool
```

What laws should instances satisfy?

# Ord

Ord is a type class for inequality comparison:

```
class Ord a where
  (<=) :: a -> a -> Bool
```

What laws should instances satisfy?

For all  $x$ ,  $y$ , and  $z$ :

- 1 *Reflexivity*:  $x \leq x$ .

# Ord

Ord is a type class for inequality comparison:

```
class Ord a where  
  (<=) :: a -> a -> Bool
```

What laws should instances satisfy?

For all  $x$ ,  $y$ , and  $z$ :

- 1 *Reflexivity*:  $x \leq x$ .
- 2 *Transitivity*: If  $x \leq y$  and  $y \leq z$  then  $x \leq z$ .

# Ord

Ord is a type class for inequality comparison:

```
class Ord a where  
  (<=) :: a -> a -> Bool
```

What laws should instances satisfy?

For all  $x$ ,  $y$ , and  $z$ :

- 1 *Reflexivity*:  $x \leq x$ .
- 2 *Transitivity*: If  $x \leq y$  and  $y \leq z$  then  $x \leq z$ .
- 3 *Antisymmetry*: If  $x \leq y$  and  $y \leq x$  then  $x == y$ .

# Ord

Ord is a type class for inequality comparison:

```
class Ord a where  
  (<=) :: a -> a -> Bool
```

What laws should instances satisfy?

For all  $x$ ,  $y$ , and  $z$ :

- 1 *Reflexivity*:  $x \leq x$ .
- 2 *Transitivity*: If  $x \leq y$  and  $y \leq z$  then  $x \leq z$ .
- 3 *Antisymmetry*: If  $x \leq y$  and  $y \leq x$  then  $x == y$ .
- 4 *Totality*: Either  $x \leq y$  or  $y \leq x$

# Ord

Ord is a type class for inequality comparison:

```
class Ord a where  
  (<=) :: a -> a -> Bool
```

What laws should instances satisfy?

For all  $x$ ,  $y$ , and  $z$ :

- 1 *Reflexivity*:  $x \leq x$ .
- 2 *Transitivity*: If  $x \leq y$  and  $y \leq z$  then  $x \leq z$ .
- 3 *Antisymmetry*: If  $x \leq y$  and  $y \leq x$  then  $x == y$ .
- 4 *Totality*: Either  $x \leq y$  or  $y \leq x$

Relations that satisfy these four properties are called *total orders*.  
Without the fourth (totality), they are called *partial orders*.



## Eq

Eq is a type class for equality or equivalence:

```
class Eq a where  
  (==) :: a -> a -> Bool
```

What laws should instances satisfy?

## Eq

Eq is a type class for equality or equivalence:

```
class Eq a where  
  (==) :: a -> a -> Bool
```

What laws should instances satisfy?

For all x, y, and z:

- 1 *Reflexivity*:  $x == x$ .

## Eq

Eq is a type class for equality or equivalence:

```
class Eq a where  
  (==) :: a -> a -> Bool
```

What laws should instances satisfy?

For all  $x$ ,  $y$ , and  $z$ :

- 1 *Reflexivity*:  $x == x$ .
- 2 *Transitivity*: If  $x == y$  and  $y == z$  then  $x == z$ .

## Eq

Eq is a type class for equality or equivalence:

```
class Eq a where  
  (==) :: a -> a -> Bool
```

What laws should instances satisfy?

For all x, y, and z:

- 1 *Reflexivity*:  $x == x$ .
- 2 *Transitivity*: If  $x == y$  and  $y == z$  then  $x == z$ .
- 3 *Symmetry*: If  $x == y$  then  $y == x$ .

## Eq

Eq is a type class for equality or equivalence:

```
class Eq a where  
  (==) :: a -> a -> Bool
```

What laws should instances satisfy?

For all  $x$ ,  $y$ , and  $z$ :

- 1 *Reflexivity*:  $x == x$ .
- 2 *Transitivity*: If  $x == y$  and  $y == z$  then  $x == z$ .
- 3 *Symmetry*: If  $x == y$  then  $y == x$ .

Relations that satisfy these are called *equivalence relations*.

## Eq

Eq is a type class for equality or equivalence:

```
class Eq a where
  (==) :: a -> a -> Bool
```

What laws should instances satisfy?

For all x, y, and z:

- 1 *Reflexivity*:  $x == x$ .
- 2 *Transitivity*: If  $x == y$  and  $y == z$  then  $x == z$ .
- 3 *Symmetry*: If  $x == y$  then  $y == x$ .

Relations that satisfy these are called *equivalence relations*.

Some argue that the Eq class should be only for *equality*, requiring stricter laws like:

If  $x == y$  then  $f\ x == f\ y$  for all functions  $f$

But this is debated.

# Homework

- 1 Do the first programming exercise, and ask us on Piazza if you get stuck. It will be due in **exactly 1 week** from the start of this lecture.
- 2 Last week's quiz is due this friday. Make sure you submit your answers.
- 3 This week's quiz is also up, due next friday (10 days away).