

COMP3141

Software System Design and Implementation

Functors, Applicatives, and Monads Practice

Christine Rizkallah
CSE, UNSW (and Data61)
Term 2 2019

Recall: Functors, Applicatives, Monads

- Functors are types for containers where we can `map` pure functions on their contents.
- Applicative Functors are types where we can combine n containers with an n -ary function.
- Monads are types \mathfrak{m} where we can *sequentially compose* functions of the form $a \rightarrow \mathfrak{m} \ b$.

Recall: Functors

```
class Functor f where  
  fmap :: (a -> b) -> f a -> f b
```

The functor type class must obey two laws:

Functor Laws

- 1 `fmap id == id`
- 2 `fmap f . fmap g == fmap (f . g)`

Recall: Applicatives

```
class Functor f => Applicative f where  
  pure :: a -> f a  
  (<*>) :: f (a -> b) -> f a -> f b
```

The functor type class must obey four additional laws:

Applicative Laws

- 1 `pure id <*> v = v`
- 2 `pure f <*> pure x = pure (f x)`
- 3 `u <*> pure y = pure ($ y) <*> u`
- 4 `pure (.) <*> u <*> v <*> w = u <*> (v <*> w)`

Alternative Applicative

It is possible to express Applicative equivalently as:

```
class Functor f => App f where
  pure  :: a -> f a
  tuple :: f a -> f b -> f (a,b)
```

Example (Alternative Applicative)

- 1 Using `,` `fmap` and `pure`, let's implement `<*>`.
- 2 And, using `<*>`, `fmap` and `pure`, let's implement `tuple`.

done in Haskell.

Proof exercise: Prove that `tuple` obeys the applicative laws.

Recall: Monads

```
class Applicative m => Monad m where  
  (>>=) :: m a -> (a -> m b) -> m b
```

We can define a composition operator with (>>=):

```
(<=<) :: (b -> m c) -> (a -> m b) -> (a -> m c)  
(f <=< g) x = g x >>= f
```

The monad type class must obey three additional laws:

Monad Laws

- 1 $f \leq\leq (g \leq\leq x) == (f \leq\leq g) \leq\leq x$ (associativity)
- 2 $\text{pure} \leq\leq f == f$ (left identity)
- 3 $f \leq\leq \text{pure} == f$ (right identity)

Alternative Monad

It is possible to express Monad equivalently as:

```
class Applicative m => Mon m where  
  join :: m (m a) -> m a
```

Example (Alternative Monad)

- 1 Using join and fmap, let's implement `>>=`.
- 2 And, using `>>=` let's implement join.

done in Haskell.

Tree Example

```
data Tree a
  = Leaf
  | Node a (Tree a) (Tree a)
  deriving (Show)
```

Example (Tree Example)

Show that Tree is an Applicative instance.
done in Haskell.

Note that Tree is not a Monad instance.

Formulas Example

```
data Formula v = Var v
               | Plus (Formula v) (Formula v)
               | Times (Formula v) (Formula v)
               | Constant Int
               deriving (Eq, Show)
```

Example (Formulas Example)

Show that Formula is a Monad instance.
done in Haskell.