

Recitation 2 - Deterministic Finite Automata

John Chilton

June 8, 2007

We will be reviewing how to construct DFAs. We will start with some simple ones and use regular operations to construct more complicated ones.

- ▶ Motivation and relevancy
- ▶ Use of Whiteboard/Chalkboard
- ▶ Slides

- ▶ For alphabet $\Sigma = \{a, b\}$, $R_1 = \{w \mid w \text{ has an odd number of } b\text{'s}\}$. Find a DFA, $M_1 = (Q_1, \Sigma, \delta_1, q_1, F_1)$, that accepts R_1
- ▶ How many and which states are required?
- ▶ What should happen when a is read?
- ▶ What should happen when b is read?
- ▶ Label start and accept states.

$$M_1 = (Q_1, \Sigma, \delta_1, q_1, F_1) = (\{q_{odd}, q_{even}\}, \Sigma, \delta_1, q_{even}, \{q_{odd}\})$$

with δ_1 as follows

δ_1	a	b
q_{odd}	q_{odd}	q_{even}
q_{even}	q_{even}	q_{odd}

- ▶ For alphabet $\Sigma = \{a, b\}$, $R_3 = \{w \mid w \text{ contains at least three } a\text{'s}\}$. Find a DFA, $M_2 = (Q_2, \Sigma, \delta_2, q_2, F_2)$, that accepts R_2
- ▶ How many and which states are required?
- ▶ What should happen when a is read?
- ▶ What should happen when b is read?
- ▶ Label start and accept states.

$$M_2 = (Q_2, \Sigma, \delta_2, q_2, F_2)$$

$$= (\{q_{20}, q_{21}, q_{22}, q_{23}\}, \Sigma, \delta_2, q_{20}, \{q_{23}\})$$

with δ_2 as follows

δ_2	a	b
q_{20}	q_{21}	q_{20}
q_{21}	q_{22}	q_{21}
q_{22}	q_{23}	q_{22}
q_{23}	q_{23}	q_{23}

- For alphabet $\Sigma = \{a, b\}$, $R_3 = \{w \mid w \text{ starts with a } b \text{ and ends with an } a\}$. Find a DFA, $M_3 = (Q_3, \Sigma, \delta_3, q_3, F_3)$, that accepts R_3

$$M_3 = (Q_3, \Sigma, \delta_3, q_3, F_3)$$

$$= (\{q_{3start}, q_{3dead}, q_{3a}, q_{3b}\}, \Sigma, \delta_3, q_{3start}, \{q_{3a}\})$$

with δ_3 as follows

δ_3	a	b
q_{3start}	q_{3dead}	q_{3b}
q_{3dead}	q_{3dead}	q_{3dead}
q_{3a}	q_{3a}	q_{3b}
q_{3b}	q_{3a}	q_{3b}


Given

$$\begin{aligned}M_1 &= (Q_1, \Sigma, \delta_1, q_1, F_1) \\&= (\{q_{\text{odd}}, q_{\text{even}}\}, \Sigma, \delta_1, q_{\text{even}}, \{q_{\text{odd}}\}) \\M_2 &= (Q_2, \Sigma, \delta_2, q_2, F_2) \\&= (\{q_{20}, q_{21}, q_{22}, q_{23}\}, \Sigma, \delta_2, q_{20}, \{q_{23}\})\end{aligned}$$

Construct DFA which accepts $R_1 \cup R_2 = (Q_{\cup}, \Sigma, \delta_{\cup}, q_0, F_{\cup})$.

Q_U


$$\begin{aligned} Q_U &= Q_1 \times Q_2 \\ &= \{(q_{\text{odd}}, q_{20}), (q_{\text{odd}}, q_{21}), (q_{\text{odd}}, q_{22}), (q_{\text{odd}}, q_{23}), \\ &\quad (q_{\text{even}}, q_{20}), (q_{\text{even}}, q_{21}), (q_{\text{even}}, q_{22}), (q_{\text{even}}, q_{23})\} \end{aligned}$$



q_0 and F_U

$$\begin{aligned} q_0 &= (q_1, q_2) \\ &= (q_{\text{even}}, q_{20}) \end{aligned}$$


$$\begin{aligned} F_U &= \{(r_1, r_2) \mid r_1 \in F_1 \text{ or } r_2 \in F_2\} \\ &= \{(q_{\text{odd}}, q_{20}), (q_{\text{odd}}, q_{21}), (q_{\text{odd}}, q_{22}), (q_{\text{odd}}, q_{23}), (q_{\text{even}}, q_{23})\} \end{aligned}$$




δ_1	a	b
q_{odd}	q_{odd}	q_{even}
q_{even}	q_{even}	q_{odd}

δ_2	a	b
q_{20}	q_{21}	q_{20}
q_{21}	q_{22}	q_{21}
q_{22}	q_{23}	q_{22}
q_{23}	q_{23}	q_{23}


δ_U	a	b
(q_{odd}, q_{20})	(q_{odd}, q_{21})	(q_{even}, q_{20})
(q_{odd}, q_{21})	(q_{odd}, q_{22})	(q_{even}, q_{21})
(q_{odd}, q_{22})	(q_{odd}, q_{23})	(q_{even}, q_{22})
(q_{odd}, q_{23})	(q_{odd}, q_{23})	(q_{even}, q_{23})
(q_{even}, q_{20})	(q_{even}, q_{21})	(q_{odd}, q_{20})
(q_{even}, q_{21})	(q_{even}, q_{22})	(q_{odd}, q_{21})
(q_{even}, q_{22})	(q_{even}, q_{23})	(q_{odd}, q_{22})
(q_{even}, q_{23})	(q_{even}, q_{23})	(q_{odd}, q_{23})



Intersection. $F_{\cap} = \{(r_1, r_2) \mid r_1 \in F_1 \text{ and } r_2 \in F_2\}$



Producing an NFA that is that accepts the union of two regular languages given by DFAs (or NFAs) is even easier.



How about intersection?

- ▶ Reminder: $R_3 = \{w \mid w \text{ starts with a } b \text{ and ends with an } a\}$
- ▶ What is the complement of R_3
- ▶ Design a DFA which accepts \bar{R}_3 .
- ▶ Does the same trick work for NFAs?

- ▶ Easy, straightforward methods given to compute union, intersection, and complement of regular languages
- ▶ Star and concatenation are are slightly more complicated general...
- ▶ $R_4 = \{w \mid w \text{ contains exactly 2 } a\text{'s}\}$
- ▶ $R_5 = \{w \mid w \text{ contains exactly 2 } b\text{'s}\}$
- ▶ $R_4 \circ R_5$ - consider *baabbab* and *baabab*
- ▶ $(R_4 \cup R_5)^*$ - difficult for same reason

- ▶ Consider $R_6 = baa^*$.
- ▶ Design a DFA which accepts R_6^*
- ▶ Design a DFA which accepts $R_6 \circ R_1$