

Project Stuff

- Each form should have a single purpose
e.g. Add a new user
OR Add a new review
Not both.

~~reports.html~~

clayton.edu/cstem/initiatives/reports.html

clayton.edu/reports.html

Regular Expressions

<https://regex101.com/>

preg_match(\$pattern, \$string) — return 1 if \$string matches \$pattern | 0 if not

↓
regular expression (Regex)

string to test
↓

metacharacters specify a RegEx pattern. In PHP they go between a pair of /

Matching Characters

/a/

/. /

- matches any single character
-

```

<?php
    $kernel_patt = '/kern.l/';
?>

<p>kernel:
    <?= preg_match($kernel_patt, 'kernel') ?>
</p>
<p>kern!l:
    <?= preg_match($kernel_patt, 'kern!l') ?>
</p>
<p>kernel mode:
    <?= preg_match('/...../', 'kernel mode') ?>
</p>

```

Anchors

- match start or end of line

^ - anchors start

\$ - anchors end

```

$url = "http://www.clayton.edu";

<h2>Anchors</h2>
<p><strong>Does <?= $url ?> start with http?</strong>
<?= preg_match('/^http/', $url) ?></p>
<p><strong>Does <?= $url ?> start with https?</strong>
<?= preg_match('/^https/', $url) ?></p>

<p><strong>Does <?= $url ?> end with .edu?</strong>
<?= preg_match('/.edu$/ ', $url) ?></p>
<p><strong>Does http://www.clayton.edu end with .edu?</strong>
<?= preg_match('/\a.edu$/ ', 'http://www.clayton.edu') ?></p>

```

Specifying Quantity

? - preceding character should appear 0 or 1 times (optional)

+ - one or more

* - zero or more

{n} - at least n times (not less than n)

{n,m} - at least n, but no more than m

⁽ⁱⁱⁱ⁾
 $\{n, m\}$ - at least n , but no more than m