

Code_generator

Generated by Doxygen 1.8.18

1 Namespace Index	1
1.1 Packages	1
2 Class Index	3
2.1 Class List	3
3 Namespace Documentation	5
3.1 Package common	5
3.1.1 Detailed Description	5
3.2 Package configurator	5
3.2.1 Detailed Description	6
3.3 Package framework	6
3.3.1 Detailed Description	6
3.4 Package gui	6
3.4.1 Detailed Description	7
3.5 Package microcontroller	7
3.5.1 Detailed Description	7
3.6 Package projectConfiguration	7
3.6.1 Detailed Description	7
3.7 Package xmlCreator	8
3.7.1 Detailed Description	8
3.8 Package xmlParser	8
3.8.1 Detailed Description	8
4 Class Documentation	9
4.1 gui.AboutWindow Class Reference	9
4.1.1 Detailed Description	9
4.1.2 Constructor & Destructor Documentation	9
4.1.2.1 AboutWindow()	9
4.1.3 Member Function Documentation	10
4.1.3.1 main()	10
4.2 microcontroller.Adc Class Reference	10
4.2.1 Constructor & Destructor Documentation	11
4.2.1.1 Adc()	11
4.2.2 Member Function Documentation	11
4.2.2.1 addChannel()	11
4.2.2.2 addClock()	11
4.2.2.3 addJustification()	11
4.2.2.4 addPrescaler()	12
4.2.2.5 addReference()	12

4.2.2.6 addResolution()	12
4.2.2.7 addSample()	13
4.2.2.8 getChannel()	13
4.2.2.9 getChannelNum()	13
4.2.2.10 getClock()	14
4.2.2.11 getClockNum()	14
4.2.2.12 getJustification()	14
4.2.2.13 getJustificationNum()	15
4.2.2.14 getName()	15
4.2.2.15 getPrescaler()	15
4.2.2.16 getPrescalerNum()	15
4.2.2.17 getReference()	16
4.2.2.18 getReferenceNum()	16
4.2.2.19 getResolution()	16
4.2.2.20 getResolutionNum()	17
4.2.2.21 getSample()	17
4.2.2.22 getSampleNum()	17
4.2.2.23 isValid()	18
4.2.2.24 setName()	18
4.3 configurator.ADC.AdcChannel Class Reference	18
4.3.1 Member Function Documentation	19
4.3.1.1 getCodeName()	19
4.3.1.2 getName()	19
4.3.1.3 getPinIndex()	19
4.3.1.4 isSelected()	20
4.3.1.5 isValid()	20
4.3.1.6 setCodeName()	20
4.3.1.7 setSelected()	20
4.4 configurator.AdcConf Class Reference	21
4.4.1 Constructor & Destructor Documentation	22
4.4.1.1 AdcConf()	22
4.4.2 Member Function Documentation	22
4.4.2.1 getClock()	22
4.4.2.2 getCodeName()	22
4.4.2.3 getJustification()	23
4.4.2.4 getPrescaler()	23
4.4.2.5 getReference()	23
4.4.2.6 getResolution()	23
4.4.2.7 getSample()	24

4.4.2.8	getSelected()	24
4.4.2.9	setChannels()	24
4.4.2.10	setClock()	24
4.4.2.11	setCodeName()	25
4.4.2.12	setJustification()	25
4.4.2.13	setPrescaler()	25
4.4.2.14	setReference()	26
4.4.2.15	setResolution()	26
4.4.2.16	setSample()	26
4.4.2.17	setSelected()	26
4.4.3	Member Data Documentation	27
4.4.3.1	DF_SELECTED	27
4.5	gui.AdcConfWindow Class Reference	27
4.5.1	Constructor & Destructor Documentation	27
4.5.1.1	AdcConfWindow()	27
4.5.2	Member Function Documentation	28
4.5.2.1	main()	28
4.6	framework.AdcGenerator Class Reference	28
4.6.1	Member Function Documentation	29
4.6.1.1	getEIDefs()	29
4.6.1.2	getElements()	29
4.6.1.3	getIncludes()	29
4.7	configurator.GPIO.AltMode Enum Reference	30
4.7.1	Detailed Description	30
4.7.2	Member Function Documentation	30
4.7.2.1	getConfFromString()	30
4.7.3	Member Data Documentation	31
4.7.3.1	ALT_MODE_ANALOG	31
4.7.3.2	ALT_MODE_I2C	31
4.7.3.3	ALT_MODE_MAX_VALUE	31
4.7.3.4	ALT_MODE_NONE	31
4.7.3.5	ALT_MODE_SPI	31
4.7.3.6	ALT_MODE_UART	32
4.7.3.7	STR_NAME	32
4.8	framework.CodeGenerator Class Reference	32
4.8.1	Detailed Description	32
4.8.2	Constructor & Destructor Documentation	32
4.8.2.1	CodeGenerator()	32
4.8.3	Member Function Documentation	33

4.8.3.1 Generate()	33
4.9 configurator.GPIO.CodeName Enum Reference	33
4.9.1 Detailed Description	33
4.9.2 Member Data Documentation	34
4.9.2.1 CODE_NAME	34
4.9.2.2 STR_NAME	34
4.10 framework.Common Class Reference	34
4.10.1 Detailed Description	35
4.10.2 Member Function Documentation	35
4.10.2.1 getCfgFileCPath()	35
4.10.2.2 getCfgFileHPath()	35
4.10.2.3 getCfgPath()	36
4.10.2.4 getCommonCfgDefinitions()	36
4.10.2.5 getCommonIncludes()	37
4.10.2.6 getFrameworkCommonFilePath()	37
4.10.2.7 getFrameworkIncludesFilePath()	37
4.10.2.8 getInstallationFwkPath()	38
4.10.2.9 getProjectFwkPath()	38
4.10.2.10 setInstallationFwkPath()	38
4.10.2.11 setProjectFwkPath()	39
4.10.3 Member Data Documentation	39
4.10.3.1 NL	39
4.10.3.2 STR_DEFINITION	39
4.10.3.3 STR_GEN_CODE_NOTICE_FOOTER	39
4.10.3.4 STR_GEN_CODE_NOTICE_HEADER	40
4.10.3.5 STR_HEADER_EXT	40
4.10.3.6 STR_INCLUDE	40
4.10.3.7 STR_MODULE_ADC	40
4.10.3.8 STR_MODULE_GPIO	40
4.11 configurator.ConfigurationFile Class Reference	40
4.11.1 Detailed Description	41
4.11.2 Member Data Documentation	41
4.11.2.1 STR_PROJ_CONF_FILE	41
4.12 xmlCreator.ConfXmlWriter Class Reference	41
4.12.1 Detailed Description	41
4.12.2 Constructor & Destructor Documentation	42
4.12.2.1 ConfXmlWriter()	42
4.12.3 Member Function Documentation	42
4.12.3.1 addPin()	42

4.12.3.2 writeXml()	42
4.13 common.ErrorCode Enum Reference	43
4.13.1 Detailed Description	43
4.13.2 Member Data Documentation	43
4.13.2.1 EX_ERROR	44
4.13.2.2 FILE_CONF_ERROR	44
4.13.2.3 FILE_READ_ERROR	44
4.13.2.4 FILE_WRITE_ERROR	44
4.13.2.5 INT_INVALID_INDEX	44
4.13.2.6 NO_ERROR	44
4.13.2.7 STR_INVALID	44
4.14 common.Features Class Reference	45
4.14.1 Detailed Description	45
4.14.2 Member Function Documentation	45
4.14.2.1 debugPrint()	45
4.14.2.2 verbosePrint()	46
4.14.3 Member Data Documentation	46
4.14.3.1 DEBUG	46
4.14.3.2 DEBUG_STR	46
4.14.3.3 SW_VERSION	46
4.14.3.4 VERBOSE	47
4.14.3.5 VERBOSE_STR	47
4.14.3.6 VERSION_NAME	47
4.14.3.7 VERSION_STATUS	47
4.15 gui.GpioConfWindow Class Reference	47
4.15.1 Detailed Description	48
4.15.2 Constructor & Destructor Documentation	48
4.15.2.1 GpioConfWindow()	48
4.15.3 Member Function Documentation	48
4.15.3.1 main()	48
4.16 gui.MainGui Class Reference	49
4.16.1 Detailed Description	49
4.16.2 Member Function Documentation	49
4.16.2.1 generateCode()	50
4.16.2.2 loadProjectFile()	50
4.16.2.3 main()	50
4.16.2.4 saveUc()	50
4.16.2.5 setNewUC()	51
4.16.2.6 showAboutWindow()	51

4.16.2.7 showAdcConfWindow()	51
4.16.2.8 showErrorDialog()	51
4.16.2.9 showGpioConfWindow()	51
4.16.3 Member Data Documentation	52
4.16.3.1 ProjectFile	52
4.16.3.2 ProjectPath	52
4.17 gui.MainWindow Class Reference	52
4.17.1 Detailed Description	53
4.17.2 Constructor & Destructor Documentation	53
4.17.2.1 MainWindow()	53
4.17.3 Member Function Documentation	53
4.17.3.1 main()	53
4.17.3.2 OpenFileChooser()	53
4.17.3.3 setProjectInformation()	54
4.17.3.4 setVisible()	54
4.17.4 Member Data Documentation	55
4.17.4.1 FrmCodeGenerator	55
4.18 gui.Messages Class Reference	55
4.18.1 Detailed Description	55
4.18.2 Member Function Documentation	55
4.18.2.1 getString()	55
4.19 microcontroller.Microcontroller Class Reference	56
4.19.1 Detailed Description	57
4.19.2 Constructor & Destructor Documentation	57
4.19.2.1 Microcontroller()	57
4.19.3 Member Function Documentation	57
4.19.3.1 getConfiguredPin()	57
4.19.3.2 getPin()	58
4.19.3.3 getUc_adcNum()	58
4.19.3.4 getUc_gpioNum()	58
4.19.3.5 getUc_manufacturer()	59
4.19.3.6 getUc_model()	59
4.19.3.7 getUc_pinNum()	59
4.19.3.8 getUc_portNum()	59
4.19.3.9 getUc_selectedAdcsNum()	60
4.19.3.10 getUc_selectedPinsNum()	60
4.19.3.11 isValid()	60
4.19.3.12 loadPinsConf()	60
4.19.3.13 processDocument()	61

4.19.4 Member Data Documentation	61
4.19.4.1 AdcCfg	61
4.19.4.2 Adcs	61
4.19.4.3 Definitions_Adc	61
4.19.4.4 Definitions_Common	62
4.19.4.5 Definitions_Gpio	62
4.19.4.6 GpioCfgPin	62
4.19.4.7 Includes_Adc	62
4.19.4.8 Includes_Common	62
4.19.4.9 Includes_Gpio	62
4.19.4.10 MAX_NUMBER_OF_ADCS	62
4.19.4.11 MAX_NUMBER_OF_PINS_PER_PORT	63
4.19.4.12 Ports	63
4.20 configurator.GPIO.Mode Enum Reference	63
4.20.1 Detailed Description	63
4.20.2 Member Function Documentation	64
4.20.2.1 getConfFromString()	64
4.20.3 Member Data Documentation	65
4.20.3.1 MODE_ALTERNATE_FUNCTION	65
4.20.3.2 MODE_INPUT	65
4.20.3.3 MODE_MAX_VALUE	65
4.20.3.4 MODE_OUTPUT	65
4.20.3.5 STR_NAME	65
4.21 configurator.GPIO.OutLevel Enum Reference	66
4.21.1 Detailed Description	66
4.21.2 Member Function Documentation	66
4.21.2.1 getConfFromString()	66
4.21.3 Member Data Documentation	67
4.21.3.1 HIGH	67
4.21.3.2 LOW	67
4.21.3.3 MAX_VALUE	67
4.21.3.4 STR_NAME	67
4.22 configurator.GPIO.OutType Enum Reference	67
4.22.1 Detailed Description	68
4.22.2 Member Function Documentation	68
4.22.2.1 getConfFromString()	68
4.22.3 Member Data Documentation	69
4.22.3.1 OTYPE_MAX_VALUE	69
4.22.3.2 OTYPE_NOT_AVAILABLE	69

4.22.3.3 OTYPE_OPEN_DRAIN	69
4.22.3.4 OTYPE_PUSH_PULL	69
4.22.3.5 STR_NAME	69
4.23 microcontroller.Pin Class Reference	70
4.23.1 Detailed Description	71
4.23.2 Constructor & Destructor Documentation	72
4.23.2.1 Pin()	72
4.23.3 Member Function Documentation	72
4.23.3.1 getAdc()	72
4.23.3.2 getAdcChannel()	72
4.23.3.3 getClock()	73
4.23.3.4 getFeat_adc()	73
4.23.3.5 getFeat_clock()	73
4.23.3.6 getFeat_i2c()	73
4.23.3.7 getFeat_int()	74
4.23.3.8 getFeat_reset()	74
4.23.3.9 getFeat_spi()	74
4.23.3.10 getFeat_timer()	74
4.23.3.11 getFeat_uart()	75
4.23.3.12 getFunc_gnd()	75
4.23.3.13 getFunc_gpio()	75
4.23.3.14 getFunc_misc()	75
4.23.3.15 getFunc_reset()	76
4.23.3.16 getFunc_vcc()	76
4.23.3.17 getI2c()	76
4.23.3.18 getInt()	76
4.23.3.19 getName()	77
4.23.3.20 getNumber()	77
4.23.3.21 getPort()	77
4.23.3.22 getPortPin()	77
4.23.3.23 getReset()	78
4.23.3.24 getSpi()	78
4.23.3.25 getTimer()	78
4.23.3.26 getUart()	78
4.23.3.27 isValid()	79
4.23.3.28 setAdc()	79
4.23.3.29 setClock()	79
4.23.3.30 setFeat_adc()	79
4.23.3.31 setFeat_clock()	80

4.23.3.32 setFeat_i2c()	80
4.23.3.33 setFeat_int()	80
4.23.3.34 setFeat_reset()	81
4.23.3.35 setFeat_spi()	81
4.23.3.36 setFeat_timer()	81
4.23.3.37 setFeat_uart()	81
4.23.3.38 setFunc_gnd()	82
4.23.3.39 setFunc_gpio()	82
4.23.3.40 setFunc_misc()	82
4.23.3.41 setFunc_reset()	83
4.23.3.42 setFunc_vcc()	83
4.23.3.43 setI2c()	83
4.23.3.44 setInt()	84
4.23.3.45 setName()	84
4.23.3.46 setNumber()	84
4.23.3.47 setPort()	84
4.23.3.48 setPortPin()	85
4.23.3.49 setReset()	85
4.23.3.50 setSpi()	85
4.23.3.51 setTimer()	86
4.23.3.52 setUart()	86
4.23.4 Member Data Documentation	86
4.23.4.1 DEF_FEATURE	86
4.23.4.2 DEF_FEATURE_AV	87
4.23.4.3 DEF_FUNCTION	87
4.23.4.4 DEF_NAME	87
4.23.4.5 DEF_NUMBER	87
4.23.4.6 DEF_PORT	87
4.23.4.7 DISABLE	87
4.23.4.8 ENABLE	87
4.24 configurator.PinConf Class Reference	88
4.24.1 Detailed Description	88
4.24.2 Constructor & Destructor Documentation	89
4.24.2.1 PinConf()	89
4.24.3 Member Function Documentation	89
4.24.3.1 getAltMode()	89
4.24.3.2 getCodeName()	89
4.24.3.3 getMode()	90
4.24.3.4 getOutLevel()	90

4.24.3.5	getOutType()	90
4.24.3.6	getPinName()	90
4.24.3.7	getPort()	91
4.24.3.8	getPortPin()	91
4.24.3.9	getPull()	91
4.24.3.10	getSelected()	91
4.24.3.11	getSpeed()	92
4.24.3.12	isAv_Adc()	92
4.24.3.13	isAv_altFunc()	92
4.24.3.14	isAv_I2c()	92
4.24.3.15	isAv_Spi()	93
4.24.3.16	isAv_Uart()	93
4.24.3.17	isValid()	93
4.24.3.18	setAltMode()	93
4.24.3.19	setCodeName()	94
4.24.3.20	setMode()	94
4.24.3.21	setOutLevel()	94
4.24.3.22	setOutType()	95
4.24.3.23	setPull()	95
4.24.3.24	setSelected()	95
4.24.3.25	setSpeed()	95
4.24.4	Member Data Documentation	96
4.24.4.1	DF_ALT_MODE	96
4.24.4.2	DF_CODE_NAME	96
4.24.4.3	DF_MODE	96
4.24.4.4	DF_OUT_LEVEL	96
4.24.4.5	DF_OUTTYPE	96
4.24.4.6	DF_PULL	97
4.24.4.7	DF_SELECTED	97
4.24.4.8	DF_SPEED	97
4.25	projectConfiguration.ProjectSettings Class Reference	97
4.25.1	Detailed Description	97
4.25.2	Constructor & Destructor Documentation	98
4.25.2.1	ProjectSettings()	98
4.25.3	Member Function Documentation	98
4.25.3.1	getConfFile()	98
4.25.3.2	getFrameworkPath()	98
4.25.3.3	getProjectName()	99
4.25.3.4	getUcFile()	99

4.25.3.5 openProjectFile()	99
4.25.3.6 processDocument()	99
4.26 configurator.GPIO.Pull Enum Reference	100
4.26.1 Detailed Description	100
4.26.2 Member Function Documentation	100
4.26.2.1 getConfFromString()	100
4.26.3 Member Data Documentation	101
4.26.3.1 PULL_DOWN	101
4.26.3.2 PULL_MAX_VALUE	101
4.26.3.3 PULL_NOT_AVAILABLE	101
4.26.3.4 PULL_UP	101
4.26.3.5 STR_NAME	101
4.27 configurator.Selected Enum Reference	102
4.27.1 Detailed Description	102
4.27.2 Member Function Documentation	102
4.27.2.1 getBoolean()	102
4.27.2.2 getConfFromBoolean()	102
4.27.2.3 getConfFromString()	103
4.27.3 Member Data Documentation	103
4.27.3.1 NOT	103
4.27.3.2 STR_NAME	103
4.27.3.3 YES	104
4.28 configurator.GPIO.Speed Enum Reference	104
4.28.1 Detailed Description	104
4.28.2 Member Function Documentation	104
4.28.2.1 getConfFromString()	104
4.28.3 Member Data Documentation	105
4.28.3.1 SPEED_FAST	105
4.28.3.2 SPEED_HIGH	105
4.28.3.3 SPEED_MAX_VALUE	105
4.28.3.4 SPEED_MEDIUM	105
4.28.3.5 SPEED_NOT_AVAILABLE	105
4.28.3.6 STR_NAME	106
4.29 xmlParser.XmlOpener Class Reference	106
4.29.1 Detailed Description	106
4.29.2 Constructor & Destructor Documentation	106
4.29.2.1 XmlOpener()	106
4.29.3 Member Function Documentation	107
4.29.3.1 getElementInfo()	107

4.29.3.2 getElementInfoFromDoc()	107
4.29.3.3 getParsedDoc()	107
4.29.3.4 OpenFile()	108

Index	109
--------------	------------

Chapter 1

Namespace Index

1.1 Packages

Here are the packages with brief descriptions (if available):

common	5
configurator	5
framework	6
gui	6
microcontroller	7
projectConfiguration	7
xmlCreator	8
xmlParser	8

Chapter 2

Class Index

2.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

gui>AboutWindow	9
microcontroller.Adc	10
configurator.ADC.AdcChannel	18
configurator.AdcConf	21
gui.AdcConfWindow	27
framework.AdcGenerator	28
configurator.GPIO.AltMode	30
framework.CodeGenerator	32
configurator.GPIO.CodeName	33
framework.Common	34
configurator.ConfigurationFile	40
xmlCreator.ConfXmlWriter	41
common.ErrorCode	43
common.Features	45
gui.GpioConfWindow	47
gui.MainGui	49
gui.MainWindow	52
gui.Messages	55
microcontroller.Microcontroller	56
configurator.GPIO.Mode	63
configurator.GPIO.OutLevel	66
configurator.GPIO.OutType	67
microcontroller.Pin	70
configurator.PinConf	88
projectConfiguration.ProjectSettings	97
configurator.GPIO.Pull	100
configurator.Selected	102
configurator.GPIO.Speed	104
xmlParser.XmlOpener	106

Chapter 3

Namespace Documentation

3.1 Package common

Classes

- enum [ErrorCode](#)
- class [Features](#)

3.1.1 Detailed Description

Common information that needs to be accessed across all the project

Author

Miguel Diaz

Version

0.1

3.2 Package configurator

Classes

- class [AdcConf](#)
- class [ConfigurationFile](#)
- class [PinConf](#)
- enum [Selected](#)

3.2.1 Detailed Description

Configuration classes

Author

Miguel Diaz

Version

0.1

3.3 Package framework

Classes

- class [AdcGenerator](#)
- class [CodeGenerator](#)
- class [Common](#)
- class [GpioGenerator](#)

3.3.1 Detailed Description

Framework information

Author

H112943

Version

0.1

3.4 Package gui

Classes

- class [AboutWindow](#)
- class [AdcConfWindow](#)
- class [GpioConfWindow](#)
- class [MainGui](#)
- class [MainWindow](#)
- class [Messages](#)

3.4.1 Detailed Description

Author

Miguel Diaz

Version

0.1

3.5 Package microcontroller

Classes

- class [Adc](#)
- class [Microcontroller](#)
- class [Pin](#)

3.5.1 Detailed Description

[Microcontroller](#) related classes

Author

Miguel Diaz

Version

0.1

3.6 Package projectConfiguration

Classes

- class [ProjectSettings](#)

3.6.1 Detailed Description

Project settings and configuration files

Author

Miguel Diaz

Version

0.1

3.7 Package xmlCreator

Classes

- class [ConfXmlWriter](#)

3.7.1 Detailed Description

Create configuration XML

Author

Miguel Diaz

Version

0.1

3.8 Package xmlParser

Classes

- class [XmlOpener](#)

3.8.1 Detailed Description

XML parser for microcontroller information and project settings

Author

Miguel Diaz

Version

0.1

Chapter 4

Class Documentation

4.1 gui.AboutWindow Class Reference

Public Member Functions

- [AboutWindow](#) ()

Static Public Member Functions

- static void [main](#) (String[] args)

4.1.1 Detailed Description

About Window, contains version and contact information

Author

ovd

4.1.2 Constructor & Destructor Documentation

4.1.2.1 AboutWindow()

```
gui.AboutWindow.AboutWindow ( )
```

Create the application.

4.1.3 Member Function Documentation

4.1.3.1 main()

```
static void gui.AboutWindow.main (
    String[] args ) [static]
```

About window main

Parameters

<i>args</i>	Init parameters
-------------	-----------------

The documentation for this class was generated from the following file:

- src/gui/AboutWindow.java

4.2 microcontroller.Adc Class Reference

Public Member Functions

- [Adc](#) ()
- void [setName](#) (String name)
- String [getName](#) ()
- void [addSample](#) (String sample)
- int [getSampleNum](#) ()
- String [getSample](#) (int index)
- void [addClock](#) (String clock)
- int [getClockNum](#) ()
- String [getClock](#) (int index)
- void [addJustification](#) (String justification)
- int [getJustificationNum](#) ()
- String [getJustification](#) (int index)
- void [addPrescaler](#) (String prescaler)
- int [getPrescalerNum](#) ()
- String [getPrescaler](#) (int index)
- void [addResolution](#) (String resolution)
- int [getResolutionNum](#) ()
- String [getResolution](#) (int index)
- void [addReference](#) (String reference)
- int [getReferenceNum](#) ()
- String [getReference](#) (int index)
- void [addChannel](#) ([AdcChannel](#) channel)
- int [getChannelNum](#) ()
- [AdcChannel](#) [getChannel](#) (int index)
- boolean [isValid](#) ()

4.2.1 Constructor & Destructor Documentation

4.2.1.1 Adc()

```
microcontroller.Adc.Adc ( )
```

ADC instance constructor

4.2.2 Member Function Documentation

4.2.2.1 addChannel()

```
void microcontroller.Adc.addChannel (
    AdcChannel channel )
```

Add ADC's channel

Parameters

<i>channel</i>	Channel
----------------	---------

4.2.2.2 addClock()

```
void microcontroller.Adc.addClock (
    String clock )
```

Add ADC supported clock source

Parameters

<i>clock</i>	Clock source
--------------	--------------

4.2.2.3 addJustification()

```
void microcontroller.Adc.addJustification (
```

```
String justification )
```

Add ADC's supported bits justification

Parameters

<i>justification</i>	Bits justification
----------------------	--------------------

4.2.2.4 addPrescaler()

```
void microcontroller.Adc.addPrescaler (
    String prescaler )
```

Add ADC's supported clock prescaler

Parameters

<i>prescaler</i>	Clock prescaler
------------------	-----------------

4.2.2.5 addReference()

```
void microcontroller.Adc.addReference (
    String reference )
```

Add ADC's supported voltage references

Parameters

<i>reference</i>	Voltage references
------------------	--------------------

4.2.2.6 addResolution()

```
void microcontroller.Adc.addResolution (
    String resolution )
```

Add ADC's supported bits resolution

Parameters

<i>resolution</i>	bits resolution
-------------------	-----------------

4.2.2.7 addSample()

```
void microcontroller.Adc.addSample (
    String sample )
```

Add ADC supported samples

Parameters

<i>sample</i>	Sample definition
---------------	-------------------

4.2.2.8 getChannel()

```
AdcChannel microcontroller.Adc.getChannel (
    int index )
```

Get ADC's channel

Parameters

<i>index</i>	Channel index
--------------	---------------

Returns

Channel

4.2.2.9 getChannelNum()

```
int microcontroller.Adc.getChannelNum ( )
```

Get ADC's number of channels

Returns

Number of channels

4.2.2.10 **getClock()**

```
String microcontroller.Adc.getClock (
    int index )
```

Get ADC's clock source

Parameters

<i>index</i>	Clock source index
--------------	--------------------

Returns

Clock source

4.2.2.11 **getClockNum()**

```
int microcontroller.Adc.getClockNum ( )
```

Get ADCs number of clock sources

Returns

Number of clock sources

4.2.2.12 **getJustification()**

```
String microcontroller.Adc.getJustification (
    int index )
```

Get ADC's bits justification

Parameters

<i>index</i>	bits justification index
--------------	--------------------------

Returns

Bits justification

4.2.2.13 getJustificationNum()

```
int microcontroller.Adc.getJustificationNum ( )
```

Get ADC's number of supported justifications

Returns

Number of supported justifications

4.2.2.14 getName()

```
String microcontroller.Adc.getName ( )
```

Get ADCs instance name

Returns

Instance name

4.2.2.15 getPrescaler()

```
String microcontroller.Adc.getPrescaler (
    int index )
```

Get ADC's clock prescaler

Parameters

<i>index</i>	Clock prescaler index
--------------	-----------------------

Returns

Clock prescaler

4.2.2.16 getPrescalerNum()

```
int microcontroller.Adc.getPrescalerNum ( )
```

Get ADC's number of supported prescalers

Returns

Number of supported prescalers

4.2.2.17 getReference()

```
String microcontroller.Adc.getReference (
    int index )
```

Get ADC's voltage references

Parameters

<i>index</i>	Voltage references index
--------------	--------------------------

Returns

Voltage references

4.2.2.18 getReferenceNum()

```
int microcontroller.Adc.getReferenceNum ( )
```

Get ADC's number of supported voltage references

Returns

Number of supported voltage references

4.2.2.19 getResolution()

```
String microcontroller.Adc.getResolution (
    int index )
```

Get ADC's bits resolution

Parameters

<i>index</i>	bits resolution index
--------------	-----------------------

Returns

bits resolution

4.2.2.20 getResolutionNum()

```
int microcontroller.Adc.getResolutionNum ( )
```

Get ADC's number of supported bits resolutions

Returns

Number of supported bits resolutions

4.2.2.21 getSample()

```
String microcontroller.Adc.getSample (
    int index )
```

Get ADC's Sample definition

Parameters

<i>index</i>	sample definition index
--------------	-------------------------

Returns

Sample definition

4.2.2.22 getSampleNum()

```
int microcontroller.Adc.getSampleNum ( )
```

Get ADCs number of samples definitions

Returns

Number of samples definitions

4.2.2.23 isValid()

```
boolean microcontroller.Adc.isValid ( )
```

Check validity of ADC

Returns

True if valid

4.2.2.24 setName()

```
void microcontroller.Adc.setName (
    String name )
```

Set ADCs instance name

Parameters

<i>name</i>	Instance name
-------------	---------------

The documentation for this class was generated from the following file:

- src/microcontroller/Adc.java

4.3 configurator.ADC.AdcChannel Class Reference

Public Member Functions

- **AdcChannel** (String name, int pinIndex)
- String [getName](#) ()
- String [getCodeName](#) ()
- void [setCodeName](#) (String codeName)
- boolean [isSelected](#) ()
- void [setSelected](#) (boolean selected)
- int [getPinIndex](#) ()
- boolean [isValid](#) ()

Static Public Attributes

- static final String **INVALID_NAME** = [ErrorCode.STR_INVALID](#)
- static final int **INVALID_INDEX** = [ErrorCode.INT_INVALID_INDEX](#)

4.3.1 Member Function Documentation

4.3.1.1 getCodeName()

```
String configurator.ADC.AdcChannel.getCodeName ( )
```

Get ADC channel's code name

Returns

ADC channel's code name

4.3.1.2 getName()

```
String configurator.ADC.AdcChannel.getName ( )
```

Get ADC channel's name

Returns

ADC channel's name

4.3.1.3 getPinIndex()

```
int configurator.ADC.AdcChannel.getPinIndex ( )
```

Get ADC channel's pin index

Returns

4.3.1.4 isSelected()

```
boolean configurator.ADC.AdcChannel.isSelected ( )
```

Get ADC channel's selection

Returns

ADC channel's selection

4.3.1.5 isValid()

```
boolean configurator.ADC.AdcChannel.isValid ( )
```

Check channel validity

Returns

True if valid

4.3.1.6 setCodeName()

```
void configurator.ADC.AdcChannel.setCodeName (
    String codeName )
```

Set ADC channel's code name

Parameters

<i>codeName</i>	ADC channel's code name
-----------------	-------------------------

4.3.1.7 setSelected()

```
void configurator.ADC.AdcChannel.setSelected (
    boolean selected )
```

Set ADC channel's selection

Parameters

<i>selected</i>	<input type="checkbox"/>
-----------------	--------------------------

The documentation for this class was generated from the following file:

- src/configurator/ADC/AdcChannel.java

4.4 configurator.AdcConf Class Reference

Public Member Functions

- [AdcConf](#) ([Adc](#) adc)
- [Selected](#) [getSelected](#) ()
- void [setSelected](#) ([Selected](#) selection)
- String [getCodeName](#) ()
- void [setCodeName](#) (String codeName)
- String [getSample](#) ()
- void [setSample](#) (String sample)
- String [getClock](#) ()
- void [setClock](#) (String clock)
- String [getJustification](#) ()
- void [setJustification](#) (String justification)
- String [getPrescaler](#) ()
- void [setPrescaler](#) (String prescaler)
- String [getResolution](#) ()
- void [setResolution](#) (String resolution)
- String [getReference](#) ()
- void [setReference](#) (String reference)
- void [setChannels](#) ([Adc](#) adc)

Public Attributes

- [Adc](#) [AdcFeatures](#)

Static Public Attributes

- static final [Selected](#) [DF_SELECTED](#) = [Selected](#).NOT
- static final String [STR_NAME](#) = "name"
- static final String [STR_CODE_NAME](#) = "codeName"
- static final String [STR_SAMPLE](#) = "sample"
- static final String [STR_CLOCK](#) = "clock"
- static final String [STR_JUSTIFICATION](#) = "justification"
- static final String [STR_PRESCALER](#) = "prescaler"
- static final String [STR_RESOLUTION](#) = "resolution"
- static final String [STR_REFERENCE](#) = "reference"

4.4.1 Constructor & Destructor Documentation

4.4.1.1 AdcConf()

```
configurator.AdcConf.AdcConf (
    Adc adc )
```

ADC configuration constructor

Parameters

<i>adc</i>	ADC instance
------------	--------------

4.4.2 Member Function Documentation

4.4.2.1 getClock()

```
String configurator.AdcConf.getClock ( )
```

Get ADC's configured clock

Returns

ADC's configured clock

4.4.2.2 getCodeName()

```
String configurator.AdcConf.getCodeName ( )
```

Get ADC's code name

Returns

ADC's code name

4.4.2.3 getJustification()

```
String configurator.AdcConf.getJustification ( )
```

Get ADC's configured justification

Returns

ADC's configured justification

4.4.2.4 getPrescaler()

```
String configurator.AdcConf.getPrescaler ( )
```

Get ADC's prescaler

Returns

ADC's prescaler

4.4.2.5 getReference()

```
String configurator.AdcConf.getReference ( )
```

Get ADC's configured reference

Returns

ADC's configured reference

4.4.2.6 getResolution()

```
String configurator.AdcConf.getResolution ( )
```

Get ADC's configured resolution

Returns

ADC's configured resolution

4.4.2.7 `getSample()`

```
String configurator.AdcConf.getSample ( )
```

Get ADC's configured samples

Returns

ADC's configured samples

4.4.2.8 `getSelected()`

```
Selected configurator.AdcConf.getSelected ( )
```

Get the ADC's selection

Returns

Selection

4.4.2.9 `setChannels()`

```
void configurator.AdcConf.setChannels (
    Adc adc )
```

Set ADC channels

Parameters

<i>adc</i>	ADC instance
------------	--------------

4.4.2.10 `setClock()`

```
void configurator.AdcConf.setClock (
    String clock )
```

Set ADC's configured clock

Parameters

<i>clock</i>	ADC's configured clock
--------------	------------------------

4.4.2.11 setCodeName()

```
void configurator.AdcConf.setCodeName (  
    String codeName )
```

Set Get ADC's code name

Parameters

<i>codeName</i>	ADC's code name
-----------------	-----------------

4.4.2.12 setJustification()

```
void configurator.AdcConf.setJustification (  
    String justification )
```

Set ADC's configured justification

Parameters

<i>justification</i>	ADC's configured justification
----------------------	--------------------------------

4.4.2.13 setPrescaler()

```
void configurator.AdcConf.setPrescaler (  
    String prescaler )
```

Set ADC's prescaler

Parameters

<i>prescaler</i>	ADC's prescaler
------------------	-----------------

4.4.2.14 setReference()

```
void configurator.AdcConf.setReference (
    String reference )
```

Set ADC's configured reference

Parameters

<i>reference</i>	ADC's configured reference
------------------	----------------------------

4.4.2.15 setResolution()

```
void configurator.AdcConf.setResolution (
    String resolution )
```

Set ADC's configured resolution

Parameters

<i>resolution</i>	ADC's configured resolution
-------------------	-----------------------------

4.4.2.16 setSample()

```
void configurator.AdcConf.setSample (
    String sample )
```

Get ADC's configured samples

Parameters

<i>sample</i>	ADC's configured samples
---------------	--------------------------

4.4.2.17 setSelected()

```
void configurator.AdcConf.setSelected (
```



```
Selected selection )
```

Set the ADC's selection

Parameters

<i>selection</i>	Selection
------------------	-----------

4.4.3 Member Data Documentation

4.4.3.1 DF_SELECTED

```
final Selected configurator.AdcConf.DF_SELECTED = Selected.NOT [static]
```

Default Pin's selection

The documentation for this class was generated from the following file:

- src/configurator/AdcConf.java

4.5 gui.AdcConfWindow Class Reference

Public Member Functions

- [AdcConfWindow](#) ([Microcontroller](#) uCtrl)

Static Public Member Functions

- static void [main](#) (String[] args)

4.5.1 Constructor & Destructor Documentation

4.5.1.1 AdcConfWindow()

```
gui.AdcConfWindow.AdcConfWindow (
    Microcontroller uCtrl )
```

Create the application.

Parameters

<i>uCtrl</i>	Microcontroller
--------------	-----------------

4.5.2 Member Function Documentation

4.5.2.1 main()

```
static void gui.AdcConfWindow.main (  
    String[] args ) [static]
```

Launch the application.

Parameters

<i>args</i>	General arguments
-------------	-------------------

The documentation for this class was generated from the following file:

- `src/gui/AdcConfWindow.java`

4.6 framework.AdcGenerator Class Reference

Static Public Member Functions

- static String **getCfgArray** ([Microcontroller](#) uC)
- static String **getElDefs** ([Microcontroller](#) uC)
- static String **getElements** ([Microcontroller](#) uC)
- static String **getIncludes** ([Microcontroller](#) uC)
- static String **getCfgDefinitions** ([Microcontroller](#) uC)

Static Public Attributes

- static final String **STR_TKN_CFG_ARRAY** = "FWK_ADC_CFG_ARRAY"
- static final String **STR_TKN_ELEMENTS** = "FWK_ADC_ELEMENTS"
- static final String **STR_TKN_INC** = "FWK_ADC_INCLUDES"
- static final String **STR_TKN_CFG_DEFS** = "FWK_ADC_CFG_DEFINITIONS"
- static final String **STR_TKN_EL_DEFS** = "FWK_ADC_ELEMENTS_DEFINITIONS"

4.6.1 Member Function Documentation

4.6.1.1 getElDefs()

```
static String framework.AdcGenerator.getElDefs (  
    Microcontroller uC ) [static]
```

Parameters

<i>uC</i>	Microcontroller used
-----------	----------------------

Returns

Elements definitions as String

4.6.1.2 getElements()

```
static String framework.AdcGenerator.getElements (  
    Microcontroller uC ) [static]
```

Parameters

<i>uC</i>	Microcontroller used
-----------	----------------------

Returns

Elements list as String

4.6.1.3 getIncludes()

```
static String framework.AdcGenerator.getIncludes (  
    Microcontroller uC ) [static]
```

Parameters

<i>uC</i>	Microcontroller used
-----------	----------------------

Returns

Headers needed for GPIO module

The documentation for this class was generated from the following file:

- `src/framework/AdcGenerator.java`

4.7 configurator.GPIO.AltMode Enum Reference

Static Public Member Functions

- static [AltMode](#) `getConfigFromString` (String conf)

Public Attributes

- [ALT_MODE_ANALOG](#)
- [ALT_MODE_UART](#)
- [ALT_MODE_I2C](#)
- [ALT_MODE_SPI](#)
- [ALT_MODE_NONE](#)
- [ALT_MODE_MAX_VALUE](#)

Static Public Attributes

- static final String [STR_NAME](#) = "AltMode"

4.7.1 Detailed Description

GPIO modes

Author

Miguel Diaz

Version

0.1

4.7.2 Member Function Documentation

4.7.2.1 `getConfigFromString()`

```
static AltMode configurator.GPIO.AltMode.getConfigFromString (  
    String conf ) [static]
```

Get the corresponding mode from its name as String

Parameters

<i>conf</i>	Configuration name
-------------	--------------------

Returns

[Mode](#)

4.7.3 Member Data Documentation

4.7.3.1 ALT_MODE_ANALOG

```
configurator.GPIO.AltMode.ALT_MODE_ANALOG
```

Analog

4.7.3.2 ALT_MODE_I2C

```
configurator.GPIO.AltMode.ALT_MODE_I2C
```

I2C

4.7.3.3 ALT_MODE_MAX_VALUE

```
configurator.GPIO.AltMode.ALT_MODE_MAX_VALUE
```

Maximum value for [Mode](#) enum

4.7.3.4 ALT_MODE_NONE

```
configurator.GPIO.AltMode.ALT_MODE_NONE
```

No alternate mode

4.7.3.5 ALT_MODE_SPI

```
configurator.GPIO.AltMode.ALT_MODE_SPI
```

SPI

4.7.3.6 ALT_MODE_UART

```
configurator.GPIO.AltMode.ALT_MODE_UART
```

UART

4.7.3.7 STR_NAME

```
final String configurator.GPIO.AltMode.STR_NAME = "AltMode" [static]
```

Name as String

The documentation for this enum was generated from the following file:

- `src/configurator/GPIO/AltMode.java`

4.8 framework.CodeGenerator Class Reference

Public Member Functions

- [CodeGenerator](#) ([Microcontroller](#) uC, [ProjectSettings](#) projectSettings)
- [ErrorCode Generate](#) ()

Static Public Attributes

- static final String **STR_TKN_CFG_DEFS_COMMON** = "FWK_GPIO_COMMON_DEFINITIONS"
- static final String **STR_TKN_CFG_DEFS_GPIO** = "FWK_GPIO_CFG_DEFINITIONS"

4.8.1 Detailed Description

Author

ovd

4.8.2 Constructor & Destructor Documentation

4.8.2.1 CodeGenerator()

```
framework.CodeGenerator.CodeGenerator (
    Microcontroller uC,
    ProjectSettings projectSettings )
```

Constructor

Parameters

<i>uC</i>	Project's microcontroller
<i>projectSettings</i>	Project's settings

4.8.3 Member Function Documentation

4.8.3.1 Generate()

```
ErrorCode framework.CodeGenerator.Generate ( )
```

Generate project's configuration files

Returns

Error code

The documentation for this class was generated from the following file:

- src/framework/CodeGenerator.java

4.9 configurator.GPIO.CodeName Enum Reference

Public Attributes

- [CODE_NAME](#)

Static Public Attributes

- static final String [STR_NAME](#) = "codeName"

4.9.1 Detailed Description

Author

Miguel Diaz

Version

0.1

4.9.2 Member Data Documentation

4.9.2.1 CODE_NAME

```
configurator.GPIO.CodeName.CODE_NAME
```

Code name for pin

4.9.2.2 STR_NAME

```
final String configurator.GPIO.CodeName.STR_NAME = "codeName" [static]
```

Name as String

The documentation for this enum was generated from the following file:

- `src/configurator/GPIO/CodeName.java`

4.10 framework.Common Class Reference

Static Public Member Functions

- static String [getInstallationFwkPath](#) ()
- static void [setInstallationFwkPath](#) (String installationFwkPath)
- static String [getProjectFwkPath](#) ()
- static void [setProjectFwkPath](#) (String projectFwkPath)
- static String [getCfgPath](#) (String fwkPath, String cfgModule)
- static String [getCfgFileCPath](#) (String fwkPath, String cfgModule)
- static String [getCfgFileHPath](#) (String fwkPath, String cfgModule)
- static String [getFrameworkCommonFilePath](#) (String fwkPath)
- static String [getFrameworkIncludesFilePath](#) (String fwkPath)
- static String [getCommonIncludes](#) ([Microcontroller](#) uC)
- static String [getCommonCfgDefinitions](#) ([Microcontroller](#) uC)

Static Public Attributes

- static final String [NL](#) = "\r\n"
- static final String [STR_GEN_CODE_NOTICE_HEADER](#)
- static final String [STR_GEN_CODE_NOTICE_FOOTER](#)
- static final String [STR_MODULE_GPIO](#) = "gpio"
- static final String [STR_MODULE_ADC](#) = "adc"
- static final String [STR_DEFINITION](#) = "#define "
- static final String [STR_INCLUDE](#) = "#include "
- static final String [STR_HEADER_EXT](#) = ".h"

4.10.1 Detailed Description

Framework common fields and methods

Author

Miguel Diaz

Version

0.1

4.10.2 Member Function Documentation

4.10.2.1 getCfgFileCPath()

```
static String framework.Common.getCfgFileCPath (  
    String fwkPath,  
    String cfgModule ) [static]
```

Get GPIO configuration file path

Parameters

<i>fwkPath</i>	Framework folder path
<i>cfgModule</i>	Configuration module name

Returns

GPIO configuration file path

4.10.2.2 getCfgFileHPath()

```
static String framework.Common.getCfgFileHPath (  
    String fwkPath,  
    String cfgModule ) [static]
```

Get GPIO configuration header file path

Parameters

<i>fwkPath</i>	Framework folder path
<i>cfgModule</i>	Configuration module name

Returns

GPIO configuration header file path

4.10.2.3 getCfgPath()

```
static String framework.Common.getCfgPath (  
    String fwkPath,  
    String cfgModule ) [static]
```

Get configuration module files folder path

Parameters

<i>fwkPath</i>	Framework folder path
<i>cfgModule</i>	Configuration module name

Returns

Configuration files folder path

4.10.2.4 getCommonCfgDefinitions()

```
static String framework.Common.getCommonCfgDefinitions (  
    Microcontroller uC ) [static]
```

Get Framework [Common](#) definitions

Parameters

<i>uC</i>	Microcontroller used
-----------	----------------------

Returns

[Common](#) definitions needed for framework

4.10.2.5 `getCommonIncludes()`

```
static String framework.Common.getCommonIncludes (
    Microcontroller uC ) [static]
```

Get Framework common headers

Parameters

<i>uC</i>	Microcontroller used
-----------	----------------------

Returns

Common headers needed for framework

4.10.2.6 `getFrameworkCommonFilePath()`

```
static String framework.Common.getFrameworkCommonFilePath (
    String fwkPath ) [static]
```

Get the framework common header path

Parameters

<i>fwkPath</i>	Framework folder path
----------------	-----------------------

Returns

Framework common header path

4.10.2.7 `getFrameworkIncludesFilePath()`

```
static String framework.Common.getFrameworkIncludesFilePath (
    String fwkPath ) [static]
```

Get the framework includes header path

Parameters

<i>fwkPath</i>	Framework folder path
----------------	-----------------------

Returns

Framework includes header path

4.10.2.8 getInstallationFwkPath()

```
static String framework.Common.getInstallationFwkPath ( ) [static]
```

Get installation framework path

Returns

installation framework path

4.10.2.9 getProjectFwkPath()

```
static String framework.Common.getProjectFwkPath ( ) [static]
```

Get project's framework path

Returns

project's framework path

4.10.2.10 setInstallationFwkPath()

```
static void framework.Common.setInstallationFwkPath (
    String installationFwkPath ) [static]
```

Set installation framework path

Parameters

<i>installationFwkPath</i>	installation framework path
----------------------------	-----------------------------

4.10.2.11 setProjectFwkPath()

```
static void framework.Common.setProjectFwkPath (
    String projectFwkPath ) [static]
```

Set project's framework path

Parameters

<i>projectFwkPath</i>	project's framework path
-----------------------	--------------------------

4.10.3 Member Data Documentation

4.10.3.1 NL

```
final String framework.Common.NL = "\r\n" [static]
```

[Common](#) implementation of New Line

4.10.3.2 STR_DEFINITION

```
final String framework.Common.STR_DEFINITION = "#define " [static]
```

Macro definition String

4.10.3.3 STR_GEN_CODE_NOTICE_FOOTER

```
final String framework.Common.STR_GEN_CODE_NOTICE_FOOTER [static]
```

Initial value:

```
= "// ##### " + Features.GENERATOR_NAME
    + " generator v" + common.Features.SW\_VERSION + ": Generated code! #####" + NL
    + "// ##### Do NOT modify code between this footer and the header above #####"
```

Footer for indicating generated code

4.10.3.4 STR_GEN_CODE_NOTICE_HEADER

```
final String framework.Common.STR_GEN_CODE_NOTICE_HEADER [static]
```

Initial value:

```
= "// ##### " + Features.GENERATOR_NAME  
  + " generator v" + common.Features.SW_VERSION + ": Generated code! #####" + NL  
  + "// ##### Do NOT modify code between this header and the footer below #####"
```

Header for indicating generated code

4.10.3.5 STR_HEADER_EXT

```
final String framework.Common.STR_HEADER_EXT = ".h" [static]
```

Header file extension

4.10.3.6 STR_INCLUDE

```
final String framework.Common.STR_INCLUDE = "#include " [static]
```

Include header file string

4.10.3.7 STR_MODULE_ADC

```
final String framework.Common.STR_MODULE_ADC = "adc" [static]
```

GPIO module name

4.10.3.8 STR_MODULE_GPIO

```
final String framework.Common.STR_MODULE_GPIO = "gpio" [static]
```

GPIO module name

The documentation for this class was generated from the following file:

- src/framework/Common.java

4.11 configurator.ConfigurationFile Class Reference

Static Public Attributes

- static final String STR_PROJ_CONF_FILE = "cgs"

4.11.1 Detailed Description

Configuration files properties

Author

Miguel Diaz

Version

0.1

4.11.2 Member Data Documentation

4.11.2.1 STR_PROJ_CONF_FILE

```
final String configurator.ConfigurationFile.STR_PROJ_CONF_FILE = "cgs" [static]
```

Public configuration file extension

The documentation for this class was generated from the following file:

- src/configurator/ConfigurationFile.java

4.12 xmlCreator.ConfXmlWriter Class Reference

Public Member Functions

- [ConfXmlWriter](#) ([Microcontroller](#) uC)
- void [addPin](#) ([PinConf](#) pin, int pinNum)
- [ErrorCode](#) [writeXml](#) (String fileName)

4.12.1 Detailed Description

Write a XML file

Author

Miguel Diaz

Version

0.1

4.12.2 Constructor & Destructor Documentation

4.12.2.1 ConfXmlWriter()

```
xmlCreator.ConfXmlWriter.ConfXmlWriter (
    Microcontroller uC )
```

Constructor

Parameters

<i>uC</i>	Microcontroller configuration
-----------	-------------------------------

4.12.3 Member Function Documentation

4.12.3.1 addPin()

```
void xmlCreator.ConfXmlWriter.addPin (
    PinConf pin,
    int pinNum )
```

Add a pin configuration to the file

Parameters

<i>pin</i>	Pin configuration
<i>pinNum</i>	Number of GPIO pin

4.12.3.2 writeXml()

```
ErrorCode xmlCreator.ConfXmlWriter.writeXml (
    String fileName )
```

Write the XML file

Parameters

<i>fileName</i>	Name of XML configuration file
-----------------	--------------------------------

Returns

Error status

The documentation for this class was generated from the following file:

- src/xmlCreator/ConfXmlWriter.java

4.13 common.ErrorCode Enum Reference

Public Attributes

- [NO_ERROR](#)
- [EX_ERROR](#)
- [FILE_READ_ERROR](#)
- [FILE_WRITE_ERROR](#)
- [FILE_CONF_ERROR](#)

Static Public Attributes

- static final String [STR_INVALID](#) = "STR_INVALID"
- static final int [INT_INVALID_INDEX](#) = -1

4.13.1 Detailed Description

Error codes enum

Author

Miguel Diaz

Version

0.1

4.13.2 Member Data Documentation

4.13.2.1 EX_ERROR

```
common.ErrorCode.EX_ERROR
```

Error during execution

4.13.2.2 FILE_CONF_ERROR

```
common.ErrorCode.FILE_CONF_ERROR
```

File configuration error

4.13.2.3 FILE_READ_ERROR

```
common.ErrorCode.FILE_READ_ERROR
```

File reading error

4.13.2.4 FILE_WRITE_ERROR

```
common.ErrorCode.FILE_WRITE_ERROR
```

File writing error

4.13.2.5 INT_INVALID_INDEX

```
final int common.ErrorCode.INT_INVALID_INDEX = -1 [static]
```

Invalid index

4.13.2.6 NO_ERROR

```
common.ErrorCode.NO_ERROR
```

No error message

4.13.2.7 STR_INVALID

```
final String common.ErrorCode.STR_INVALID = "STR_INVALID" [static]
```

Error string

The documentation for this enum was generated from the following file:

- `src/common/ErrorCode.java`

4.14 common.Features Class Reference

Static Public Member Functions

- static void `verbosePrint` (String verboseMessage)
- static void `debugPrint` (String debugMessage)
- static void `initLog` ()

Static Public Attributes

- static final boolean `DEBUG` = true
- static final boolean `VERBOSE` = true
- static boolean `LOG_FILE` = true
- static final String `VERBOSE_STR` = "# "
- static final String `DEBUG_STR` = "#\$ "
- static final String `SW_VERSION` = VERSION_MAJOR + "." + VERSION_MINOR + "." + VERSION_PATCH
- static final String `VERSION_STATUS` = "Alpha"
- static final String `VERSION_NAME` = "Dagobah"
- static final String `GENERATOR_NAME` = "Kamino"

4.14.1 Detailed Description

Class that includes all project features

Author

Miguel Diaz

Version

0.1

4.14.2 Member Function Documentation

4.14.2.1 `debugPrint()`

```
static void common.Features.debugPrint (  
    String debugMessage ) [static]
```

Print Debug message to console

Parameters

<i>debugMessage</i>	Message to display
---------------------	--------------------

4.14.2.2 verbosePrint()

```
static void common.Features.verbosePrint (
    String verboseMessage ) [static]
```

Print Verbose message to console

Parameters

<i>verboseMessage</i>	Message to display
-----------------------	--------------------

4.14.3 Member Data Documentation**4.14.3.1 DEBUG**

```
final boolean common.Features.DEBUG = true [static]
```

Enables debug functions

4.14.3.2 DEBUG_STR

```
final String common.Features.DEBUG_STR = "#$ " [static]
```

Debug messages indicator on system console

4.14.3.3 SW_VERSION

```
final String common.Features.SW_VERSION = VERSION_MAJOR + "." + VERSION_MINOR + "." + VERSION_PATCH  
TCH [static]
```

Complete Software version

4.14.3.4 VERBOSE

```
final boolean common.Features.VERBOSE = true [static]
```

Enables console messages

4.14.3.5 VERBOSE_STR

```
final String common.Features.VERBOSE_STR = "# " [static]
```

Verbose messages indicator on system console

4.14.3.6 VERSION_NAME

```
final String common.Features.VERSION_NAME = "Dagobah" [static]
```

Code name of the software version

4.14.3.7 VERSION_STATUS

```
final String common.Features.VERSION_STATUS = "Alpha" [static]
```

Status of the software version

The documentation for this class was generated from the following file:

- `src/common/Features.java`

4.15 gui.GpioConfWindow Class Reference

Public Member Functions

- [GpioConfWindow](#) ([Microcontroller](#) uCtrl)

Static Public Member Functions

- static void [main](#) (String[] args)

4.15.1 Detailed Description

Window for configuring GPIO pins

Author

Miguel Diaz

Version

0.1

4.15.2 Constructor & Destructor Documentation

4.15.2.1 GpioConfWindow()

```
gui.GpioConfWindow.GpioConfWindow (
    Microcontroller uCtrl )
```

Create the GPIO configuration window and show it

Parameters

<i>uCtrl</i>	Microcontroller object containing all pin's information
--------------	---

4.15.3 Member Function Documentation

4.15.3.1 main()

```
static void gui.GpioConfWindow.main (
    String[] args ) [static]
```

Gpio configuration window main

Parameters

<i>args</i>	Init parameters
-------------	-----------------

The documentation for this class was generated from the following file:

- src/gui/GpioConfWindow.java

4.16 gui.MainGui Class Reference

Static Public Member Functions

- static void [main](#) (String[] args)
- static [ErrorCode](#) [loadProjectFile](#) (File inFile)
- static void [showErrorDialog](#) (String message)
- static void [showAboutWindow](#) ()
- static void [showGpioConfWindow](#) ()
- static void [showAdcConfWindow](#) ()
- static void [setNewUC](#) ([Microcontroller](#) uC)
- static void [saveUc](#) ()
- static [ErrorCode](#) [generateCode](#) ()

Static Public Attributes

- static File [ProjectFile](#)
- static String [ProjectPath](#)

4.16.1 Detailed Description

Main GUI state machine

Author

Miguel Diaz

Version

0.1

4.16.2 Member Function Documentation

4.16.2.1 generateCode()

```
static ErrorCode gui.MainGui.generateCode ( ) [static]
```

Generate source code files

Returns

Error code

4.16.2.2 loadProjectFile()

```
static ErrorCode gui.MainGui.loadProjectFile (
    File inFile ) [static]
```

Load the project settings file

Parameters

<i>inFile</i>	Settings file
---------------	---------------

Returns

Error status

4.16.2.3 main()

```
static void gui.MainGui.main (
    String[] args ) [static]
```

Parameters

<i>args</i>	TBD
-------------	-----

4.16.2.4 saveUc()

```
static void gui.MainGui.saveUc ( ) [static]
```

Save the microcontroller's configuration to disk

4.16.2.5 setNewUC()

```
static void gui.MainGui.setNewUC (
    Microcontroller uC ) [static]
```

Set the project's microcontroller configuration

Parameters

<i>uC</i>	Microcontroller configuration
-----------	-------------------------------

4.16.2.6 showAboutWindow()

```
static void gui.MainGui.showAboutWindow ( ) [static]
```

Show about information window

4.16.2.7 showAdcConfWindow()

```
static void gui.MainGui.showAdcConfWindow ( ) [static]
```

Show the ADCs configuration window

4.16.2.8 showErrorDialog()

```
static void gui.MainGui.showErrorDialog (
    String message ) [static]
```

Show an error dialog

Parameters

<i>message</i>	Message to display
----------------	--------------------

4.16.2.9 showGpioConfWindow()

```
static void gui.MainGui.showGpioConfWindow ( ) [static]
```

Show the GPIOs configuration window

4.16.3 Member Data Documentation

4.16.3.1 ProjectFile

```
File gui.MainGui.ProjectFile [static]
```

Project configuration file

4.16.3.2 ProjectPath

```
String gui.MainGui.ProjectPath [static]
```

Project's location

The documentation for this class was generated from the following file:

- `src/gui/MainGui.java`

4.17 gui.MainWindow Class Reference

Public Member Functions

- [MainWindow](#) ()
- void [setVisible](#) (boolean status)
- File [OpenFileChooser](#) (String initialPath, String title, FileNameExtensionFilter fileFilter)
- [ErrorCode](#) [setProjectInformation](#) (String projectName, String ucManufacturer, String ucName)

Static Public Member Functions

- static void [main](#) (String[] args)

Public Attributes

- JFrame [FrmCodeGenerator](#)

4.17.1 Detailed Description

Main application window

Author

Miguel Diaz

Version

0.1

4.17.2 Constructor & Destructor Documentation

4.17.2.1 MainWindow()

```
gui.MainWindow.MainWindow ( )
```

Create the application.

4.17.3 Member Function Documentation

4.17.3.1 main()

```
static void gui.MainWindow.main (
    String[] args ) [static]
```

Open main window

Parameters

<i>args</i>	To be determined
-------------	------------------

4.17.3.2 OpenFileChooser()

```
File gui.MainWindow.OpenFileChooser (
    String initialPath,
```

```
String title,  
FileNameExtensionFilter fileFilter )
```

Open file chooser dialog and get the selected file

Parameters

<i>initialPath</i>	Path to search the file in
<i>title</i>	Dialog title
<i>fileFilter</i>	Extension filter

Returns

Selected file

4.17.3.3 setProjectInformation()

```
ErrorCode gui.MainWindow.setProjectInformation (  
    String projectName,  
    String ucManufacturer,  
    String ucName )
```

Set Project's name in its label

Parameters

<i>projectName</i>	Project's name
<i>ucManufacturer</i>	Microcontroller's manufacturer
<i>ucName</i>	Microcontroller's model

Returns

Error status

4.17.3.4 setVisible()

```
void gui.MainWindow.setVisible (  
    boolean status )
```

Set visibility of About window

Parameters

<i>status</i>	true if visible
---------------	-----------------

4.17.4 Member Data Documentation

4.17.4.1 FrmCodeGenerator

```
JFrame gui.MainWindow.FrmCodeGenerator
```

Frame for the main Window

The documentation for this class was generated from the following file:

- src/gui/MainWindow.java

4.18 gui.Messages Class Reference

Static Public Member Functions

- static String [getString](#) (String key)

4.18.1 Detailed Description

[Messages](#) window

Author

ovd

4.18.2 Member Function Documentation

4.18.2.1 getString()

```
static String gui.Messages.getString (  
    String key ) [static]
```

Get String

Parameters

<i>key</i>	Key
------------	-----

Returns

String

The documentation for this class was generated from the following file:

- src/gui/Messages.java

4.19 microcontroller.Microcontroller Class Reference

Public Member Functions

- [Microcontroller](#) (Document ucDoc)
- [ErrorCode processDocument](#) ()
- [ErrorCode loadPinsConf](#) (Document confDoc)
- [ErrorCode loadAdcsConf](#) (Document confDoc)
- [Pin getPin](#) (int pinNum)
- String [getUc_model](#) ()
- String [getUc_manufacturer](#) ()
- int [getUc_pinNum](#) ()
- int [getUc_gpioNum](#) ()
- int [getUc_portNum](#) ()
- int [getUc_adcNum](#) ()
- int [getUc_selectedPinsNum](#) ()
- int [getUc_selectedAdcsNum](#) ()
- [PinConf getConfiguredPin](#) (String gpioName)
- boolean [isValid](#) ()

Public Attributes

- String[] [Ports](#)
- String[] [Includes_Common](#)
- String[] [Includes_Gpio](#)
- String[] [Includes_Adc](#)
- String[] [Definitions_Common](#)
- String[] [Definitions_Gpio](#)
- String[] [Definitions_Adc](#)
- [PinConf\[\] GpioCfgPin](#)
- String[] [Adcs](#)
- [AdcConf\[\] AdcCfg](#)

Static Public Attributes

- static final int `MAX_NUMBER_OF_PINS_PER_PORT` = 32
- static final int `MAX_NUMBER_OF_ADCS` = 16

4.19.1 Detailed Description

[Microcontroller](#) related methods

Author

Miguel Diaz

Version

0.1

4.19.2 Constructor & Destructor Documentation

4.19.2.1 Microcontroller()

```
microcontroller.Microcontroller.Microcontroller (  
    Document ucDoc )
```

Constructor

Parameters

<code><i>ucDoc</i></code>	Document obtained from XML file
---------------------------	---------------------------------

4.19.3 Member Function Documentation

4.19.3.1 getConfiguredPin()

```
PinConf microcontroller.Microcontroller.getConfiguredPin (  
    String gpioName )
```

Get the configuration of a pin

Parameters

<i>gpioName</i>	Name of the pin
-----------------	-----------------

Returns

[Pin](#) configuration

4.19.3.2 getPin()

```
Pin microcontroller.Microcontroller.getPin (
    int pinNum )
```

Get a pin's characteristics

Parameters

<i>pinNum</i>	Number of pin
---------------	---------------

Returns

[Pin's](#) characteristics

4.19.3.3 getUc_adcNum()

```
int microcontroller.Microcontroller.getUc_adcNum ( )
```

Get the number of ADCs in the microcontroller

Returns

Number of ADCs

4.19.3.4 getUc_gpioNum()

```
int microcontroller.Microcontroller.getUc_gpioNum ( )
```

Get the number of GPIOs in the microcontroller

Returns

Number of GPIOs

4.19.3.5 getUc_manufacturer()

```
String microcontroller.Microcontroller.getUc_manufacturer ( )
```

Get the microcontroller's manufacturer

Returns

[Microcontroller](#)'s manufacturer

4.19.3.6 getUc_model()

```
String microcontroller.Microcontroller.getUc_model ( )
```

Get the microcontroller's model

Returns

[Microcontroller](#)'s model

4.19.3.7 getUc_pinNum()

```
int microcontroller.Microcontroller.getUc_pinNum ( )
```

Get the microcontroller's pins number

Returns

Number of pins

4.19.3.8 getUc_portNum()

```
int microcontroller.Microcontroller.getUc_portNum ( )
```

Get the number of ports in the microcontroller

Returns

Number of ports

4.19.3.9 `getUc_selectedAdcsNum()`

```
int microcontroller.Microcontroller.getUc_selectedAdcsNum ( )
```

Get the total ADCs selected

Returns

Total of ADCs selected

4.19.3.10 `getUc_selectedPinsNum()`

```
int microcontroller.Microcontroller.getUc_selectedPinsNum ( )
```

Get the total pins selected

Returns

Total of pins selected

4.19.3.11 `isValid()`

```
boolean microcontroller.Microcontroller.isValid ( )
```

Check if the microcontroller configuration is valid

Returns

true if valid

4.19.3.12 `loadPinsConf()`

```
ErrorCode microcontroller.Microcontroller.loadPinsConf (
    Document confDoc )
```

Load pins' configuration

Parameters

<i>confDoc</i>	Document with pins
----------------	--------------------

Returns

Error Code

4.19.3.13 processDocument()

```
ErrorCode microcontroller.Microcontroller.processDocument ( )
```

Process the document obtained from XML file

Returns

Error status

4.19.4 Member Data Documentation**4.19.4.1 AdcCfg**

```
AdcConf [ ] microcontroller.Microcontroller.AdcCfg
```

Configured ADCs list

4.19.4.2 Adcs

```
String [ ] microcontroller.Microcontroller.Adcs
```

List of ADCs

4.19.4.3 Definitions_Adc

```
String [ ] microcontroller.Microcontroller.Definitions_Adc
```

List of definitions for ADC module

4.19.4.4 Definitions_Common

```
String [] microcontroller.Microcontroller.Definitions_Common
```

List of common definitions that will be available for all framework

4.19.4.5 Definitions_Gpio

```
String [] microcontroller.Microcontroller.Definitions_Gpio
```

List of definitions for GPIO module

4.19.4.6 GpioCfgPin

```
PinConf [] microcontroller.Microcontroller.GpioCfgPin
```

Configured pins list

4.19.4.7 Includes_Adc

```
String [] microcontroller.Microcontroller.Includes_Adc
```

List of Includes for ADC module

4.19.4.8 Includes_Common

```
String [] microcontroller.Microcontroller.Includes_Common
```

List of common includes that will be available for all framework

4.19.4.9 Includes_Gpio

```
String [] microcontroller.Microcontroller.Includes_Gpio
```

List of Includes for GPIO module

4.19.4.10 MAX_NUMBER_OF_ADCS

```
final int microcontroller.Microcontroller.MAX_NUMBER_OF_ADCS = 16 [static]
```

Maximum number of ADCs allowed

4.19.4.11 MAX_NUMBER_OF_PINS_PER_PORT

```
final int microcontroller.Microcontroller.MAX_NUMBER_OF_PINS_PER_PORT = 32 [static]
```

Maximum number of pins allowed in a single port

4.19.4.12 Ports

```
String [] microcontroller.Microcontroller.Ports
```

Ports name list

The documentation for this class was generated from the following file:

- src/microcontroller/Microcontroller.java

4.20 configurator.GPIO.Mode Enum Reference

Static Public Member Functions

- static [Mode](#) [getConfFromString](#) (String conf)

Public Attributes

- [MODE_INPUT](#)
- [MODE_OUTPUT](#)
- [MODE_ALTERNATE_FUNCTION](#)
- [MODE_MAX_VALUE](#)

Static Public Attributes

- static final String [STR_NAME](#) = "Mode"

4.20.1 Detailed Description

GPIO modes

Author

Miguel Diaz

Version

0.1

4.20.2 Member Function Documentation

4.20.2.1 getConfFromString()

```
static Mode configurator.GPIO.Mode.getConfFromString (
    String conf ) [static]
```

Get the corresponding mode from its name as String

Parameters

<i>conf</i>	Configuration name
-------------	--------------------

Returns

[Mode](#)

4.20.3 Member Data Documentation

4.20.3.1 MODE_ALTERNATE_FUNCTION

```
configurator.GPIO.Mode.MODE_ALTERNATE_FUNCTION
```

Alternate function

4.20.3.2 MODE_INPUT

```
configurator.GPIO.Mode.MODE_INPUT
```

Input

4.20.3.3 MODE_MAX_VALUE

```
configurator.GPIO.Mode.MODE_MAX_VALUE
```

Maximum value for [Mode](#) enum

4.20.3.4 MODE_OUTPUT

```
configurator.GPIO.Mode.MODE_OUTPUT
```

Output

4.20.3.5 STR_NAME

```
final String configurator.GPIO.Mode.STR_NAME = "Mode" [static]
```

Name as String

The documentation for this enum was generated from the following file:

- src/configurator/GPIO/Mode.java

4.21 configurator.GPIO.OutLevel Enum Reference

Static Public Member Functions

- static [OutLevel](#) `getConfigFromString` (String *conf*)

Public Attributes

- [LOW](#)
- [HIGH](#)
- [MAX_VALUE](#)

Static Public Attributes

- static final String [STR_NAME](#) = "OutLevel"

4.21.1 Detailed Description

Pin's output/input level

Author

Miguel Diaz

Version

0.1

4.21.2 Member Function Documentation

4.21.2.1 `getConfigFromString()`

```
static OutLevel configurator.GPIO.OutLevel.getConfigFromString (  
    String conf ) [static]
```

Get the corresponding mode from its name as String

Parameters

<i>conf</i>	Configuration name
-------------	--------------------

Returns

level

4.21.3 Member Data Documentation

4.21.3.1 HIGH

```
configurator.GPIO.OutLevel.HIGH
```

High, logical 1, Vcc

4.21.3.2 LOW

```
configurator.GPIO.OutLevel.LOW
```

Low, logical 0, Ground

4.21.3.3 MAX_VALUE

```
configurator.GPIO.OutLevel.MAX_VALUE
```

Maximum value for [OutLevel](#) enum

4.21.3.4 STR_NAME

```
final String configurator.GPIO.OutLevel.STR_NAME = "OutLevel" [static]
```

Name as String

The documentation for this enum was generated from the following file:

- `src/configurator/GPIO/OutLevel.java`

4.22 configurator.GPIO.OutType Enum Reference

Static Public Member Functions

- static [OutType](#) `getConfFromString` (String conf)

Public Attributes

- [OTYPE_PUSH_PULL](#)
- [OTYPE_OPEN_DRAIN](#)
- [OTYPE_NOT_AVAILABLE](#)
- [OTYPE_MAX_VALUE](#)

Static Public Attributes

- static final String [STR_NAME](#) = "OutType"

4.22.1 Detailed Description

Pin's output type

Author

Miguel Diaz

Version

0.1

4.22.2 Member Function Documentation

4.22.2.1 `getConfFromString()`

```
static OutType configurator.GPIO.OutType.getConfFromString (  
    String conf ) [static]
```

Get the corresponding output type from its name as String

Parameters

<i>conf</i>	Configuration name
-------------	--------------------

Returns

Output type

4.22.3 Member Data Documentation

4.22.3.1 OTYPE_MAX_VALUE

```
configurator.GPIO.OutType.OTYPE_MAX_VALUE
```

Maximum value for [OutType](#) enum

4.22.3.2 OTYPE_NOT_AVAILABLE

```
configurator.GPIO.OutType.OTYPE_NOT_AVAILABLE
```

If the pin is configured as input

4.22.3.3 OTYPE_OPEN_DRAIN

```
configurator.GPIO.OutType.OTYPE_OPEN_DRAIN
```

Open Drain

4.22.3.4 OTYPE_PUSH_PULL

```
configurator.GPIO.OutType.OTYPE_PUSH_PULL
```

Push [Pull](#), totem

4.22.3.5 STR_NAME

```
final String configurator.GPIO.OutType.STR_NAME = "OutType" [static]
```

Name as String

The documentation for this enum was generated from the following file:

- src/configurator/GPIO/OutType.java

4.23 microcontroller.Pin Class Reference

Public Member Functions

- [Pin](#) ()
- void [setFunc_vcc](#) (boolean funcState)
- boolean [getFunc_vcc](#) ()
- void [setFunc_gnd](#) (boolean funcState)
- boolean [getFunc_gnd](#) ()
- void [setFunc_gpio](#) (boolean funcState)
- boolean [getFunc_gpio](#) ()
- void [setFunc_reset](#) (boolean funcState)
- boolean [getFunc_reset](#) ()
- void [setFunc_misc](#) (boolean funcState)
- boolean [getFunc_misc](#) ()
- void [setFeat_int](#) (boolean featState)
- boolean [getFeat_int](#) ()
- void [setFeat_adc](#) (boolean featState)
- boolean [getFeat_adc](#) ()
- void [setFeat_uart](#) (boolean featState)
- boolean [getFeat_uart](#) ()
- void [setFeat_i2c](#) (boolean featState)
- boolean [getFeat_i2c](#) ()
- void [setFeat_spi](#) (boolean featState)
- boolean [getFeat_spi](#) ()
- void [setFeat_clock](#) (boolean featState)
- boolean [getFeat_clock](#) ()
- void [setFeat_timer](#) (boolean featState)
- boolean [getFeat_timer](#) ()
- void [setFeat_reset](#) (boolean featState)
- boolean [getFeat_reset](#) ()
- void [setInt](#) (String feature)
- String [getInt](#) ()
- void [setAdc](#) (String instance, String channel)
- String [getAdc](#) ()
- String [getAdcChannel](#) ()
- void [setUart](#) (String feature)
- String [getUart](#) ()
- void [setI2c](#) (String feature)
- String [getI2c](#) ()
- void [setSpi](#) (String feature)
- String [getSpi](#) ()
- void [setClock](#) (String feature)
- String [getClock](#) ()
- void [setReset](#) (String feature)
- String [getReset](#) ()
- void [setTimer](#) (String feature)
- String [getTimer](#) ()
- void [setName](#) (String pinName)
- String [getName](#) ()

- void [setNumber](#) (int pinNum)
- int [getNumber](#) ()
- String [getPortPin](#) ()
- void [setPortPin](#) (String portPin)
- void [setPort](#) (String pinPort)
- String [getPort](#) ()
- boolean [isValid](#) ()

Static Public Attributes

- static final boolean [ENABLE](#) = true
- static final boolean [DISABLE](#) = false
- static final boolean [DEF_FUNCTION](#) = DEF_BOOLEAN
- static final boolean [DEF_FEATURE_AV](#) = DEF_BOOLEAN
- static final String [DEF_FEATURE](#) = DEF_STRING
- static final String [DEF_NAME](#) = DEF_STRING
- static final int [DEF_NUMBER](#) = DEF_INT
- static final String [DEF_PORT](#) = DEF_STRING

4.23.1 Detailed Description

Basic pin object.

- [Pin](#) necessary characteristics:
 - Name
 - Number
- [Pin](#) optional characteristics:
 - Port
- [Pin](#) main functions:
 - VCC
 - GND
 - GPIO
 - RESET
 - MISC
- [Pin](#) features:
 - Interruption
 - ADC
 - UART
 - I2C
 - SPI
 - Clock
 - Reset

Author

Miguel Diaz

Version

0.1

4.23.2 Constructor & Destructor Documentation

4.23.2.1 Pin()

```
microcontroller.Pin.Pin ( )
```

Initialize all pin's characteristics and features to their default values

4.23.3 Member Function Documentation

4.23.3.1 getAdc()

```
String microcontroller.Pin.getAdc ( )
```

Get the pin's ADC name

Returns

[Pin's ADC](#)

4.23.3.2 getAdcChannel()

```
String microcontroller.Pin.getAdcChannel ( )
```

Get the pin's ADC channel

Returns

[Pin's ADC channel](#)

4.23.3.3 getClock()

```
String microcontroller.Pin.getClock ( )
```

Get the pin's clock name

Returns

Pin's clock

4.23.3.4 getFeat_adc()

```
boolean microcontroller.Pin.getFeat_adc ( )
```

See if the pin has an ADC

Returns

Feature availability

4.23.3.5 getFeat_clock()

```
boolean microcontroller.Pin.getFeat_clock ( )
```

See if the pin supports a clock

Returns

Feature availability

4.23.3.6 getFeat_i2c()

```
boolean microcontroller.Pin.getFeat_i2c ( )
```

See if the pin has I2C

Returns

Feature availability

4.23.3.7 getFeat_int()

```
boolean microcontroller.Pin.getFeat_int ( )
```

See if the pin has an interruption

Returns

Feature availability

4.23.3.8 getFeat_reset()

```
boolean microcontroller.Pin.getFeat_reset ( )
```

See if the pin has a reset feature

Returns

Feature availability

4.23.3.9 getFeat_spi()

```
boolean microcontroller.Pin.getFeat_spi ( )
```

See if the pin has SPI

Returns

Feature availability

4.23.3.10 getFeat_timer()

```
boolean microcontroller.Pin.getFeat_timer ( )
```

See if the pin supports a timer

Returns

Feature availability

4.23.3.11 getFeat_uart()

```
boolean microcontroller.Pin.getFeat_uart ( )
```

See if the pin has a UART

Returns

Feature availability

4.23.3.12 getFunc_gnd()

```
boolean microcontroller.Pin.getFunc_gnd ( )
```

See if the pin is GND

Returns

Function availability

4.23.3.13 getFunc_gpio()

```
boolean microcontroller.Pin.getFunc_gpio ( )
```

See if the pin is GPIO

Returns

Function availability

4.23.3.14 getFunc_misc()

```
boolean microcontroller.Pin.getFunc_misc ( )
```

See if the pin is MISC

Returns

Function availability

4.23.3.15 getFunc_reset()

```
boolean microcontroller.Pin.getFunc_reset ( )
```

See if the pin is RESET

Returns

Function availability

4.23.3.16 getFunc_vcc()

```
boolean microcontroller.Pin.getFunc_vcc ( )
```

See if the pin is Vcc

Returns

Function availability

4.23.3.17 getI2c()

```
String microcontroller.Pin.getI2c ( )
```

Get the pin's I2C name

Returns

[Pin's I2C](#)

4.23.3.18 getInt()

```
String microcontroller.Pin.getInt ( )
```

Get the pin's interruption name

Returns

[Pin's interruption](#)

4.23.3.19 getName()

```
String microcontroller.Pin.getName ( )
```

Get the pin's name

Returns

Pin's name

4.23.3.20 getNumber()

```
int microcontroller.Pin.getNumber ( )
```

Get the pin's number

Returns

Pin's number

4.23.3.21 getPort()

```
String microcontroller.Pin.getPort ( )
```

Get the pin's port

Returns

Pin's port

4.23.3.22 getPortPin()

```
String microcontroller.Pin.getPortPin ( )
```

Get port pin number

Returns

port pin number

4.23.3.23 `getReset()`

```
String microcontroller.Pin.getReset ( )
```

Get the pin's reset name

Returns

[Pin's reset](#)

4.23.3.24 `getSpi()`

```
String microcontroller.Pin.getSpi ( )
```

Get the pin's SPI name

Returns

[Pin's SPI](#)

4.23.3.25 `getTimer()`

```
String microcontroller.Pin.getTimer ( )
```

Get the pin's timer name

Returns

[Pin's timer](#)

4.23.3.26 `getUart()`

```
String microcontroller.Pin.getUart ( )
```

Get the pin's UART name

Returns

[Pin's UART](#)

4.23.3.27 isValid()

```
boolean microcontroller.Pin.isValid ( )
```

Check if the pin is correctly initialized

Returns

True if the pin is correctly initialized

4.23.3.28 setAdc()

```
void microcontroller.Pin.setAdc (
    String instance,
    String channel )
```

Set the pin's ADC

Parameters

<i>feature</i>	Pin's ADC
----------------	-----------

4.23.3.29 setClock()

```
void microcontroller.Pin.setClock (
    String feature )
```

Set the pin's clock

Parameters

<i>feature</i>	Pin's clock
----------------	-------------

4.23.3.30 setFeat_adc()

```
void microcontroller.Pin.setFeat_adc (
    boolean featState )
```

Set the pin's ADC feature

Parameters

<i>featState</i>	Feature availability
------------------	----------------------

4.23.3.31 setFeat_clock()

```
void microcontroller.Pin.setFeat_clock (  
    boolean featState )
```

Set the pin's Clock feature

Parameters

<i>featState</i>	Feature availability
------------------	----------------------

4.23.3.32 setFeat_i2c()

```
void microcontroller.Pin.setFeat_i2c (  
    boolean featState )
```

Set the pin's I2C feature

Parameters

<i>featState</i>	Feature availability
------------------	----------------------

4.23.3.33 setFeat_int()

```
void microcontroller.Pin.setFeat_int (  
    boolean featState )
```

Set the pin's interruption feature

Parameters

<i>featState</i>	Feature availability
------------------	----------------------

4.23.3.34 setFeat_reset()

```
void microcontroller.Pin.setFeat_reset (
    boolean featState )
```

Set the pin's reset feature

Parameters

<i>featState</i>	Feature availability
------------------	----------------------

4.23.3.35 setFeat_spi()

```
void microcontroller.Pin.setFeat_spi (
    boolean featState )
```

Set the pin's SPI feature

Parameters

<i>featState</i>	Feature availability
------------------	----------------------

4.23.3.36 setFeat_timer()

```
void microcontroller.Pin.setFeat_timer (
    boolean featState )
```

Set the pin's timer feature

Parameters

<i>featState</i>	Feature availability
------------------	----------------------

4.23.3.37 setFeat_uart()

```
void microcontroller.Pin.setFeat_uart (
```

```
boolean featState )
```

Set the pin's UART feature

Parameters

<i>featState</i>	Feature availability
------------------	----------------------

4.23.3.38 setFunc_gnd()

```
void microcontroller.Pin.setFunc_gnd (
    boolean funcState )
```

Set the pin to GND status

Parameters

<i>funcState</i>	Function availability
------------------	-----------------------

4.23.3.39 setFunc_gpio()

```
void microcontroller.Pin.setFunc_gpio (
    boolean funcState )
```

Set the pin to GPIO status

Parameters

<i>funcState</i>	Function availability
------------------	-----------------------

4.23.3.40 setFunc_misc()

```
void microcontroller.Pin.setFunc_misc (
    boolean funcState )
```

Set the pin to MISC status

Parameters

<i>funcState</i>	Function availability
------------------	-----------------------

4.23.3.41 setFunc_reset()

```
void microcontroller.Pin.setFunc_reset (
    boolean funcState )
```

Set the pin to RESET status

Parameters

<i>funcState</i>	Function availability
------------------	-----------------------

4.23.3.42 setFunc_vcc()

```
void microcontroller.Pin.setFunc_vcc (
    boolean funcState )
```

Set the pin to Vcc status

Parameters

<i>funcState</i>	Function availability
------------------	-----------------------

4.23.3.43 setI2c()

```
void microcontroller.Pin.setI2c (
    String feature )
```

Set the pin's I2C

Parameters

<i>feature</i>	Pin's I2C
----------------	-----------

4.23.3.44 `setInt()`

```
void microcontroller.Pin.setInt (
    String feature )
```

Set the pin's interruption

Parameters

<i>feature</i>	Pin's interruption
----------------	--------------------

4.23.3.45 `setName()`

```
void microcontroller.Pin.setName (
    String pinName )
```

Set the pin's name

Parameters

<i>pinName</i>	Pin's name
----------------	------------

4.23.3.46 `setNumber()`

```
void microcontroller.Pin.setNumber (
    int pinNum )
```

Set the pin's number

Parameters

<i>pinNum</i>	Pin's number
---------------	--------------

4.23.3.47 `setPort()`

```
void microcontroller.Pin.setPort (
```

```
String pinPort )
```

Set the pin's port

Parameters

<i>pinPort</i>	Pin's port
----------------	------------

4.23.3.48 setPortPin()

```
void microcontroller.Pin.setPortPin (
    String portPin )
```

Set port pin number

Parameters

<i>portPin</i>	Port pin number
----------------	-----------------

4.23.3.49 setReset()

```
void microcontroller.Pin.setReset (
    String feature )
```

Set the pin's reset

Parameters

<i>feature</i>	Pin's reset
----------------	-------------

4.23.3.50 setSpi()

```
void microcontroller.Pin.setSpi (
    String feature )
```

Set the pin's SPI

Parameters

<i>feature</i>	Pin's SPI
----------------	---------------------------

4.23.3.51 setTimer()

```
void microcontroller.Pin.setTimer (
    String feature )
```

Set the pin's timer

Parameters

<i>feature</i>	Pin's timer
----------------	-----------------------------

4.23.3.52 setUart()

```
void microcontroller.Pin.setUart (
    String feature )
```

Set the pin's UART

Parameters

<i>feature</i>	Pin's UART
----------------	----------------------------

4.23.4 Member Data Documentation**4.23.4.1 DEF_FEATURE**

```
final String microcontroller.Pin.DEF_FEATURE = DEF_STRING [static]
```

Default value for pin's feature as not available

4.23.4.2 DEF_FEATURE_AV

```
final boolean microcontroller.Pin.DEF_FEATURE_AV = DEF_BOOLEAN [static]
```

Default value for pin's feature availability as not available

4.23.4.3 DEF_FUNCTION

```
final boolean microcontroller.Pin.DEF_FUNCTION = DEF_BOOLEAN [static]
```

Default value for pin's function as not enabled

4.23.4.4 DEF_NAME

```
final String microcontroller.Pin.DEF_NAME = DEF_STRING [static]
```

Default value for pin's name

4.23.4.5 DEF_NUMBER

```
final int microcontroller.Pin.DEF_NUMBER = DEF_INT [static]
```

Default value for pin's number

4.23.4.6 DEF_PORT

```
final String microcontroller.Pin.DEF_PORT = DEF_STRING [static]
```

Default value for pin's port

4.23.4.7 DISABLE

```
final boolean microcontroller.Pin.DISABLE = false [static]
```

Disable value for features and functions

4.23.4.8 ENABLE

```
final boolean microcontroller.Pin.ENABLE = true [static]
```

Enable value for features and functions

The documentation for this class was generated from the following file:

- src/microcontroller/Pin.java

4.24 configurator.PinConf Class Reference

Public Member Functions

- [PinConf](#) ([Pin](#) gpioPin)
- boolean [isValid](#) ()
- String [getPort](#) ()
- String [getPortPin](#) ()
- String [getPinName](#) ()
- String [getCodeName](#) ()
- void [setCodeName](#) (String name)
- [Selected](#) [getSelected](#) ()
- void [setSelected](#) ([Selected](#) selection)
- [Mode](#) [getMode](#) ()
- void [setMode](#) ([Mode](#) mode)
- [AltMode](#) [getAltMode](#) ()
- void [setAltMode](#) ([AltMode](#) altMode)
- [OutType](#) [getOutType](#) ()
- void [setOutType](#) ([OutType](#) outType)
- [OutLevel](#) [getOutLevel](#) ()
- void [setOutLevel](#) ([OutLevel](#) level)
- [Speed](#) [getSpeed](#) ()
- void [setSpeed](#) ([Speed](#) speed)
- [Pull](#) [getPull](#) ()
- void [setPull](#) ([Pull](#) pull)
- boolean [isAv_Adc](#) ()
- boolean [isAv_Uart](#) ()
- boolean [isAv_I2c](#) ()
- boolean [isAv_Spi](#) ()
- boolean [isAv_altFunc](#) ()

Static Public Attributes

- static final [Selected](#) [DF_SELECTED](#) = [Selected](#).NOT
- static final [Mode](#) [DF_MODE](#) = [Mode](#).MODE_INPUT
- static final [AltMode](#) [DF_ALT_MODE](#) = [AltMode](#).ALT_MODE_NONE
- static final [Speed](#) [DF_SPEED](#) = [Speed](#).SPEED_FAST
- static final [OutType](#) [DF_OUTTYPE](#) = [OutType](#).OTYPE_PUSH_PULL
- static final [OutLevel](#) [DF_OUT_LEVEL](#) = [OutLevel](#).LOW
- static final [Pull](#) [DF_PULL](#) = [Pull](#).PULL_NOT_AVAILABLE
- static final String [DF_CODE_NAME](#) = ""

4.24.1 Detailed Description

GPIO pin configuration

Author

Miguel Diaz

Version

0.1

4.24.2 Constructor & Destructor Documentation

4.24.2.1 PinConf()

```
configurator.PinConf.PinConf (
    Pin gpioPin )
```

Constructor

Parameters

<i>gpioPin</i>	Pin information
----------------	-----------------

4.24.3 Member Function Documentation

4.24.3.1 getAltMode()

```
AltMode configurator.PinConf.getAltMode ( )
```

Get pin's alternative mode

Returns

Alternative mode

4.24.3.2 getCodeName()

```
String configurator.PinConf.getCodeName ( )
```

Get the pin's user selected name

Returns

pin's name

4.24.3.3 `getMode()`

```
Mode configurator.PinConf.getMode ( )
```

Get the pin's mode configuration

Returns

Mode

4.24.3.4 `getOutLevel()`

```
OutLevel configurator.PinConf.getOutLevel ( )
```

Get the pin's output level

Returns

Pin's output level

4.24.3.5 `getOutType()`

```
OutType configurator.PinConf.getOutType ( )
```

Get the pin's output configuration

Returns

Output configuration

4.24.3.6 `getPinName()`

```
String configurator.PinConf.getPinName ( )
```

Get the pin's number

Returns

Pin's number

4.24.3.7 getPort()

```
String configurator.PinConf.getPort ( )
```

Get the pin's port

Returns

Port

4.24.3.8 getPortPin()

```
String configurator.PinConf.getPortPin ( )
```

Get the port pin number

Returns

Port pin number

4.24.3.9 getPull()

```
Pull configurator.PinConf.getPull ( )
```

Get the pin's pull resistor configuration

Returns

Pull Resistor configuration

4.24.3.10 getSelected()

```
Selected configurator.PinConf.getSelected ( )
```

Get the pin's selection

Returns

Selection

4.24.3.11 `getSpeed()`

```
Speed configurator.PinConf.getSpeed ( )
```

Get the pin's speed

Returns

Speed

4.24.3.12 `isAv_Adc()`

```
boolean configurator.PinConf.isAv_Adc ( )
```

Check availability of ADC

Returns

True if ADC is available

4.24.3.13 `isAv_altFunc()`

```
boolean configurator.PinConf.isAv_altFunc ( )
```

Check the availability of alternate function

Returns

True if alternate function is available

4.24.3.14 `isAv_I2c()`

```
boolean configurator.PinConf.isAv_I2c ( )
```

Check availability of I2C

Returns

True if I2C is available

4.24.3.15 isAv_Spi()

```
boolean configurator.PinConf.isAv_Spi ( )
```

Check availability of SPI

Returns

True if SPI is available

4.24.3.16 isAv_Uart()

```
boolean configurator.PinConf.isAv_Uart ( )
```

Check availability of UART

Returns

True id UART is available

4.24.3.17 isValid()

```
boolean configurator.PinConf.isValid ( )
```

Check if the GPIO pin is valid

Returns

True if valid

4.24.3.18 setAltMode()

```
void configurator.PinConf.setAltMode (
    AltMode altMode )
```

Set pin's alternative mode

Parameters

<i>altMode</i>	Alternative mode
----------------	------------------

4.24.3.19 setCodeName()

```
void configurator.PinConf.setCodeName (
    String name )
```

Set the pin's user selected name

Parameters

<i>name</i>	Pin's name
-------------	------------

4.24.3.20 setMode()

```
void configurator.PinConf.setMode (
    Mode mode )
```

Set the pin's mode configuration

Parameters

<i>mode</i>	Mode
-------------	------

4.24.3.21 setOutLevel()

```
void configurator.PinConf.setOutLevel (
    OutLevel level )
```

Set the pin's output level

Parameters

<i>level</i>	Pin's output level
--------------	--------------------

4.24.3.22 setOutType()

```
void configurator.PinConf.setOutType (
    OutType outType )
```

Set the pin's output configuration

Parameters

<i>outType</i>	Output configuration
----------------	----------------------

4.24.3.23 setPull()

```
void configurator.PinConf.setPull (
    Pull pull )
```

Set the pull resistor configuration

Parameters

<i>pull</i>	Resistor configuration
-------------	------------------------

4.24.3.24 setSelected()

```
void configurator.PinConf.setSelected (
    Selected selection )
```

Set the pin's selection

Parameters

<i>selection</i>	Selection
------------------	-----------

4.24.3.25 setSpeed()

```
void configurator.PinConf.setSpeed (
```

```
Speed speed )
```

Set the pin's speed

Parameters

<i>speed</i>	Speed
--------------	-------

4.24.4 Member Data Documentation

4.24.4.1 DF_ALT_MODE

```
final AltMode configurator.PinConf.DF_ALT_MODE = AltMode.ALT_MODE_NONE [static]
```

Default Pin alternative mode

4.24.4.2 DF_CODE_NAME

```
final String configurator.PinConf.DF_CODE_NAME = "" [static]
```

Default pin's code name

4.24.4.3 DF_MODE

```
final Mode configurator.PinConf.DF_MODE = Mode.MODE_INPUT [static]
```

Default Pin mode

4.24.4.4 DF_OUT_LEVEL

```
final OutLevel configurator.PinConf.DF_OUT_LEVEL = OutLevel.LOW [static]
```

Default pin's output level

4.24.4.5 DF_OUTTYPE

```
final OutType configurator.PinConf.DF_OUTTYPE = OutType.OTYPE_PUSH_PULL [static]
```

Default pin's output type

4.24.4.6 DF_PULL

```
final Pull configurator.PinConf.DF_PULL = Pull.PULL_NOT_AVAILABLE [static]
```

Default pin's pull resistor

4.24.4.7 DF_SELECTED

```
final Selected configurator.PinConf.DF_SELECTED = Selected.NOT [static]
```

Default Pin's selection

4.24.4.8 DF_SPEED

```
final Speed configurator.PinConf.DF_SPEED = Speed.SPEED_FAST [static]
```

Default pin's speed

The documentation for this class was generated from the following file:

- src/configurator/PinConf.java

4.25 projectConfiguration.ProjectSettings Class Reference

Public Member Functions

- [ProjectSettings](#) ()
- [ErrorCode processDocument](#) ()
- [ErrorCode openProjectFile](#) (File inFile)
- File [getConfFile](#) ()
- File [getUcFile](#) ()
- String [getProjectName](#) ()
- String [getFrameworkPath](#) ()

4.25.1 Detailed Description

Project settings class

Author

Miguel Diaz

Version

0.2

4.25.2 Constructor & Destructor Documentation

4.25.2.1 ProjectSettings()

```
projectConfiguration.ProjectSettings.ProjectSettings ( )
```

Constructor

4.25.3 Member Function Documentation

4.25.3.1 getConfFile()

```
File projectConfiguration.ProjectSettings.getConfFile ( )
```

Get the project configuration file

Returns

Project configuration file

4.25.3.2 getFrameworkPath()

```
String projectConfiguration.ProjectSettings.getFrameworkPath ( )
```

Get the framework folder

Returns

framework folder

4.25.3.3 getProjectName()

```
String projectConfiguration.ProjectSettings.getProjectName ( )
```

Get the project's name

Returns

Project's name

4.25.3.4 getUcFile()

```
File projectConfiguration.ProjectSettings.getUcFile ( )
```

Get the project microcontroller file

Returns

Project microcontroller file

4.25.3.5 openProjectFile()

```
ErrorCode projectConfiguration.ProjectSettings.openProjectFile (
    File inFile )
```

Open the project settings file

Parameters

<i>inFile</i>	Project file
---------------	--------------

Returns

Error Status

4.25.3.6 processDocument()

```
ErrorCode projectConfiguration.ProjectSettings.processDocument ( )
```

Process the document obtained from the XML file

Returns

Error Status

The documentation for this class was generated from the following file:

- src/projectConfiguration/ProjectSettings.java

4.26 configurator.GPIO.Pull Enum Reference

Static Public Member Functions

- static [Pull](#) [getConfigFromString](#) (String conf)

Public Attributes

- [PULL_UP](#)
- [PULL_DOWN](#)
- [PULL_NOT_AVAILABLE](#)
- [PULL_MAX_VALUE](#)

Static Public Attributes

- static final String [STR_NAME](#) = "Pull"

4.26.1 Detailed Description

Pin's pull resistor

Author

Miguel Diaz

Version

0.1

4.26.2 Member Function Documentation

4.26.2.1 getConfigFromString()

```
static Pull configurator.GPIO.Pull.getConfigFromString (  
    String conf ) [static]
```

Get the corresponding [Pull](#) configuration from its name as String

Parameters

<i>conf</i>	Configuration name
-------------	--------------------

Returns

[Pull](#) configuration

4.26.3 Member Data Documentation

4.26.3.1 PULL_DOWN

```
configurator.GPIO.Pull.PULL_DOWN
```

[Pull](#) Down

4.26.3.2 PULL_MAX_VALUE

```
configurator.GPIO.Pull.PULL_MAX_VALUE
```

Maximum value for [Pull](#) enum

4.26.3.3 PULL_NOT_AVAILABLE

```
configurator.GPIO.Pull.PULL_NOT_AVAILABLE
```

If the pin is configured as output, or there is no resistor available

4.26.3.4 PULL_UP

```
configurator.GPIO.Pull.PULL_UP
```

[Pull](#) Up

4.26.3.5 STR_NAME

```
final String configurator.GPIO.Pull.STR_NAME = "Pull" [static]
```

Name as String

The documentation for this enum was generated from the following file:

- src/configurator/GPIO/Pull.java

4.27 configurator.Selected Enum Reference

Public Member Functions

- boolean [getBoolean](#) ()

Static Public Member Functions

- static [Selected](#) [getConfFromString](#) (String conf)
- static [Selected](#) [getConfFromBoolean](#) (Boolean conf)

Public Attributes

- [NOT](#)
- [YES](#)

Static Public Attributes

- static final String [STR_NAME](#) = "selected"

4.27.1 Detailed Description

Pin's selection

Author

Miguel Díaz

Version

0.1

4.27.2 Member Function Documentation

4.27.2.1 [getBoolean\(\)](#)

```
boolean configurator.Selected.getBoolean ( )
```

Get the corresponding boolean from its selection

Returns

[Selected](#) pin state

4.27.2.2 [getConfFromBoolean\(\)](#)

```
static Selected configurator.Selected.getConfFromBoolean (
    Boolean conf ) [static]
```

Get the corresponding mode from a boolean

Parameters

<i>conf</i>	Configuration value
-------------	---------------------

Returns

[Selected](#)

4.27.2.3 getConfigFromString()

```
static Selected configurator.Selected.getConfigFromString (  
    String conf ) [static]
```

Get the corresponding mode from its name as String

Parameters

<i>conf</i>	Configuration name
-------------	--------------------

Returns

[Selected](#)

4.27.3 Member Data Documentation

4.27.3.1 NOT

```
configurator.Selected.NOT
```

Pin not selected

4.27.3.2 STR_NAME

```
final String configurator.Selected.STR_NAME = "selected" [static]
```

Name as String

4.27.3.3 YES

```
configurator.Selected.YES
```

Pin selected

The documentation for this enum was generated from the following file:

- src/configurator/Selected.java

4.28 configurator.GPIO.Speed Enum Reference

Static Public Member Functions

- static [Speed](#) [getConfigFromString](#) (String conf)

Public Attributes

- [SPEED_FAST](#)
- [SPEED_MEDIUM](#)
- [SPEED_HIGH](#)
- [SPEED_NOT_AVAILABLE](#)
- [SPEED_MAX_VALUE](#)

Static Public Attributes

- static final String [STR_NAME](#) = "Speed"

4.28.1 Detailed Description

Pin's speed

Author

Miguel Diaz

Version

0.1

4.28.2 Member Function Documentation

4.28.2.1 getConfigFromString()

```
static Speed configurator.GPIO.Speed.getConfigFromString (  
    String conf ) [static]
```

Get the corresponding [Speed](#) configuration from its name as String

Parameters

<i>conf</i>	Configuration name
-------------	--------------------

Returns

[Speed](#)

4.28.3 Member Data Documentation

4.28.3.1 SPEED_FAST

```
configurator.GPIO.Speed.SPEED_FAST
```

Fast

4.28.3.2 SPEED_HIGH

```
configurator.GPIO.Speed.SPEED_HIGH
```

High

4.28.3.3 SPEED_MAX_VALUE

```
configurator.GPIO.Speed.SPEED_MAX_VALUE
```

Maximum value for [Speed](#) enum

4.28.3.4 SPEED_MEDIUM

```
configurator.GPIO.Speed.SPEED_MEDIUM
```

Medium

4.28.3.5 SPEED_NOT_AVAILABLE

```
configurator.GPIO.Speed.SPEED_NOT_AVAILABLE
```

Not all MCUs will have this setting

4.28.3.6 STR_NAME

```
final String configurator.GPIO.Speed.STR_NAME = "Speed" [static]
```

Name as String

The documentation for this enum was generated from the following file:

- src/configurator/GPIO/Speed.java

4.29 xmlParser.XmlOpener Class Reference

Public Member Functions

- [XmlOpener](#) ()
- [ErrorCode OpenFile](#) (File inFile)
- Document [getParsedDoc](#) ()

Static Public Member Functions

- static String [getElementInfoFromDoc](#) (Document doc, String elementName)
- static String [getElementInfo](#) (Element element, String elementName)

4.29.1 Detailed Description

Open and process XML files

Author

H112943

Version

0.1

4.29.2 Constructor & Destructor Documentation

4.29.2.1 XmlOpener()

```
xmlParser.XmlOpener.XmlOpener ( )
```

Constructor

4.29.3 Member Function Documentation

4.29.3.1 getElementInfo()

```
static String xmlParser.XmlOpener.getElementInfo (
    Element element,
    String elementName ) [static]
```

Get an XML sub element information

Parameters

<i>element</i>	XML main element
<i>elementName</i>	Sub element's name

Returns

Sub element's information

4.29.3.2 getElementInfoFromDoc()

```
static String xmlParser.XmlOpener.getElementInfoFromDoc (
    Document doc,
    String elementName ) [static]
```

Get an XML element information

Parameters

<i>doc</i>	Document from XML file
<i>elementName</i>	Element's name

Returns

Element's information

4.29.3.3 getParsedDoc()

```
Document xmlParser.XmlOpener.getParsedDoc ( )
```

Get the parsed document AFTER opening the file

Returns

Parsed document

4.29.3.4 OpenFile()

```
ErrorCode xmlParser.XmlOpener.OpenFile (
    File inFile )
```

Open the XML file

Parameters

<i>inFile</i>	XML file
---------------	----------

Returns

Error code

The documentation for this class was generated from the following file:

- src/xmlParser/XmlOpener.java

Index

- AboutWindow
 - gui>AboutWindow, [9](#)
- Adc
 - microcontroller.Adc, [11](#)
- AdcCfg
 - microcontroller.Microcontroller, [61](#)
- AdcConf
 - configurator.AdcConf, [22](#)
- AdcConfWindow
 - gui.AdcConfWindow, [27](#)
- Adcs
 - microcontroller.Microcontroller, [61](#)
- addChannel
 - microcontroller.Adc, [11](#)
- addClock
 - microcontroller.Adc, [11](#)
- addJustification
 - microcontroller.Adc, [11](#)
- addPin
 - xmlCreator.ConfXmlWriter, [42](#)
- addPrescaler
 - microcontroller.Adc, [12](#)
- addReference
 - microcontroller.Adc, [12](#)
- addResolution
 - microcontroller.Adc, [12](#)
- addSample
 - microcontroller.Adc, [13](#)
- ALT_MODE_ANALOG
 - configurator.GPIO.AltMode, [31](#)
- ALT_MODE_I2C
 - configurator.GPIO.AltMode, [31](#)
- ALT_MODE_MAX_VALUE
 - configurator.GPIO.AltMode, [31](#)
- ALT_MODE_NONE
 - configurator.GPIO.AltMode, [31](#)
- ALT_MODE_SPI
 - configurator.GPIO.AltMode, [31](#)
- ALT_MODE_UART
 - configurator.GPIO.AltMode, [31](#)
- CODE_NAME
 - configurator.GPIO.CodeName, [34](#)
- CodeGenerator
 - framework.CodeGenerator, [32](#)
- common, [5](#)
- common.ErrorCode, [43](#)
 - EX_ERROR, [43](#)
 - FILE_CONF_ERROR, [44](#)
 - FILE_READ_ERROR, [44](#)
 - FILE_WRITE_ERROR, [44](#)
 - INT_INVALID_INDEX, [44](#)
 - NO_ERROR, [44](#)
 - STR_INVALID, [44](#)
- common.Features, [45](#)
 - DEBUG, [46](#)
 - DEBUG_STR, [46](#)
 - debugPrint, [45](#)
 - SW_VERSION, [46](#)
 - VERBOSE, [46](#)
 - VERBOSE_STR, [47](#)
 - verbosePrint, [46](#)
 - VERSION_NAME, [47](#)
 - VERSION_STATUS, [47](#)
- configurator, [5](#)
- configurator.ADC.AdcChannel, [18](#)
 - getCodeName, [19](#)
 - getName, [19](#)
 - getPinIndex, [19](#)
 - isSelected, [19](#)
 - isValid, [20](#)
 - setCodeName, [20](#)
 - setSelected, [20](#)
- configurator.AdcConf, [21](#)
 - AdcConf, [22](#)
 - DF_SELECTED, [27](#)
 - getClock, [22](#)
 - getCodeName, [22](#)
 - getJustification, [22](#)
 - getPrescaler, [23](#)
 - getReference, [23](#)
 - getResolution, [23](#)
 - getSample, [23](#)
 - getSelected, [24](#)
 - setChannels, [24](#)
 - setClock, [24](#)
 - setCodeName, [25](#)
 - setJustification, [25](#)
 - setPrescaler, [25](#)
 - setReference, [26](#)
 - setResolution, [26](#)

- setSample, 26
 - setSelected, 26
- configurator.ConfigurationFile, 40
 - STR_PROJ_CONF_FILE, 41
- configurator.GPIO.AltMode, 30
 - ALT_MODE_ANALOG, 31
 - ALT_MODE_I2C, 31
 - ALT_MODE_MAX_VALUE, 31
 - ALT_MODE_NONE, 31
 - ALT_MODE_SPI, 31
 - ALT_MODE_UART, 31
 - getConfFromString, 30
 - STR_NAME, 32
- configurator.GPIO.CodeName, 33
 - CODE_NAME, 34
 - STR_NAME, 34
- configurator.GPIO.Mode, 63
 - getConfFromString, 64
 - MODE_ALTERNATE_FUNCTION, 65
 - MODE_INPUT, 65
 - MODE_MAX_VALUE, 65
 - MODE_OUTPUT, 65
 - STR_NAME, 65
- configurator.GPIO.OutLevel, 66
 - getConfFromString, 66
 - HIGH, 67
 - LOW, 67
 - MAX_VALUE, 67
 - STR_NAME, 67
- configurator.GPIO.OutType, 67
 - getConfFromString, 68
 - OTYPE_MAX_VALUE, 69
 - OTYPE_NOT_AVAILABLE, 69
 - OTYPE_OPEN_DRAIN, 69
 - OTYPE_PUSH_PULL, 69
 - STR_NAME, 69
- configurator.GPIO.Pull, 100
 - getConfFromString, 100
 - PULL_DOWN, 101
 - PULL_MAX_VALUE, 101
 - PULL_NOT_AVAILABLE, 101
 - PULL_UP, 101
 - STR_NAME, 101
- configurator.GPIO.Speed, 104
 - getConfFromString, 104
 - SPEED_FAST, 105
 - SPEED_HIGH, 105
 - SPEED_MAX_VALUE, 105
 - SPEED_MEDIUM, 105
 - SPEED_NOT_AVAILABLE, 105
 - STR_NAME, 105
- configurator.PinConf, 88
 - DF_ALT_MODE, 96
 - DF_CODE_NAME, 96
 - DF_MODE, 96
 - DF_OUT_LEVEL, 96
 - DF_OUTTYPE, 96
 - DF_PULL, 96
 - DF_SELECTED, 97
 - DF_SPEED, 97
 - getAltMode, 89
 - getCodeName, 89
 - getMode, 89
 - getOutLevel, 90
 - getOutType, 90
 - getPinName, 90
 - getPort, 90
 - getPortPin, 91
 - getPull, 91
 - getSelected, 91
 - getSpeed, 91
 - isAv_Adc, 92
 - isAv_altFunc, 92
 - isAv_I2c, 92
 - isAv_Spi, 92
 - isAv_Uart, 93
 - isValid, 93
 - PinConf, 89
 - setAltMode, 93
 - setCodeName, 94
 - setMode, 94
 - setOutLevel, 94
 - setOutType, 95
 - setPull, 95
 - setSelected, 95
 - setSpeed, 95
- configurator.Selected, 102
 - getBoolean, 102
 - getConfFromBoolean, 102
 - getConfFromString, 103
 - NOT, 103
 - STR_NAME, 103
 - YES, 103
- ConfXmlWriter
 - xmlCreator.ConfXmlWriter, 42
- DEBUG
 - common.Features, 46
- DEBUG_STR
 - common.Features, 46
- debugPrint
 - common.Features, 45
- DEF_FEATURE
 - microcontroller.Pin, 86
- DEF_FEATURE_AV
 - microcontroller.Pin, 86
- DEF_FUNCTION
 - microcontroller.Pin, 87

- DEF_NAME
 - microcontroller.Pin, [87](#)
- DEF_NUMBER
 - microcontroller.Pin, [87](#)
- DEF_PORT
 - microcontroller.Pin, [87](#)
- Definitions_Adc
 - microcontroller.Microcontroller, [61](#)
- Definitions_Common
 - microcontroller.Microcontroller, [61](#)
- Definitions_Gpio
 - microcontroller.Microcontroller, [62](#)
- DF_ALT_MODE
 - configurator.PinConf, [96](#)
- DF_CODE_NAME
 - configurator.PinConf, [96](#)
- DF_MODE
 - configurator.PinConf, [96](#)
- DF_OUT_LEVEL
 - configurator.PinConf, [96](#)
- DF_OUTTYPE
 - configurator.PinConf, [96](#)
- DF_PULL
 - configurator.PinConf, [96](#)
- DF_SELECTED
 - configurator.AdcConf, [27](#)
 - configurator.PinConf, [97](#)
- DF_SPEED
 - configurator.PinConf, [97](#)
- DISABLE
 - microcontroller.Pin, [87](#)
- ENABLE
 - microcontroller.Pin, [87](#)
- EX_ERROR
 - common.ErrorCode, [43](#)
- FILE_CONF_ERROR
 - common.ErrorCode, [44](#)
- FILE_READ_ERROR
 - common.ErrorCode, [44](#)
- FILE_WRITE_ERROR
 - common.ErrorCode, [44](#)
- framework, [6](#)
- framework.AdcGenerator, [28](#)
 - getElDefs, [29](#)
 - getElements, [29](#)
 - getIncludes, [29](#)
- framework.CodeGenerator, [32](#)
 - CodeGenerator, [32](#)
 - Generate, [33](#)
- framework.Common, [34](#)
 - getCfgFileCPath, [35](#)
 - getCfgFileHPath, [35](#)
 - getCfgPath, [36](#)
 - getCommonCfgDefinitions, [36](#)
 - getCommonIncludes, [37](#)
 - getFrameworkCommonFilePath, [37](#)
 - getFrameworkIncludesFilePath, [37](#)
 - getInstallationFwkPath, [38](#)
 - getProjectFwkPath, [38](#)
 - NL, [39](#)
 - setInstallationFwkPath, [38](#)
 - setProjectFwkPath, [39](#)
 - STR_DEFINITION, [39](#)
 - STR_GEN_CODE_NOTICE_FOOTER, [39](#)
 - STR_GEN_CODE_NOTICE_HEADER, [39](#)
 - STR_HEADER_EXT, [40](#)
 - STR_INCLUDE, [40](#)
 - STR_MODULE_ADC, [40](#)
 - STR_MODULE_GPIO, [40](#)
- FrmCodeGenerator
 - gui.MainWindow, [55](#)
- Generate
 - framework.CodeGenerator, [33](#)
- generateCode
 - gui.MainGui, [49](#)
- getAdc
 - microcontroller.Pin, [72](#)
- getAdcChannel
 - microcontroller.Pin, [72](#)
- getAltMode
 - configurator.PinConf, [89](#)
- getBoolean
 - configurator.Selected, [102](#)
- getCfgFileCPath
 - framework.Common, [35](#)
- getCfgFileHPath
 - framework.Common, [35](#)
- getCfgPath
 - framework.Common, [36](#)
- getChannel
 - microcontroller.Adc, [13](#)
- getChannelNum
 - microcontroller.Adc, [13](#)
- getClock
 - configurator.AdcConf, [22](#)
 - microcontroller.Adc, [13](#)
 - microcontroller.Pin, [72](#)
- getClockNum
 - microcontroller.Adc, [14](#)
- getCodeName
 - configurator.ADC.AdcChannel, [19](#)
 - configurator.AdcConf, [22](#)
 - configurator.PinConf, [89](#)
- getCommonCfgDefinitions
 - framework.Common, [36](#)
- getCommonIncludes

- framework.Common, 37
- getConfFile
 - projectConfiguration.ProjectSettings, 98
- getConfFromBoolean
 - configurator.Selected, 102
- getConfFromString
 - configurator.GPIO.AltMode, 30
 - configurator.GPIO.Mode, 64
 - configurator.GPIO.OutLevel, 66
 - configurator.GPIO.OutType, 68
 - configurator.GPIO.Pull, 100
 - configurator.GPIO.Speed, 104
 - configurator.Selected, 103
- getConfiguredPin
 - microcontroller.Microcontroller, 57
- getElDefs
 - framework.AdcGenerator, 29
- getElementInfo
 - xmlParser.XmlOpener, 107
- getElementInfoFromDoc
 - xmlParser.XmlOpener, 107
- getElements
 - framework.AdcGenerator, 29
- getFeat_adc
 - microcontroller.Pin, 73
- getFeat_clock
 - microcontroller.Pin, 73
- getFeat_i2c
 - microcontroller.Pin, 73
- getFeat_int
 - microcontroller.Pin, 73
- getFeat_reset
 - microcontroller.Pin, 74
- getFeat_spi
 - microcontroller.Pin, 74
- getFeat_timer
 - microcontroller.Pin, 74
- getFeat_uart
 - microcontroller.Pin, 74
- getFrameworkCommonFilePath
 - framework.Common, 37
- getFrameworkIncludesFilePath
 - framework.Common, 37
- getFrameworkPath
 - projectConfiguration.ProjectSettings, 98
- getFunc_gnd
 - microcontroller.Pin, 75
- getFunc_gpio
 - microcontroller.Pin, 75
- getFunc_misc
 - microcontroller.Pin, 75
- getFunc_reset
 - microcontroller.Pin, 75
- getFunc_vcc
 - microcontroller.Pin, 76
- getI2c
 - microcontroller.Pin, 76
- getIncludes
 - framework.AdcGenerator, 29
- getInstallationFwkPath
 - framework.Common, 38
- getInt
 - microcontroller.Pin, 76
- getJustification
 - configurator.AdcConf, 22
 - microcontroller.Adc, 14
- getJustificationNum
 - microcontroller.Adc, 14
- getMode
 - configurator.PinConf, 89
- getName
 - configurator.ADC.AdcChannel, 19
 - microcontroller.Adc, 15
 - microcontroller.Pin, 76
- getNumber
 - microcontroller.Pin, 77
- getOutLevel
 - configurator.PinConf, 90
- getOutType
 - configurator.PinConf, 90
- getParsedDoc
 - xmlParser.XmlOpener, 107
- getPin
 - microcontroller.Microcontroller, 58
- getPinIndex
 - configurator.ADC.AdcChannel, 19
- getPinName
 - configurator.PinConf, 90
- getPort
 - configurator.PinConf, 90
 - microcontroller.Pin, 77
- getPortPin
 - configurator.PinConf, 91
 - microcontroller.Pin, 77
- getPrescaler
 - configurator.AdcConf, 23
 - microcontroller.Adc, 15
- getPrescalerNum
 - microcontroller.Adc, 15
- getProjectFwkPath
 - framework.Common, 38
- getProjectName
 - projectConfiguration.ProjectSettings, 98
- getPull
 - configurator.PinConf, 91
- getReference
 - configurator.AdcConf, 23
 - microcontroller.Adc, 16

- getReferenceNum
 - microcontroller.Adc, 16
- getReset
 - microcontroller.Pin, 77
- getResolution
 - configurator.AdcConf, 23
 - microcontroller.Adc, 16
- getResolutionNum
 - microcontroller.Adc, 17
- getSample
 - configurator.AdcConf, 23
 - microcontroller.Adc, 17
- getSampleNum
 - microcontroller.Adc, 17
- getSelected
 - configurator.AdcConf, 24
 - configurator.PinConf, 91
- getSpeed
 - configurator.PinConf, 91
- getSpi
 - microcontroller.Pin, 78
- getString
 - gui.Messages, 55
- getTimer
 - microcontroller.Pin, 78
- getUart
 - microcontroller.Pin, 78
- getUc_adcNum
 - microcontroller.Microcontroller, 58
- getUc_gpioNum
 - microcontroller.Microcontroller, 58
- getUc_manufacturer
 - microcontroller.Microcontroller, 58
- getUc_model
 - microcontroller.Microcontroller, 59
- getUc_pinNum
 - microcontroller.Microcontroller, 59
- getUc_portNum
 - microcontroller.Microcontroller, 59
- getUc_selectedAdcsNum
 - microcontroller.Microcontroller, 59
- getUc_selectedPinsNum
 - microcontroller.Microcontroller, 60
- getUcFile
 - projectConfiguration.ProjectSettings, 99
- GpioCfgPin
 - microcontroller.Microcontroller, 62
- GpioConfWindow
 - gui.GpioConfWindow, 48
- gui, 6
 - AboutWindow, 9
 - AboutWindow, 9
 - main, 10
 - AdcConfWindow, 27
 - main, 28
 - gui.GpioConfWindow, 47
 - GpioConfWindow, 48
 - main, 48
 - gui.MainGui, 49
 - generateCode, 49
 - loadProjectFile, 50
 - main, 50
 - ProjectFile, 52
 - ProjectPath, 52
 - saveUc, 50
 - setNewUC, 50
 - showAboutWindow, 51
 - showAdcConfWindow, 51
 - showErrorDialog, 51
 - showGpioConfWindow, 51
 - gui.MainWindow, 52
 - FrmCodeGenerator, 55
 - main, 53
 - MainWindow, 53
 - OpenFileChooser, 53
 - setProjectInformation, 54
 - setVisible, 54
 - gui.Messages, 55
 - getString, 55
- HIGH
 - configurator.GPIO.OutLevel, 67
- Includes_Adc
 - microcontroller.Microcontroller, 62
- Includes_Common
 - microcontroller.Microcontroller, 62
- Includes_Gpio
 - microcontroller.Microcontroller, 62
- INT_INVALID_INDEX
 - common.ErrorCode, 44
- isAv_Adc
 - configurator.PinConf, 92
- isAv_altFunc
 - configurator.PinConf, 92
- isAv_I2c
 - configurator.PinConf, 92
- isAv_Spi
 - configurator.PinConf, 92
- isAv_Uart
 - configurator.PinConf, 93
- isSelected
 - configurator.ADC.AdcChannel, 19
- isValid
 - configurator.ADC.AdcChannel, 20
 - configurator.PinConf, 93
 - microcontroller.Adc, 17
 - microcontroller.Microcontroller, 60

- microcontroller.Pin, 78
- loadPinsConf
 - microcontroller.Microcontroller, 60
- loadProjectFile
 - gui.MainGui, 50
- LOW
 - configurator.GPIO.OutLevel, 67
- main
 - gui.AboutWindow, 10
 - gui.AdcConfWindow, 28
 - gui.GpioConfWindow, 48
 - gui.MainGui, 50
 - gui.MainWindow, 53
- MainWindow
 - gui.MainWindow, 53
- MAX_NUMBER_OF_ADCS
 - microcontroller.Microcontroller, 62
- MAX_NUMBER_OF_PINS_PER_PORT
 - microcontroller.Microcontroller, 62
- MAX_VALUE
 - configurator.GPIO.OutLevel, 67
- Microcontroller
 - microcontroller.Microcontroller, 57
- microcontroller, 7
- microcontroller.Adc, 10
 - Adc, 11
 - addChannel, 11
 - addClock, 11
 - addJustification, 11
 - addPrescaler, 12
 - addReference, 12
 - addResolution, 12
 - addSample, 13
 - getChannel, 13
 - getChannelNum, 13
 - getClock, 13
 - getClockNum, 14
 - getJustification, 14
 - getJustificationNum, 14
 - getName, 15
 - getPrescaler, 15
 - getPrescalerNum, 15
 - getReference, 16
 - getReferenceNum, 16
 - getResolution, 16
 - getResolutionNum, 17
 - getSample, 17
 - getSampleNum, 17
 - isValid, 17
 - setName, 18
- microcontroller.Microcontroller, 56
 - AdcCfg, 61
 - Adcs, 61
 - Definitions_Adc, 61
 - Definitions_Common, 61
 - Definitions_Gpio, 62
 - getConfiguredPin, 57
 - getPin, 58
 - getUc_adcNum, 58
 - getUc_gpioNum, 58
 - getUc_manufacturer, 58
 - getUc_model, 59
 - getUc_pinNum, 59
 - getUc_portNum, 59
 - getUc_selectedAdcsNum, 59
 - getUc_selectedPinsNum, 60
 - GpioCfgPin, 62
 - Includes_Adc, 62
 - Includes_Common, 62
 - Includes_Gpio, 62
 - isValid, 60
 - loadPinsConf, 60
 - MAX_NUMBER_OF_ADCS, 62
 - MAX_NUMBER_OF_PINS_PER_PORT, 62
 - Microcontroller, 57
 - Ports, 63
 - processDocument, 61
- microcontroller.Pin, 70
 - DEF_FEATURE, 86
 - DEF_FEATURE_AV, 86
 - DEF_FUNCTION, 87
 - DEF_NAME, 87
 - DEF_NUMBER, 87
 - DEF_PORT, 87
 - DISABLE, 87
 - ENABLE, 87
 - getAdc, 72
 - getAdcChannel, 72
 - getClock, 72
 - getFeat_adc, 73
 - getFeat_clock, 73
 - getFeat_i2c, 73
 - getFeat_int, 73
 - getFeat_reset, 74
 - getFeat_spi, 74
 - getFeat_timer, 74
 - getFeat_uart, 74
 - getFunc_gnd, 75
 - getFunc_gpio, 75
 - getFunc_misc, 75
 - getFunc_reset, 75
 - getFunc_vcc, 76
 - getI2c, 76
 - getInt, 76
 - getName, 76
 - getNumber, 77
 - getPort, 77

- getPortPin, [77](#)
- getReset, [77](#)
- getSpi, [78](#)
- getTimer, [78](#)
- getUart, [78](#)
- isValid, [78](#)
- Pin, [72](#)
- setAdc, [79](#)
- setClock, [79](#)
- setFeat_adc, [79](#)
- setFeat_clock, [80](#)
- setFeat_i2c, [80](#)
- setFeat_int, [80](#)
- setFeat_reset, [81](#)
- setFeat_spi, [81](#)
- setFeat_timer, [81](#)
- setFeat_uart, [81](#)
- setFunc_gnd, [82](#)
- setFunc_gpio, [82](#)
- setFunc_misc, [82](#)
- setFunc_reset, [83](#)
- setFunc_vcc, [83](#)
- setI2c, [83](#)
- setInt, [84](#)
- setName, [84](#)
- setNumber, [84](#)
- setPort, [84](#)
- setPortPin, [85](#)
- setReset, [85](#)
- setSpi, [85](#)
- setTimer, [86](#)
- setUart, [86](#)
- MODE_ALTERNATE_FUNCTION
 - configurator.GPIO.Mode, [65](#)
- MODE_INPUT
 - configurator.GPIO.Mode, [65](#)
- MODE_MAX_VALUE
 - configurator.GPIO.Mode, [65](#)
- MODE_OUTPUT
 - configurator.GPIO.Mode, [65](#)
- NL
 - framework.Common, [39](#)
- NO_ERROR
 - common.ErrorCode, [44](#)
- NOT
 - configurator.Selected, [103](#)
- OpenFile
 - xmlParser.XmlOpener, [108](#)
- OpenFileChooser
 - gui.MainWindow, [53](#)
- openProjectFile
 - projectConfiguration.ProjectSettings, [99](#)
- OTYPE_MAX_VALUE
 - configurator.GPIO.OutType, [69](#)
- OTYPE_NOT_AVAILABLE
 - configurator.GPIO.OutType, [69](#)
- OTYPE_OPEN_DRAIN
 - configurator.GPIO.OutType, [69](#)
- OTYPE_PUSH_PULL
 - configurator.GPIO.OutType, [69](#)
- Pin
 - microcontroller.Pin, [72](#)
- PinConf
 - configurator.PinConf, [89](#)
- Ports
 - microcontroller.Microcontroller, [63](#)
- processDocument
 - microcontroller.Microcontroller, [61](#)
 - projectConfiguration.ProjectSettings, [99](#)
- projectConfiguration, [7](#)
- projectConfiguration.ProjectSettings, [97](#)
 - getConfFile, [98](#)
 - getFrameworkPath, [98](#)
 - getProjectName, [98](#)
 - getUcFile, [99](#)
 - openProjectFile, [99](#)
 - processDocument, [99](#)
 - ProjectSettings, [98](#)
- ProjectFile
 - gui.MainGui, [52](#)
- ProjectPath
 - gui.MainGui, [52](#)
- ProjectSettings
 - projectConfiguration.ProjectSettings, [98](#)
- PULL_DOWN
 - configurator.GPIO.Pull, [101](#)
- PULL_MAX_VALUE
 - configurator.GPIO.Pull, [101](#)
- PULL_NOT_AVAILABLE
 - configurator.GPIO.Pull, [101](#)
- PULL_UP
 - configurator.GPIO.Pull, [101](#)
- saveUc
 - gui.MainGui, [50](#)
- setAdc
 - microcontroller.Pin, [79](#)
- setAltMode
 - configurator.PinConf, [93](#)
- setChannels
 - configurator.AdcConf, [24](#)
- setClock
 - configurator.AdcConf, [24](#)
 - microcontroller.Pin, [79](#)
- setCodeName
 - configurator.ADC.AdcChannel, [20](#)
 - configurator.AdcConf, [25](#)

- configurator.PinConf, 94
- setFeat_adc
 - microcontroller.Pin, 79
- setFeat_clock
 - microcontroller.Pin, 80
- setFeat_i2c
 - microcontroller.Pin, 80
- setFeat_int
 - microcontroller.Pin, 80
- setFeat_reset
 - microcontroller.Pin, 81
- setFeat_spi
 - microcontroller.Pin, 81
- setFeat_timer
 - microcontroller.Pin, 81
- setFeat_uart
 - microcontroller.Pin, 81
- setFunc_gnd
 - microcontroller.Pin, 82
- setFunc_gpio
 - microcontroller.Pin, 82
- setFunc_misc
 - microcontroller.Pin, 82
- setFunc_reset
 - microcontroller.Pin, 83
- setFunc_vcc
 - microcontroller.Pin, 83
- setI2c
 - microcontroller.Pin, 83
- setInstallationFwkPath
 - framework.Common, 38
- setInt
 - microcontroller.Pin, 84
- setJustification
 - configurator.AdcConf, 25
- setMode
 - configurator.PinConf, 94
- setName
 - microcontroller.Adc, 18
 - microcontroller.Pin, 84
- setNewUC
 - gui.MainGui, 50
- setNumber
 - microcontroller.Pin, 84
- setOutLevel
 - configurator.PinConf, 94
- setOutType
 - configurator.PinConf, 95
- setPort
 - microcontroller.Pin, 84
- setPortPin
 - microcontroller.Pin, 85
- setPrescaler
 - configurator.AdcConf, 25
- setProjectFwkPath
 - framework.Common, 39
- setProjectInformation
 - gui.MainWindow, 54
- setPull
 - configurator.PinConf, 95
- setReference
 - configurator.AdcConf, 26
- setReset
 - microcontroller.Pin, 85
- setResolution
 - configurator.AdcConf, 26
- setSample
 - configurator.AdcConf, 26
- setSelected
 - configurator.ADC.AdcChannel, 20
 - configurator.AdcConf, 26
 - configurator.PinConf, 95
- setSpeed
 - configurator.PinConf, 95
- setSpi
 - microcontroller.Pin, 85
- setTimer
 - microcontroller.Pin, 86
- setUart
 - microcontroller.Pin, 86
- setVisible
 - gui.MainWindow, 54
- showAboutWindow
 - gui.MainGui, 51
- showAdcConfWindow
 - gui.MainGui, 51
- showErrorDialog
 - gui.MainGui, 51
- showGpioConfWindow
 - gui.MainGui, 51
- SPEED_FAST
 - configurator.GPIO.Speed, 105
- SPEED_HIGH
 - configurator.GPIO.Speed, 105
- SPEED_MAX_VALUE
 - configurator.GPIO.Speed, 105
- SPEED_MEDIUM
 - configurator.GPIO.Speed, 105
- SPEED_NOT_AVAILABLE
 - configurator.GPIO.Speed, 105
- STR_DEFINITION
 - framework.Common, 39
- STR_GEN_CODE_NOTICE_FOOTER
 - framework.Common, 39
- STR_GEN_CODE_NOTICE_HEADER
 - framework.Common, 39
- STR_HEADER_EXT
 - framework.Common, 40

- STR_INCLUDE
 - framework.Common, [40](#)
- STR_INVALID
 - common.ErrorCode, [44](#)
- STR_MODULE_ADC
 - framework.Common, [40](#)
- STR_MODULE_GPIO
 - framework.Common, [40](#)
- STR_NAME
 - configurator.GPIO.AltMode, [32](#)
 - configurator.GPIO.CodeName, [34](#)
 - configurator.GPIO.Mode, [65](#)
 - configurator.GPIO.OutLevel, [67](#)
 - configurator.GPIO.OutType, [69](#)
 - configurator.GPIO.Pull, [101](#)
 - configurator.GPIO.Speed, [105](#)
 - configurator.Selected, [103](#)
- STR_PROJ_CONF_FILE
 - configurator.ConfigurationFile, [41](#)
- SW_VERSION
 - common.Features, [46](#)
- VERBOSE
 - common.Features, [46](#)
- VERBOSE_STR
 - common.Features, [47](#)
- verbosePrint
 - common.Features, [46](#)
- VERSION_NAME
 - common.Features, [47](#)
- VERSION_STATUS
 - common.Features, [47](#)
- writeXml
 - xmlCreator.ConfXmlWriter, [42](#)
- xmlCreator, [8](#)
- xmlCreator.ConfXmlWriter, [41](#)
 - addPin, [42](#)
 - ConfXmlWriter, [42](#)
 - writeXml, [42](#)
- XmlOpener
 - xmlParser.XmlOpener, [106](#)
- xmlParser, [8](#)
- xmlParser.XmlOpener, [106](#)
 - getElementInfo, [107](#)
 - getElementInfoFromDoc, [107](#)
 - getParsedDoc, [107](#)
 - OpenFile, [108](#)
 - XmlOpener, [106](#)
- YES
 - configurator.Selected, [103](#)