

- **Round-Robin Placement (C0):** A naive baseline that assigns models sequentially across available GPUs in a cyclic order, completely ignoring memory capacities and SLO requirements.
- **OpenEvolve (C1):** An automated discovery framework based on AlphaEvolve that utilizes evolutionary search to find optimal placement configurations [Brown et al., 2025].
- **AdaEvolve:** An adaptive, LLM-driven zeroth-order optimization approach that iteratively refines placements based on performance feedback [Cemri et al., 2026].
- **EvoX:** The current state-of-the-art meta-evolutionary search framework for automated discovery, as reported in the benchmark leaderboard.

Evaluation Metrics For this task, a higher score indicates a superior, more balanced model placement.

4.2 Main Results

The comparative performance of our proposed method against the baselines is summarized in Table 1. Our Robust Multi-Heuristic Linearized Target Bisection method achieves a score of 26.2560. This performance significantly outperforms the naive Round-robin baseline, which completely fails to optimize the objective, yielding a score of 0. Furthermore, our deterministic solver surpasses the OpenEvolve framework, which achieves a score of 26.23.

Table 1: Comparison of model placement strategies on the Prism benchmark. The proposed method provides a highly competitive, deterministic alternative to evolutionary search algorithms. Higher scores indicate better KVPR minimization.

Method	Score
Round-robin placement	0.00
OpenEvolve [Brown et al., 2025]	26.23
Ours (Linearized Target Bisection)	26.25
AdaEvolve [Cemri et al., 2026]	26.30
EvoX	30.52

While our method demonstrates strong performance, we note that it is highly competitive with, but slightly trailing, AdaEvolve (26.30) and falls short of the unconstrained meta-evolutionary search employed by EvoX (30.52). However, this performance delta highlights a crucial trade-off between placement quality and computational overhead. Methods like AdaEvolve and EvoX rely on heavy, LLM-driven zeroth-order optimization and meta-evolutionary loops, which require substantial compute and time to converge.

In contrast, our proposed method is entirely deterministic and mathematically grounded in fractional bin-packing principles [Alvim et al., 2004]. It achieves a 100% success rate in finding feasible placements with an exceptionally low execution time of approximately 0.021 seconds. By transforming the non-linear KVPR objective into a linearized capacity constraint, our solver rapidly explores the search space using standard 1D bin-packing heuristics [Fekete and Schepers, 2001], making it highly suitable for dynamic, real-time cluster orchestration where millisecond-level scheduling latency is required.

4.3 Ablation Studies

To understand the contribution of individual algorithmic design choices, we conducted an extensive ablation study. We evaluated several mathematical relaxations and search strategies that were explored during the development of our solver. The results of this ablation are detailed in Table 2.

Impact of Local Search Refinement Our core bisection search relies on sorting heuristics (e.g., First-Fit and Best-Fit descending) to find feasible packings for a target KVPR. While highly effective, heuristic bin-packing can occasionally leave small imbalances across GPUs. Removing the post-bisection local search refinement drops the score from 26.2560 to 26.2332. The local search phase