

VD-STrans: ULTRA-LOW-LATENCY INCREMENTAL BYTE PAIR ENCODING VIA VECTORIZED DIRECT-INTERVAL SUFFIX TRANSDUCTION

Anonymous authors

Paper under double-blind review

ABSTRACT

Byte Pair Encoding (BPE) subword tokenization is a foundational computational primitive in large language model (LLM) pipelines, yet its dynamic greedy priority heap maintenance and pointer-chasing search tree traversals present significant throughput bottlenecks in streaming inference and massive data preprocessing. While theoretical incremental algorithms achieve $O(\log^2 t)$ worst-case time bounds per byte using Centroid Search Trees (CST), they incur severe instruction overheads, non-contiguous pointer dereferences, and branch mispredictions on physical CPUs. In this work, we present **Vectorized Direct-Interval Suffix Transducer (VD-STrans)**, an ultra-low-latency incremental BPE framework. VD-STrans exploits a structural insight into real-world LLM token topologies: over 99.1% to 99.8% of all Suffix-Successor Trees $\text{SufSucTree}(\tau)$ in production vocabularies contain at most 8 nodes. VD-STrans flattens these compact tree topologies into 256-bit aligned Compact Flat Decision Vectors (FDVs) and resolves candidate last-token selection via a branchless 256-bit AVX2 SIMD parallel range comparison kernel in $O(1)$ cycle time. Furthermore, an Atomic Fast-Path Bypass overlays a 256-bit transition mask on the Aho–Corasick root state to immediately emit single-byte atomic tokens without accessing history state arrays, while deep trees (> 8 nodes) seamlessly fall back to CST traversals to preserve the theoretical $O(\log^2 t)$ worst-case guarantee. Extensive evaluations across 12 major open-source and proprietary tokenizers (including Llama-4, Qwen-3, DeepSeek-3.2, and tiktoken variants) on English, Chinese, and Code text streams demonstrate that VD-STrans achieves a geometric mean throughput speedup of $1.123\times$ over state-of-the-art incremental BPE (with peak speedups of $1.271\times$) and up to $23.64\times$ over standard heap-based BPE, while maintaining 100% exact tokenization fidelity.

1 INTRODUCTION

Subword tokenization is an essential preprocessing step in modern large language model (LLM) pipelines, serving as the bridge between raw character streams and discrete token representations (Sennrich et al., 2015; Dubey et al., 2024). As neural architectures and attention computations have been dramatically accelerated through IO-aware implementations such as FlashAttention (Dao et al., 2022), text preprocessing operations—traditionally regarded as minor administrative overheads—increasingly emerge as significant latency bottlenecks in real-time inference, streaming text generation, and massive data ingestion pipelines.

Among various subword segmentation schemes, Byte Pair Encoding (BPE) (Sennrich et al., 2015) remains the de facto standard due to its deterministic greedy merge logic and effective vocabulary compression, alongside probabilistic alternatives such as Unigram language modeling (Kudo, 2018; Bostrom & Durrett, 2020) and regularized variants like BPE-dropout (Provilkov et al., 2019). Standard offline BPE tokenizers (e.g., SentencePiece (Kudo & Richardson, 2018) and tiktoken) employ dynamic priority heaps to iteratively select highest-priority token pairs. On unpartitioned or long text sequences, this greedy heap mechanism exhibits $O(n \log n)$ to $O(n^2)$ time complexity, often relying on coarse regex pre-tokenization heuristics to restrict merge scopes at the expense of generality.