

Theoretical investigations into BPE have established that optimal compression via pair encoding is APX-complete (Kozma & Voderholzer 2024), reinforcing the reliance on heuristic merge structures.

To enable streaming processing without full-sequence buffering or regex dependencies, recent work by Jiang & Gong (2026) introduced an incremental BPE algorithm. By formalizing the *Prefix Consistency* property (Berglund & van der Merwe 2023) and introducing Suffix-Successor Trees and Centroid Search Trees (CST), this approach incrementally updates the valid tokenization prefix in $O(\log^2 t)$ worst-case time per byte, supported by fast Aho–Corasick state tracking (Kanda et al. 2022).

However, a critical performance gap exists between this theoretical tree-search bound and physical processor execution. Our structural analysis across modern open-source LLM vocabularies reveals an extreme topology distribution: over 98.6% to 99.8% of all Suffix-Successor Trees $\text{SufSucTree}(\tau)$ contain at most 8 nodes, with an average tree depth of only 2 to 3 nodes. Despite this compactness, existing CST-based incremental algorithms perform pointer-chasing tree traversals, indirect memory accesses, and branchy binary search iterations during every last-token search step. On modern CPU architectures, these search loops induce frequent branch mispredictions, cache misses, and pipeline stalls, preventing incremental tokenizers from reaching peak memory throughput.

To resolve these computational inefficiencies, we propose the **Vectorized Direct-Interval Suffix Transducer (VD-STrans)**, an ultra-low-latency incremental BPE framework that replaces explicit search tree traversals with branchless SIMD parallel range evaluation and atomic fast-path bypassing. VD-STrans introduces three core technical innovations:

1. **Compact Flat Decision Vectors (FDV):** For every canonical token whose Suffix-Successor Tree contains 8 or fewer nodes (≤ 8), VD-STrans flattens the hierarchical tree topology into a contiguous memory layout storing candidate token IDs, suffix history offsets $|\text{suc}(t_i)|$, and Depth-First Search (DFS) pre-order entry/exit interval timestamps $[L_{t_i}, R_{t_i}]$.
2. **Branchless SIMD Parallel Interval Range Kernel:** Rather than executing iterative tree searches or binary loops, VD-STrans fetches history timestamps $\text{dfs}_{\text{in}}(H(|sc| - |\text{suc}(t_i)|))$ for all candidates simultaneously and evaluates interval membership $[L_{t_i}, R_{t_i}]$ in parallel using a single 256-bit AVX2 SIMD vector comparison (`_mm256_cmpgt_epi32` and `_mm256_and_si256`). A bitmask extraction (`_mm256_movemask_ps`) and trailing-zero-count instruction (`tzcnt`) identify the exact valid last token $\theta(sc)$ in $O(1)$ branchless execution time.
3. **Atomic Fast-Path Bypass & Hybrid CST Fallback:** VD-STrans incorporates a 256-bit transition bitmask on the Aho–Corasick root node to immediately output single-byte atomic tokens when no multi-byte suffix extensions exist, bypassing history state array maintenance entirely. For rare deep trees (> 8 nodes, representing $< 1\%$ of vocabulary entries), VD-STrans seamlessly falls back to CST search, strictly maintaining the theoretical $O(\log^2 t)$ worst-case time bound.

We evaluate VD-STrans across 12 diverse LLM tokenizers (including Llama 3.1, Qwen-3, DeepSeek-3.2, and OpenAI tiktoken encodings) and real-world datasets spanning English, Chinese, and Code text domains. Across all 72 evaluated benchmark configurations, VD-STrans achieves a geometric mean speedup of $1.123\times$ over the state-of-the-art CST incremental algorithm (with peak speedups up to $1.271\times$) and up to $23.64\times$ over standard offline heap implementations on non-pretokenized text streams, while guaranteeing 100% byte-identical tokenization accuracy and robust worst-case stability. While the state-of-the-art CST baseline already captured the primary algorithmic gains over naive priority heaps, VD-STrans eliminates the remaining physical CPU execution bottlenecks—yielding a vital 12.3% average throughput boost (and up to 27.1% peak) that directly translates into hardware infrastructure savings for streaming inference serving.

2 RELATED WORK

Subword tokenization and offline BPE. Subword tokenization is a foundational component of modern NLP pipelines (Sennrich et al. 2015, Kudo 2018, Bostrom & Durrett 2020). Byte Pair Encoding (BPE), adapted from dictionary compression (Gallé 2019), iteratively merges the most frequent adjacent pairs into vocabulary entries. Practical implementations—Hugging Face