

tokenizers, SentencePiece (Kudo & Richardson, 2018), and OpenAI tiktoken—employ dynamic priority heaps and rely on regex pre-tokenization (Dagan et al., 2024) to keep heap operations from scaling quadratically. Recent theory formalizes tokenization structurally: Geng et al. (2024) model byte BPE as an inverse string homomorphism, and Cagnetta & Okazaki (2024) compile subword algorithms into finite-state transducers. To accelerate batch pretraining, BlockBPE (You, 2025) executes concurrent intra-block merges on GPUs; however, these offline frameworks require buffering blocks or re-tokenizing prefixes from scratch, making them ill-suited to streaming text.

Incremental tokenization and search-tree structures. Incremental tokenization targets streaming input arriving byte-by-byte. Its theoretical basis is the *Prefix Consistency* property (Berglund & van der Merwe, 2023): truncating a valid BPE token sequence yields a valid tokenization of the corresponding prefix. Building on this, Berglund et al. (2024) study DFA constructions for BPE transduction and Mamouras et al. (2026) give bounded-delay sequence transduction for linear-time streaming. To maintain exact standard BPE semantics without delay bounds or regex partitioning, Jiang & Gong (2026) introduced an incremental BPE algorithm over Aho–Corasick automata (Kanda et al., 2022) and Suffix-Successor Trees, applying Centroid Decomposition (Gagie et al., 2013) to precompute Centroid Search Trees (CST) with an $O(\log^2 t)$ per-byte bound. Yet CST traversals incur heavy pointer-chasing on modern CPUs. VD-STrans resolves this by observing that $> 99\%$ of Suffix-Successor Trees are small (≤ 8 nodes), replacing pointer searches with branchless vector comparisons over flat arrays.

Hardware-accelerated string processing and SIMD. SIMD has driven major throughput gains in text parsing and state-machine execution. In document parsing, `simdjson` (Langdale & Lemire, 2019) and Mison (Li et al., 2017) replace FSM control flow with SIMD structural indexing and bit-mask operations, eliminating branch mispredictions at multi-GB/s. For comparison-based search, Khuong & Morin (2015) show that contiguous, cache-aligned layouts with branchless vector instructions outperform pointer-based trees for small sets ($N \leq 16$). VD-STrans adapts these principles to tokenization, mapping DFS interval tests into 256-bit AVX2 register comparisons and converting branch-heavy tree searches into $O(1)$ branchless data-parallel operations.

3 METHODOLOGY

In this section, we present the mathematical and structural framework of Vectorized Direct-Interval Suffix Transduction (VD-STrans). We first review the formal topological foundations of incremental Byte Pair Encoding (BPE), define the Prefix Last-Token Condition and Depth-First Search (DFS) linearization, and then detail our high-performance hardware vectorization scheme, atomic fast-path bypass, and hybrid centroid search fallback.

3.1 STRUCTURAL FOUNDATIONS OF INCREMENTAL BPE

Let Σ be a finite byte alphabet, and let $V \subset \Sigma^+$ denote a finite subword vocabulary consisting of atomic tokens ($|t| = 1$) and non-atomic tokens ($|t| > 1$). A merge dictionary $D = [r_1, r_2, \dots, r_m]$ defines an ordered sequence of merge rules, where each rule $r_i = (x, y) \rightarrow z$ merges adjacent tokens $x, y \in V$ into $z = xy$ with priority rank i .

The tokenization $T_D(s)$ of a string $s \in \Sigma^+$ under dictionary D is obtained by mapping s to byte sequence ϕ_0 and sequentially applying priority merge rules:

$$T_D(s) = (T_{r_m} \circ \dots \circ T_{r_2} \circ T_{r_1})(\phi_0) \quad (1)$$

Incremental BPE relies on the *Prefix Consistency* property (Berglund & van der Merwe, 2023), stated below.

Lemma 1 (Prefix Consistency). *Let s be a string and $\varphi = T(s)$ be its valid BPE token sequence. For any proper prefix token sequence $\mu \subseteq \varphi$, $T(\pi(\mu)) = \mu$, where $\pi(\mu)$ is the detokenized string concatenation of μ .*

By Lemma 1, the BPE sequence of s can be expressed recursively in terms of its *Last Token* $\theta(s) = \text{last}(T(s))$:

$$T(s) = T(s_{\text{pre}}) \oplus [\theta(s)] \quad (2)$$