

DFS Linearization and Interval Validation. To evaluate Definition 1 in $O(1)$ time, we perform a pre-order Depth-First Search (DFS) over F_{suc} , visiting children in increasing order of rule priority. Each node u is assigned entry timestamp $\text{dfs}_{\text{in}}(u)$ and exit timestamp $\text{dfs}_{\text{out}}(u)$, mapping its subtree to half-open interval $[\text{dfs}_{\text{in}}(u), \text{dfs}_{\text{out}}(u))$. For each non-atomic t , we precompute a valid entry interval $I_t = [L_t, R_t)$:

$$L_t = \text{dfs}_{\text{in}}(\text{pre}(t)), \quad R_t = \text{dfs}_{\text{in}}(u_{\text{high}}) \quad (3)$$

where u_{high} is the first child of $\text{pre}(t)$ in DFS order with rule priority greater than or equal to t (or $\text{dfs}_{\text{out}}(\text{pre}(t))$ if none). Thus, candidate t is valid if and only if $\text{dfs}_{\text{in}}(\theta(sc - \text{suc}(t))) \in [L_t, R_t)$.

3.2 COMPACT FLAT DECISION VECTOR (FDV) FORMULATION

Existing incremental BPE implementations resolve the valid last token $\theta(sc)$ by performing Centroid Decomposition search traversals over $\text{SufSucTree}(\tau)$, which incurs dynamic pointer dereferences, non-contiguous memory accesses, and binary search branch loops.

Our empirical profiling across 12 modern LLM vocabularies reveals an extreme topological property: **over 99.1% to 99.8% of all Suffix-Successor Trees contain at most 8 nodes**, with average tree depth ranging from 2.8 to 3.2. Inspired by this structural compactness, VD-STrans replaces explicit pointer-based tree structures with **Compact Flat Decision Vectors (FDVs)**.

For every canonical token τ where $|\text{SufSucTree}(\tau)| \leq 8$, we flatten its tree topology in reverse topological order (deepest candidate tokens first) into a contiguous 256-bit SIMD-aligned memory vector structure. An FDV entry packs candidate attributes into parallel arrays:

$$\begin{aligned} \mathbf{t} &= [t_0, t_1, \dots, t_7] \in \mathbb{Z}_{32}^8 \quad (\text{Candidate Token IDs}) \\ \mathbf{d} &= [|\text{suc}(t_0)|, \dots, |\text{suc}(t_7)|] \in \mathbb{Z}_{32}^8 \quad (\text{Suffix Offsets}) \\ \mathbf{L} &= [L_{t_0}, L_{t_1}, \dots, L_{t_7}] \in \mathbb{Z}_{32}^8 \quad (\text{Interval Lower Bounds}) \\ \mathbf{R} &= [R_{t_0}, R_{t_1}, \dots, R_{t_7}] \in \mathbb{Z}_{32}^8 \quad (\text{Interval Upper Bounds}) \end{aligned} \quad (4)$$

Unused vector lanes for trees with fewer than 8 nodes are padded with sentinel values ($L_i = \infty, R_i = 0$) that evaluate to false under range checks. By structuring the decision space as contiguous vectors, FDV eliminates pointer chasing, dynamic heap allocation, and indirect function calls entirely.

Architecture Adaptation and Cross-Platform Portability. While configured for 256-bit AVX2 SIMD registers ($K = 8$ lanes) on server-grade x86 CPUs, the FDV layout seamlessly adapts to 128-bit SIMD architectures such as ARM Neon (standard on AWS Graviton, Apple Silicon, and edge devices). Under a 128-bit SIMD regime ($K = 4$ lanes), a single 128-bit vector pass covers **55.0%** of all vocabulary trees in a single cycle (achieving a $1.074\times$ speedup over CST baselines), while two 128-bit passes handle **99.2%** of trees, demonstrating high structural flexibility across CPU ISA targets.

3.3 BRANCHLESS SIMD PARALLEL INTERVAL EVALUATION KERNEL

Given an input string sc with current length $|sc|$, VD-STrans evaluates all candidates t_i in an FDV concurrently using 256-bit AVX2 SIMD instructions. The search pipeline executes in five branchless stages, illustrated in Panel B of Fig. 1.

1. **Parallel History State Retrieval:** Using candidate suffix offsets $\mathbf{d}$, the engine queries the history array $H(\cdot)$ to extract prefix last-tokens $k_i = H(|sc| - |\text{suc}(t_i)|)$ and gathers their DFS entry timestamps into vector register YMM0:

$$\mathbf{H} = [\text{dfs}_{\text{in}}(k_0), \text{dfs}_{\text{in}}(k_1), \dots, \text{dfs}_{\text{in}}(k_7)] \quad (5)$$

2. **Vectorized Range Comparison:** The lower bound check $\mathbf{H} \geq \mathbf{L}$ (equivalent to $\mathbf{H} > \mathbf{L} - 1$) and upper bound check $\mathbf{H} < \mathbf{R}$ are executed in parallel via vector comparisons:

$$\mathbf{M}_{\text{lower}} = _mm256_cmpgt_epi32(\mathbf{H}, \mathbf{L} - 1) \quad (6)$$

$$\mathbf{M}_{\text{upper}} = _mm256_cmpgt_epi32(\mathbf{R}, \mathbf{H}) \quad (7)$$