



Figure 2: End-to-end throughput comparison across twelve open-source and proprietary tokenizers evaluated on English, Chinese, and Code datasets under concatenated and per-document evaluation regimes. Results contrast original heap-based BPE (Base), the original incremental BPE algorithm based on centroid search tree traversal (Inc-orig), and VD-STrans incremental BPE (Inc-VD). Annotations above the Inc-VD bars denote the relative throughput speedup factor achieved over Inc-orig.

Table 2: Vocabulary topology statistics and Suffix-Successor Tree size distribution across 12 LLM vocabularies. Flat trees (≤ 8 nodes) are handled in $O(1)$ time by FDV SIMD evaluation.

Tokenizer Model	Vocab Size	Total Trees	Flat (≤ 8)	% Flat	Max Nodes
CodeLlama	31,917	25,402	25,368	99.866%	16
Qwen-3	151,643	151,643	150,309	99.120%	86
DeepSeek-3.2	127,997	127,997	127,497	99.609%	58
Ouro	49,152	49,135	48,714	99.143%	45
Llama-3.1*	128,000	127,412	125,986	98.881%	86
GPT-OSS	199,998	199,998	198,920	99.461%	84
Llama-4	200,000	200,000	198,678	99.339%	77
Mistral-3	131,072	130,072	129,659	99.683%	64
P50K	50,280	50,280	50,018	99.479%	25
R50K	50,256	50,256	50,011	99.513%	23
CL100K	100,256	100,256	98,926	98.673%	86
O200K	199,998	199,998	198,920	99.461%	84

stalls, non-contiguous pointer dereferences, and branch mispredictions. VD-STrans directly attacks these microarchitectural bottlenecks. In high-throughput serving systems and large-scale data pre-processing pipelines handling trillions of subword tokens, achieving an additional **12.3% average throughput gain (and up to 27.1% peak)** on top of an algorithmically optimal baseline represents a substantial hardware efficiency victory, unlocking gigabyte-per-second streaming preprocessing on standard commodity hardware.

4.3 VOCABULARY TOPOLOGY AND SufSUC TREE SIZE DISTRIBUTION

Table 2 provides structural topological statistics for all evaluated vocabularies. Across every model, Suffix-Successor Trees containing 8 or fewer nodes (≤ 8) represent **98.67% to 99.87%** of the entire vocabulary space.

Dynamic node depth histograms reveal that the mean tree size exercised during natural text processing is only ~ 2.8 to 3.2 nodes. This empirical finding validates our 8-lane (256-bit SIMD) FDV register alignment choice: a single AVX2 register covers virtually the entire distribution with zero wasted capacity.