

DYNASPEC-RAG: DYNAMIC SPECTRAL RESIDUAL FUSION WITH MULTI-SCALE SAFETY GATING FOR ZERO-SHOT TIME SERIES FORECASTING

Anonymous authors

Paper under double-blind review

ABSTRACT

Retrieval-Augmented Generation (RAG) enhances zero-shot time series forecasting by leveraging historical analogue sequences from external knowledge bases. However, existing time series RAG approaches treat retrieved target horizons as monolithic sequence vectors during cross-attention or output blending. This monolithic integration introduces critical failure modes, including entangled trend/seasonal interference, severe step-discontinuities across the context-forecast boundary interface, and negative transfer on non-stationary or noisy domains. To address these challenges, we introduce **DynaSpec-RAG**, a lightweight, dynamic spectral residual fusion framework operating in the output space of frozen Time Series Foundation Models (TSFMs). DynaSpec-RAG incorporates (1) single-step differentiable context-boundary continuation to eliminate interface step-discontinuities, (2) real-FFT multi-scale spectral target decomposition into low-frequency trend and high-frequency seasonal sub-bands, (3) content+distance retrieval cross-attention across top- k neighbours, (4) a content-adaptive per-sample, per-band, per-timestep gating network $g(x_q)$ that learns *when and where* to trust retrieved analogues, and (5) a post-hoc validation-calibrated dual-metric safety guard (β). Evaluated across seven standard zero-shot benchmarks (ETT_{h1}, ETT_{h2}, ETT_{m1}, ETT_{m2}, Weather, Electricity, and Exchange Rate), DynaSpec-RAG reduces the average test Mean Squared Error (MSE) of the strong frozen TS-RAG baseline from 0.1940 to 0.1892 while adding only 0.27M trainable parameters ($\sim 0.1\%$ of the foundation model backbone) and strictly eliminating negative transfer through validation-calibrated baseline fallback. DynaSpec-RAG further outperforms recent retrieval-augmented baselines (RAF/RAEF) and transfers zero-shot to the GIFT-Eval multi-domain suite (-5.6% MSE with no retraining).

1 INTRODUCTION

Time series forecasting plays a crucial role across diverse operational domains, ranging from smart energy grid regulation and meteorological monitoring to industrial load planning and financial market analysis. Historically, forecasting pipelines have relied on per-dataset neural or statistical model optimization, incurring substantial computational costs and limiting immediate deployment to novel series. Recently, the emergence of Time Series Foundation Models (TSFMs) has established a paradigm shift towards zero-shot temporal forecasting, where a unified model pretrained on extensive heterogeneous datasets predicts future trajectories across unseen targets without task-specific retraining (Garza et al., 2023; Ansari et al., 2024; Woo et al., 2024; Das et al., 2023; Rasul et al., 2023; John, 2026). Architectures such as TimesFM (Das et al., 2023), Chronos (Ansari et al., 2024), Moirai (Woo et al., 2024), MOMENT (Goswami et al., 2024), TTM (Ekambaram et al., 2024), and Time-MoE (Shi et al., 2024), alongside synthetic pretraining frameworks (Dooley et al., 2023) and language-reprogramming formulations (Nie et al., 2022; Zhou et al., 2023; Jin et al., 2023; Liu et al., 2023a), demonstrate strong empirical transferability across comprehensive benchmark suites like GIFT-Eval (Ibrahim Aksu et al., 2024) as well as established real-world benchmarks including ETT (Zhou et al., 2020), Weather (Rasp et al., 2020), and Exchange Rate (Lai et al., 2017; Kottapalli et al., 2025).