

Table 3: Zero-shot forecasting MSE across extended horizons $L \in \{96, 192, 336, 720\}$ (lookback $T = 512$), comparing the baseline TSFM (w/o RAG) against DynaSpec-RAG (Ours). Lower is better; best per cell in **bold**.

Dataset	$L=96$ (w/o / Ours)	$L=192$ (w/o / Ours)	$L=336$ (w/o / Ours)	$L=720$ (w/o / Ours)
ETTh1	0.3859 / 0.3772	0.4446 / 0.4306	0.4850 / 0.4650	0.4841 / 0.4703
ETTh2	0.2899 / 0.2812	0.3603 / 0.3474	0.4045 / 0.3839	0.4143 / 0.4017
Electricity	0.1242 / 0.1226	0.1428 / 0.1413	0.1613 / 0.1593	0.2069 / 0.2050
Exchange	0.0993 / 0.0927	0.1926 / 0.1831	0.3437 / 0.3157	0.8100 / 0.6968

calibration eliminates negative transfer on validation splits and achieves the best joint performance (0.1892 MSE / 0.2488 MAE).

Ablation 5: Spectral Loss Contribution. Table 8 evaluates loss objectives. The full objective (Huber + $\lambda = 0.1$ real-FFT L_1) achieves the best trade-off across time-domain MSE (0.2513), MAE (0.2855), and frequency-domain Mean Absolute Spectral Error (1.9227 MASE), confirming the auxiliary spectral term acts as a light-touch regularizer yielding cleaner spectral residuals.

Ablation 6: Neighbour Aggregation & Attention. Table 9 compares neighbour fusion strategies. Using a single neighbour (Top-1) degrades accuracy (0.1922 MSE), confirming the value of multi-neighbour aggregation, whereas learnable Content+Distance Attention (0.1891 MSE) and Inverse-Distance Softmax (0.1890 MSE) both outperform it at negligible latency (~ 4 ms/batch).

Ablation 7: Spectral Cutoff Sensitivity. We probe robustness to the fixed low-pass cutoff c_h (default $c_h = 4$ low bins for the $L = 64$ horizon) by sweeping the low/high split across 10/90, 25/75, and 50/50 fractions and a data-driven *Adaptive Energy-80* rule (smallest set of low bins capturing $\geq 80\%$ of cumulative spectral energy per series). As detailed in Appendix B (Table 11), average MSE/MAE/MASE are near-invariant across all schemes, and the Adaptive Energy-80 rule matches the fixed cutoff (0.2084 vs. 0.2084 avg MSE). The content-adaptive gate $g(x_q)$ re-balances sub-band residuals per timestep, rendering the spectral boundary non-brittle and removing any need for per-dataset cutoff tuning.

4.6 EXTENDED FORECASTING HORIZONS & EFFICIENCY

To assess performance under extended prediction horizons, we evaluate DynaSpec-RAG across forecast lengths $L \in \{96, 192, 336, 720\}$ with an autoregressive rolling setup: at each rolling step the retriever fetches the top- k analogues for the updated context and applies dynamic spectral residual refinement. Table 3 reports MSE against the baseline backbone (without RAG) on ETTh1, ETTh2, Electricity, and Exchange Rate. DynaSpec-RAG consistently achieves lower MSE across *all* extended horizons, demonstrating that dynamic spectral residual fusion mitigates cumulative error drift during multi-step rolling prediction.

Efficiency. DynaSpec-RAG maintains high computational efficiency. Trainable parameters are restricted to 0.27M, adding negligible memory overhead ($\sim 0.1\%$) relative to the frozen backbone (200M+ parameters). The spectral residual module requires only 4.02 ms per batch of 256 on an A100 GPU, and FAISS retrieval indexing executes in 9.2 ms per iteration, demonstrating suitability for real-time deployment.

5 CONCLUSION

We introduced DynaSpec-RAG, a dynamic spectral residual fusion framework for retrieval-augmented zero-shot time series forecasting. It addresses the limitations of monolithic target fusion through four innovations: single-step boundary continuation, real-FFT sub-band decomposition, a content-adaptive per-sample/per-band/per-timestep gating network $g(x_q)$ that learns when and where to trust retrieval, and a validation-calibrated dual-metric safety guard (β). Across seven benchmarks, DynaSpec-RAG reduces average MSE from 0.1940 to 0.1892 with only 0.27M trainable parameters, further surpassing RAF/RAEF and transferring zero-shot to GIFT-Eval (-5.6%) while strictly preventing negative transfer. Future work includes extending dynamic spectral gating