

Table 4: Ablation 1: Frequency decomposition isolation (subset test split). MSE / MAE and boundary continuity error (SDE); lower is better.

Variant	ETTh1	ETTm1	Weather	Electricity	Avg MSE / MAE	Avg SDE
ARM Baseline	0.3556 / 0.3623	0.2904 / 0.3113	0.1453 / 0.1770	0.1120 / 0.2003	0.2258 / 0.2627	0.1275
Full Dual-Band	0.3459 / 0.3617	0.2817 / 0.3092	0.1394 / 0.1750	0.1128 / 0.2044	0.2199 / 0.2626	0.1248
Low-Only	0.3492 / 0.3622	0.2819 / 0.3092	0.1390 / 0.1752	0.1117 / 0.2008	0.2205 / 0.2619	0.1272
High-Only	0.3509 / 0.3633	0.2895 / 0.3111	0.1450 / 0.1774	0.1130 / 0.2037	0.2246 / 0.2638	0.1293
Monolithic	0.3479 / 0.3618	0.2810 / 0.3090	0.1392 / 0.1749	0.1129 / 0.2045	0.2203 / 0.2626	0.1246

Table 5: Ablation 2: Boundary continuation on ETTh1, ETTh2, and Weather (MSE / MAE and SDE). “Raw residual” inserts the retrieved horizons without boundary alignment.

Variant	ETTh1 MSE/MAE	ETTh2 MSE/MAE	Weather MSE/MAE	Avg MSE / MAE	Avg SDE
TS-RAG Base ($\beta = 0$)	0.3556 / 0.3623	0.2451 / 0.2981	0.1453 / 0.1770	0.2487 / 0.2792	0.1026
With Boundary Continuation	0.3464 / 0.3623	0.2401 / 0.2966	0.1433 / 0.1767	0.2433 / 0.2785	0.1026
Raw Residual (no boundary)	0.3502 / 0.3623	0.2424 / 0.2970	0.1446 / 0.1780	0.2457 / 0.2791	0.1026

A EXTENDED ARCHITECTURAL & MATHEMATICAL DETAILS

A.1 DERIVATION OF SINGLE-STEP CONTEXT-BOUNDARY CONTINUATION

Let $x_q \in \mathbb{R}^T$ be the query context and $y_i \in \mathbb{R}^L$ the i -th retrieved target horizon with historical context $x_i \in \mathbb{R}^T$. Standard instance normalization maps sequences into zero-mean, unit-variance space:

$$\text{rz}_q = \frac{x_q - \text{loc}_q}{\text{scale}_q}, \quad \text{rz}_{i,\text{ctx}} = \frac{x_i - \text{loc}_i}{\text{scale}_i}, \quad \text{rz}_{i,\text{fut}} = \frac{y_i - \text{loc}_i}{\text{scale}_i}, \quad (8)$$

with $\text{loc}_q = \text{mean}(x_q)$ and $\text{scale}_q = \text{std}(x_q)$. Direct substitution yields $\hat{y}_i = \text{loc}_q + \text{scale}_q \cdot \text{rz}_{i,\text{fut}}$; however $\hat{y}_i(1) \neq x_q(T)$ in general, creating a step-discontinuity at $t = T + 1$. The single-step continuation operator instead propagates the context tail using candidate future increments:

$$\tilde{y}_i(t) = x_q(T) + \text{scale}_q \cdot (\text{rz}_{i,\text{fut}}(t) - \text{rz}_{i,\text{ctx}}(T)), \quad t = 1, \dots, L. \quad (9)$$

As $\text{rz}_{i,\text{fut}}(1) \approx \text{rz}_{i,\text{ctx}}(T)$ at the interface, $\tilde{y}_i(1) \rightarrow x_q(T)$, ensuring C^0 boundary continuity.

A.2 GATING NETWORK FEATURE REPRESENTATION

The input feature vector $\mathbf{f}_{\text{trust}}(x_q, \mathcal{C})$ provided to the gating network $g(x_q)$ concatenates six per-timestep signals (each in $\mathbb{R}^L$) with eight broadcast scalar trust indicators, giving an input of dimension $6L + 8$ that is layer-normalized before the MLP. The **per-timestep signals** are: the low- and high-band analogue residuals $r_{\text{low}}, r_{\text{high}}$; the neighbour spreads $\text{std}_i(y_i^{\text{low}}), \text{std}_i(y_i^{\text{high}})$ (per-step disagreement across the k candidates in each band); and the baseline sub-band magnitudes $|y_{\text{base}}^{\text{low}}|, |y_{\text{base}}^{\text{high}}|$. The **scalar indicators** are: (1) the mean, minimum, and standard deviation of the retrieval distances $\{d(e_q, e_i)\}_{i=1}^k$; (2) the mean absolute boundary offset between the query context tail and the retrieved context tails; (3) a local AR(1) continuity coefficient of the context low band (a first-order Koopman/AR estimate of the trend dynamics); (4) the query high-frequency energy; and (5) the mean low- and high-band neighbour spreads. The layer-normalized features pass through a two-layer GELU MLP whose sigmoid output yields the per-band, per-timestep gates $g_{\text{low}}, g_{\text{high}} \in [0, 1]^L$.

B FULL ABLATION TABLES

This appendix provides the complete numeric tables underlying the ablation figures in Section 4.5

C SUPPLEMENTARY DATASET DETAILS

Table 12 provides detailed statistics for the seven benchmark datasets used in zero-shot evaluation.