

Despite their strong performance, purely parametric TSFMs exhibit fundamental bottlenecks: when encountering test distributions characterized by novel dynamic regimes, severe non-stationarity, or long-tail structural shifts, parametric weights optimized during pretraining can prove insufficient for capturing localized transient patterns. To complement parametric memory, non-parametric Retrieval-Augmented Generation (RAG) frameworks have been adapted to temporal forecasting (Jing et al., 2022; Tire et al., 2024; Ning et al., 2025). Time series RAG frameworks construct external historical knowledge bases and retrieve top- k nearest context-horizon analogue pairs to augment the backbone TSFM during inference.

However, existing retrieval-augmented forecasting methods suffer from critical structural limitations. Current RAG approaches (Tire et al., 2024; Li, 2025; Xiao et al., 2025; Ravuru et al., 2024; Ning et al., 2025) treat retrieved future target horizons as monolithic latent vectors or plain scalar output blends during cross-attention and output fusion. Monolithically integrating retrieved targets introduces three major failure modes:

1. **Entangled Trend/Seasonal Interference:** Blending raw retrieved targets as a single vector mixes reliable macro-trend structure with volatile high-frequency seasonal detail, so unreliable high-frequency content contaminates the trend correction, inducing destructive interference and oversmoothing.
2. **Boundary Step-Discontinuities:** Inserting retrieved target horizons at the context mean level introduces step-discontinuities across the context–forecast interface ($t = T + 1$).
3. **Negative Transfer on Out-of-Distribution Domains:** When retrieved analogues contain noisy or uninformative signals, naive scalar fusion forces suboptimal modifications on the frozen baseline prediction, degrading zero-shot forecasting performance.

To address these challenges, we present **DynaSpec-RAG** (Dynamic Spectral Residual Fusion with Multi-Scale Safety Gating), a lightweight, parameter-efficient framework that dynamically refines frozen TSFM forecasts in the output space. DynaSpec-RAG introduces four key innovations. *First*, to resolve boundary step-discontinuities, we project retrieved candidate target horizons into the query context frame using a single-step differentiable context-tail boundary continuation operator inspired by local state-transition continuity (Takeishi et al., 2017; Azencot et al., 2020; bin Shi & Meng, 2022; Liu et al., 2023b), enforcing smooth context-to-future continuity at the interface $t = T + 1$. *Second*, we perform real-FFT spectral target decomposition to disentangle retrieved trajectories into low-frequency macro trends and high-frequency seasonal dynamics, so that each sub-band can be corrected and trusted independently. *Third*, rather than relying on uniform or static scalar weights, we employ a content-adaptive gating network ($g(x_q) \in [0, 1]^{L \times 2}$) that dynamically modulates low- and high-frequency residual adjustments across individual time steps and context queries based on retrieval-trust indicators (distance metrics, boundary continuity, and neighbour agreement). *Fourth*, to strictly prevent negative transfer, we introduce a validation-calibrated dual-metric safety guard (D-Guard) operating via a dataset-level scale parameter $\beta \in [0, 1]$. Calibrated using a scale-free dual-metric (MSE+MAE) validation objective whose search grid includes zero, D-Guard guarantees a strict do-no-harm fall-back: if retrieved analogues yield no validation improvement, $\beta \rightarrow 0$, naturally preserving the baseline TSFM forecast.

We summarize our primary contributions as follows:

- **Frequency-Disentangled Residual Target Formulation.** We introduce a residual target formulation combining single-step context-boundary continuation and real-FFT sub-band decomposition, preventing boundary discontinuities and separating reliable trend structure from volatile seasonal detail.
- **Content-Adaptive Multi-Scale Gating and Validation-Calibrated Safety Guard.** We design a lightweight per-timestep, per-band gating network that learns when and where to trust retrieval, paired with a validation-calibrated dual-metric safety guard (β) that provides a strict do-no-harm fall-back to the frozen baseline.
- **Empirical Verification on Zero-Shot Benchmarks.** On a 512-lookback / 64-horizon setup across seven benchmarks, DynaSpec-RAG refines the frozen TS-RAG (Chronos-Bolt + ARM) baseline, reducing average MSE from 0.1940 to 0.1892 with only 0.27M trainable parameters, further outperforming recent retrieval-augmented baselines (RAF/RAEF) and transferring zero-shot to the GIFT-Eval multi-domain suite (-5.6% MSE).