

- **Comprehensive Ablation Studies.** We perform focused ablations confirming the contributions of boundary continuation, sub-band decomposition, temporal gating granularity, safety-scale calibration, spectral loss regularization, neighbour attention, and spectral cut-off sensitivity.

2 RELATED WORK

Time Series Foundation Models & Zero-Shot Forecasting. The development of pretrained foundation models has significantly transformed time series forecasting. Inspired by natural language processing and vision backbones, parametric TSFMs learn transferable temporal representations from massive multi-domain corpora to execute zero-shot forecasting on unseen targets (Garza et al. 2023; Ansari et al. 2024; Woo et al. 2024; Das et al. 2023; Rasul et al. 2023; John 2026). Architectures such as TimesFM (Das et al. 2023), Chronos (Ansari et al. 2024), Moirai (Woo et al. 2024), MOMENT (Goswami et al. 2024), TTM (Ekambaram et al. 2024), Time-MoE (Shi et al. 2024), Timer (Liu et al. 2024), and ForecastPFN (Dooley et al. 2023) leverage patched transformers, decoder-only designs, and mixture-of-experts blocks. Concurrently, reprogramming frameworks utilize pretrained language backbones for sequence modeling, as in PatchTST (Nie et al. 2022), One Fits All (Zhou et al. 2023), Time-LLM (Jin et al. 2023), and UniTime (Liu et al. 2023a). Surveys and benchmarks such as GIFT-Eval (Ibrahim Aksu et al. 2024) and foundational reviews (Kottapalli et al. 2025; Zhang et al. 2024) highlight both strengths and failure modes of zero-shot TSFMs. Nevertheless, purely parametric models encounter bottlenecks on test distributions exhibiting novel non-stationary regimes or long-tail shifts unsupported by pretraining weights. DynaSpec-RAG addresses these bottlenecks by non-parametrically augmenting frozen TSFM outputs with retrieved external analogues without modifying backbone parameters.

Retrieval-Augmented Time Series Forecasting. RAG paradigms enhance neural models by incorporating explicit external knowledge bases during inference. Initially explored for time series by ReTime (Jing et al. 2022), retrieval-augmented forecasting has recently gained traction alongside foundation models. Frameworks such as RAF (Tire et al. 2024; Li 2025), TS-RAG (Ning et al. 2025), FinSrag (Xiao et al. 2025), and Agentic RAG (Ravuru et al. 2024) retrieve semantically similar context-horizon sequences and integrate them into model context, while patch-wise structural losses (Kudrat et al. 2025) align predicted temporal statistics. Despite these advances, existing time series RAG systems predominantly treat retrieved target trajectories as monolithic sequence vectors or plain scalar output blends, inducing trend/seasonal interference, boundary step-discontinuities, and negative transfer on noisy domains. DynaSpec-RAG addresses these issues through single-step boundary continuation, frequency-disentangled real-FFT sub-band cross-attention, and sample-level content-adaptive safety gating.

Dynamical Systems and Spectral Decomposition in Forecasting. Spectral analysis and linear dynamical system theory offer powerful tools for modeling complex temporal dynamics. Operator-theoretic formulations map non-linear dynamic systems into linear measurement spaces, enabling data-driven trajectory evolution (Takeishi et al. 2017; Azencot et al. 2020; bin Shi & Meng 2022). Koopa (Liu et al. 2023b) disentangles time-variant and time-invariant dynamics, while Sonnet (Shu & Lamos, 2025) combines learnable wavelets with spectral projection layers. Frequency-domain neural networks decompose multi-periodic series to capture long-range dependencies, including TimesNet (Wu et al. 2022), FEDformer (Zhou et al. 2022b), FiLM (Zhou et al. 2022a), FreTS (Yi et al. 2023), WaveForM (qiang Yang et al. 2023), AMD (Hu et al. 2024), StemGNN (Cao et al. 2020), and Wave-Net (Yu et al. 2025), frequently optimizing objectives such as the Huber loss (Huber 1964). However, conventional spectral models apply static or global frequency filters across whole sequences, failing to adaptively modulate residual spectral corrections per-timestep based on retrieval trustworthiness. DynaSpec-RAG bridges this gap by coupling a differentiable single-step boundary operator with a content-adaptive multi-scale gating network and validation safety guards.