

3.2 CONTEXT-BOUNDARY CONTINUATION & SPECTRAL DECOMPOSITION

All operations in this section are carried out in the query’s instance-normalized frame (subtracting $\text{loc}_q = \text{mean}(x_q)$ and dividing by $\text{scale}_q = \text{std}(x_q)$), so that a single shared residual module transfers across the seven heterogeneous domains; the resulting residual is rescaled by scale_q before injection (Eq. 1). Directly fusing retrieved horizons $\{y_i\}_{i=1}^k$ into query predictions introduces interface step-discontinuities at $t = T + 1$ and entangles reliable trend structure with volatile seasonal detail. To ensure continuous boundary handoff without matrix-level Koopman operator solving or Dynamic Mode Decomposition iterations during inference, we deploy a lightweight, single-step differentiable context-boundary continuation operator.

Single-Step Context-Boundary Continuation. For each retrieved pair (x_i, y_i) , we compute normalized context-future increment projections. Let $x_q(T)$ be the terminal context observation of the query. Rather than inserting y_i at the raw mean level loc_i , we construct the boundary-aligned retrieved horizon $\tilde{y}_i \in \mathbb{R}^L$ by preserving context-tail slope continuity:

$$\tilde{y}_i(t) = x_q(T) + \text{scale}_q \cdot (\text{rz}_{i,\text{fut}}(t) - \text{rz}_{i,\text{ctx}}(T)), \quad t = 1, \dots, L, \quad (2)$$

where $\text{rz}_{i,\text{fut}}$ and $\text{rz}_{i,\text{ctx}}$ denote instance-standardized temporal trajectories. Equation 2 anchors the retrieved normalized future trajectory directly at $x_q(T)$, preserving relative future increments while enforcing C^0 boundary continuity at $t = T + 1$. While inspired by local state-transition continuity (Takeishi et al. 2017; Azencot et al. 2020), this operator is an explicit first-order context-tail delta projection designed to eliminate boundary steps without solving expensive matrix regressions. Robustness to context-tail outliers is provided by the downstream gate: the trust feature vector monitors the boundary slope mismatch $\Delta x_q(T) = x_q(T) - x_q(T-1)$ against historical analogue slopes, so an anomalous context-tail jump suppresses the residual weights ($g(x_q) \rightarrow 0$), defaulting safely to the frozen forecast.

Real-FFT Sub-Band Decomposition. We apply a real-valued FFT low-pass filter to separate each boundary-aligned trajectory $\tilde{y}_i$ into a macro-trend low-frequency component y_i^{low} and a complementary seasonal high-frequency detail component y_i^{high} :

$$y_i^{\text{low}} = \mathcal{F}^{-1}(\mathcal{H}_{\text{low}} \odot \mathcal{F}(\tilde{y}_i)), \quad y_i^{\text{high}} = \tilde{y}_i - y_i^{\text{low}}, \quad (3)$$

where $\mathcal{F}, \mathcal{F}^{-1}$ are the forward and inverse real-FFT operations and $\mathcal{H}_{\text{low}}$ is a hard low-pass mask that retains the lowest c_h of the $N_{\text{freq}} = \lfloor L/2 \rfloor + 1$ non-redundant real-FFT bins ($\mathcal{H}_{\text{low}}(f) = 1$ for $f < c_h$, 0 otherwise). We use a fixed cutoff $c_h = 4$ for the $L = 64$ horizon, so the low band captures the coarse trend while the complementary high band carries seasonal and transient dynamics; the query context is split analogously with a proportionally larger cutoff $c_c \approx c_h \cdot T/L$. The cutoff is a single fixed hyperparameter and is *not* tuned per dataset; Section 4.5 (Ablation 7) shows the model is near-invariant to its exact value, as the content-adaptive gate re-balances the sub-bands per timestep.

3.3 CONTENT+DISTANCE RETRIEVAL ATTENTION & ADAPTIVE GATING

Content+Distance Retrieval Cross-Attention. To aggregate candidate sub-bands across the top- k neighbours, we compute normalized attention weights w_i combining the metric retrieval distance with a learned content affinity between the query and neighbour contexts:

$$w_i = \frac{\exp\left(-d(e_q, e_i)/(\bar{d}_q \tau) + \alpha_{\text{content}} \cdot \langle \phi(\tilde{x}_q), \phi(\tilde{x}_i) \rangle / \sqrt{\bar{d}}\right)}{\sum_{j=1}^k \exp\left(-d(e_q, e_j)/(\bar{d}_q \tau) + \alpha_{\text{content}} \cdot \langle \phi(\tilde{x}_q), \phi(\tilde{x}_j) \rangle / \sqrt{\bar{d}}\right)}, \quad (4)$$

where $\tau > 0$ is a learnable (softplus-parameterized) temperature, $\bar{d}_q$ is the per-query mean retrieval distance (normalizing the distance kernel across neighbours), α_{content} is a learnable content-affinity weight initialized to 0 (so attention starts distance-only), $\phi(\cdot)$ is a shared learnable linear encoder applied to the instance-normalized query context $\tilde{x}_q$ and each instance-normalized neighbour context $\tilde{x}_i$, and $\langle \cdot, \cdot \rangle$ denotes the dot product between the L_2 -normalized encodings. The aggregated analogue sub-bands are $y_{\text{knn}}^{\text{band}} = \sum_{i=1}^k w_i y_i^{\text{band}}$, and the (unscaled) spectral residuals relative to the baseline sub-bands are $r_{\text{low}} = y_{\text{knn}}^{\text{low}} - y_{\text{base}}^{\text{low}}$ and $r_{\text{high}} = y_{\text{knn}}^{\text{high}} - y_{\text{base}}^{\text{high}}$, where $y_{\text{base}}^{\text{band}}$ are the sub-bands of the frozen forecast $\hat{y}_q^{\text{base}}$.