

Content-Adaptive Multi-Scale Gating Network. The central lever of DynaSpec-RAG is a dynamic gating network $g(x_q) = [g_{\text{low}}(x_q), g_{\text{high}}(x_q)] \in [0, 1]^{L \times 2}$ that decides, per sample, per band, and per timestep, *how much* of the analogue residual to inject—replacing the fixed scalar weights of prior fusion schemes. A retrieval-trust feature vector $\mathbf{f}_{\text{trust}}(x_q, \mathcal{C})$ is assembled by concatenating per-timestep signals (the low/high analogue residuals $r_{\text{low}}, r_{\text{high}}$; the neighbour spreads $\text{std}_i(y_i^{\text{low}}), \text{std}_i(y_i^{\text{high}})$; and the baseline sub-band magnitudes $|y_{\text{base}}^{\text{low}}|, |y_{\text{base}}^{\text{high}}|$) with a small set of broadcast scalar trust indicators (mean/min/std of the retrieval distances, mean absolute boundary offset, a local AR(1) continuity coefficient of the context trend, query high-frequency energy, and the mean low/high-band neighbour spreads). After layer normalization, a two-layer GELU MLP maps these features to the gates:

$$[g_{\text{low}}(x_q), g_{\text{high}}(x_q)] = \sigma(\text{MLP}_{\text{gate}}(\text{LN}(\mathbf{f}_{\text{trust}}(x_q, \mathcal{C})))) , \quad (5)$$

where $\sigma(\cdot)$ is the sigmoid, yielding temporal, per-band trust weights in $[0, 1]$ (feature details in Appendix A). Diagnostically, a fixed global base $\leftrightarrow$ analogue blend recovers only $\sim 1\text{--}5\%$ MSE whereas an oracle per-sample blend recovers $\sim 13\text{--}60\%$: the retrieved analogue is strongly useful, but only on a subset of windows, which is exactly the headroom this adaptive gate is designed to unlock.

3.4 VALIDATION-CALIBRATED SAFETY GUARD (D-GUARD) & TRAINING STRATEGY

Conservative Initialization. The gate head is initialized to be near-inert: its output-layer weights are zero-initialized and its bias set to $\sigma^{-1}(g_{\text{init}})$ with $g_{\text{init}} = 0.15$, so at step 0 the gate emits a small input-independent blend weight ($g_{\text{low}} \equiv g_{\text{high}} \equiv 0.15$) rather than a large uncontrolled correction, and the content-affinity weight α_{content} starts at 0 (distance-only attention). This yields a conservative starting point; the *strict* do-no-harm guarantee is provided separately by the validation-calibrated safety scale β below, whose search grid includes 0.

Training Objective. All parameters of the TSFM backbone, retrieval encoder, and knowledge base remain strictly frozen. The trainable module (0.27M parameters) is optimized on pooled training splits with a combined Huber and spectral objective:

$$\mathcal{L}_{\text{total}} = \text{Huber}(\hat{y}_q^{\text{final}}, y_q; \delta = 1.0) + \lambda \cdot \|\text{rFFT}(\hat{y}_q^{\text{final}}) - \text{rFFT}(y_q)\|_1 , \quad (6)$$

with spectral regularization weight $\lambda = 0.1$.

Validation-Calibrated Safety Guard (D-Guard). To eliminate negative transfer on out-of-distribution or noisy test domains, we perform post-hoc dataset-level calibration of the global scale $\beta \in [0, 1]$. Using a grid search over $\beta \in \{0.0, 0.025, \dots, 1.0\}$ on validation splits, β minimizes a scale-free dual-metric objective:

$$\beta^* = \arg \min_{\beta \in [0, 1]} \left(\frac{\text{MSE}_{\text{val}}(\beta)}{\text{MSE}_{\text{base, val}}} + \frac{\text{MAE}_{\text{val}}(\beta)}{\text{MAE}_{\text{base, val}}} \right) . \quad (7)$$

Because $\beta = 0$ yields an objective value of exactly 2.0, D-Guard guarantees that the calibrated forecast never degrades the combined MSE+MAE below the frozen baseline on validation data. If retrieved analogues offer no predictive utility, $\beta^* \rightarrow 0$, falling back safely to $\hat{y}_q^{\text{base}}$. The guarantee is a validation-set property: it transfers cleanly to test on 6/7 datasets, with only Electricity exhibiting a small validation-to-test distribution shift (Section 4.2).

4 EXPERIMENTS

4.1 EXPERIMENTAL SETUP

Benchmark Datasets. We evaluate zero-shot forecasting across seven widely recognized benchmarks: ETTh1, ETTh2, ETTm1, ETTm2, Weather, Electricity, and Exchange Rate. Split ratios follow established protocols: 6 : 2 : 2 for ETT datasets and 7 : 1 : 2 for Weather, Electricity, and Exchange Rate (statistics in Appendix C).

Evaluation Protocol & Knowledge Base. Following standardized TSFM zero-shot protocols, the context lookback is $T = 512$ and the horizon is fixed at $L = 64$, with $k = 10$ nearest analogue pairs retrieved from in-domain training splits. In heterogeneous multi-domain or cross-domain deployments (Ning et al., 2025), retrieved analogues may introduce domain shift; DynaSpec-RAG’s