

Learned layer weights per scheme

```
layer: 1 2 3 4 5 6 7 8 9 10 11 12 Uniform (w_l = 1/L) : 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083
0.083 0.083 0.083 Trace-only (X-Maha) : 0.000 0.002 0.002 0.004 0.011 0.026 0.057 0.092 0.114 0.130 0.197
0.365 HSKP softmax (tau=0.5) : 0.082 0.082 0.082 0.082 0.083 0.083 0.084 0.084 0.084 0.084 0.085 0.085 Pure
Fisher ratio (S_b/S_w)^2 : 0.030 0.034 0.031 0.030 0.040 0.058 0.101 0.092 0.081 0.102 0.165 0.238 Fisher-disc
gamma=0.5 : 0.000 0.001 0.002 0.003 0.008 0.020 0.052 0.082 0.098 0.119 0.203 0.412 Fisher-disc gamma=1.0 :
0.000 0.001 0.001 0.002 0.006 0.016 0.047 0.072 0.083 0.107 0.207 0.459 Fisher-disc gamma=2.0 <- final.py
default: 0.000 0.000 0.000 0.001 0.003 0.009 0.036 0.053 0.058 0.083 0.206 0.549 Fisher-disc gamma=3.0 : 0.000
0.000 0.000 0.000 0.001 0.005 0.027 0.038 0.039 0.063 0.197 0.629 raw HSKP_l (pre-softmax): 0.105 0.109 0.110
0.111 0.113 0.116 0.119 0.119 0.118 0.120 0.124 0.127
```

HSKP range = [0.105, 0.127] (spread 0.022); after softmax it stays near-uniform, confirming the feedback finding that HSKP fails to discriminate layers. The proposed Fisher-discriminability weighting instead concentrates mass on the late representation layers (l=11,12) and suppresses early layers.

Key insights

- **Best average AUROC:** `Fisher-disc gamma=3.0` at 99.58. **Best average FPR95:** `Fisher-disc gamma=3.0` at 2.13.
- **Uniform** (99.32 / 3.30) and **Trace-only / X-Maha** (99.52 / 2.46) trail the proposed scheme, most visibly on near-
OOD CIFAR-10 (uniform 95.97/19.66, trace 97.19/14.43).
- **HSKP softmax** (99.32 / 3.27) collapses to near-uniform layer weights and gives no advantage, reproducing the reported failure of the original idea.
- **Fisher-discriminability (proposed)** combines global spread (trace) with class separation (S_b/S_w); sweeping gamma shows the sensitivity of the exponent, with gamma=2.0 (the `final.py` default) among the strongest and the method robust across gamma in [0.5, 3.0].

How to reproduce

```
cd tasks/x_maha/logs/code_ablation0 CUDA_VISIBLE_DEVICES=0 python ablation.py
```

Reuses the AdaptFormer-PEFT checkpoint and the cached 12-layer features written by `final.py`; only the layer-weight vector is varied.