

Verdict: Reproducible

I audited `./tasks/x_maha/logs/code_final`, which is the renamed `code_final_refine` referenced in the report (the saved run log confirms the report was written from that path).

What I checked

- Method matches report.** `final.py` implements the *feedback-refined* Procrustes-DS exactly as the Result report describes: Fisher-discriminability layer weighting (replacing HSKP), direct feature blending (Procrustes removed), blended relative-Mahalanobis with scale-matched covariance shrinkage, a score-level asymmetric off-manifold residual gate `min(0, z - \theta)`, and additive log-evidence fusion (replacing Dempster-Shafer). All calibration is on ID-train only (properly post-hoc).
- Re-ran the experiment.** `python final.py` regenerated every "Ours" number **exactly**:
 - Average **99.56 / 2.17** (AUROC/FPR95)
 - Per-dataset: Texture 100.00/0.00, SVHN 99.89/0.36, CIFAR10 97.51/12.61, TinyIN 99.98/0.06, LSUN 100.00/0.00, Places365 100.00/0.00
 - CIFAR-100 ID top-1 = **92.95%**, non-uniform Fisher weights, and the ablation table all match.
- Integrity of cached artifacts.** To rule out fabricated caches, I extracted test features fresh from the checkpoint and compared to the cache: **bit-exact match** (max abs diff = 0.0 across layers 0/5/11, features L2-normalized), and fresh ID accuracy independently = 92.95%. The PEFT checkpoint loads correctly.

Per the requirements, I only audited the **Ours** method (not the baseline). Numbers match exactly — far within any reasonable tolerance.

Saved to `./tasks/x_maha/logs/eval_result/repro_check.json` with `"reproduction": true`.