

- Code: `_shrink_prec` (`final.py:252-257`) implements exactly $(1-s)\Sigma + s(\text{tr}\Sigma/d)I$ (since `torch.diag( $\Sigma$ ).mean() =  $\text{tr}\Sigma/d$`) with `s=0.01` . `_tied_stats / _bg_stats` (259-270) fit the tied and background precisions. `_rel_maha` (272-283) computes the relative-Mahalanobis contrast with `$\gamma=0.5$` . ✓

3.4 Off-Manifold Residual via Mid-Layer Relative Mahalanobis — ALIGNED

- Paper: mid-layers `M={5,6,7,8}` on single-layer `$\tilde{x}_l$` (not blended), per-layer relative-Maha `$r_l$` , standardized by ID-train median/IQR, averaged into `$z_{\text{mani}}$` , re-standardized, gated `$z_{\text{resid}} = \min(0, \hat{z}_{\text{mani}} - \tau)$` , `$\tau=-3.0$` .
- Code: `final.py:354-372` fits per-layer stats on `TR[1]` (single-layer), computes `mid_raw` (relative-Maha), calibrates with per-layer median/IQR, averages (`mid_manifold`). `final.py:377,389-390` re-standardize and apply the asymmetric gate `$\lambda \cdot \min(0, z_m - \theta)$` with `$\theta=-3.0$` . The gate is 0 unless `$z_m < -3$` , i.e. only strongly off-manifold far-OOD are penalized. ✓

3.5 Asymmetric Additive Log-Evidence Fusion — ALIGNED

- Paper: energy `$z_{\text{energy}} = T \cdot \log \Sigma \exp(z_c/T)$` , `T=1.0` ; each source standardized by ID median/IQR; `$s_{\text{fused}} = \hat{z}_{\text{sem}} + \beta \cdot \hat{z}_{\text{energy}} + \lambda \cdot z_{\text{resid}}$` , with reliability weights `$\beta=\lambda=0.5$` ; DS mass fusion is shown to collapse to a plain linear sum, so it is *replaced* by this additive rule.
- Code: `_energy` (`final.py:285-287`) is `logsumexp` (`T=1`). `fuse` (382-391) sums the primary semantic term (weight 1.0) + `$\beta \cdot$` standardized energy (`$\beta=0.5$`) + `$\lambda \cdot$` gated residual (`$\lambda=0.5$`). DS is deliberately not used (comment at 380-381), matching the paper's stated motivation. ✓
- Note: the paper's Eq. (9) "reliability weights = 0.5" is applied in code as `$\beta=\lambda=0.5$` on the energy and residual terms while the primary semantic term carries weight 1.0. This is only a relative-weighting/hyperparameter convention (the additive structure and all three components are identical), well within acceptable simplification — not a different algorithm.

Post-hoc calibration & backbone — ALIGNED

All statistics (Fisher weights, class/background means & precisions, per-source and per-mid-layer median/IQR) are fit on **ID-train only** (`TR / tr_logits`). The backbone is the reused AdaptFormer-PEFT IN21K-ViT-B/16 X-Maha checkpoint (`final.py:66,77-89,455-465`). ✓

3. Specification-Violation Audit

Checked for reward hacking / rule breaking:

1. **Test / OOD data leakage into calibration** — None. Layer weights, means, precisions, and all median/IQR standardizations are computed exclusively from ID-train (`final.py:335,343-359,365,375-377`). ID-test and OOD features only ever pass through the frozen `fuse()` at scoring time (`final.py:393-399`). No OOD or ID-test statistic is fit.
2. **Hardcoded answers for known test cases** — None. The dictionaries `PAPER_XMAHA` (`final.py:114-121`) and the paper/baseline numbers in `procrustes_ds.py` are used **only** for printing comparison columns in the markdown report; they are never fed into scoring, thresholds, or `get_measures` .