

The ablation studies reveal critical flaws and discrepancies between the proposed theoretical components and their actual empirical behavior:

1. **HSKP Layer Weighting:** HSKP values across Transformer layers are nearly uniform (~ 0.11 – 0.13), causing HSKP-softmax weighting to collapse to near-uniform weighting. The performance actually relies heavily on X-Maha's trace-variance factor rather than HSKP itself.
2. **Orthogonal Procrustes Alignment:** Procrustes frame transport provides virtually zero marginal improvement ($+0.01\%$ AUROC) over direct unaligned feature blending, indicating that orthogonal cross-layer alignment adds complexity without clear benefit.
3. **Class-Subspace Nullspace Residual Gating:** Feature-level instance gating using nullspace residuals severely harms performance on near-OOD data (CIFAR-10 AUROC drops from 96.83% to 88.02% at $\beta = 0.5$), forcing the practical implementation to move residuals to score-level addition rather than feature gating.
4. **Graphical Elastic-Net Precision:** Theoretical default regularization parameters ($\lambda_0, \mu_0 = 0.1$) cause catastrophic failure (79.89% AUROC on CIFAR-100-LT) because feature variance is orders of magnitude smaller; precision regularization must be dynamically scale-matched to feature variance.
5. **Dempster-Shafer Evidential Fusion:** DS fusion mathematically reduces to an unweighted linear sum in logit space when using Sigmoid belief functions. It fails to handle heterogeneous evidence reliability on near-OOD data, where asymmetric score-level threshold gating significantly outperforms DS fusion.