

Novel Idea: Orthogonal Procrustes Layer Transport and Dempster-Shafer Evidential Fusion (Procrustes-DS)

Overview

Procrustes-DS is a training-free, post-hoc OOD detection framework designed for visual and vision-language Transformers. It addresses the fundamental limitations of multi-layer representation mixing by geometrically aligning intermediate layer spaces using Orthogonal Procrustes Frame Transport, weighting layer discriminativity via Hilbert-Schmidt Kernel Polarization, dynamically gating instances using Class-Subspace Nullspace Residuals, estimating sparse class precision matrices via Power-Law Scaled Graphical Elastic-Net, and combining multimodal scores using Dempster-Shafer Evidential Mass Fusion.

Key Technical Components

1. Hilbert-Schmidt Kernel Polarization Layer Weighting (Addressing Limitation 1)

Instead of class-blind total variance, Procrustes-DS evaluates layer importance α_l using **Hilbert-Schmidt Kernel Polarization (HSKP)**, which measures the structural alignment between the layer Gram matrix $K^l \in \mathbb{R}^{N \times N}$ and the ideal class-membership Gram matrix $K^Y = YY^\top \in \mathbb{R}^{N \times N}$ ($Y \in \mathbb{R}^{N \times C}$ one-hot encoded):

$$K_{ij}^l = \exp\left(-\frac{\|x_i^l - x_j^l\|_2^2}{2\sigma_l^2}\right) \text{ HSKP}_l = \frac{\langle K^l, K^Y \rangle_F}{\|K^l\|_F \cdot \|K^Y\|_F} = \frac{\text{Tr}(K^l K^Y)}{\sqrt{\text{Tr}((K^l)^2) \cdot \text{Tr}((K^Y)^2)}}$$

$\text{HSKP}_l \in [0, 1]$ is strictly scale-invariant and class-aware. Global static layer weights are assigned via temperature-scaled Softmax: $\alpha_l = \frac{\exp(\text{HSKP}_l/\tau)}{\sum_{k=1}^L \exp(\text{HSKP}_k/\tau)}$

2. Orthogonal Procrustes Frame Transport Alignment (Addressing Limitation 2)

To eliminate feature interference caused by direct element-wise summation across disparate depth levels, Procrustes-DS maps intermediate activations $x_l \in \mathbb{R}^d$ into alignment with the terminal layer space L via the **Orthogonal Procrustes Transport Operator** $Q_l \in O(d)$.

For centered feature matrices $X^l, X^L \in \mathbb{R}^{N \times d}$, Q_l solves the Riemannian optimization problem $\arg \min_{Q \in O(d)} \|X^l Q - X^L\|_F^2$. The closed-form solution is derived via Singular Value Decomposition (SVD) of the cross-layer covariance matrix: $(X^l)^\top X^L = U_l S_l V_l^\top \implies Q_l = U_l V_l^\top$. The transported feature representation is: $\tilde{x}_l = Q_l(x_l - \mu^l) + \mu^L$

3. Class-Subspace Nullspace Residual Instance Gating (Addressing Limitation 3)

For a test input x , global weight α_l is dynamically modulated based on how closely the transported vector $\tilde{x}_l$ adheres to the principal subspace of its candidate ID class $c^*(x) = \arg \min_c \|\tilde{x}_l - \mu_c^l\|_2$.

Let $P_{c,l} = U_{c,l} U_{c,l}^\top \in \mathbb{R}^{d \times d}$ be the projection matrix onto the top- k principal components of class c at layer l . The

Nullspace Reconstruction Residual $r_l(x)$ quantifies off-manifold deviation: $r_l(x) = \|(I - P_{c^*,l})(\tilde{x}_l - \mu_{c^*}^l)\|_2$

$w_l(x) = \alpha_l \cdot \exp\left(-\beta \cdot \frac{r_l(x)}{\sigma_{r,l}}\right)$, $\gamma_l(x) = \frac{w_l(x)}{\sum_{k=1}^L w_k(x)}$ where $\sigma_{r,l}$ is the standard deviation of residuals computed over ID training data. The instance-blended vector is $\Phi(x) = \sum_{l=1}^L \gamma_l(x) \tilde{x}_l$.