

4. Power-Law Scaled Graphical Elastic-Net Precision Estimation (Addressing Limitation 4)

To estimate reliable class-specific precision matrices $\Theta_c = \Sigma_c^{-1}$ under class heteroscedasticity and long-tailed sample imbalance, Procrustes-DS solves a **Class-Aware Graphical Elastic-Net** objective in the blended space $\Phi(x)$: $\hat{\Theta}_c = \arg \min_{\Theta \succ 0} \left(\text{Tr}(\hat{\Sigma}_c \Theta) - \log \det \Theta + \lambda_c \|\Theta\|_{1,\text{off}} + \mu_c \|\Theta\|_F^2 \right)$ where $\hat{\Sigma}_c$ is the empirical class covariance, and penalty coefficients are adaptively scaled based on class sample counts N_c : $\lambda_c = \lambda_0 N_c^{-1/2}$, $\mu_c = \mu_0 N_c^{-1}$. For minority/tail classes (small N_c), λ_c and μ_c automatically increase, enforcing sparsity on off-diagonal elements while stabilizing inversion with Frobenius ridge regularization.

The Mahalanobis score for test sample x is: $M_{\text{PDS}}(x) = \max_{c \in [C]} -(\Phi(x) - \bar{\mu}_c)^\top \hat{\Theta}_c (\Phi(x) - \bar{\mu}_c)$

5. Dempster-Shafer Evidential Mass Calibration for VLMs (Addressing Limitation 5)

To unify unbounded Mahalanobis distances $M(x) = -M_{\text{PDS}}(x)$ and bounded VLM prompt similarities $S(x) = 1 - \max_c \text{sim}(v, t_c)$ without arbitrary scaling parameters, Procrustes-DS models both modalities as evidence sources under **Dempster-Shafer Theory of Evidence**.

1. Define the Frame of Discernment $\Omega = \{\text{ID}, \text{OOD}\}$.
2. Convert continuous scores into Basic Belief Assignments (BBAs) $m(\cdot)$ using soft-thresholded Sigmoid belief functions calibrated on ID training quantiles: $m_{\text{Mah}}(\text{OOD}) = \frac{1}{1 + \exp(-\eta_M(M(x) - \theta_M))}$, $m_{\text{Mah}}(\text{ID}) = 1 - m_{\text{Mah}}(\text{OOD})$
 $m_{\text{VLM}}(\text{OOD}) = \frac{1}{1 + \exp(-\eta_V(S(x) - \theta_V))}$, $m_{\text{VLM}}(\text{ID}) = 1 - m_{\text{VLM}}(\text{OOD})$
3. Combine mass functions using **Dempster's Rule of Combination**: $K = m_{\text{Mah}}(\text{OOD})m_{\text{VLM}}(\text{ID}) + m_{\text{Mah}}(\text{ID})m_{\text{VLM}}(\text{OOD})$ (Conflict Factor) $G_{\text{PDS}}(x) = m_{\text{fused}}(\text{OOD}) = \frac{m_{\text{Mah}}(\text{OOD}) \cdot m_{\text{VLM}}(\text{OOD})}{1 - K}$

The fused mass $G_{\text{PDS}}(x) \in [0, 1]$ serves as a calibrated, parameter-free OOD belief score.