

Step-by-Step Implementation Algorithm

```
import torch
import torch.nn.functional as F
import numpy as np

def compute_hskp_layer_weights(layer_features, labels, num_classes, tau=0.5):
    """
    layer_features: List of L tensors [N, D]
    labels: Tensor [N]
    """
    L = len(layer_features)
    N = labels.shape[0]

    Y = F.one_hot(labels, num_classes=num_classes).float()
    K_Y = Y @ Y.T
    norm_KY = torch.norm(K_Y, p='fro') + 1e-8

    hskp_scores = []
    for l in range(L):
        X_l = layer_features[l]
        dist_sq = torch.cdist(X_l, X_l, p=2) ** 2
        sigma2 = torch.median(dist_sq).item() + 1e-6
        K_l = torch.exp(-dist_sq / (2.0 * sigma2))

        norm_Kl = torch.norm(K_l, p='fro') + 1e-8
        hskp = torch.trace(K_l @ K_Y) / (norm_Kl * norm_KY)
        hskp_scores.append(hskp.item())

    scores_t = torch.tensor(hskp_scores)
    return F.softmax(scores_t / tau, dim=0)

def compute_procrustes_operators(layer_features):
    """
    Computes orthogonal Procrustes matrices Q_l mapping layer l to terminal layer L.
    """
    L = len(layer_features)
    X_L = layer_features[-1]
    mean_L = X_L.mean(dim=0, keepdim=True)
    X_L_centered = X_L - mean_L

    Q_operators = []
    means = []

    for l in range(L):
        X_l = layer_features[l]
        mean_l = X_l.mean(dim=0, keepdim=True)
        means.append(mean_l)

        if l == L - 1:
            Q_operators.append(torch.eye(X_l.shape[1], device=X_l.device))
            continue

        X_l_centered = X_l - mean_l
        cov_cross = X_l_centered.T @ X_L_centered
```