

```

        U, S, Vt = torch.linalg.svd(cov_cross)
        Q_l = U @ Vt
        Q_operators.append(Q_l)

    return Q_operators, means, mean_L

def graphical_elastic_net_precision(X_c, N_c, lambda0=0.1, mu0=0.1):
    """
    Class-aware Graphical Elastic-Net precision matrix estimation.
    """
    D = X_c.shape[1]
    if N_c <= 1:
        return torch.eye(D, device=X_c.device)

    X_centered = X_c - X_c.mean(dim=0, keepdim=True)
    S = (X_centered.T @ X_centered) / (N_c - 1)

    lam = lambda0 / np.sqrt(N_c)
    mu = mu0 / float(N_c)

    # Soft-thresholding off-diagonals
    S_off = S * (1.0 - torch.eye(D, device=X_c.device))
    S_thresh = torch.sign(S_off) * torch.clamp(torch.abs(S_off) - lam, min=0.0)
    S_reg = S_thresh + (S * torch.eye(D, device=X_c.device)) + mu * torch.eye(D, device=X_c.device)

    # Invert stabilized covariance matrix
    evals, evecs = torch.linalg.eigh(S_reg)
    evals = torch.clamp(evals, min=1e-4)
    precision = evecs @ torch.diag(1.0 / evals) @ evecs.T
    return precision

def dempster_shafer_fusion(m1_ood, m2_ood):
    """
    Dempster's Rule of Combination for two OOD belief mass functions.
    m1_ood: Mahalanobis OOD mass in [0, 1]
    m2_ood: VLM OOD mass in [0, 1]
    """
    m1_id = 1.0 - m1_ood
    m2_id = 1.0 - m2_ood

    # Conflict factor K
    K = m1_ood * m2_id + m1_id * m2_ood

    if K >= 1.0 - 1e-6:
        return 0.5

    fused_ood = (m1_ood * m2_ood) / (1.0 - K)
    return float(np.clip(fused_ood, 0.0, 1.0))

```