

Here are the core methodological limitations of the proposed **X-Maha** method, structured to provide clear entry points for novel research improvements:

1. Total Variance as a Weighting Proxy Lacks Class-Separability Awareness

- **Methodological Flaw:** The weight α_l for the l -th layer is calculated strictly based on total feature variance ($\text{Tr}((A^l)^T A^l)$) across all training samples. Total variance measures overall data dispersion, but it completely ignores label information and class separability. High feature variance in a layer can be caused by uninformative noise, background variations, or feature scale differences, rather than discriminative ID vs. OOD patterns.
 - **Why it limits the method:** A layer with noisy, non-discriminative activations that happen to have large magnitudes will be heavily weighted, corrupting the blended feature space $\Phi(x)$ with irrelevant signals.
 - **Opportunity for Improvement:** Replace simple total variance with class-aware metrics (e.g., the ratio of between-class variance to within-class variance, Fisher's discriminant criteria, or mutual information with labels).
-

2. Direct Element-Wise Summation Assumes Layer Feature Alignment

- **Methodological Flaw:** The fusion formula $\Phi(x) = \sum_{l=1}^L \alpha_l x_l$ performs direct element-wise addition across layer representations. While Vision Transformers maintain the same activation dimension across layers, feature dimensions at different depths represent fundamentally different abstraction levels (e.g., early layers represent low-level textures/edges, while late layers represent high-level semantics).
 - **Why it limits the method:** Direct linear summation enforces a rigid component-to-component correspondence across disparate semantic spaces, causing destructive feature interference and destroying subtle non-linear manifold structures needed for anomaly detection.
 - **Opportunity for Improvement:** Incorporate layer-wise learnable linear/non-linear projection heads, orthogonal sub-space projections, or attention-based feature alignment before fusion.
-

3. Global Static Layer Weighting Ignores Instance-Level Variability

- **Methodological Flaw:** The layer weights $\alpha_1, \dots, \alpha_L$ are computed globally from the entire training dataset and remain fixed for every test sample.
 - **Why it limits the method:** Different types of OOD inputs require different layer dynamics. For instance, "far-OOD" or structural anomalies (e.g., corruptions, textures) are best caught by shallow layers, whereas "near-OOD" or semantic anomalies (e.g., fine-grained unseen classes) rely heavily on deeper layers. A static weight distribution cannot dynamically adjust based on the incoming test instance.
 - **Opportunity for Improvement:** Design an instance-adaptive (dynamic) layer weighting module (e.g., via a light hyper-network or input-dependent gating function) that adjusts $\alpha_l(x)$ per test sample.
-

4. Tied Covariance Assumption Weakens in Fused Multi-Layer Spaces

- **Methodological Flaw:** The method uses a single tied global covariance matrix $\tilde{\Sigma}$ calculated across all classes in the fused feature space $\Phi(x)$.