

- **Why it limits the method:** Blending features from early and late layers increases feature variance heteroscedasticity across classes. This issue is severely exacerbated in long-tailed scenarios, where majority classes exhibit vastly different feature spreads compared to minority classes. Assuming a shared covariance structure across all classes in this highly complex blended space leads to inaccurate Mahalanobis distance boundaries for minority/tail classes.
 - **Opportunity for Improvement:** Introduce class-specific covariance estimation with shrinkage/regularization, or adapt adaptive low-rank class-wise Mahalanobis metrics specifically tailored for blended representations.
-

5. Uncalibrated Scale Mismatch in Vision-Language Integration

- **Methodological Flaw:** When extending to VLMs, the scoring function linearly combines the Mahalanobis distance with prompt cosine similarity: $G(x) = \max_c M_{X\text{-Maha}}(x) + \lambda \cdot \text{sim}(v, t_c)$.
- **Why it limits the method:** Mahalanobis distances are unbounded negative continuous metrics whose scale depends heavily on feature dimensionality and layer count, whereas cosine similarities are strictly bounded in $[-1, 1]$ (or $[0, 1]$ post-softmax). Adding them directly via a single static scalar multiplier λ lacks mathematical calibration, making the hyperparameter fragile and highly sensitive across different backbones and datasets.
- **Opportunity for Improvement:** Transform both Mahalanobis distances and text similarities into normalized, calibrated probability/energy distributions (e.g., using Softmax temperature scaling or empirical cumulative distribution function mapping) before score fusion.