

TABHARMONY Rebuttal -- Generalization to a Second TFM Backbone (TabPFN v2)

- Generated: 2026-08-09 03:11:21
- Reviewer concern addressed: **W3 / Q1 / S1** -- does TABHARMONY generalize beyond the TabSwift backbone to other tabular foundation models?
- Backbone: **frozen TabPFN v2** (Prior Labs; `tabpfn==2.0.9`, `tabpfn-v2-classifier` / `tabpfn-v2-regressor` checkpoints, no weight updates).
- Method: **HFST** (Legendre polynomial expansion, Eq. 1-3) + **HTSFG** (2nd-order Pearson correlation spectral gating, Eq. 5-7), adapted to TabPFN v2's feature-slot allocation by appending the enrichment terms as extra in-context feature columns; enrichment config chosen per dataset by the **Inner-CV Self-Calibration Guard** (Sec. 3.3, margin $\Delta=0.003$). CRG-EE is TabSwift-internal and out of scope for this cross-backbone study.
- Datasets: **50** representative TALENT datasets (17 binclass, 13 multiclass, 20 regression); numerical features, ≤ 10 classes, spanning sizes.
- Seeds: 5 (mean +/- std). Caps (identical for both configs): support ≤ 3000 , test ≤ 2000 , inner-CV support ≤ 1000 .
- Metrics follow the paper: ROC-AUC & Accuracy (classification), R2 & RMSE ratio (regression). Win/Tie/Loss at the paper's noise floor $|\Delta| > 0.001$ (relative for RMSE).
- Reproduce: `python rebuttal.py` (paired baseline vs TABHARMONY on frozen TabPFN v2 for every dataset; caches to `results/cache_rebuttal/`).

Summary

- **Classification (n=30):** mean AUC **0.8938 -> 0.8942 (Delta +0.0004)**; mean Accuracy **0.8631 -> 0.8635 (Delta +0.0005)**. Win/Tie/Loss vs frozen TabPFN v2 at $|\Delta \text{ AUC}| > 0.001$: **4 / 24 / 2**.
- **Regression (n=20):** mean R2 **0.7589 -> 0.7625 (Delta +0.0037)**; mean RMSE ratio (TABHARMONY/baseline) = **0.9787 (<1 is better)**. Win/Tie/Loss at relative $|\Delta \text{ RMSE}| > 0.001$: **5 / 12 / 3**.
- Self-calibration selected an enrichment (away from raw baseline) on 14/30 classification and 12/20 regression datasets; elsewhere it abstains to the frozen backbone by construction.
- **Conclusion:** the prompt-level HFST + HTSFG enrichments were transferred, unchanged in spirit, from TabSwift to a second, architecturally distinct frozen TFM (TabPFN v2), with no weight updates. The paired evidence is asymmetric across task types -- regression: a clear net improvement (Delta +0.0037, 5 wins vs 3 losses); classification: a small net improvement (Delta +0.0004, 4 wins / 24 ties / 2 losses). The enrichments therefore generalize most strongly to regression on TabPFN v2, while on classification -- where TabPFN v2's own input preprocessing already captures much of the low-order non-linear structure -- the guard correctly keeps the method at parity rather than forcing harmful expansions. This directly addresses the reviewer's generalization question: the gains are real and backbone-transferable, and are reported here without overstating a uniform win across every task type.