

Dataset	#Feat	Baseline R2	TABHARMONY R2	Delta R2	RMSE ratio	Selected config
weather_izmir	9	0.9936±0.0001	0.9936±0.0001	+0.0000	1.0000	baseline

Mean R2 over 20 datasets: 0.7589 -> 0.7625 (Delta +0.0037); mean RMSE ratio 0.9787.

Notes

- **Adaptation to TabPFN v2's feature slots.** TabSwift zero-pads to a fixed width and TABHARMONY fills those slots; TabPFN v2 instead ingests a variable number of feature columns, so the faithful analogue is to append the HFST/HTSFG terms as additional in-context feature columns. Real feature columns are never modified; all enrichment statistics are fit on the support (train) rows only.
- **Training-free & paired.** No TabPFN v2 weights are updated. Baseline and TABHARMONY use identical support/test subsamples per seed, so any difference is attributable solely to the enrichment.
- **Self-calibration guard** (K=5 folds x 3 repeats, N_calib <= 1000, margin delta=0.003) selects the enrichment config per dataset and abstains to baseline unless the inner gain clears the margin.
- **Scope.** CRG-EE (Sec. 3.4) needs per-layer read-outs not exposed by the TabPFN v2 API and is a within-backbone efficiency mechanism; this study evaluates the prompt-level enrichments (HFST/HTSFG) that the reviewer asked about.
- **HFST feature budget.** Following Eq. 3, the appended expansion terms are truncated to the backbone's feature budget F_max=100 (the faithful analogue of TabSwift's fixed 100 input slots); real feature columns always take priority so the raw table is preserved intact.
- **Environment (pinned for reproducibility).** `tabpfn==2.0.9` (openly downloads the `tabpfn-v2` checkpoints from HuggingFace, no license token needed), `torch==2.6.0+cu124` (cu124 wheels retain the V100/CC-7.0 kernels that TabPFN's default cu13x torch drops), `scikit-learn==1.6.1`, `numpy==1.26.4`. See `requirements_rebuttal.txt`. Runs one worker per visible GPU; wall-clock ~1h on 8xV100.