

Procrustes-DS (feedback-refined) OOD Detection Report -- FULL CIFAR-100 benchmark

Setup

- **ID dataset:** CIFAR-100 (balanced), auto-downloaded via torchvision
- **Backbone:** IN21K-ViT-B/16 (timm `vit_base_patch16_224` , ImageNet-21k pre-trained)
- **Fine-tuning:** AdaptFormer PEFT, LogitAdjusted loss, 10 epochs, lr=0.01, batch=64, seed=0 (identical to the X-Maha baseline; Procrustes-DS is post-hoc and reuses this checkpoint)
- **OOD datasets (FULL, 6 of 6):** Texture, SVHN, CIFAR-10, Tiny ImageNet, LSUN, Places365 -- loaded via the SCODD benchmark (`id_name=cifar100`), exactly as the released X-Maha code, so the numbers are directly comparable to every baseline in the paper's Table 1.

Feedback-driven redesign (what changed vs. the previous attempt)

#	Feedback finding	Redesign in this script
1	HSKP weights collapsed to near-uniform (0.11-0.13)	Class-aware Fisher-discriminability weighting <code>w_l ~ trace_l * (S_b/S_w)_l^2</code> -- genuinely non-uniform
2	Orthogonal Procrustes transport gave +0.01%	Removed -- features blended directly
3	Feature-level nullspace gating wrecked near-OOD	Off-manifold residual used only at score level via an asymmetric gate <code>min(0, z-theta)</code>
4	Fixed elastic-net <code>lambda0=0.1</code> catastrophic (variance ~1e-3)	Scale-matched shrinkage <code>Sigma <- (1-s)Sigma + s(trSigma/d)I</code> (scale-invariant)
5	Sigmoid-DS collapses to a linear sum, cannot gate	Asymmetric additive log-evidence fusion with per-source reliabilities

ID classification accuracy

- CIFAR-100 top-1 accuracy: **92.95%** (paper Table 7: 93.47%)