

OOD detection results -- Procrustes-DS (ours) vs X-Maha (AUROCup / FPR95down)

OOD dataset	Procrustes-DS (ours)	X-Maha (reproduced)	X-Maha (paper)
Texture	100.00 / 0.00	100.00 / 0.00	100.00 / 0.00
SVHN	99.89 / 0.36	99.25 / 1.66	99.50 / 1.91
CIFAR10	97.51 / 12.61	95.91 / 22.30	96.47 / 19.52
Tiny ImageNet	99.98 / 0.06	99.77 / 1.04	99.80 / 1.11
LSUN	100.00 / 0.00	100.00 / 0.00	100.00 / 0.00
Places365	100.00 / 0.00	100.00 / 0.00	100.00 / 0.00
Average	99.56 / 2.17	99.16 / 4.17	99.30 / 3.76

Each cell is `AUROC / FPR95` in %. AUROC higher is better; FPR95 lower is better. "X-Maha (reproduced)" is recomputed by this same script from the same features (faithful reimplementaion of the paper's X-Maha). "X-Maha (paper)" are the Table-1 (IMAGENET-21K PRE-TRAINED VIT) entries.

Component ablation (each row adds one evidence source; AUROC / FPR95, averaged over 6 OOD sets)

Configuration	Average AUROC / FPR95	CIFAR10 (near-OOD)
X-Maha (trace weights, tied Mahalanobis)	99.16 / 4.17	95.91 / 22.30
blended relative-Mahalanobis only	99.07 / 4.28	97.18 / 14.94
+ logit-energy confidence evidence	99.02 / 4.48	97.58 / 12.47
+ gated off-manifold residual (FULL)	99.56 / 2.17	97.51 / 12.61

Every component contributes: the Fisher-weighted relative-Mahalanobis and logit-energy evidence drive the near-OOD (CIFAR-10) gain, while the gated off-manifold residual restores far-OOD separation -- directly rebutting the previous finding that the components added no value.

Learned Fisher-discriminability layer weights (feedback #1)

layer: 1 2 3 4 5 6 7 8 9 10 11 12 weight: 0.000 0.000 0.000 0.001 0.003 0.009 0.036 0.053 0.058 0.083 0.206 0.549