

Unlike the near-uniform HSKP softmax, this weighting is strongly non-uniform and class-aware.

Table-1 drop-in row (Procrustes-DS, CIFAR-100 ID, IN21K ViT)

Method	Texture	SVHN	CIFAR10	Tiny ImageNet	LSUN	Places365	Average
X-Maha (paper)	100.00 / 0.00	99.50 / 1.91	96.47 / 19.52	99.80 / 1.11	100.00 / 0.00	100.00 / 0.00	99.30 / 3.76
Procrustes-DS (ours)	100.00 / 0.00	99.89 / 0.36	97.51 / 12.61	99.98 / 0.06	100.00 / 0.00	100.00 / 0.00	99.56 / 2.17

Values are `AUROC / FPR95` (%).

Summary

- **Average AUROC:** Procrustes-DS 99.56 vs X-Maha repro 99.16 vs X-Maha paper 99.30.
- **Average FPR95:** Procrustes-DS 2.17 vs X-Maha repro 4.17 vs X-Maha paper 3.76.
- The refined method improves average FPR95 by **1.99pp** over the reproduced X-Maha and **1.58pp** over the paper, with the largest gain on the hardest near-OOD set CIFAR-10 (FPR95 12.61 vs paper 19.52).

How to reproduce

```
cd tasks/x_maha/logs/code_final_refine CUDA_VISIBLE_DEVICES=0 python final.py
```

The script reuses the AdaptFormer-PEFT checkpoint fine-tuned by `reproduce_xmaha.py` (re-trains it with the identical config if absent), extracts the 12 L2-normalised layer features for CIFAR-100 train/test and all 6 SCOOD OOD sets, then scores both Procrustes-DS and the X-Maha baseline and writes this report.