

# GIT-Training

## Agenda

### 1. Geschichten / Grundlagen

- [GIT Pdf](#)

### 2. Commands (with tips & tricks)

- [git add + Tipps & Tricks](#)
- [git commit](#)
- [git log](#)
- [git config](#)
- [git show](#)
- [Needed commands for starters](#)
- [git branch](#)
- [git checkout](#)
- [git merge](#)
- [git tag](#)

### 3. Advanced Commands

- [git reflog](#)
- [git reset - Back in Time](#)

### 4. Tips & tricks

- [Beautified log](#)
- [Change already committed files and message](#)
- [Best practice - Delete origin, tracking and local branch after pull request/merge request](#)
- [Einzelne Datei auschecken](#)
- [Always rebase on pull - setting](#)
- [Arbeit mit submodules](#)
- [Integration von Änderungen \(commits, einzelne Dateien\) aus anderen commits in den Master](#)
- [Fix conflict you have in merge-request \(gitlab\)](#)
- [SETUP.sql zu setup.sql in Windows \(Groß- und Kleinschreibung\)](#)
- [Force specific commit message](#)
- [Alle Dateien, die sich geändert haben anzeigen z.B. heute](#)

### 5. Exercises

- [merge feature/4712 - conflict](#)
- [merge request with bitbucket](#)

### 6. Snippets

- [publish lokal repo to server - bitbucket](#)
- [failure-on-push-fix](#)
- [failure-on-push-with-conflict](#)

### 7. Extras

- [Best practices](#)
- [Using a mergetool to solve conflicts](#)

## 8. Help

- [Help from commandline](#)

## 9. subtrees

- [subtrees](#)

## 10. Authentication

- [Work with different credentials](#)

## 11. Documentation

- [GIT Pdf](#)
- [GIT Book EN](#)
- [GIT Book DE](#)
- [GIT Book - submodules](#)
- [GIT Guis](#)
- [Third Party Tools](#)
- [Specification Conventional Commits](#)
- <https://www.innog.com/de/talks/2019/05/commit-message-101/>
- <https://github.com/GitAlias/gitalias/blob/main/gitalias.txt>
- <https://education.github.com/git-cheat-sheet-education.pdf>

# Backlog

## 1. Installation

- [GIT auf Ubuntu/Debian installieren](#)
- [GIT unter Windows installieren](#)

## Geschichten / Grundlagen

### GIT Pdf

- <http://schulung.t3isp.de/documents/pdfs/git/git-training.pdf>

## Commands (with tips & tricks)

### git add + Tipps & Tricks

#### Trick with -A

```
## only adds from the folder you are in recursively
## but not above (you might miss some files, when you are in a subfolder
git add .

### Fix -A
## adds everything no matter in which folder you are in your project
git add -A
```

### git commit

#### commit with multiple lines on commandline (without editor)

```
git commit -am "New entry in todo.txt

* nonsense commit-message because of missing text-expertise"
## enter on last line
```

#### Change last commit-message (description)

```
git commit --amend
## now you can change the description, but you will get a new commit-id
```

### git log

#### Show last x entries

```
##
## git log -x
## Example: show last 2 entries
git log -2
```

#### Show all branches

```
git log --all
## oder wenn alias alias.lg besteht:
## git lg --all
```

## Show first log entry

```
## Step 1 - log needs to only show one line per commit
git log --oneline --reverse

## Step 2: combine with head
git log --oneline --reverse | head -1
```

## Multiple commands with an alias

```
git config --global alias.sl '!git log --oneline -2 && git status'
```

## git config

### How to delete an entry from config

```
## Important: Find exact level, where it was added --global, --system, --local
## test before
## should contain this entry
git config --global --list

git config --unset --global alias.log
```

## git show

### Show information about an object e.g. commit

```
git show <commit-ish>
## example with commit-id
git show 342a
```

## Needed commands for starters

```
git add -A
git status
git log // git log -4 // or beautified version if setup as alias git lg
git commit -am "commit message" // "commit message" can be freely chosen
## for more merge conflict resolution use only
git commit # to not change commit - message: must be message with merge
## the first time
git push -u origin master
## after that
git push
git pull
```

## git branch

### Create branch based on commit (also past commit)

```
git branch lookaround 5f10ca
```

## Delete unmerged branch

```
git branch -d branchname # does not work in this case  
git branch -D branchname # <- is the solution
```

## git checkout

### Checkout (change to) existing branch

```
git checkout feature/4711
```

### Checkout and create branch

```
## Only possible once  
git checkout -b feature/4712
```

### File aus einem Commit holen (oder HEAD)

```
git checkout HEAD -- todo.txt
```

## git merge

### Merge without conflict with fast-forward

```
## Disadvantage: No proper history, because only one branch visible in log  
## after fast-forward - merge  
  
## Important that no changes are in master right before merging  
git checkout master  
git merge feature/4711
```

### Merge (3-way) also on none-conflict (no conflicts present)

```
git merge --no-ff feature/4711
```

## git tag

### Creating tags, Working with tags

```
## set tag on current commit -> HEAD of branch  
git tag -a v1.0 -m "my message for tag"  
## publish  
git push --tags  
  
## set on specific commit  
git tag -a v0.1 -m "Initial Release" a23c
```

```
## checkout files of a specific tag
git checkout v0.1
## or
git checkout tags/v0.1
```

## git delete tag

```
## Tag local löschen und danach online löschen
git tag -d test.tag
git push --delete origin test.tag

## Tag online löschen und danach lokal
## Schritt 1: Über das interface (web) löschen
## Schritt 2: aktualisieren
git fetch --prune --prune-tags
```

## Misc

```
## Fetch new tags from online
git fetch --tags

## Update master branch (rebase) and fetch all tags in addition from online
git checkout master
git pull --rebase --tags
```

## Advanced Commands

### git reflog

#### command

- show everything you (last 30 days), also stuff that is not visible in branch anymore

#### Example

```
git reflog
```

### when many entries a pager like less (aka man less) will be used

```
## you can get out of the page with pressing the key 'q'
```

### git reset - Back in Time

#### Why ?

- Back in time -> reset
- e.g. git reset --hard e2d5
- attention: only use it, when changes are not published (remotely) yet.
- → It is your command, IN CASE your are telling yourself, omg, what's that, what did i do here, let me undo that

## Example

```
git reset --hard 2343
```

## Tips & tricks

### Beautified log

### Walkthrough

```
git config --global alias.lg "log --color --graph --pretty=format:'%Cred%h%Creset \
-%C(yellow)%d%Creset %s %Cgreen(%cr) %C(bold blue)<%an>%Creset'"
```

## PRETTY FORMATS

- all documented in git help log (section PRETTY FORMAT)
- <https://git-scm.com/docs/git-log>

## Change already committed files and message

```
## Walkthrough
touch newfile.txt
git add .
git commit -am "new file added"

## Ups forgotten README
touch README
git add .
git commit --amend # README will be in same commit as newfile.txt
## + you can also changed the commit message
```

## Best practice - Delete origin,tracking and local branch after pull request/merge request

```
## After a succesful merge or pull request und gitlab / github
## Follow these steps for a succesful cleanup

## 1. Delete feature branch in web interface (e.g. gitlab / github)
## e.g. feature/4811

## 2. Locally on your system prune the remote tracking branch
git fetch --prune

## 3. Switch to master or main (depending on what you master branch is)
git checkout master

## 4. Delete local branch
git branch -d feature/4811
```

## Einzelne Datei auschecken

## aus anderem Commit

```
## aus commit 11ed

git checkout 11ed -- todo.txt
## unterverzeichnis
git checkout 11ed -- tmp/test.txt
```

## ...und direkt umbenennen

```
## datei todo.txt aus 11ae -> Inhalt anzeigen und direkt neue datei umleiten
git show 11ae^:todo.txt > todoneu.txt
```

## Always rebase on pull - setting

```
git config branch.master.rebase true
```

## Arbeit mit submodules

### Best practice

```
clone repo use for submodule seperately
(in seperate folder)
if you want to change it
```

## Updating commands for updating subfolder

```
git submodule update --remote
## use other branch from submodule then master
git config -f .gitmodules submodule.DbConnector.branch stable
```

## Ref.

- <https://git-scm.com/book/de/v2/Git-Tools-Submodule>

## Integration von Änderungen (commits, einzelne Dateien) aus anderen commits in den Master

### Walkthrough

```
## 1. Schritt - erstellen integrationsbranch von dev/staging branch
git checkout -b integrate/1

## Möglichkeit 1: cherry-pick - komplette commit inkl. aller Änderungen mit reinnehmen
## Hier wird gemerged: Gemerged
## Evtl. Konflikt, den muss ich dann lösen
git cherry-pick c5906c0

## Möglichkeit 2: Einzelne files aus commit: Achtung, wenn im Work-Directory
```



```

## bereits vorhanden überschrieben
## commit wird bereits durchgeführt
git checkout ddb0 -- armin3.txt

## Möglichkeit 3: cherry-pick ohne commit
git cherry-pick -n 4497
git status
## alle files rausnehmen, die wir nicht haben möchten, wie folgt.
git restore --staged agenda.txt
## Achtung, jetzt sind diese so im Working Directory als unstaged
## d.h. die alte Version aus dem letzten Commit holen
git checkout HEAD -- agenda.txt

## 3. Schritt
## Änderungen commiten
git commit -am "Revised version"

## 4. Nach online pushed
git push -u origin integrate/1

## 5. Merge request in gitlab: integrate/1 -> master
## und dann mergen online

```

## Fix conflict you have in merge-request (gitlab)

### Walkthrough

```

## create feature-branch and worked on it
git checkout -b feautre/4711
## ... changes
git add .; git commit -am "new feature"
## pushed branch online
git push -u origin feature/4711
## then created merge online
## feature/4711 --> master

##### TaDa - It was NOT possible to merge because of conflict
## unfortunately advice on gitlab/bitbucket is not worth the dime

## locally, update you feature-branch like so
## NO git pull --rebase please, otherwise, you have to redo you merge_request
afterwards
## get changes from master
git pull origin master

## fix conflicts
git add .
git commit

## push new version of feature - branch online
git push

```

```
## now you can merge in the merge-request interface on gitlab
```

## SETUP.sql zu setup.sql in Windows (Groß- und Kleinschreibung)

### Problem

- Windows erkennt in git keine Änderung der Groß- und Kleinschreibung
- Workaround: `git rm --cached; git commit -am`

### Walkthrough

```
touch SETUP.sql
git add .; git commit -am "SETUP neu"

## Ups, verschrieben ! Was jetzt ?
git rm --cached SETUP.sql # Datei wird aus git rausgenommen
git commit -am "und dingfest machen"
## Beweis
git show HEAD # letztes commit mit Änderungen anzeigen

## Jetzt auf ein Neues
## oder im Explorer
mv SETUP.sql setup.sql
git add .; git commit -am "setup.sql neu"
git show HEAD
```

## Force specific commit message

### Basics

- Done on Server-Side
- Specific to server - Software (like github/gitlab)

### Example - pre-receive-hook

- <https://git-scm.com/book/en/v2/Customizing-Git-An-Example-Git-Enforced-Policy>

### Ref:

- [https://docs.gitlab.com/ee/user/project/repository/push\\_rules.html](https://docs.gitlab.com/ee/user/project/repository/push_rules.html) (not free)
- [https://docs.gitlab.com/ee/administration/server\\_hooks.html](https://docs.gitlab.com/ee/administration/server_hooks.html)

## Alle Dateien, die sich geändert haben anzeigen z.B. heute

### Files

```
git log --after="2015-11-05T16:36:00-02:00" --before="2022-09-28" --pretty=format:"" --name-only | sort -u
```

### Mit loop

```
for i in $(git log --after="2022-09-26" --before="2022-09-27" --pretty=format:"" --name-only | sort -u); do git log -- $i; done
```

## Änderungen einer datei

```
git log --after="2022-09-26" --before="2022-09-27" --pretty=format:"" --follow -p --  
todo.txt
```

## Exercises

### merge feature/4712 - conflict

#### Exercise

```
1. You are in master-branch  
2. Checkout new branch feature/4712  
3. Change line1 in todo.txt  
4. git add -A; git commit -am "feature-4712 done"  
5. Change to master  
6. Change line1 in todo.txt  
7. git add -A; git commit -am "change line1 in todo.txt in master"  
8. git merge feature/4712
```

### merge request with bitbucket

```
## Local  
git checkout -b feature/4822  
ls -la  
touch f1.txt  
git add .  
git commit -am "f1.txt"  
touch f2.txt  
git add .  
git commit -am "f2.txt"  
git push -u origin feature/4822
```

### Online bitbucket / gitlab

```
## create merge request  
## and merge
```

### Delete branch online after merge

#### Cleanup locally

```
git fetch --prune  
git checkout master  
git branch -D feature/4822  
git pull --rebase
```

## Snippets

## publish lokal repo to server - bitbucket

```
# Step 1: Create repo on server without README and .gitignore /set both to NO when
creating

# Step 2: on commandline locally
cd /path/to/repo
git remote add origin https://erding2017@bitbucket.org/erding2017/git-remote-
jochen.git
git push -u origin master

# Step 3: for further commits
echo "test" > testdatei
git add .
git commit -am "added testdatei"
git push
```

## failure-on-push-fix

```
## Step 1: push produces error
## you have done git push -u origin master the last to setup remote tracking branch by
option -u
git push
Password for 'https://erding2017@bitbucket.org':
To https://bitbucket.org/erding2017/git-remote-jochen.git
 ! [rejected] (fetch first)
error: failed to push some refs to 'https://erding2017@bitbucket.org/erding2017/git-
remote-jochen.git'
hint: Updates were rejected because the remote contains work that you do
hint: not have locally. This is usually caused by another repository pushing
hint: to the same ref. You may want to first integrate the remote changes
hint: (e.g., 'git pull ...') before pushing again.
hint: See the 'Note about fast-forwards' in 'git push --help' for details.
## Step 2: Integrate changes from online
git pull
## Step 2a: Editor opens and you need to save and ext (without changing anything)

## Step 3: re-push
git push
```

## failure-on-push-with-conflict

## Failure push

```
## Step 1: push produces error
## you have done git push -u origin master the last to setup remote tracking branch by
option -u
git push
Password for 'https://erding2017@bitbucket.org':
To https://bitbucket.org/erding2017/git-remote-jochen.git
```

```

! [rejected] (fetch first)
....
## Step 2: Integrate changes from online
git pull

## Step 3: Solve conflict
Auto-merging agenda.txt
CONFLICT (content): Merge conflict in agenda.txt
Automatic merge failed; fix conflicts and then commit the result.
kurs@ubuntu-tr01:~/training$ git status
On branch master
Your branch and 'origin/master' have diverged,
and have 1 and 1 different commits each, respectively.
    (use "git pull" to merge the remote branch into yours)

## Step 3a: Open file agenda.txt
## Decide for which version
## - remove all <<<<< and ===== and >>>>>>>> - lines

## Step 3b: then: save + exit from editor

## Step 3c: mark resolution
git status
git add todo.txt

## Step 3d:
git status
## as written there
git commit

## Step 4: re-push
git push

```

## recipe

```

git push # failure
git pull
git add todo.txt
git commit
git push

```

## Extras

### Best practices

- Delete branches, not needed anymore
- `git merge --no-ff ->` for merging local branches (to get a good history from local)
- from online: `git pull --rebase` // clean history from online, not to many branches
- nur auf einem Arbeiten mit max. 2 Teilnehmern, wenn mehr feature-branch

## Teil 2:

- Be careful with git commands that change history.
  - never change commits, that have already been pushed
- Choose workflow wisely
- Avoid git push -f in any case // should not be possible
- Disable possibility to push -f for branch or event repo

## Using a mergetool to solve conflicts

### Meld (Windows) - Install

- <https://meldmerge.org/>

### Find out if mergetool meld is available

```
git mergetool --tool-help
```

### Configure, when it is found by mergetool --tool-help

```
## you have to be in a git project
git config --global merge.tool meld
git config --global diff.tool meld
git config --global mergetool.keepBackup false
git config --list
```

### If not found bei mergetool --tool-help :: Configuration in Git for Windows (git bash)

```
## you have to be in a git project
git config --global merge.tool meld
git config --global diff.tool meld
## Should be on Windows 10
git config --global mergetool.meld.path
"/c/Users/Admin/AppData/Local/Programs/Meld/Meld.exe"
## sometimes here
git config --global mergetool.meld.path "/c/Program Files/Meld/Meld.exe"
## do not create an .orig - file before merge
git config --global mergetool.keepBackup false
```

### How to use it

```
## when you have conflict you can open the mergetool (graphical tool with )
git mergetool
```

## Help

### Help from commandline

### On Windows

```
## on git bash enter
git help <command>
## e.g.
git help log

## --> a webpage will open with content
```

## subtrees

### subtrees

#### Prerequisites - Existing local repo

```
## in der bash
cd ..
cp -a training training-neu
cd training-neu
```

#### Walkthrough

```
git remote add -f training-git https://github.com/jmetzger/training-git.git
## weird, but needed
git status
git subtree add --prefix training training-git main --squash
```

#### Updating

```
git fetch training-git main
git subtree pull --prefix training training-git main --squash
```

#### Push

```
git subtree push --prefix=training training-git main
```

#### Ref.

- <https://www.atlassian.com/git/tutorials/git-subtree>

## Authentication

#### Work with different credentials

#### Ref:

<https://de.linkedin.com/pulse/mehrere-gitlabgithub-accounts-bzw-ssh-keys-zum-host-mit-mindermann>

## Documentation

#### GIT Pdf

- <http://schulung.t3isp.de/documents/pdfs/git/git-training.pdf>

## **GIT Book EN**

- <https://git-scm.com/book/en/v2>

## **GIT Book DE**

- <https://git-scm.com/book/de/v2>

## **GIT Book - submodules**

- <https://git-scm.com/book/de/v2/Git-Tools-Submodule>

## **GIT Guis**

- <https://git-scm.com/downloads/guis/>

## **Third Party Tools**

## **Continuous Integration / Continuous Deployment (CI/CD)**

```
## Test often / Test automated (CI)

* Jenkins
* Github Actions
* Git Webhooks

## Publish new versions frequently (CD)

* Jenkins
* Github Action
* Git Webhooks
```

## **Specification Conventional Commits**

- <https://www.conventionalcommits.org/en/v1.0.0/>

## **Installation**

### **GIT auf Ubuntu/Debian installieren**

#### **Installation**

```
sudo apt update
sudo apt install git
```

## **Language to english please !!**

```
sudo update-locale LANG=en_US.UTF-8
su - kurs

## back to german

sudo update-locale LANG=de_DE.UTF-8
su - kurs
```



```
## Reference:
https://www.thomas-krenn.com/de/wiki/Locales_unter_Ubuntu_konfigurieren

## update-locale does a change in
$ cat /etc/default/locale
LANG=en_US.UTF-8
```

## **Git unter Windows installieren**

- <https://git-scm.com/download/win>