

Phase 17 Demo : Semicolon - Separated Bindings

Example 1 : Two bindings

Simple case with two binding groups:

$$\forall x: N \bullet \forall y: N \bullet x + y > 0$$

Example 2 : Three bindings

Three levels of nesting:

$$\forall x: T \bullet \forall y: U \bullet \forall z: V \bullet x = y$$

Example 3 : Mixed comma and semicolon

First quantifier has multiple variables with shared domain:

$$\forall x, y: N \bullet \forall z: N \bullet x + y = z$$

Example 4 : Real - world example from Solution 41

$$\forall r: \text{ran } records \bullet \forall i1, i2: \text{dom } r \bullet i1 \neq i2 \Rightarrow \text{true}$$

Example 5 : Conditional with semicolon bindings

Combining Phase 16 and Phase 17:

$$\forall x: N \bullet \forall y: N \bullet (\text{if } x > y \text{ then } x \text{ else } y)$$

Example 6 : Nested mu operator

Definite description with multiple bindings:

$$(\mu p: \text{ran } hd \bullet \mu q: \text{ran } hd \bullet p \neq q \text{--- p.2 } \text{!} \text{ q.2})$$

Example 7 : With exists quantifier

Multiple bindings with exists:

$$\exists x: N \bullet \exists y: N \bullet x > y \wedge y > 0$$