

PS2Win

Software Requirement Specification

Keep Your Time

João Girão; Mário Oliveira
25-04-2013

Content

1.	Introduction	1
1.1.	Purpose	1
1.2.	Vision of the Solution	1
1.3.	Major Features	1
1.4.	Assumptions and Dependencies	1
1.5.	References.....	1
2.	Use Cases Model	2
2.1.	Actors	3
2.2.	Use Cases.....	3
2.2.1.	UC-001-Create Task.....	3
2.2.2.	UC-002-Edit task.....	4
2.2.3.	UC-003-Delete task	5
2.2.4.	UC-004-Start time tracking	5
2.2.5.	UC-005-Stop Time	6
2.2.6.	UC-006-ChangeRunningTask.....	7
2.2.7.	UC-007-ChangeTask Status	7
2.2.8.	UC-008-Answer to Inactivity	8
2.2.9.	UC-011-Configure System	9
2.2.10.	UC-012-Configure Inactive Time	9
2.2.11.	UC-013-Configure Shortcuts	10
2.2.12.	UC-014-Visualize Task Details	11
2.2.13.	UC-015-Filter Inactive Tasks.....	11
2.2.14.	UC-016-Export Data	11
2.2.15.	UC-017 - Show/Hide tasks list	12
3.	Functional Requirements	13
3.1.	1CT-001:Task.create.....	13
3.2.	1CT-002:Task.create.validate	13
3.3.	1CT-003:Task.create.validate.notEqual	13
3.4.	1CT-004:Task.create.AutoComplete	13
3.5.	2ET-001: EditTask.....	13

3.6.	2ET-002: EditTask.save.....	14
3.7.	2ET-003: EditTask.save.true	14
3.8.	2ET-004: EditTask.save.false	14
3.9.	3DT-001: DeleteTask	14
3.10.	4STT-001: StartTime.....	14
3.11.	5ST-001: StopTime	14
3.12.	6CT-001: ChangeRunningTask.....	15
3.13.	6CT-002: ChangeRunningTask.CombinationFail	15
3.14.	6CT-003: ChangeRunningTask.Success	15
3.15.	7CT-001: ChangeTask Status	15
3.16.	8AI-001: Inactivity	15
3.17.	8AI-002: Inactivity.Notify	16
3.18.	8AI-003: Inactivity.Notify.Adds	16
3.19.	8AI-003: Inactivity.Notify.Ignores	16
3.20.	12CIT-001: ConfigureInactiveTime.....	16
3.21.	12CIT-002: ConfigureInactiveTime.Validate	16
3.22.	12CIT-003: ConfigureInactiveTime.Validate.False	16
3.23.	12CIT-004: ConfigureInactiveTime.Validate.True	17
3.24.	13CS-001: ConfigureShortcuts	17
3.25.	13CS-002: ConfigureShortcuts.Validate	17
3.26.	13CS-003: ConfigureShortcuts.Validate.True	17
3.27.	13CS-004: ConfigureShortcuts.Validate.False.....	17
3.28.	14VTD-001: TaskDetails	17
3.29.	14VTD-002: TaskDetails.Calculate.....	18
3.30.	15FIT-001: FilterTask.....	18
3.31.	15FIT-002: FilterTask.ShowAll.....	18
3.32.	16ED-001: ExportData.....	18
3.33.	16ED-002: ExportData.Export	18
3.34.	17TL-001: TaskList	18
3.35.	17TL-002: TaskList.DefaultSort	19
3.36.	17TL-003: TaskList.DefaultSort.CurrentTask.....	19
3.37.	17TL-004: TaskList.Sort	19
3.38.	17TL-005: TaskList.TotalTime	19

3.39.	17TL-006: TaskList.Today	19
3.40.	17TL-007: TaskList.StopDate	19
3.41.	17TL-008: TaskList.Actions	20
4.	Interface Requirements	20
4.1.	UI-001: MainWindow	20
4.2.	UI-002: Buttons that are always active	20
4.3.	UI-003: Expand list button	20
4.4.	UI-004: TextBox filled with a new task name	20
4.5.	UI-005: TextBox filled with Existence task name	21
4.6.	UI-006: TextBox with running task	21
4.7.	UI-007: Clicking in view details button	21
4.8.	UI-008: Clicking in edit button	21
4.9.	UI-009: Clicking in configuration button	21
4.10.	UI-010: Visual distinction between active and inactive tasks	22
4.11.	UI-011: Modal Window	22
5.	Performance Requirements	22
5.1.	PR-001: Startup of the application	22
5.2.	PR-002: Transition time	22
	Appendix A: Data Dictionary	23

Images

Figure 1: Use Case Diagram	2
----------------------------------	---

Tables

Table 1: List of Contributors	iv
Table 2: Version history	iv

Authors and Contributors			
Date	Name	Contacts	Contribution
25-04-2013	João Girão	a21170831@alunos.isec.pt	Author
	Mário Oliveira	a21170292@alunos.isec.pt	
25-04-2013	Carla Machado	a21170460@alunos.isec.pt	Contributor

Table 1: List of Contributors

Revision History					
Date	Description	Author	Version	Approvers	State
25-04-2013	Creation Document: initial draft	João Girão & Mário Oliveira	0.1		Draft
25-04-2013	Adding the use cases and requirements exported from Enterprise Architect	Carla Machado	0.2		Draft
26-04-2013	Revision of text and English	Carla Machado	0.3		Draft
26-04-2013	Formatting Document and change state	João Girão	0.4		Ready for Revision
26-04-2013	Some changes due to input from Rui Ganhoto	Carla Machado	0.5		Ready for Revision
03/05/2013	Some changes based on previous inspection	João Girão & Mário Oliveira	0.6		Ready for Approval

Table 2: Version history

1. Introduction

1.1. Purpose

The purpose of this document is the presentation of the use cases and requirements of the application Keep Your Time.

All the functionalities will be identified with recourse to the definition of use cases and requirements that intend to reflect the way the application should be used and how the system should perform.

1.2. Vision of the Solution

The application to be developed will be composed in the first release of one component:

- Desktop: for task time management;

The application will allow the users to manage their time in a structured way allowing task identification both of the ongoing one or in case of idle time detection decide whether to add the time to the current task or ignore the time. . Furthermore the application will provide a history of performed tasks.

The application will be developed using .NET platform and C#. The desktop component will have the functional interface where the user can add tasks easily and view the tasks historical.

1.3. Major Features

FE-1: Adding, editing and deleting tasks;

FE-2: Inactivity alerts during task;

FE-3: Registering and timing individual tasks;

FE-4: Exporting the application data;

1.4. Assumptions and Dependencies

AS-1: The computer will have a Windows OS with at least the Vista version;

AS-2: The computer will have framework .Net 4.5;

This application doesn't have any dependencies with external software;

1.5. References

- Mockups: "*KeepYourTime_Mockups.pdf*";

2. Use Cases Model

In this section the identification and description of the actors related to the application and the different use cases will be presented. These actors and use cases can be seen in the use case diagram show in Figure 1.




Figure 1: Use Case Diagram

The use cases UC-009 and UC-010 don't exist in the diagram because they are in the deprecated state.

2.1. Actors

User: The user with full access to the application and its features.

2.2. Use Cases

2.2.1. UC-001-Create Task

The user creates a new task. The user inserts the name for the task and selects the option of creating and starting the task. The task is created in the database, added to the tasks list and the timer starts.

[MKU001: Main Window; MKU001.1: Main Window (status)]

Basic Path

Creates and starts the task:

¹ The user inserts the task name and selects the option to create the task. ² The user inserts the task name and starts the task. ³ The system inserts the task in the database and adds the task to the tasks list [Invokes: UC-004-Start time tracking].

Exceptions

(at ³)

An error occurs when inserting the data in the database. The application returns an error message.

2.2.2. UC-002-Edit task

The user selects a task to edit. The edition form is presented to the user that makes the alterations and saves the changes.

[MKU003: Edit Task]

Basic Path

Editing Task:

¹ The user click in the edit button to edit a task. ² The system presents the edition form to the user. ³ The user makes the changes and saves them. ⁴ The system updates the information in the database and the tasks list.

Alternate Paths

Editing tasks:

¹ The user click in the details button to view the task's information. ² The system presents the details form. ³ The user click in the edit button to edit the task. ⁴ The system presents the edition form to the user. ⁵ The user makes the changes and saves them. ⁶ The system updates the information in the database and the tasks list.

Cancel Edition:

(at ³)

⁴The user cancels the edition. ⁵The system closes the edition form.

Exceptions

(at ⁴)

An error occurs when inserting the data in the database. The application returns an error message.

Pre-condition

Existence of tasks

2.2.3.UC-003-Delete task

The user selects one task and selects the remove button. The task is removed from the tasks list and all the information related to the task is removed from the database.

[MKU001: Main Window]

Basic Path

Delete task:

¹ The user click in the delete button to delete a task. ² The system presents a message to confirm the operation. ³ The user accepts the operation. ⁴ The system deletes the task from the database and updates the tasks list.

Alternate Path

Cancel deleting:

(at ³)

¹The user doesn't accept the operation. ²The system cancels the operation.

Exceptions

(at ²)

An error occurs when accessing the database. An error message is presented to the user.

Pre-condition

Existence of tasks

Open the tasks list

2.2.4.UC-004-Start time tracking

The user chooses a task and starts the time tracking. The system starts counting the time and presents a timer to the user.

[MKU001: Main Window; MKU001.1: Main Window (status)]

Basic Path

Starting Time:

¹ The user selects an active task and starts the time. ² The system starts the timer.

Pre-condition

Existence of tasks

2.2.5.UC-005-Stop Time

The user stops the time. The system stops the time and updates the information of the task.

[MKU001: Main Window; MKU001.1: Main Window (status)]

Basic Path

Stopping Time:

¹ The user stops the time. ² The system stops the timer and updates the task information.

Exceptions

(at ²)

³An error occurs while accessing the database. ⁴An error message must be presented to the user.

Pre-condition

There must be a task running.

2.2.6.UC-006-ChangeRunningTask

The user uses a shortcut to change the running task.

Basic Path

Existing running task:

¹ The system is tracking the time of a running task. ² The user uses a pre-defined shortcut to start timing a task. ³ The system stops the time of the current running task and updates the task information. The system selects the task assigned to the shortcut the user pressed and starts the timer.

Alternate Paths

No running task:

(at ¹)

The user presses a pre-defined shortcut to start a task. ³ The system selects the task and starts the timer.

Exceptions

(at ³)

An error occurs while accessing the database. An error message must be presented to the user.

Pre-condition

There must be more than one active task

There must be a match between the active tasks and the used shortcut

2.2.7.UC-007-ChangeTask Status

The user selects a task from the list and selects the option to change the task status between Active and Inactive

[MKU001: Main Window]

Basic Path

Activate Task:

¹ The user selects the task to change the status and selects Activate/Inactivate. ² The system changes the status of the task and updates the database information.

Exceptions

(at ²)

An error occurs when updating the information in the database. The application returns an error message to the user.

Pre-condition

Existence of tasks

2.2.8.UC-008-Answer to Inactivity

The system must detect inactivity times according with the system configuration and prompt the user for a response.

[MKU004: Configurations; MKU005: Alert Inactivity]

Basic Path

Adding time:

¹ The system detects an inactivity time. The system stops the timer and prompts the user for an action. ² The user adds the time to the running task. ³ The system adds the time to the running task. ⁴ The system presents the main window and updates the information in the database.

Alternate Paths

Ignore time:

(at ¹)

² The user ignores the time. ³ The system ignores the time.

Exceptions

(at ³)

An error occurs when updating the information in the database. The application returns an error message to the user.

Pre-condition

There must be a task running.

The user hasn't interaction with the system during the defined time.

2.2.9. UC-011-Configure System

The user changes the system configurations.

[MKU004: Configurations]

Basic Path

Configure:

¹ The user opens a configuration window. ² The system presents the configuration window.

³ The user changes the definitions and saves. ⁴ The system saves the changes and applies the changes to the system.

Alternate Paths

Cancel Edition:

(at ³)

⁴The user closes the window without saving.

Exceptions

(at ⁴)

An error occurs while accessing the database. An error message must be presented to the user.

2.2.10. UC-012-Configure Inactive Time

The user accesses the configurations page and activates the configuration system and sets the inactivity time to a value between 1 and 60 minutes.

[MKU004: Configurations]

Basic Path

Activate Inactivity:

¹ The user accesses the configuration page and activates the inactivity alert. ² The system activates the configuration of inactivity time. ³ The user inserts a time between 1 and 60 minutes. ⁴ The system updates the information in the database and puts the new configuration in effect.

Alternate Paths

Deactivate inactivity time:

(at ¹)

² The user accesses the configuration page and deactivates the inactivity alert. ³ The system blocks the configuration of inactivity time. ⁴ Updates the database information and puts the new configurations in effect.

Exceptions

(at ⁴)

An error occurs while accessing the database. An error message must be presented to the user.

2.2.11. UC-013-Configure Shortcuts

The user accesses the configuration page and defines shortcuts for changing between five chosen tasks

[MKU004: Configurations]

Basic Path

Configure Shortcuts:

¹ The user accesses the configurations page and defines the shortcuts by defining the shortcuts and the corresponding task. ² The system updates the information in the database and applies the new definitions.

Exceptions

(at ²)

If the user duplicates a task or the shortcuts, the system presents an error message.

(at ²)

An error occurs while accessing the database. An error message must be presented to the user.

Pre-condition

Existence of active tasks

2.2.12. UC-014-Visualize Task Details

The user chooses a task to view the details.

[MKU002: Task Details]

Basic Path

¹ The user clicks in the details button to view the task details. ² The system presents the task details.

Alternate Path

¹ The user expands the tasks list. (at ¹)

Exceptions

(at ²)

An error occurs while accessing the database. An error message must be presented to the user.

Pre-condition

Existence of tasks

2.2.13. UC-015-Filter Inactive Tasks

The user activates/deactivates a filter in order to see or hide the inactive tasks.

[MKU001: Main Window]

Basic Path

Present tasks list:

¹ The system presents a list of all the tasks to the user. ² The user selects the option to hide the inactive tasks. ³ The system filters the task list and only shows the active tasks.

2.2.14. UC-016-Export Data

The user selects the option corresponding to the settings. In the section settings then selects the functionality of all exporting data.

[MKU004: Configurations]

Basic Path

¹ The user selects the settings functionality. ² The system redirects the user to the settings form where an option for exporting data is available. ³ The user selects the export option. ⁴ The user chooses the path to save the exported file. ⁵ The system exports all data.

259 **Exceptions**

260 (at ⁴)

261 The system doesn't have writing permissions in the destination folder or an error occurs
262 when accessing the database. The system presents an error message to the user.

263 **Pre-condition**

264 Existence of tasks

265 **2.2.15. UC-017 - Show/Hide tasks list**

266 User presses a button to show or hide the tasks list.

267 [MKU001: Main Window]

268 **Basic Path**

269 Show Tasks List:

270 ¹ The system presents a minimal view without the tasks list. ² The user presses a button to
271 expand the window and view the task list. ³ The system expands the window and presents
272 the complete task list.

273 **Alternate Paths**

274 Hide Tasks List:

275 (at ¹)

276 ²The system presents a view with the tasks list. ³The user presses a button to hide the tasks
277 list. ⁴The system minimizes the window and stops showing the tasks list.

3. Functional Requirements

3.1. 1CT-001:Task.create

The system receives a task name from a text box. This text box allows auto complete.

Priority: High

Difficulty: High

3.2. 1CT-002:Task.create.validate

The system validates the task name.

Priority: High

Difficulty: Low

3.3. 1CT-003:Task.create.validate.notEqual

The system saves the task name in the database with an ID, name and initial date. The task is started.

Priority: High

Difficulty: Low

3.4. 1CT-004:Task.create.AutoComplete

The system analyzes the text box. When the user enters three or more characters, the system presents a set of suggested active tasks in a drop down list. The suggested task name start with the characters inserted by the user.

Priority: High

Difficulty: Medium

3.5. 2ET-001: EditTask

The system allows the edition of the fields name and description. The system allows insert, update and delete of individual times of a task.

Priority: Medium

Difficulty: Medium

3.6. 2ET-002: EditTask.save

The system validates the name and times between start date and end date

Priority: Medium

Difficulty: Medium

3.7. 2ET-003: EditTask.save.true

The system updates the task name in the database with the name, start and end date of individual times and description of a task

Priority: Medium

Difficulty: Medium

3.8. 2ET-004: EditTask.save.false

In each field, the system presents an error message "Invalid field!" and the reason.

Priority: Medium

Difficulty: Medium

3.9. 3DT-001: DeleteTask

The system deletes the selected task and updates the database. The system should ask for confirmation before deleting the task. The system only allows to delete tasks stopped.

Priority: Medium

Difficulty: Low

3.10. 4STT-001: StartTime

The system stops the current task if there is one and starts counting the time for the selected task.

Priority: High

Difficulty: Medium

3.11. 5ST-001: StopTime

The system stops the time and updates the information of the task and saves it in database.

Priority: High

Difficulty: Medium

3.12. 6CT-001: ChangeRunningTask

The system allows the change of the running task through a combination keys or stopping the current task and starting another.

Priority: High

Difficulty: High

3.13. 6CT-002: ChangeRunningTask.CombinationFail

The system plays a beep if the pressed shortcut isn't associated with a task.

Priority: High

Difficulty: High

3.14. 6CT-003: ChangeRunningTask.Success

When a task is started the system presents a brief popup to the user that disappears without user intervention.

Priority: High

Difficulty: High

3.15. 7CT-001: ChangeTask Status

The system loads all tasks from database and allows selecting them for change of status. It doesn't allow to change the status of running tasks.

Priority: Medium

Difficulty: Low

3.16. 8AI-001: Inactivity

The system verifies the user's inactivity for a period of time.

Priority: High

Difficulty: High

3.17. 8AI-002: Inactivity.Notify

The system blocks the screen and asks the user what he wants to do. The user chooses to ignore the time or add the time to the running task.

Priority: High

Difficulty: Medium

3.18. 8AI-003: Inactivity.Notify.Adds

The system adds the time to the running task.

Priority: High

Difficulty: Medium

3.19. 8AI-003: Inactivity.Notify.Ignores

The system ignores the time until last activity.

Priority: Medium

Difficulty: Low

3.20. 12CIT-001: ConfigureInactiveTime

The system receives a duration for the inactivity time if the user activated the inactivity alert.

Priority: Medium

Difficulty: Low

3.21. 12CIT-002: ConfigureInactiveTime.Validate

The system validates the inactive time field.

Priority: Medium

Difficulty: Low

3.22. 12CIT-003: ConfigureInactiveTime.Validate.False

The system presents a message with the reason it failed the validation.

Priority: Medium

Difficulty: Low

3.23. 12CIT-004: ConfigureInactiveTime.Validate.True

The system saves the inactivity time in the database.

Priority: Medium

Difficulty: Low

3.24. 13CS-001: ConfigureShortcuts

The system allows the user to associate five active tasks with keyboard shortcuts. The user selects an existing active task and a combination of keys to define the shortcut.

Priority: Medium

Difficulty: Low

3.25. 13CS-002: ConfigureShortcuts.Validate

The system validates the entered choices. The system verifies if a shortcut was entered and a task chosen. It also verifies the existence of duplicated shortcuts or tasks.

Priority: Medium

Difficulty: Low

3.26. 13CS-003: ConfigureShortcuts.Validate.True

The system saves the information into database: task name and shortcuts.

Priority: Medium

Difficulty: Low

3.27. 13CS-004: ConfigureShortcuts.Validate.False

The system presents message with the reason it failed the validation.

Priority: Medium

Difficulty: Low

3.28. 14VTD-001: TaskDetails

The system loads the selected task information from the database and presents the task name, description and the individual times list with start date, end date and time spent.

Priority: High

Difficulty: Medium

3.29. 14VTD-002: TaskDetails.Calculate

The system calculates the time spent for each individual time entry.

Priority: High

Difficulty: Medium

3.30. 15FIT-001: FilterTask

The system allows the filtering of the inactive tasks and only presents the active tasks.

Priority: High

Difficulty: Medium

3.31. 15FIT-002: FilterTask.ShowAll

The system groups the active tasks and inactive tasks in different groups.

Priority: High

Difficulty: High

3.32. 16ED-001: ExportData

The system allows the user to choose the path to save the exported file.

Priority: Medium

Difficulty: Medium

3.33. 16ED-002: ExportData.Export

The system loads all the data to be exported from the database. The data is exported to a .csv file.

Priority: Medium

Difficulty: Medium

3.34. 17TL-001: TaskList

The system allows the show/hide of the task list. This list can be sorted by name, total time, spent time of day or stop date.

Priority: High

Difficulty: Medium

3.35. 17TL-002: TaskList.DefaultSort

The system sorts the tasks by descending order of stop date.

Priority: High

Difficulty: Medium

3.36. 17TL-003: TaskList.DefaultSort.CurrentTask

The system shows at the top of the list the current task followed by the others.

Priority: High

Difficulty: Medium

3.37. 17TL-004: TaskList.Sort

The system sorts the tasks by name, total time, spent time of day or stop date. Even if a task is running it will assume the sorted position.

Priority: High

Difficulty: Low

3.38. 17TL-005: TaskList.TotalTime

The system presents the total time for each task in the format hh:mm.

Priority: High

Difficulty: Low

3.39. 17TL-006: TaskList.Today

The system presents the today time for each task in the format hh:mm. If a task doesn't have time registered in the current day the today time should present 00:00.

Priority: High

Difficulty: Low

3.40. 17TL-007: TaskList.StopDate

The system presents the stop date for each task in date format. If the task was performed in the current day, it is presented in the format hh:mm (last stop of day).

Priority: High

Difficulty: Low

3.41. 17TL-008: TaskList.Actions

The system allows for each task a set of actions so the user can view the details, start/stop, delete tasks and activate or inactivate them.

Priority: High

Difficulty: High

4. Interface Requirements

4.1. UI-001: MainWindow

The system shows minimal view with a textbox to insert the task name, a button to start/stop and add the task, a timer, a button to view the task details, a button to edit the task, a button to show the configurations form, a button to hide/show the tasks list and a button to close the application.

Priority: Medium

Difficulty: Medium

4.2. UI-002: Buttons that are always active

The button to show configurations, to hide/show tasks list and the button to close the application are always active.

Priority: Medium

Difficulty: Medium

4.3. UI-003: Expand list button

When the tasks list isn't expanded, the expand button should show the symbol of a down arrow. When the tasks list is expanded it should show an up arrow.

Priority: Medium

Difficulty: Medium

4.4. UI-004: TextBox filled with a new task name

The system activates the button to add task.

Priority: Medium

Difficulty: Medium

4.5. UI-005: TextBox filled with Existence task name

The system enables the start, edit and view details buttons. If the Enter key is pressed the system changes the start button to stop button.

Priority: Medium

Difficulty: Medium

4.6. UI-006: TextBox with running task

The system changes the start/add button to the stop button, view details button and it starts timer. The edit button is disabled.

Priority: Medium

Difficulty: Medium

4.7. UI-007: Clicking in view details button

The system presents a form with the details of the task and an edit button.

Priority: Medium

Difficulty: Medium

4.8. UI-008: Clicking in edit button

The edition must be inline. In times table, each line has a button to delete that line.

Priority: Medium

Difficulty: Medium

4.9. UI-009: Clicking in configuration button

The system presents a form with:

- an export button;
- a checkbox to check/uncheck inactivity alerts and a textbox to define the inactivity time. This text box is enable only if the inactivity alert is checked;
- five lines for shortcuts definition with the following composition:
 - one combo box for selecting an existing task;
 - three checkboxes for check/uncheck the control keys ctrl, alt, shift;
 - one textbox for and additional key.

Priority: Medium

Difficulty: Medium

4.10. UI-010: Visual distinction between active and inactive tasks

The system should differentiate visually the active from inactive tasks

Priority: Medium

Difficulty: Medium

4.11. UI-011: Modal Window

Always that the user open a form, the system doesn't allow any actions on the previous form.

Priority: Medium

Difficulty: Medium

5. Performance Requirements

5.1. PR-001: Startup of the application

The startup of the application shouldn't last longer than 15 seconds.

Priority: Medium

Difficulty: Low

5.2. PR-002: Transition time

The transition between forms, when the total number of tasks doesn't exceed 100, shouldn't last longer than 10 seconds.

Priority: Medium

Difficulty: Low

Appendix A: Data Dictionary

Term	Definition
Description	The field description accepts until 500 characters and accepts special characters.
End date	The field end date is of datetime type with the format dd-mm-yyyy hh:mm.
Inactive time	The inactive time field must be an integer number between 1 and 60.
Name	The field name accepts until 50 characters and special characters. The name is unique.
Start date	The field start date is of datetime type with the format dd-mm-yyyy hh:mm.
Status	A task has two status, active or inactive.
Time spent	The time spent field is calculated and should be presented with the following format hh:mm.
Total time	The total time field is calculated and should be presented with the following format hh:mm.