

Krypton Calibration

Run 7433

Krypton Calibration Group

Table: Conditions and data for run 7433

Conditions	Data
run number	7433
file range	(0,8920)
date	2019-08-12
lab temperature:	20.2 deg
Total number of S2s	3437863
Total number of events	1731799





Figure: Run data.

Table: S1 & S2 for run 7433

Conditions	Data
fraction of S1s	0.52
fraction of S2s (1 S1)	0.57
fraction 1 S2 & 1 S1	0.3

Table: S1 & S2 selection for run 7433

Variables	Data
s_1 energy	3 pes to 25 pes
s_2 energy (PMTs)	3000 pes to 13000 pes
s_2 charge (SiPMs)	200 pes to 800 pes
s_2 width	$5 \mu s$ to $15 \mu s$
n_{sipm} min	15




Figure: S1 distributions.




Figure: S2 distributions.




Figure: XY distribution.




Figure: S1, S2 & Q distributions.

Lifetime distributions




Figure: Distributions of lifetime and E_0 for 5 radial sectors (40, 80, 120, 160, 200).




Figure: Lifetime and geometrical map.

Lifetime maps




Figure: Average lifetime.

Lifetime and geometry correction




Figure: Lifetime and geometry correction.

R Profile showing R dropout




Figure: R profile shows that fiducial volume must be $R < 180\text{mm}$.

Profiles after $R < 180\text{mm}$




Figure: Profiles showing correction is robust.

Resolution fits as a function of R and Z




Figure: Resolution fits.

Resolution as a function of R and Z




Figure: Resolution fits.

Efficiency over time




Figure: Efficiency tracking over time.

Response over time




Figure: Response tracking over time.




Figure: Lifetime tracking over time.




Figure: Resolution tracking over time.