Krypton Calibration

Run 6826

Krypton Calibration Group

Conditions and data

Table: Conditions and data for run 6826

Conditions	Data
run number	6826
file range	(0,3910)
date	2019-01-28
lab temperature:	21.1 deg
Total number of S2s	1339904
Total number of events	788209





Figure: Run data.

Table: S1 & S2 for run 6826

Conditions	Data
fraction of S1s	0.59
fraction of S2s (1 S1)	0.63
fraction 1 S2 & 1 S1	0.37

Table: S1 & S2 selection for run 6826

Variables	Data
s_1 energy	3 pes to 25 pes
s_2 energy (PMTs)	3000 pes to 13000 pes
s_2 charge (SiPMs)	200 pes to 800 pes
s_2 width	5 μs to 15 μs
n_{sipm} min	15



Figure: S1 distributions.



Figure: S2 distributions.

Control distributions



Figure: XY distribution.



Figure: S1, S2 & Q distributions.

Lifetime distributions



Figure: Distributions of lifetime and E_0 for 5 radial sectors (40, 80, 120, 160, 200).

Lifetime maps



Figure: Lifetime and geometrical map.

Lifetime maps



Figure: Average lifetime.

Lifetime and geometry correction



Figure: Lifetime and geometry correction.

R Profile showing R dropout



Figure: R profile shows that fiducial volume must be $R < 180$mm.

Profiles after $R < 180$mm



Figure: Profiles showing correction is robust.

Resolution fits as a function of R and Z



Figure: Resolution fits.

Resolution as a function of R and Z



Figure: Resolution fits.