

Installation of Quantis drivers and libraries

Jarosław A. Miszczak
Institute of Theoretical and Applied Informatics, Polish Academy of Sciences
Bałtycka 5, 44-100 Gliwice, Poland

27/06/2012 (v.0.05)

Abstract

The following instructions provide an overview of the installation procedure for device drivers and libraries required to use Quantis quantum random number generator on Linux-based systems. Please consult the documentation provided with the Quantis software package for more information.

1 Device drivers

In the following instructions `Quantis-v11.12.13` should be replaced by the appropriate directory depending on the version of Quantis software package you are using during the installation.

One should also note that most of the command issued during the installations process require super-user (root) privileges. On most modern Linux systems this can be achieved using `sudo` or `su` commands.

1.1 PCI and PCI-express version

1. Install module-assistant package

```
apt-get install module-assistant
```

Note: On RedHat/Fedora-based systems you need to install `kernel-devel` package and collection of development tools

```
yum install kernel-devel  
yum groupinstall "Development Tools"
```

2. Prepare your system for module compilation

```
m-a prepare
```

3. Unpack the Quantis software package and go to

```
Quantis-v11.12.13/Drivers/Unix/QuantisPci.
```

4. Compile the module

```
make
```

5. Install the module

```
make install  
and check if the module has been installed properly  
find /lib/modules/ -name quantis_pci.ko
```

6. Make sure that the driver will be loaded during the next boot
`echo "quantis_pci" >> /etc/modules`
7. Follow the instructions in Section 1.3.

1.2 USB version

1. Install `libusb` and `libusb-dev` packages
`apt-get install libusb-1.0-0 libusb-1.0-0-dev`
2. Check your device with `lsusb`
`lsusb -d 0aba:0102 -v` or `lsusb -v | grep Quantis`
3. Follow the instructions in Section 1.3.

1.3 Device permissions

1. Make sure that the `plugdev` group exists
`cat /etc/group | grep plugdev`
2. Add the user that will be permitted to use Quantis to the `plugdev` group
`usermod -G plugdev -a LOGIN,`
 where `LOGIN` is the login name of the user
3. Copy file `Quantis-v11.12.13/Drivers/Unix/idq-quantis.rules`,
 to `/etc/udev/rules.d/` directory and reload the UDEV rules
`udevadm control --reload-rules`

2 Libraries

1. Unpack distribution files from `Quantis-v11.12.13/Packages/Linux` to a selected directory, e.g `/usr/local/IDQ/Quantis`
`mkdir /usr/local/IDQ`
`tar xjvf QuantisRNG-2.5.0-Linux-amd64.tar.bz2`
`mv QuantisRNG-2.5.0-Linux-amd64 /usr/local/IDQ/Quantis`
After this step the EasyQuantis application should be in
`/usr/local/IDQ/Quantis/bin/EasyQuantis`
2. Copy `Quantis.h` and `DIIMain.h` from
`Quantis-v11.12.13/Libs-Apps/Quantis`
 to
`/usr/local/IDQ/Quantis/include`
3. Add `/usr/local/IDQ/Quantis/lib` (or `/usr/local/IDQ/Quantis/lib64`) to
`/etc/ld.so.conf` or some file which is included by this file e.g
`/etc/ld.so.conf.d/quantis.conf`
4. Update the loader cache
`ldconfig`