

statistics

September 10, 2026

1 Data Analysis

1.1 Participant-Group Differences in TTU and DOU Across Tasks, and Task Properties

todo concept

```
[1]: #TODO:  
# language = EN everywhere,  
# formatting
```

2 Set-up

```
[2]: library(nparLD)  
library(dplyr)  
library(tidyr)  
library(ggplot2)  
  
library(psych) # for ICC  
library(irr) # for ICC alternative  
library(blandr) # for Bland-Altman
```

Attache Paket: 'dplyr'

Die folgenden Objekte sind maskiert von 'package:stats':

filter, lag

Die folgenden Objekte sind maskiert von 'package:base':

intersect, setdiff, setequal, union

Attache Paket: 'psych'

Die folgenden Objekte sind maskiert von 'package:ggplot2':

%+%, alpha

Lade nötiges Paket: lpSolve

```
[3]: html_print <- function(text) {  
  IRdisplay::display_html(text)  
}  
  
bold <- function(text) {  
  paste0("<b>", text, "</b>")  
}  
  
italic <- function(text) {  
  paste0("<i>", text, "</i>")  
}  
  
heading <- function(text, level = 2) {  
  IRdisplay::display_html(  
    paste0("<h", level, ">", text, "</h", level, ">")  
  )  
}  
  
line <- function() {  
  IRdisplay::display_html("<hr>")  
}
```

```
[ ]:
```

Global significance level:

```
[4]: alpha <- 0.05
```

```
[ ]:
```

Loading data from csv (saved via py):

```
[5]: dat <- read.csv(  
  "study_data.csv",  
  sep = ";",  
  header = TRUE,  
  check.names = FALSE, # keep column names identical  
  stringsAsFactors = FALSE  
)
```

```

[6]: # Python-Listenrepräsentation als R-Vektor einlesen:
# '['COMP', 'CELL', 'VAL']" -> c("COMP", "CELL", "VAL")
parse_list_column <- function(x) {

  if (is.na(x)) {
    return(character(0))
  }

  x <- trimws(x)

  # Leere Listen / leere Werte
  if (x %in% c("", "[]", "NA", "None", "NULL")) {
    return(character(0))
  }

  # Alle eckigen Klammern entfernen
  x <- gsub("[", "", x, fixed = TRUE)
  x <- gsub("]", "", x, fixed = TRUE)
  x <- trimws(x)

  if (!nzchar(x)) {
    return(character(0))
  }

  # Am Komma trennen
  values <- strsplit(x, ",", fixed = TRUE)[[1]]

  # Leerzeichen und äußere Anführungszeichen entfernen
  values <- trimws(values)
  values <- gsub("^['\\\"]|['\\\"]$", "", values)

  # Leere Einträge entfernen
  values[nzchar(values)]
}

# Assert:
stopifnot(
  identical(
    parse_list_column("['COMP', 'CELL', 'VAL', 'BACK', 'ON']"),
    c("COMP", "CELL", "VAL", "BACK", "ON")
  )
)

```

```

[7]: # Eigene Importfunktion
read_study_data <- function(path) {

```

```

dat <- read.csv(
  "study_data.csv",
  sep = ";",
  header = TRUE,
  check.names = FALSE, # keep column names identical
  stringsAsFactors = FALSE,
  na.strings = c("", "NA")
)

# Diese Spalten enthalten Listen
list_columns <- c(
  "structural_aspects",
  "operation_type",
  "operand_type",
  "result_type",
  "Ref_direction",
  "Ref_dispersion"
)

# Nur vorhandene Spalten bearbeiten
list_columns <- intersect(list_columns, names(dat))

for (column in list_columns) {
  dat[[column]] <- lapply(dat[[column]], parse_list_column)
}

dat
}

```

```
[8]: dat <- read_study_data("study_data.csv")
```

```
[9]: head(dat)
```

A data.frame: 6 × 11

	participant	task_id	group	TTU	DOU	structural_aspects
	<chr>	<int>	<chr>	<int>	<dbl>	<list>
1	p01	1	Formula construction	17	1.0	COMP, CELL, VAL
2	p31	1	Formula construction	23	0.6	COMP, CELL, VAL
3	p34	1	Formula construction	14	1.0	COMP, CELL, VAL
4	p33	1	Formula construction	28	1.0	COMP, CELL, VAL
5	p26	1	Formula construction	92	0.6	COMP, CELL, VAL
6	p21	1	Formula construction	33	1.0	COMP, CELL, VAL

```

[10]: # Faktoren und Reihenfolge vorbereiten
dat <- dat %>%
  mutate(
    participant = factor(participant),
    group = factor(group),

```

```

    task_id = factor(task_id, levels = 1:17),
    TTU = as.numeric(TTU),
    DOU = as.numeric(DOU)
  )

```

```
[ ]:
```

```

[11]: plot_by_group_and_task <- function(
  data,
  measure,
  pdf_file = NULL,
  y_break = NULL,
  break_scale = 1 / 10,
  width = 10,
  height = 5
) {

  # -----
  # Checks
  # -----

  required_cols <- c("task_id", "group", measure)
  missing_cols <- setdiff(required_cols, names(data))

  if (length(missing_cols) > 0) {
    stop("Missing column(s): ", paste(missing_cols, collapse = ", "))
  }

  if (!is.numeric(data[[measure]])) {
    stop(sprintf("%s' must be numeric.", measure))
  }

  if (!is.null(y_break)) {
    if (
      length(y_break) != 2 ||
      !is.numeric(y_break) ||
      any(!is.finite(y_break)) ||
      y_break[1] >= y_break[2]
    ) {
      stop(
        "y_break must contain two increasing numeric values, ",
        "e.g. c(300, 2220)."
      )
    }
  }

  # -----

```

```

# Prepare data
# -----

plot_data <- data[
  is.finite(data[[measure]]) &
  !is.na(data$task_id) &
  !is.na(data$group),
  ,
  drop = FALSE
]

if (nrow(plot_data) == 0) {
  stop("No valid observations available for plotting.")
}

# Preserve original ordering in the data
task_levels <- unique(as.character(plot_data$task_id))
group_levels <- unique(as.character(plot_data$group))

plot_data$task_id <- factor(
  plot_data$task_id,
  levels = task_levels
)

plot_data$group <- factor(
  plot_data$group,
  levels = group_levels
)

n_groups <- length(group_levels)
n_tasks <- length(task_levels)

# Requested y-axis label
y_label <- if (measure == "TTU") {
  "TTU [s]"
} else {
  "DOU [ ]"
}

# Group colours
group_colours <- grDevices::hcl.colors(
  n = n_groups,
  palette = "Dark 3"
)
names(group_colours) <- group_levels

# Default output filename

```

```

if (is.null(pdf_file)) {
  safe_measure <- gsub("[^A-Za-z0-9_-]", "_", measure)
  pdf_file <- paste0(safe_measure, "_by_group_and_task.pdf")
}

# -----
# Facet-specific x-axis variable
#
# Separate internal x-axis levels are required so that the middle facet can
# use labels 2, 4, 6, ... while the other facets use labels 1, 3, 5, ...
# -----

make_task_key <- function(group, task) {
  paste(
    as.character(group),
    as.character(task),
    sep = "\\r"
  )
}

task_plot_levels <- unlist(
  lapply(
    group_levels,
    function(current_group) {
      make_task_key(current_group, task_levels)
    }
  ),
  use.names = FALSE
)

plot_data$task_id_plot <- factor(
  make_task_key(
    plot_data$group,
    plot_data$task_id
  ),
  levels = task_plot_levels
)

# -----
# X-axis labels
#
# The middle facet labels positions 2, 4, 6, ...
# All other facets label positions 1, 3, 5, ...
#
# All labels reserve three lines. This prevents vertical movement.
# "Task" is shown below the labelled tick nearest to the centre.
# -----

```

```

middle_group_index <- ceiling(n_groups / 2)

x_axis_labels <- stats::setNames(
  rep("\n\n", length(task_plot_levels)),
  task_plot_levels
)

for (group_index in seq_along(group_levels)) {

  current_group <- group_levels[group_index]

  label_start <- if (group_index == middle_group_index) {
    2
  } else {
    1
  }

  if (label_start <= n_tasks) {
    labelled_indices <- seq(
      from = label_start,
      to = n_tasks,
      by = 2
    )
  } else {
    labelled_indices <- integer(0)
  }

  if (length(labelled_indices) > 0) {

    middle_task <- labelled_indices[
      which.min(
        abs(labelled_indices - ceiling(n_tasks / 2))
      )
    ]

    current_keys <- make_task_key(
      current_group,
      task_levels[labelled_indices]
    )

    x_axis_labels[current_keys] <- paste0(
      task_levels[labelled_indices],
      "\n\n"
    )

    middle_key <- make_task_key(

```

```

        current_group,
        task_levels[middle_task]
    )

    x_axis_labels[middle_key] <- paste0(
        task_levels[middle_task],
        "\nTask"
    )
}
}

# -----
# Axis scaffold
#
# Retain all task positions in every facet, including positions for which
# an individual group may have no valid observation.
# -----

axis_scaffold_data <- expand.grid(
    group = group_levels,
    task_id = task_levels,
    stringsAsFactors = FALSE
)

axis_scaffold_data$group <- factor(
    axis_scaffold_data$group,
    levels = group_levels
)

axis_scaffold_data$task_id <- factor(
    axis_scaffold_data$task_id,
    levels = task_levels
)

axis_scaffold_data$task_id_plot <- factor(
    make_task_key(
        axis_scaffold_data$group,
        axis_scaffold_data$task_id
    ),
    levels = task_plot_levels
)

# -----
# Median values per group and task
# -----

median_data <- stats::aggregate(

```

```

plot_data[[measure]],
by = list(
  group = plot_data$group,
  task_id = plot_data$task_id
),
FUN = stats::median,
na.rm = TRUE
)

names(median_data)[3] <- "median"

median_data$group <- factor(
  median_data$group,
  levels = group_levels
)

median_data$task_id <- factor(
  median_data$task_id,
  levels = task_levels
)

median_data$task_id_plot <- factor(
  make_task_key(
    median_data$group,
    median_data$task_id
  ),
  levels = task_plot_levels
)

# -----
# Main plot
# -----

p <- ggplot2::ggplot(
  plot_data,
  ggplot2::aes(
    x = task_id_plot,
    y = .data[[measure]],
    fill = group,
    colour = group
  )
) +

# Retain every task position in every facet.
ggplot2::geom_blank(
  data = axis_scaffold_data,
  ggplot2::aes(

```

```

    x = task_id_plot,
    y = NA_real_
  ),
  inherit.aes = FALSE
) +

# Box = IQR; whiskers = non-outlier range; dots = outliers.
# The box border has the same colour as the fill.
ggplot2::geom_boxplot(
  width = 0.62,
  linewidth = 0.45,
  alpha = 0.85,
  outlier.shape = 16,
  outlier.size = 1.8,
  outlier.colour = "black",
  show.legend = FALSE
) +

# Median: black, and exactly the same width as the box (0.62).
ggplot2::geom_errorbar(
  data = median_data,
  ggplot2::aes(
    x = task_id_plot,
    ymin = median,
    ymax = median
  ),
  inherit.aes = FALSE,
  width = 0.62,
  colour = "black",
  linewidth = 0.75
) +

ggplot2::facet_wrap(
  ~ group,
  nrow = 1,
  scales = "free_x",
  axes = "all_x",
  axis.labels = "all_x"
) +

ggplot2::scale_fill_manual(values = group_colours) +
ggplot2::scale_colour_manual(values = group_colours) +

ggplot2::scale_x_discrete(
  labels = x_axis_labels,
  expand = ggplot2::expansion(add = 0.20)
) +

```

```

ggplot2::labs(
  x = NULL,
  y = y_label
) +

ggplot2::theme_classic(
  base_size = 12,
  base_family = "sans"
) +

ggplot2::theme(

  # Group headings
  strip.background = ggplot2::element_blank(),
  strip.text = ggplot2::element_text(
    face = "bold",
    size = 12,
    colour = "black",
    margin = ggplot2::margin(b = 5)
  ),

  # X-axis task IDs and "Task" label
  axis.text.x = ggplot2::element_text(
    angle = 0,
    hjust = 0.5,
    vjust = 1,
    colour = "black",
    size = 10,
    lineheight = 1.15,
    margin = ggplot2::margin(t = 5)
  ),

  axis.text.y = ggplot2::element_text(
    colour = "black",
    size = 10
  ),

  axis.title.y = ggplot2::element_text(
    face = "bold",
    size = 12,
    margin = ggplot2::margin(r = 8)
  ),

  axis.title.x = ggplot2::element_blank(),

  # Remove upper x-axis

```

```

axis.text.x.top = ggplot2::element_blank(),
axis.ticks.x.top = ggplot2::element_blank(),
axis.line.x.top = ggplot2::element_blank(),
axis.title.x.top = ggplot2::element_blank(),

# Separate facets visually
panel.border = ggplot2::element_rect(
  fill = NA,
  colour = "grey45",
  linewidth = 0.45
),

panel.spacing.x = grid::unit(0.20, "lines"),

panel.grid.major.y = ggplot2::element_line(
  colour = "grey90",
  linewidth = 0.30
),

panel.grid.minor = ggplot2::element_blank(),

axis.line = ggplot2::element_line(
  colour = "black",
  linewidth = 0.45
),

axis.ticks = ggplot2::element_line(
  colour = "black",
  linewidth = 0.4
),

axis.ticks.length = grid::unit(0.14, "cm"),

legend.position = "none",

plot.margin = ggplot2::margin(
  t = 8,
  r = 8,
  b = 18,
  l = 8
)
)

# -----
# Ordinary or broken y-axis
# -----

```

```

y_min <- min(plot_data[[measure]], na.rm = TRUE)
y_max <- max(plot_data[[measure]], na.rm = TRUE)

if (is.null(y_break)) {

  # Ordinary y axis
  p <- p +
    ggplot2::scale_y_continuous(
      expand = ggplot2::expansion(mult = c(0.04, 0.06))
    )

} else {

  if (y_max <= y_break[2]) {
    stop(
      "The upper end of y_break must be below the largest plotted value. ",
      "Current maximum: ", y_max, "."
    )
  }

  # Lower section: roughly five integer ticks
  lower_ticks <- round(
    pretty(c(y_min, y_break[1]), n = 5)
  )

  lower_ticks <- unique(
    lower_ticks[
      lower_ticks >= floor(y_min) &
      lower_ticks <= ceiling(y_break[1])
    ]
  )

  # -----
  # Upper section
  #
  # Create a larger range above the actual maximum. This is used only to
  # train the scale and does not control the physical panel-height ratio.
  # -----

  upper_data_span <- y_max - y_break[2]

  upper_buffer <- max(
    0.35 * upper_data_span,
    2
  )

  upper_top <- y_max + upper_buffer

```

```

# Find natural, integer-valued upper ticks. If pretty() initially returns
# fewer than two usable ticks, increase the invisible upper headroom until
# at least two are available.
for (i in seq_len(20)) {

  upper_ticks <- unique(
    as.integer(
      round(
        pretty(
          c(y_break[2], upper_top),
          n = 4
        )
      )
    )
  )

  upper_ticks <- upper_ticks[
    upper_ticks > y_break[2] &
    upper_ticks < upper_top
  ]

  if (length(upper_ticks) >= 2) {
    break
  }

  upper_buffer <- max(
    upper_buffer * 1.5,
    upper_buffer + 1
  )

  upper_top <- y_max + upper_buffer
}

# Defensive fallback for extremely narrow or unusual ranges.
if (length(upper_ticks) < 2) {

  first_upper_tick <- floor(y_break[2]) + 1L
  second_upper_tick <- first_upper_tick + 1L

  upper_ticks <- c(
    first_upper_tick,
    second_upper_tick
  )

  upper_top <- max(
    upper_top,

```

```

    second_upper_tick + 1
  )
}

upper_ticks <- sort(unique(upper_ticks))

y_ticks <- sort(unique(c(
  lower_ticks,
  upper_ticks
)))

# One invisible observation per group trains the common fixed y-scale up
# to upper_top. No y-axis limits are set, so ggbreak remains free to retain
# the panel-height ratio specified by break_scale.
upper_spacer_data <- data.frame(
  group = factor(
    group_levels,
    levels = group_levels
  ),
  task_id_plot = factor(
    make_task_key(
      group_levels,
      rep(task_levels[1], n_groups)
    ),
    levels = task_plot_levels
  ),
  upper_top = rep(upper_top, n_groups)
)

p <- p +

ggplot2::geom_blank(
  data = upper_spacer_data,
  mapping = ggplot2::aes(
    x = task_id_plot,
    y = upper_top
  ),
  inherit.aes = FALSE
) +

ggplot2::scale_y_continuous(
  breaks = y_ticks,
  labels = function(x) {
    format(
      x,
      scientific = FALSE,
      trim = TRUE
    )
  }
)

```

```

    )
  },
  expand = ggplot2::expansion(
    mult = c(0.04, 0)
  )
) +

  # This remains the only setting that controls the physical height
  # of the short upper section.
  ggbreak::scale_y_break(
    breaks = y_break,
    scales = break_scale,
    space = 0.03
  )
}

# -----
# Export as one-page vector PDF
# -----

grDevices::pdf(
  file = pdf_file,
  width = width,
  height = height,
  onefile = FALSE,
  useDingbats = FALSE
)

tryCatch(
  print(p),
  finally = grDevices::dev.off()
)

message(
  "PDF saved to: ",
  normalizePath(pdf_file, mustWork = FALSE)
)

return(p)
}

```

```

[12]: # p_ttu <- plot_by_group_and_task(
#   data = dat,
#   measure = "TTU",
#   # y_break = c(300, 2220),
#   # break_scale = 1 / 10,
#   width = 10,


```

```
# height = 5
# )

# p_ttu

plot_by_group_and_task(dat, "TTU", width=10)
```


PDF saved to: /home/judith/Schreibtisch/angew. Informatik - system engineering/Study_DrawingAttention/TTU_by_group_and_task.pdf



note: box = interquartile range, line = median, whiskers = 1.5 IQR, dots = outliers

```
[13]: plot_by_group_and_task(dat, "DOU", width=10)
```

PDF saved to: /home/judith/Schreibtisch/angew. Informatik - system engineering/Study_DrawingAttention/DOU_by_group_and_task.pdf



```
[ ]:
```

3

4 Inter-Rater Agreement

```
[14]: rmse <- function(x) {  
  sqrt(mean(x ^ 2))  
}
```

```
[15]: get_coding_alignment_dat <- function(dat, metric = "ttu") {  
  
  metric <- tolower(metric)  
  
  if (!metric %in% c("ttu", "dou", "timestamp_where_participant_realizes")) {  
    stop("metric must be 'ttu' or 'dou'")  
  }  
  
  if (metric == "ttu") {  
    x_var <- "TTU"  
    y_var <- "TTU_second_coder"  
  } else {  
    if (metric == "timestamp_where_participant_realizes") {  
      x_var <- "timestamp_where_participant_realizes"  
      y_var <- "timestamp_where_participant_realizes_second_coder"  
    } else {  
      x_var <- "DOU"  
      y_var <- "DOU_second_coder"  
    }  
  }  
  
  split_id <- strsplit(as.character(dat$task_id), "_")  
  dat$participant <- vapply(split_id, `[`, character(1), 1)  
  
  plot_df <- dat[complete.cases(dat[, c(x_var, y_var)]), ]  
  
  min_val <- min(plot_df[[x_var]], plot_df[[y_var]])  
  max_val <- max(plot_df[[x_var]], plot_df[[y_var]])  
  
  p <- ggplot(  
    plot_df,  
    aes_string(x = x_var, y = y_var, colour = "participant")  
  ) +  
    geom_point(alpha = 0.7, size = 3) +  
    geom_abline(  
      intercept = 0,  
      slope = 1,  
      linetype = "dashed",  
      colour = "red"  
    )  
}
```

```

) +
coord_equal(
  xlim = c(min_val, max_val),
  ylim = c(min_val, max_val)
) +
labs(
  x = paste0(toupper(metric), " (Coder 1)"),
  y = paste0(toupper(metric), " (Coder 2)"),
  colour = "Participant"
) +
theme_minimal() +
theme(legend.position = "right")

# ggsave(
#   paste0(metric, "_coding_alignment.png"),
#   p,
#   width = 8,
#   height = 8,
#   dpi = 300
# )

print(p)
invisible(p)
}

```

```

[16]: coder_error_measures <- function(ratings, tol = 5) {
  if (!is.numeric(tol) || length(tol) != 1L || is.na(tol) || tol < 0) {
    stop("`tol` must be one non-negative numeric value.")
  }

  ratings <- as.data.frame(ratings)

  # Identify numeric rating columns
  numeric_columns <- vapply(ratings, is.numeric, logical(1))
  ratings <- ratings[, numeric_columns, drop = FALSE]

  if (ncol(ratings) < 2L) {
    stop("`ratings` must contain at least two numeric rating columns.")
  }

  # Use the first two numeric columns
  ratings <- ratings[, 1:2, drop = FALSE]

  # Retain complete paired observations
  ratings <- ratings[complete.cases(ratings), , drop = FALSE]

  if (nrow(ratings) == 0L) {

```

```

  stop("There are no complete paired observations.")
}

diff_vec <- ratings[[1]] - ratings[[2]]
abs_diff <- abs(diff_vec)

c(
  mean_difference           = mean(diff_vec),
  mean_absolute_error       = mean(abs_diff),
  median_absolute_error     = median(abs_diff),
  sd_difference             = sd(diff_vec),
  maximum_absolute_difference = max(abs_diff),
  rmse                     = sqrt(mean(diff_vec^2)),
  proportion_within_tolerance = mean(abs_diff <= tol)
)
}

```

[]:

[]:

4.0.1 TTU


```
[17]: get_coding_alignment_dat(dat, metric = "ttu")
```

Warning message:

"`aes\_string()` was deprecated in ggplot2 3.0.0.

Please use tidy evaluation idioms with `aes()`.

See also `vignette("ggplot2-in-packages")` for more information."



[]:

```
[18]: # Keep only complete paired observations
ratings <- dat[, c("TTU", "TTU_second_coder")]
ratings <- ratings[complete.cases(ratings), ]

# Two-way, absolute-agreement ICC for single coders
icc_res <- irr::icc(
  ratings,
  model = "twoway",
  type = "agreement",
  unit = "single"
)
```

```
print(icc_res)
```

Single Score Intraclass Correlation

Model: twoway
Type : agreement

Subjects = 357
Raters = 2
ICC(A,1) = 0.949

F-Test, H0: $r_0 = 0$; H1: $r_0 > 0$
F(356,356) = 40.4 , p = 5.71e-185

95%-Confidence Interval for ICC Population Values:
0.936 < ICC < 0.96

Inter-rater agreement for Time to Understand (TTU) was excellent: - ICC(A,1) = 0.99 - 95% CI = [0.985, 0.993] - based on 102 paired observations.

```
[19]: error_summary <- coder_error_measures(ratings, tol = 5)
print(error_summary)
```

mean_difference	mean_absolute_error
2.6302521	6.5238095
median_absolute_error	sd_difference
2.0000000	11.5815614
maximum_absolute_difference	rmse
73.0000000	11.8606522
proportion_within_tolerance	
0.6498599	


However, absolute differences indicated a systematic discrepancy:

Coder 1 coded TTU values 6.79 seconds higher on average than Coder 2.

The mean absolute difference was 9.5 seconds (median = 10 seconds), and only 46% of codings were within ± 5 seconds.

```
[ ]:
```

```
[20]: # timestamp_where_participant_realizes
get_coding_alignment_dat(dat, metric = "timestamp_where_participant_realizes")
```



```
[21]: # Keep only complete paired observations
ratings <- dat[, c("timestamp_where_participant_realizes",
  ↪ "timestamp_where_participant_realizes_second_coder")]
ratings <- ratings[complete.cases(ratings), ]

# Two-way, absolute-agreement ICC for single coders
icc_res <- irr::icc(
  ratings,
  model = "twoway",
  type = "agreement",
  unit = "single"
)
```

```
print(icc_res)

error_summary <- coder_error_measures(ratings, tol = 5)
print(error_summary)
```

Single Score Intraclass Correlation

Model: twoway
Type : agreement

Subjects = 357
Raters = 2
ICC(A,1) = 0.999

F-Test, H0: $r_0 = 0$; H1: $r_0 > 0$
F(356,356) = 3263 , p = 0


95%-Confidence Interval for ICC Population Values:

0.999 < ICC < 0.999

mean_difference	mean_absolute_error
2.9327731	6.1484594
median_absolute_error	sd_difference
2.0000000	11.1113348
maximum_absolute_difference	rmse
72.0000000	11.4768065
proportion_within_tolerance	
0.6834734	

[]:

[22]: `get_coding_alignment_dat(dat, metric = "dou")`



```
[23]: # Keep only complete paired observations
ratings <- dat[, c("DOU", "DOU_second_coder")]
ratings <- ratings[complete.cases(ratings), ]

# Two-way, absolute-agreement ICC for single coders
icc_res <- irr::icc(
  ratings,
  model = "twoway",
  type = "agreement",
  unit = "single"
)

print(icc_res)
```

Single Score Intraclass Correlation

Model: twoway
Type : agreement

Subjects = 357
Raters = 2
ICC(A,1) = 0.689

F-Test, H0: $r_0 = 0$; H1: $r_0 > 0$
F(356,356) = 5.41 , p = 7.51e-52

95%-Confidence Interval for ICC Population Values:
0.63 < ICC < 0.74

Inter-rater agreement for DOU was moderate: - ICC(A,1) = 0.501 - 95% CI [0.342, 0.633] - based on 102 paired codings.

```
[24]: error_summary <- coder_error_measures(ratings, tol = 0.2)
      print(error_summary)
```

mean_difference	mean_absolute_error
-0.004096184	0.063296228
median_absolute_error	sd_difference
0.000000000	0.139669025
maximum_absolute_difference	rmse
1.000000000	0.139533410
proportion_within_tolerance	
0.899159664	

4.0.2 Saving the results:

```
[25]: ratings_list <- list(
      TTU = dat[, c("TTU", "TTU_second_coder")],
      DOU = dat[, c("DOU", "DOU_second_coder")],
      TIMESTAMP_REALIZATION = dat[, c("timestamp_where_participant_realizes",
      ↪ "timestamp_where_participant_realizes_second_coder")]
    )

# Keep complete pairs for each measure
ratings_list <- lapply(
  ratings_list,
  function(x) x[complete.cases(x), , drop = FALSE]
)
```

```
[26]: tolerances <- c(
      TTU = 3,
      DOU = 0.2,
```

```

    TIMESTAMP_REALIZATION=3
  )

  error_results <- Map(
    function(ratings, tol) {
      coder_error_measures(ratings, tol = tol)
    },
    ratings_list,
    tolerances
  )

  icc_results <- lapply(
    ratings_list,
    function(ratings) {
      irr::icc(
        ratings,
        model = "twoway",
        type = "agreement",
        unit = "single",
        conf.level = 0.95
      )
    }
  )

```

```

[27]: selected_measures <- c(
  "mean_difference",
  "rmse",
  "median_absolute_error"
)

error_table <- do.call(
  rbind,
  lapply(error_results, function(x) x[selected_measures])
)

error_table <- data.frame(
  Measure = names(error_results),
  error_table,
  row.names = NULL,
  check.names = FALSE
)

names(error_table) <- c(
  "Measure",
  "Mean difference",
  "RMSE",
  "Median absolute error"
)

```

```

)

# Extract ICC estimates and confidence limits
error_table$ICC <- vapply(
  icc_results,
  function(x) x$value,
  numeric(1)
)

error_table$CI_lower <- vapply(
  icc_results,
  function(x) x$lbound,
  numeric(1)
)

error_table$CI_upper <- vapply(
  icc_results,
  function(x) x$ubound,
  numeric(1)
)

# Combine ICC and CI into one conventionally formatted column
error_table$`ICC(2,1) [95% CI]` <- sprintf(
  "%.2f [%.2f, %.2f]",
  error_table$ICC,
  error_table$CI_lower,
  error_table$CI_upper
)

# Remove the separate intermediate ICC columns
error_table$ICC <- NULL
error_table$CI_lower <- NULL
error_table$CI_upper <- NULL

# Put ICC immediately after the measure name
error_table <- error_table[, c(
  "Measure",
  "ICC(2,1) [95% CI]",
  "Mean difference",
  "RMSE"
)]

error_table

```

	Measure <chr>	ICC(2,1) [95% CI] <chr>	Mean difference <dbl>	RMSE <dbl>
A data.frame: 3 × 4	TTU	0.95 [0.94, 0.96]	2.630252101	11.8606522
	DOU	0.69 [0.63, 0.74]	-0.004096184	0.1395334
	TIMESTAMP_REALIZATION	1.00 [1.00, 1.00]	2.932773109	11.4768065

```
[28]: latex_table_data <- error_table

numeric_columns <- c(
  "Mean difference",
  "RMSE"
)

latex_table_data[numeric_columns] <- lapply(
  latex_table_data[numeric_columns],
  function(x) sprintf("%.6f", x)
)

latex_table <- knitr::kable(
  latex_table_data,
  format = "latex",
  booktabs = TRUE,
  escape = TRUE,
  align = c("l", "c", "r", "r"),
  caption = "Inter-coder agreement and error measures",
  label = "tab:intercoder-agreement"
)

cat(latex_table)
```

```
\begin{table}

\caption{\label{tab:tab:intercoder-agreement}Inter-coder agreement and error
measures}
\centering
\begin{tabular}[t]{lccrr}
\toprule
Measure & ICC(2,1) [95\% CI] & Mean difference & RMSE\\
\midrule
TTU & 0.95 [0.94, 0.96] & 2.630252 & 11.860652\\
DOU & 0.69 [0.63, 0.74] & -0.004096 & 0.139533\\
TIMESTAMP\_REALIZATION & 1.00 [1.00, 1.00] & 2.932773 & 11.476806\\
\bottomrule
\end{tabular}
\end{table}
```

```
[ ]:
```

5 Is there evidence for differences between groups, tasks, or differing task patterns across groups?

```
[29]: report_atgs <- function(
  fit,
  outcome,
  within = "task_id",
  between = "group"
) {

  ats <- as.data.frame(fit$ATS)
  ats$effect <- rownames(ats)
  rownames(ats) <- NULL

  # Identify relevant columns
  p_col <- grep(
    "p.value|p-value|pval|^p$",
    names(ats),
    ignore.case = TRUE,
    value = TRUE
  )[1]

  statistic_col <- grep(
    "statistic|ATS",
    names(ats),
    ignore.case = TRUE,
    value = TRUE
  )[1]

  df_col <- grep(
    "^df$|degrees",
    names(ats),
    ignore.case = TRUE,
    value = TRUE
  )[1]

  if (is.na(p_col)) {
    stop("No p-value column found. Check names(fit$ATS).")
  }

  make_hypothesis <- function(effect) {

    # Interaction effect, e.g. task_id:group
    if (grepl(":", effect, fixed = TRUE)) {

      parts <- strsplit(effect, ":", fixed = TRUE)[[1]]
```

```

return(
  paste0(
    "H0: The effect of ", parts[1],
    " on ", outcome,
    " does not differ across levels of ", parts[2],
    " (no ", parts[1], " × ", parts[2], " interaction)."
  )
)
}

# Between-subject effect
if (effect == between) {
  return(
    paste0(
      "H0: There is no overall difference in ", outcome,
      " between levels of ", between, "."
    )
  )
}

# Within-subject effect
if (effect == within) {
  return(
    paste0(
      "H0: There is no difference in ", outcome,
      " between levels of ", within, "."
    )
  )
}

# Fallback for additional effects
paste0(
  "H0: There is no difference in ", outcome,
  " between levels of ", effect, "."
)
}

# Ensure numeric p-values
p_values <- as.numeric(unlist(ats[[p_col]]))

data.frame(
  outcome = outcome,
  effect = ats$effect,

  ANOVA_Type_Statistic = if (!is.na(statistic_col)) {
    as.numeric(unlist(ats[[statistic_col]]))
  } else {

```

```

    NA_real_
  },

  degrees_of_freedom = if (!is.na(df_col)) {
    as.numeric(unlist(ats[[df_col]]))
  } else {
    NA_real_
  },

  null_hypothesis = vapply(
    ats$effect,
    make_hypothesis,
    character(1)
  ),

  p_value = p_values,

  significant = p_values < alpha,

  conclusion = ifelse(
    p_values < alpha,
    "Significant: reject H0",
    "Not significant: do not reject H0"
  ),

  row.names = NULL,
  check.names = FALSE
)
}

```

```

[30]: format_table_significant_column_bold <- function(table) {
  display_table <- table %>%
    dplyr::mutate(
      significant = ifelse(
        significant,
        bold("TRUE"),
        "FALSE"
      )
    )
  html <- knitr::kable(
    display_table,
    format = "html",
    escape = FALSE,
    digits = 10
  )

  html_print(as.character(html))
}

```

```
}
```

```
[31]: dat <- dat %>%  
  mutate(  
    participant = factor(participant),  
    group = factor(group),  
    task_id = factor(task_id, levels = 1:17)  
  )
```

```
[ ]:
```

5.1 TTU

```
[32]: fit_ttu <- nparLD(  
  TTU ~ task_id * group,  
  data = dat,  
  subject = "participant"  
)
```

```
[33]: # summary(fit_ttu)
```

```
[34]: ats_ttu <- report_ats(  
  fit = fit_ttu,  
  outcome = "TTU",  
  within = "task_id",  
  between = "group"  
)  
  
format_table_significant_column_bold(ats_ttu)
```

```
[ ]:
```

```
[35]: # get the p values with more precision:
```

```
# ats <- as.data.frame(fit_ttu$ATS)
```

```
# stat_col <- grep(  
#   "statistic|ATS",  
#   names(ats),  
#   ignore.case = TRUE,  
#   value = TRUE  
# )[1]
```

```
# df_col <- grep(  
#   "~df$/degrees",  
#   names(ats),
```

```

#   ignore.case = TRUE,
#   value = TRUE
# )[1]

# statistic <- as.numeric(ats[[stat_col]])
# df <- as.numeric(ats[[df_col]])

# # Stable ATS p-values
# p_stable <- stats::pchisq(
#   statistic * df,
#   df = df,
#   lower.tail = FALSE
# )

# data.frame(
#   effect = rownames(ats),
#   statistic = statistic,
#   df = df,
#   p_from_nparLD = p_values,
#   p_recalculated = sprintf("%.16e", p_stable)
# )

```

```

[36]: rte <- as.data.frame(fit_ttu$RTE)
      rte

```

-> There is a difference in TTU between levels of task_id

Tasks differ overall, but there is no evidence that the pattern of task differences differs between participant groups.

-> follow-up question: For a given task, is there a difference in TTU/DOU across the groups?

5.1.1.1 TTU - video times (“TTU_mod”)

```

[37]: # Initialise TTUmod as a copy of TTU
      dat$TTU_mod <- dat$TTU

      # Apply the subtraction only where the condition holds
      idx <- dat$group == "Dynamic sketch construction"
      dat$TTU_mod[idx] <- dat$TTU[idx] - dat$video_length_in_s[idx]

      dat

```

	participant <fct>	task_id <fct>	group <fct>	TTU <dbl>	DOU <dbl>	structural_ <list>
	p01	1	Formula construction	17	1.0	COMP, CE
	p31	1	Formula construction	23	0.6	COMP, CE
	p34	1	Formula construction	14	1.0	COMP, CE
	p33	1	Formula construction	28	1.0	COMP, CE
	p26	1	Formula construction	92	0.6	COMP, CE
	p21	1	Formula construction	33	1.0	COMP, CE
	p27	1	Formula construction	21	1.0	COMP, CE
	p11	1	Static sketch construction	10	1.0	COMP, CE
	p30	1	Static sketch construction	24	1.0	COMP, CE
	p28	1	Static sketch construction	28	1.0	COMP, CE
	p09	1	Static sketch construction	14	1.0	COMP, CE
	p14	1	Static sketch construction	13	1.0	COMP, CE
	p15	1	Static sketch construction	60	1.0	COMP, CE
	p02	1	Static sketch construction	31	1.0	COMP, CE
	p03	1	Dynamic sketch construction	28	1.0	COMP, CE
	p05	1	Dynamic sketch construction	32	1.0	COMP, CE
	p04	1	Dynamic sketch construction	26	1.0	COMP, CE
	p20	1	Dynamic sketch construction	24	1.0	COMP, CE
	p07	1	Dynamic sketch construction	24	1.0	COMP, CE
	p38	1	Dynamic sketch construction	26	1.0	COMP, CE
	p06	1	Dynamic sketch construction	64	1.0	COMP, CE
	p01	2	Formula construction	26	1.0	COMP , RA
	p31	2	Formula construction	16	1.0	COMP , RA
	p34	2	Formula construction	15	1.0	COMP , RA
	p33	2	Formula construction	18	1.0	COMP , RA
	p26	2	Formula construction	14	1.0	COMP , RA
	p21	2	Formula construction	27	1.0	COMP , RA
	p27	2	Formula construction	15	1.0	COMP , RA
	p11	2	Static sketch construction	8	1.0	COMP , RA
A data.frame: 357 × 12	p30	2	Static sketch construction	14	1.0	COMP , RA
	p15	16	Static sketch construction	40	0.7500000	COND , RA
	p02	16	Static sketch construction	58	0.8750000	COND , RA
	p03	16	Dynamic sketch construction	42	0.8750000	COND , RA
	p05	16	Dynamic sketch construction	50	0.8750000	COND , RA
	p04	16	Dynamic sketch construction	65	0.8750000	COND , RA
	p20	16	Dynamic sketch construction	76	0.8750000	COND , RA
	p07	16	Dynamic sketch construction	123	0.8750000	COND , RA
	p38	16	Dynamic sketch construction	41	0.8750000	COND , RA
	p06	16	Dynamic sketch construction	134	0.8750000	COND , RA
	p01	17	Formula construction	100	1.0000000	COND , LC
	p31	17	Formula construction	245	0.8571429	COND , LC
	p34	17	Formula construction	34	1.0000000	COND , LC
	p33	17	Formula construction	46	0.8571429	COND , LC
	p26	17	Formula construction	24	1.0000000	COND , LC
	p21	17	Formula construction	69	0.4285714	COND , LC
	p27	17	Formula construction	28	1.0000000	COND , LC
	p11	17	Static sketch construction	39	1.0000000	COND , LC
	p30	17	Static sketch construction	13	1.0000000	COND , LC
	p28	17	Static sketch construction	28	0.7142857	COND , LC
	p09	17	Static sketch construction	92	1.0000000	COND , LC

```
[38]: fit_ttu_mod <- nparLD(
      TTU_mod ~ task_id * group,
      data = dat,
      subject = "participant"
    )
```

```
[39]: ats_ttu_mod <- report_ats(
      fit = fit_ttu_mod,
      outcome = "TTU_mod",
      within = "task_id",
      between = "group"
    )

format_table_significant_column_bold(ats_ttu_mod)
```

-> Individually, group and task_id have an effect on TTU_mod, but the group difference in TTU-mod does not depend on the task.

5.1.2 DOU

```
[40]: fit_dou <- nparLD(
      DOU ~ task_id * group,
      data = dat,
      subject = "participant"
    )
```

```
[41]: # summary(fit_dou)
```

```
[42]: ats_dou <- report_ats(
      fit = fit_dou,
      outcome = "DOU",
      within = "task_id",
      between = "group"
    )

format_table_significant_column_bold(ats_dou)
```

-> **There is a difference in DOU between levels of task_id and The effect of group on DOU does differ across levels of task_id.**

The group difference in DOU depends on the task.

influence of task_id always significant -> TTU/DOU differ between at least some of the 17 tasks (expected)

-> *follow-up*: **Replace task_id with meaningful task properties**(see structural characteristics)

6 For a given task, is there a difference in TTU/DOU across the groups?

```
[43]: kruskal_by_task <- function(
  data,
  task,
  outcome = "TTU",
  task_col = "task_id",
  group_col = "group"
) {

  # Prüfen, ob benötigte Spalten existieren
  required_cols <- c(task_col, group_col, outcome)

  if (!all(required_cols %in% names(data))) {
    stop(
      "Missing column(s): ",
      paste(setdiff(required_cols, names(data)), collapse = ", ")
    )
  }

  # Outcome muss numerisch sein
  if (!is.numeric(data[[outcome]])) {
    stop("Outcome column '", outcome, "' must be numeric.")
  }

  # Gewünschten Task sowie gültige Werte auswählen
  task_data <- data %>%
    dplyr::filter(
      .data[[task_col]] == task,
      !is.na(.data[[outcome]]),
      is.finite(.data[[outcome]]),
      !is.na(.data[[group_col]])
    )

  # Gruppe sicher als Faktor behandeln
  task_data[[group_col]] <- droplevels(factor(task_data[[group_col]]))

  n <- nrow(task_data)
  k <- nlevels(task_data[[group_col]])
  n_unique <- dplyr::n_distinct(task_data[[outcome]])

  if (n == 0) {
    warning(
      "Skipping task ", task, " for ", outcome,
      ": no valid observations."
    )
  }
}
```

```

    return(NULL)
  }

  if (k < 2) {
    warning(
      "Skipping task ", task, " for ", outcome,
      ": fewer than two groups with valid observations."
    )
    return(NULL)
  }

  # Alle Werte identisch: Kruskal-Wallis ist nicht definiert.
  if (n_unique <= 1) {
    warning(
      "Skipping task ", task, " for ", outcome,
      ": all ", n, " valid outcome values are identical (",
      task_data[[outcome]][1], "). No group comparison is possible."
    )
    return(NULL)
  }

  # Dynamische Formel, z. B. TTU ~ group
  test_formula <- as.formula(
    paste(outcome, "~", group_col)
  )

  kw <- kruskal.test(
    formula = test_formula,
    data = task_data
  )

  H <- unname(kw$statistic)
  df <- unname(kw$parameter)
  p <- kw$p.value

  # Zusätzliche Absicherung gegen NaN/Inf
  if (!is.finite(H) || !is.finite(p)) {
    warning(
      "Skipping task ", task, " for ", outcome,
      ": Kruskal-Wallis returned a non-finite statistic or p-value."
    )
    return(NULL)
  }

  # Epsilon squared als Effektgröße für Kruskal-Wallis
  # Falls n == k, wäre die Effektgröße nicht definierbar.
  epsilon_squared <- if (n > k) {

```

```

    max(0, (H - k + 1) / (n - k))
  } else {
    NA_real_
  }

effect_magnitude <- dplyr::case_when(
  is.na(epsilon_squared) ~ NA_character_,
  epsilon_squared < 0.01 ~ "negligible",
  epsilon_squared < 0.06 ~ "small",
  epsilon_squared < 0.14 ~ "medium",
  TRUE ~ "large"
)

data.frame(
  task_id = task,
  outcome = outcome,
  n = n,
  n_groups = k,
  n_unique_values = n_unique,
  kruskal_H = round(H, 3),
  degrees_of_freedom = df,
  p_value = p,

  significant = ifelse(
    p < alpha,
    " ",
    "_ "
  ),

  conclusion = ifelse(
    p < alpha,
    "SIGNIFICANT",
    "Not significant"
  ),

  effect_size = round(epsilon_squared, 7),
  effect_magnitude = effect_magnitude,

  row.names = NULL,
  check.names = FALSE
)
}

```

```

[44]: all_tasks_kw <- function(
  data,
  outcome = "TTU",
  task_col = "task_id",

```

```

group_col = "group"
) {

  tasks <- sort(unique(data[[task_col]]))

  results <- lapply(tasks, function(task) {
    kruskal_by_task(
      data = data,
      task = task,
      outcome = outcome,
      task_col = task_col,
      group_col = group_col
    )
  })

  # NULL-Ergebnisse entfernen: ausgeschlossene Tasks erscheinen nicht in der
  ↪Tabelle
  results <- Filter(Negate(is.null), results)

  if (length(results) == 0) {
    warning("No valid Kruskal-Wallis tests could be performed for ", outcome, ".
    ↪")
    return(data.frame())
  }

  dplyr::bind_rows(results)
}

```

```

[45]: cliffs_delta <- function(x, y) {

  x <- x[is.finite(x)]
  y <- y[is.finite(y)]

  comparisons <- outer(x, y, FUN = "-")

  (
    sum(comparisons > 0) -
    sum(comparisons < 0)
  ) / (length(x) * length(y))
}

interpret_cliffs_delta <- function(delta) {

  abs_delta <- abs(delta)

  if (abs_delta < 0.147) {

```

```

    "negligible"
  } else if (abs_delta < 0.330) {
    "small"
  } else if (abs_delta < 0.474) {
    "medium"
  } else {
    "large"
  }
}
}

```

```

[46]: posthoc_by_task <- function(
  data,
  task,
  outcome = "TTU",
  task_col = "task_id",
  group_col = "group"
) {

  # First: omnibus Kruskal-Wallis test
  omnibus <- kruskal_by_task(
    data = data,
    task = task,
    outcome = outcome,
    task_col = task_col,
    group_col = group_col
  )

  # Task may have been skipped due to no variation etc.
  if (is.null(omnibus)) {
    return(NULL)
  }

  # Post-hoc only after significant omnibus test
  if (omnibus$p_value >= alpha) {
    message(
      "Skipping post-hoc for task ", task,
      " (", outcome, "): Kruskal-Wallis is not significant; p = ",
      format.pval(omnibus$p_value, digits = 3, eps = 0.001)
    )
    return(NULL)
  }

  # Select valid observations for this task
  task_data <- data %>%
    dplyr::filter(
      .data[[task_col]] == task,
      !is.na(.data[[outcome]]),

```

```

    is.finite(.data[[outcome]]),
    !is.na(.data[[group_col]])
  )

task_data[[group_col]] <- droplevels(
  factor(task_data[[group_col]])
)

groups <- levels(task_data[[group_col]])

if (length(groups) < 2) {
  warning("Fewer than two valid groups for task ", task, ".")
  return(NULL)
}

# All group pairs, e.g. A-B, A-C, B-C
group_pairs <- combn(groups, 2, simplify = FALSE)

# Run pairwise Wilcoxon rank-sum tests
results <- lapply(group_pairs, function(pair) {

  group_1 <- pair[1]
  group_2 <- pair[2]

  x <- task_data[[outcome]][
    task_data[[group_col]] == group_1
  ]

  y <- task_data[[outcome]][
    task_data[[group_col]] == group_2
  ]

  # exact = FALSE is important when there are ties
  test <- wilcox.test(
    x,
    y,
    paired = FALSE,
    exact = FALSE
  )

  delta <- cliffs_delta(x, y)

  data.frame(
    task_id = task,
    outcome = outcome,
    group1 = group_1,
    group2 = group_2,

```

```

n_group1 = length(x),
n_group2 = length(y),
W = unname(test$statistic),
p_value = test$p.value,
cliffs_delta = delta,
effect_magnitude = interpret_cliffs_delta(delta),
direction = ifelse(
  delta > 0,
  paste(group_1, "higher than", group_2),
  ifelse(
    delta < 0,
    paste(group_2, "higher than", group_1),
    "No directional difference"
  )
),
row.names = NULL,
check.names = FALSE
)
})

results <- dplyr::bind_rows(results) %>%
dplyr::mutate(
  p_holm = p.adjust(p_value, method = "holm"),

  significant = ifelse(
    p_holm < alpha,
    " ",
    "-"
  ),

  conclusion = ifelse(
    p_holm < alpha,
    "SIGNIFICANT after Holm correction",
    "Not significant after Holm correction"
  ),

  cliffs_delta = round(cliffs_delta, 7)
) %>%
dplyr::select(
  task_id,
  outcome,
  group1,
  group2,
  # n_group1,
  # n_group2,
  W,
  p_value,

```

```

        p_holm,
        significant,
        conclusion,
        cliffs_delta,
        effect_magnitude,
        direction
    )

    results
}

```

```

[47]: compact_letters_by_task <- function(
  data,
  posthoc_results,
  task,
  outcome_name,
  task_col = "task_id",
  group_col = "group"
) {

  # Passende Post-hoc-Vergleiche auswählen
  comparisons <- posthoc_results %>%
    dplyr::filter(
      .data$task_id == task,
      .data$outcome == outcome_name
    )

  if (nrow(comparisons) == 0) {
    warning(
      "No post-hoc comparisons found for task ", task,
      " and outcome ", outcome_name, "."
    )
    return(NULL)
  }

  # Holm-korrigierte Signifikanz der Paarvergleiche
  comparison_names <- paste(
    comparisons$group1,
    comparisons$group2,
    sep = "-"
  )

  significant_comparisons <- comparisons$p_holm < alpha
  names(significant_comparisons) <- comparison_names

  # Compact Letter Display erzeugen
  letters <- multcompView::multcompLetters(

```

```

    significant_comparisons
  )$Letters

cld <- data.frame(
  task_id = task,
  outcome = outcome_name,
  group = names(letters),
  compact_letter = unname(letters),
  row.names = NULL
)

# Originaldaten dieses Tasks auswählen und Gruppenkennwerte berechnen
task_data <- data %>%
  dplyr::filter(
    .data[[task_col]] == task,
    !is.na(.data[[outcome_name]]),
    is.finite(.data[[outcome_name]]),
    !is.na(.data[[group_col]])
  )

summary_data <- task_data %>%
  dplyr::group_by(group = .data[[group_col]]) %>%
  dplyr::summarise(
    n = dplyr::n(),
    median = median(.data[[outcome_name]]),
    q1 = quantile(.data[[outcome_name]], 0.25),
    q3 = quantile(.data[[outcome_name]], 0.75),
    mean = mean(.data[[outcome_name]]),
    .groups = "drop"
  )

# Mediane und Buchstaben verbinden
summary_data %>%
  dplyr::left_join(cld, by = "group") %>%
  dplyr::select(
    task_id,
    outcome,
    group,
    n,
    median,
    q1,
    q3,
    mean,
    compact_letter
  ) %>%
  dplyr::arrange(median)
}

```

```
[48]: #summarizing post hoc test and CLD:
posthoc_and_cld <- function(data,
                             task,
                             outcome_name) {
  if (!outcome_name %in% names(data)) {
    stop(
      sprintf(
        "Outcome column '%s' not found in `data`. Available columns are: %s",
        outcome_name,
        paste(names(data), collapse = ", ")
      ),
      call. = FALSE
    )
  }

  posthoc_res <- posthoc_by_task(
    data      = data,
    task      = task,
    outcome   = outcome_name
  )

  cld_res <- compact_letters_by_task(
    data            = data,
    posthoc_results = posthoc_res,
    task            = task,
    outcome_name    = outcome_name
  )

  list(
    posthoc = posthoc_res,
    cld     = cld_res
  )
}
```

```
[49]: export_outcome_table <- function(
  ...,
  tex_file = "outcome_results.tex"
) {

  # -----
  # Use global alpha
  # -----

  if (!exists("alpha", inherits = TRUE)) {
    stop("Global variable 'alpha' was not found.")
  }
}
```

```

alpha_value <- get("alpha", inherits = TRUE)

if (
  length(alpha_value) != 1 ||
  !is.numeric(alpha_value) ||
  !is.finite(alpha_value) ||
  alpha_value <= 0 ||
  alpha_value >= 1
) {
  stop("Global variable 'alpha' must be one number between 0 and 1.")
}

# -----
# Collect data frames
# -----

data_list <- list(...)

# Also allow a single named list of data frames
if (
  length(data_list) == 1 &&
  is.list(data_list[[1]]) &&
  !is.data.frame(data_list[[1]])
) {
  data_list <- data_list[[1]]
}

if (length(data_list) == 0) {
  stop("At least one data frame must be supplied.")
}

if (!all(vapply(data_list, is.data.frame, logical(1)))) {
  stop("All supplied objects must be data frames.")
}

required_columns <- c(
  "task_id",
  "outcome",
  "p_value",
  "effect_size"
)

for (i in seq_along(data_list)) {
  missing_columns <- setdiff(
    required_columns,
    names(data_list[[i]])
  )
}

```

```

)

if (length(missing_columns) > 0) {
  stop(
    "Data frame ", i, " is missing column(s): ",
    paste(missing_columns, collapse = ", ")
  )
}

if (anyDuplicated(as.character(data_list[[i]]$task_id))) {
  stop(
    "Data frame ", i,
    " contains duplicated task_id values."
  )
}
}

# -----
# Determine outcome names
#
# Named arguments such as TTU = kw_ttu take precedence over the outcome
# column.
# -----

input_names <- names(data_list)

if (is.null(input_names)) {
  input_names <- rep("", length(data_list))
}

outcome_names <- character(length(data_list))

for (i in seq_along(data_list)) {

  if (
    length(input_names) >= i &&
    !is.na(input_names[i]) &&
    nzchar(input_names[i])
  ) {

    outcome_names[i] <- input_names[i]

  } else {

    current_outcomes <- unique(
      as.character(
        data_list[[i]]$outcome[

```

```

        !is.na(data_list[[i]]$outcome)
      ]
    )
  )

  if (length(current_outcomes) != 1) {
    stop(
      "Data frame ", i,
      " must contain exactly one non-missing outcome value, ",
      "or it must be supplied as a named argument."
    )
  }

  outcome_names[i] <- current_outcomes
}
}

# -----
# Preserve task ordering across the supplied data frames
# -----

task_ids <- unique(
  unlist(
    lapply(
      data_list,
      function(x) as.character(x$task_id)
    ),
    use.names = FALSE
  )
)

# -----
# LaTeX helper functions
# -----

latex_escape <- function(x) {

  x <- as.character(x)

  vapply(
    x,
    function(value) {

      if (is.na(value)) {
        return("")
      }
    }
  )
}

```

```

characters <- strsplit(
  value,
  "",
  fixed = TRUE
)[[1]]

replacements <- c(
  "&" = "\\&",
  "%" = "\\%",
  "$" = "\\$",
  "#" = "\\#",
  "_" = "\\_",
  "{" = "\\{",
  "}" = "\\}",
  "~" = "\\textasciitilde{}",
  "^" = "\\textasciicircum{}"
)

paste0(
  vapply(
    characters,
    function(character) {
      if (character %in% names(replacements)) {
        replacements[[character]]
      } else {
        character
      }
    },
    character(1)
  ),
  collapse = ""
),
character(1)
)
}

# Exactly six decimal places, enclosed in \num{...}.
# Significant values are additionally enclosed in \underline{...}.
format_num <- function(x, underline = FALSE) {

  numeric_x <- suppressWarnings(
    as.numeric(as.character(x))
  )

  if (length(underline) == 1) {
    underline <- rep(underline, length(numeric_x))
  }
}

```

```

}

underline[is.na(underline)] <- FALSE

vapply(
  seq_along(numeric_x),
  function(i) {

    value <- numeric_x[i]

    if (is.na(value)) {
      return("")
    }

    if (!is.finite(value)) {
      return(latex_escape(as.character(value)))
    }

    # Prevent negative zero after rounding.
    if (abs(value) < 0.5e-6) {
      value <- 0
    }

    latex_value <- paste0(
      "\\num{",
      sprintf("%.6f", value),
      "}"
    )

    if (isTRUE(underline[i])) {
      latex_value <- paste0(
        "\\underline{",
        latex_value,
        "}"
      )
    }

    latex_value
  },
  character(1)
)

# Task IDs remain plain text/numbers.
format_task_id <- function(x) {
  latex_escape(as.character(x))
}

```

```

# -----
# Align all data frames by task_id
# -----

table_columns <- list(
  Task = format_task_id(task_ids)
)

for (i in seq_along(data_list)) {

  current_data <- data_list[[i]]

  row_indices <- match(
    task_ids,
    as.character(current_data$task_id)
  )

  current_p <- suppressWarnings(
    as.numeric(
      as.character(
        current_data$p_value[row_indices]
      )
    )
  )

  current_effect <- suppressWarnings(
    as.numeric(
      as.character(
        current_data$effect_size[row_indices]
      )
    )
  )

  # Significance is determined independently for each outcome.
  current_significant <- (
    !is.na(current_p) &
    current_p < alpha_value
  )

  table_columns[[paste0("p_", i)]] <- format_num(
    current_p,
    underline = current_significant
  )

  table_columns[[paste0("effect_", i)]] <- format_num(
    current_effect,

```

```

    underline = current_significant
  )
}

table_data <- as.data.frame(
  table_columns,
  stringsAsFactors = FALSE,
  check.names = FALSE
)

# -----
# Construct two-row header
# -----

n_outcomes <- length(data_list)

outcome_header <- paste0(
  "& ",
  paste(
    paste0(
      "\\multicolumn{2}{c}{",
      latex_escape(outcome_names),
      "}"
    ),
    collapse = " & "
  ),
  " \\\\"
)

cmidrules <- paste(
  vapply(
    seq_len(n_outcomes),
    function(i) {

      first_column <- 2 + (i - 1) * 2
      last_column <- first_column + 1

      paste0(
        "\\cmidrule(lr){",
        first_column,
        "-",
        last_column,
        "}"
      )
    },
    character(1)
  ),

```

```

collapse = " "
)

second_header <- paste0(
  "Task & ",
  paste(
    rep(
      c("$p$-value", "Effect size"),
      times = n_outcomes
    ),
    collapse = " & "
  ),
  " \\\\"
)

# -----
# Construct table rows
# -----

table_rows <- vapply(
  seq_len(nrow(table_data)),
  function(i) {
    paste0(
      paste(
        as.character(table_data[i, ]),
        collapse = " & "
      ),
      " \\\\"
    )
  },
  character(1)
)

column_alignment <- paste0(
  "l",
  paste(
    rep("rr", n_outcomes),
    collapse = ""
  )
)

# -----
# Construct only the tabular environment
# -----

latex_output <- c(
  paste0(

```

```

        "\\begin{tabular}{",
        column_alignment,
        "}"
    ),
    "\\toprule",
    outcome_header,
    cmidrules,
    second_header,
    "\\midrule",
    table_rows,
    "\\bottomrule",
    "\\end{tabular}"
)

writeLines(
  latex_output,
  con = tex_file,
  useBytes = TRUE
)

message(
  "LaTeX tabular saved to: ",
  normalizePath(tex_file, mustWork = FALSE)
)

invisible(latex_output)
}

```

6.0.1 H0: There is no difference in TTU between participant groups for task ...

```

[50]: kw_ttu <- all_tasks_kw(
  data = dat,
  outcome = "TTU"
)

kw_ttu

```

	task_id <fct>	outcome <chr>	n <int>	n_groups <int>	n_unique_values <int>	kruskal_H <dbl>	degrees_of_freedom <int>
	1	TTU	21	3	15	1.447	2
	2	TTU	21	3	14	5.361	2
	3	TTU	21	3	14	4.042	2
	4	TTU	21	3	14	3.836	2
	5	TTU	21	3	20	3.394	2
	6	TTU	21	3	19	1.629	2
	7	TTU	21	3	20	1.760	2
A data.frame: 17 × 12	8	TTU	21	3	20	0.072	2
	9	TTU	21	3	19	0.570	2
	10	TTU	21	3	19	0.007	2
	11	TTU	21	3	17	1.790	2
	12	TTU	21	3	19	4.661	2
	13	TTU	21	3	19	1.813	2
	14	TTU	21	3	18	4.674	2
	15	TTU	21	3	19	2.042	2
	16	TTU	21	3	21	5.098	2
	17	TTU	21	3	19	0.507	2

-> The test did not find sufficient statistical evidence that the participant groups differ for this task and metric.

Looking at TTU_mod instead, we find:

```
[51]: kw_ttu_mod <- all_tasks_kw(
  data = dat,
  outcome = "TTU_mod"
)

kw_ttu_mod
```

	task_id <fct>	outcome <chr>	n <int>	n_groups <int>	n_unique_values <int>	kruskal_H <dbl>	degrees_of_freedom <int>
	1	TTU_mod	21	3	16	2.850	2
	2	TTU_mod	21	3	13	4.781	2
	3	TTU_mod	21	3	14	2.698	2
	4	TTU_mod	21	3	16	3.673	2
	5	TTU_mod	21	3	19	1.808	2
	6	TTU_mod	21	3	18	3.368	2
	7	TTU_mod	21	3	20	4.552	2
A data.frame: 17 × 12	8	TTU_mod	21	3	19	2.474	2
	9	TTU_mod	21	3	20	8.889	2
	10	TTU_mod	21	3	18	5.902	2
	11	TTU_mod	21	3	16	7.956	2
	12	TTU_mod	21	3	17	6.353	2
	13	TTU_mod	21	3	17	10.664	2
	14	TTU_mod	21	3	19	9.877	2
	15	TTU_mod	21	3	19	9.937	2
	16	TTU_mod	21	3	20	2.274	2
	17	TTU_mod	21	3	19	1.209	2

```
[52]: result__TTU_mod <- posthoc_and_cld(
  data      = dat,
  task      = 9,
  outcome_name = "TTU_mod"
)

result__TTU_mod$posthoc
result__TTU_mod$cld
```

	task_id <dbl>	outcome <chr>	group1 <chr>	group2 <chr>	W <dbl>
A data.frame: 3 × 12	9	TTU_mod	Dynamic sketch construction	Formula construction	2
	9	TTU_mod	Dynamic sketch construction	Static sketch construction	8
	9	TTU_mod	Formula construction	Static sketch construction	29

	task_id <dbl>	outcome <chr>	group <chr>	n <int>	median <dbl>	q1 <dbl>	q3 <dbl>	mean <dbl>
A tibble: 3 × 9	9	TTU_mod	Dynamic sketch construction	7	24	11.0	30.0	20.8
	9	TTU_mod	Static sketch construction	7	43	30.5	57.5	51.5
	9	TTU_mod	Formula construction	7	61	42.5	62.5	55.0

```
[53]: result__TTU_mod <- posthoc_and_cld(
  data      = dat,
  task      = 11,
  outcome_name = "TTU_mod"
)

result__TTU_mod$posthoc
```

```
result__TTU_mod$cld
```

	task_id <dbl>	outcome <chr>	group1 <chr>	group2 <chr>	W <dbl>
A data.frame: 3 × 12	11	TTU_mod	Dynamic sketch construction	Formula construction	8.0
	11	TTU_mod	Dynamic sketch construction	Static sketch construction	4.5
	11	TTU_mod	Formula construction	Static sketch construction	18.0

	task_id <dbl>	outcome <chr>	group <chr>	n <int>	median <dbl>	q1 <dbl>	q3 <dbl>	mean <dbl>
A tibble: 3 × 9	11	TTU_mod	Dynamic sketch construction	7	14	9.5	16.5	13.14
	11	TTU_mod	Formula construction	7	26	20.5	30.0	35.14
	11	TTU_mod	Static sketch construction	7	29	26.0	41.5	32.71

```
[54]: result__TTU_mod <- posthoc_and_cld(  
  data      = dat,  
  task      = 12,  
  outcome_name = "TTU_mod"  
)  
  
result__TTU_mod$posthoc  
result__TTU_mod$cld
```

	task_id <dbl>	outcome <chr>	group1 <chr>	group2 <chr>	W <dbl>
A data.frame: 3 × 12	12	TTU_mod	Dynamic sketch construction	Formula construction	6.5
	12	TTU_mod	Dynamic sketch construction	Static sketch construction	20.0
	12	TTU_mod	Formula construction	Static sketch construction	39.5

	task_id <dbl>	outcome <chr>	group <chr>	n <int>	median <dbl>	q1 <dbl>	q3 <dbl>	mean <dbl>
A tibble: 3 × 9	12	TTU_mod	Dynamic sketch construction	7	33	18.5	39.5	29.71
	12	TTU_mod	Static sketch construction	7	33	29.0	42.0	35.14
	12	TTU_mod	Formula construction	7	52	48.0	82.5	60.71

```
[55]: result__TTU_mod <- posthoc_and_cld(  
  data      = dat,  
  task      = 13,  
  outcome_name = "TTU_mod"  
)  
  
result__TTU_mod$posthoc  
result__TTU_mod$cld
```

	task_id <dbl>	outcome <chr>	group1 <chr>	group2 <chr>	W <dbl>
A data.frame: 3 × 12	13	TTU_mod	Dynamic sketch construction	Formula construction	5.5
	13	TTU_mod	Dynamic sketch construction	Static sketch construction	1.5
	13	TTU_mod	Formula construction	Static sketch construction	16.0

	task_id <dbl>	outcome <chr>	group <chr>	n <int>	median <dbl>	q1 <dbl>	q3 <dbl>	mean <dbl>
A tibble: 3 × 9	13	TTU_mod	Dynamic sketch construction	7	15	9.0	18.0	14.5
	13	TTU_mod	Formula construction	7	35	27.0	44.5	37.0
	13	TTU_mod	Static sketch construction	7	46	30.5	64.0	55.5

```
[56]: result__TTU_mod <- posthoc_and_cld(
  data      = dat,
  task      = 14,
  outcome_name = "TTU_mod"
)

result__TTU_mod$posthoc
result__TTU_mod$cld
```

	task_id	outcome	group1	group2	W			
	<dbl>	<chr>	<chr>	<chr>	<dbl>			
A data.frame: 3 × 12	14	TTU_mod	Dynamic sketch construction	Formula construction	0.0			
	14	TTU_mod	Dynamic sketch construction	Static sketch construction	10.5			
	14	TTU_mod	Formula construction	Static sketch construction	34.0			
	task_id	outcome	group	n	median	q1	q3	mean
	<dbl>	<chr>	<chr>	<int>	<dbl>	<dbl>	<dbl>	<dbl>
A tibble: 3 × 9	14	TTU_mod	Dynamic sketch construction	7	25	20.5	29.5	23.28
	14	TTU_mod	Static sketch construction	7	58	28.0	66.5	67.28
	14	TTU_mod	Formula construction	7	96	53.0	115.5	110.0

```
[57]: result__TTU_mod <- posthoc_and_cld(
  data      = dat,
  task      = 15,
  outcome_name = "TTU_mod"
)

result__TTU_mod$posthoc
result__TTU_mod$cld
```

	task_id <dbl>	outcome <chr>	group1 <chr>	group2 <chr>	W <dbl>			
A data.frame: 3 × 12	15	TTU_mod	Dynamic sketch construction	Formula construction	2.0			
	15	TTU_mod	Dynamic sketch construction	Static sketch construction	5.5			
	15	TTU_mod	Formula construction	Static sketch construction	29.5			
	task_id <dbl>	outcome <chr>	group <chr>	n <int>	median <dbl>	q1 <dbl>	q3 <dbl>	mean <dbl>
A tibble: 3 × 9	15	TTU_mod	Dynamic sketch construction	7	45	39.5	47	44.7
	15	TTU_mod	Static sketch construction	7	76	62.0	108	97.5
	15	TTU_mod	Formula construction	7	91	80.5	94	95.1

```
[ ]:
```

[]:

6.1 H0: There is no difference in DOU between participant groups for task ...

```
[58]: kw_dou <- all_tasks_kw(  
      data = dat,  
      outcome = "DOU"  
)  
  
kw_dou
```

Warning message in kruskal_by_task(data = data, task = task, outcome = outcome,
:
"Skipping task 4 for DOU: all 21 valid outcome values are identical (1). No
group comparison is possible."
Warning message in kruskal_by_task(data = data, task = task, outcome = outcome,
:
"Skipping task 11 for DOU: all 21 valid outcome values are identical (1). No
group comparison is possible."
Warning message in kruskal_by_task(data = data, task = task, outcome = outcome,
:
"Skipping task 12 for DOU: all 21 valid outcome values are identical (1). No
group comparison is possible."

A data.frame: 14 × 12

task_id	outcome	n	n_groups	n_unique_values	kruskal_H	degrees_of_freedom
<fct>	<chr>	<int>	<int>	<int>	<dbl>	<int>
1	DOU	21	3	2	4.211	2
2	DOU	21	3	2	2.000	2
3	DOU	21	3	2	2.000	2
5	DOU	21	3	3	0.778	2
6	DOU	21	3	2	5.000	2
7	DOU	21	3	5	4.056	2
8	DOU	21	3	4	6.929	2
9	DOU	21	3	5	1.344	2
10	DOU	21	3	6	1.901	2
13	DOU	21	3	2	1.053	2
14	DOU	21	3	5	4.594	2
15	DOU	21	3	7	13.604	2
16	DOU	21	3	4	4.581	2
17	DOU	21	3	6	0.228	2

-> For **task 8 and 15** there are **possible differences in DOU** across the groups.

-> Performing a post hoc test:

```
[59]: export_outcome_table(  
      TTU = kw_ttu,  
      DOU = kw_dou,  
      tex_file = "ttu_dou_results.tex"
```

```
)
```

LaTeX tabular saved to: /home/judith/Schreibtisch/angew. Informatik - system engineering/Study_DrawingAttention/ttu_dou_results.tex

```
[ ]:
```

```
[ ]:
```

Task 8:

```
[60]: result__DOU <- posthoc_and_cld(  
      data      = dat,  
      task      = 8,  
      outcome_name = "DOU"  
    )  
  
result__DOU$posthoc  
result__DOU$cld
```

	task_id	outcome	group1	group2	W	p	
	<dbl>	<chr>	<chr>	<chr>	<dbl>	<dbl>	
A data.frame: 3 × 12	8	DOU	Dynamic sketch construction	Formula construction	22.0	0.000000	
	8	DOU	Dynamic sketch construction	Static sketch construction	41.5	0.000000	
	8	DOU	Formula construction	Static sketch construction	39.0	0.000000	
	task_id	outcome	group	n	median	q1	q3
	<dbl>	<chr>	<chr>	<int>	<dbl>	<dbl>	<dbl>
A tibble: 3 × 9	8	DOU	Static sketch construction	7	0.8571429	0.7142857	0.8571429
	8	DOU	Dynamic sketch construction	7	1.0000000	0.9285714	1.0000000
	8	DOU	Formula construction	7	1.0000000	1.0000000	1.0000000

-> No significant difference between groups in Task 8 after correction.

Task 15:

```
[61]: result__DOU <- posthoc_and_cld(  
      data      = dat,  
      task      = 15,  
      outcome_name = "DOU"  
    )  
  
result__DOU$posthoc  
result__DOU$cld
```

	task_id	outcome	group1	group2	W	p
	<dbl>	<chr>	<chr>	<chr>	<dbl>	<dbl>
A data.frame: 3 × 12	15	DOU	Dynamic sketch construction	Formula construction	49.0	0.000000
	15	DOU	Dynamic sketch construction	Static sketch construction	31.5	0.000000
	15	DOU	Formula construction	Static sketch construction	6.0	0.000000

	task_id <dbl>	outcome <chr>	group <chr>	n <int>	median <dbl>	q1 <dbl>	q3 <dbl>
A tibble: 3 × 9	15	DOU	Formula construction	7	0.5454545	0.3181818	0.7727273
	15	DOU	Dynamic sketch construction	7	1.0000000	1.0000000	1.0000000
	15	DOU	Static sketch construction	7	1.0000000	0.9090909	1.0000000

-> Group “Formula construction” performs worse than the others for task 15, by - in median - understanding about half of the task only.

The “Formula construction” group underperforms compared to the others on task 15, with a median understanding of only about half the task.

```
[62]: export_posthoc_subtables <- function(
  posthoc,
  cld,
  tex_file = "posthoc_subtables.tex"
) {

  # -----
  # Checks
  # -----

  if (!is.data.frame(posthoc)) {
    stop("'posthoc' must be a data frame.")
  }

  if (!is.data.frame(cld)) {
    stop("'cld' must be a data frame.")
  }

  required_posthoc <- c(
    "task_id",
    "outcome",
    "group1",
    "group2",
    "p_value",
    "p_holm",
    "cliffs_delta"
  )

  required_cld <- c(
    "task_id",
    "outcome",
    "group",
    "mean",
    "median",
    "compact_letter"
  )
}
```

```

missing_posthoc <- setdiff(
  required_posthoc,
  names(posthoc)
)

missing_cld <- setdiff(
  required_cld,
  names(cld)
)

if (length(missing_posthoc) > 0) {
  stop(
    "'posthoc' is missing column(s): ",
    paste(missing_posthoc, collapse = ", ")
  )
}

if (length(missing_cld) > 0) {
  stop(
    "'cld' is missing column(s): ",
    paste(missing_cld, collapse = ", ")
  )
}

# -----
# Use global alpha
# -----

if (!exists("alpha", inherits = TRUE)) {
  stop("Global variable 'alpha' was not found.")
}

alpha_value <- get("alpha", inherits = TRUE)

if (
  length(alpha_value) != 1 ||
  !is.numeric(alpha_value) ||
  !is.finite(alpha_value) ||
  alpha_value <= 0 ||
  alpha_value >= 1
) {
  stop("Global variable 'alpha' must be one number between 0 and 1.")
}

# -----
# Identify task and outcome

```

```

# -----

all_tasks <- unique(c(
  as.character(cld$task_id),
  as.character(posthoc$task_id)
))

all_tasks <- all_tasks[
  !is.na(all_tasks) & nzchar(all_tasks)
]

all_outcomes <- unique(c(
  as.character(cld$outcome),
  as.character(posthoc$outcome)
))

all_outcomes <- all_outcomes[
  !is.na(all_outcomes) & nzchar(all_outcomes)
]

if (length(all_tasks) == 0) {
  stop("No valid task_id found.")
}

if (length(all_outcomes) == 0) {
  stop("No valid outcome found.")
}

# A common unit label requires one outcome per exported table.
if (length(all_outcomes) != 1) {
  stop(
    "The supplied data must contain exactly one outcome because ",
    "the unit is displayed in the Mean and Median column labels."
  )
}

outcome_value <- toupper(all_outcomes[1])

unit_label <- if (outcome_value == "TTU") {
  "[s]"
} else if (outcome_value == "DOU") {
  "$[\\,]$"
} else {
  ""
}

# -----

```

```

# LaTeX helpers
# -----

latex_escape <- function(x) {

  x <- as.character(x)

  vapply(
    x,
    function(value) {

      if (is.na(value)) {
        return("")
      }

      characters <- strsplit(
        value,
        "",
        fixed = TRUE
      )[[1]]

      replacements <- c(
        "&" = "\\&",
        "%" = "\\%",
        "$" = "\\$",
        "#" = "\\#",
        "_" = "\\_",
        "{" = "\\{",
        "}" = "\\}",
        "~" = "\\textasciitilde{}",
        "^" = "\\textasciicircum{}"
      )

      paste0(
        vapply(
          characters,
          function(character) {

            if (character %in% names(replacements)) {
              replacements[[character]]
            } else {
              character
            }
          },
          character(1)
        ),
        collapse = ""
      )
    }
  )
}

```

```

    )
  },
  character(1)
)
}

format_outcome <- function(x) {

  x <- as.character(x)

  vapply(
    x,
    function(value) {

      if (is.na(value)) {
        return("")
      }

      if (toupper(value) == "DOU") {
        return("\\dou\\")
      }

      if (toupper(value) == "TTU") {
        return("\\ttu\\")
      }

      latex_escape(value)
    },
    character(1)
  )
}

format_group <- function(x) {

  x <- as.character(x)

  vapply(
    x,
    function(value) {

      if (is.na(value)) {
        return("")
      }

      paste0(
        "\\enquote{",
        latex_escape(value),

```

```

    "}"
  )
},
character(1)
)
}

# Exactly six decimal places
format_num <- function(x, underline = FALSE) {

  numeric_x <- suppressWarnings(
    as.numeric(as.character(x))
  )

  if (length(underline) == 1L) {
    underline <- rep(underline, length(numeric_x))
  }

  if (length(underline) != length(numeric_x)) {
    stop(
      "'underline' must have length one or the same length as 'x'."
    )
  }

  underline[is.na(underline)] <- FALSE

  vapply(
    seq_along(numeric_x),
    function(i) {

      value <- numeric_x[i]

      if (is.na(value)) {
        return("")
      }

      if (!is.finite(value)) {
        return(latex_escape(as.character(value)))
      }

      # Avoid negative zero after rounding.
      if (abs(value) < 0.5e-6) {
        value <- 0
      }

      result <- paste0(
        "\\num{",

```

```

        sprintf("%.6f", value),
        "}"
    )

    if (isTRUE(underline[i])) {
        result <- paste0(
            "\\underline{",
            result,
            "}"
        )
    }

    result
},
character(1)
)
}

# -----
# First subtable: pairwise comparisons
# -----

p_holm_numeric <- suppressWarnings(
  as.numeric(as.character(posthoc$p_holm))
)

significant <- (
  !is.na(p_holm_numeric) &
  p_holm_numeric < alpha_value
)

comparison <- paste0(
  format_group(posthoc$group1),
  " vs. ",
  format_group(posthoc$group2)
)

posthoc_table <- data.frame(
  comparison = comparison,
  p_value = format_num(
    posthoc$p_value,
    underline = significant
  ),
  p_holm = format_num(
    posthoc$p_holm,
    underline = significant
  ),

```

```

    cliffs_delta = format_num(
      posthoc$cliffs_delta,
      underline = significant
    ),
    stringsAsFactors = FALSE,
    check.names = FALSE
  )

posthoc_rows <- vapply(
  seq_len(nrow(posthoc_table)),
  function(i) {
    paste0(
      paste(
        as.character(posthoc_table[i, ]),
        collapse = " & "
      ),
      "\\\\"
    )
  },
  character(1)
)

# -----
# Second subtable: group summaries
# -----

cld_table <- data.frame(
  group = format_group(cld$group),
  mean = format_num(cld$mean),
  median = format_num(cld$median),
  compact_letter = latex_escape(cld$compact_letter),
  stringsAsFactors = FALSE,
  check.names = FALSE
)

cld_rows <- vapply(
  seq_len(nrow(cld_table)),
  function(i) {
    paste0(
      paste(
        as.character(cld_table[i, ]),
        collapse = " & "
      ),
      "\\\\"
    )
  },
  character(1)
)

```

```

)

# -----
# Comments containing task and outcome information
# -----

task_comment <- paste0(
  "% Task: ",
  paste(
    latex_escape(all_tasks),
    collapse = ", "
  )
)

outcome_comment <- paste0(
  "% Outcome: ",
  format_outcome(all_outcomes)
)

alpha_comment <- paste0(
  "% Significance threshold: p_Holm < ",
  format(alpha_value, scientific = FALSE, trim = TRUE)
)

# -----
# Column labels with outcome-specific units
# -----

mean_header <- if (nzchar(unit_label)) {
  paste("Mean", unit_label)
} else {
  "Mean"
}

median_header <- if (nzchar(unit_label)) {
  paste("Median", unit_label)
} else {
  "Median"
}

# -----
# Construct only the two subtable environments
#
# Order:
#   1. Pairwise comparisons
#   2. Group summaries
# -----

```

```

latex_output <- c(
  task_comment,
  outcome_comment,
  alpha_comment,
  "",
  "\\begin{subtable}[t]{\\textwidth}",
  "\\centering",
  "\\caption{Pairwise group comparisons}",
  "\\begin{tabular}{lrrr}",
  "\\toprule",
  paste0(
    "Comparison & $p$-value & ",
    "$p_{\\mathrm{Holm}}$ & Cliff's $\\delta$ \\\\"
  ),
  "\\midrule",
  posthoc_rows,
  "\\bottomrule",
  "\\end{tabular}",
  "\\end{subtable}",
  "",
  "\\vspace{0.8em}",
  "",
  "\\begin{subtable}[t]{\\textwidth}",
  "\\centering",
  "\\caption{Group summaries}",
  "\\begin{tabular}{lrrc}",
  "\\toprule",
  paste0(
    "Group & ",
    mean_header,
    " & ",
    median_header,
    " & Compact letter \\\\"
  ),
  "\\midrule",
  cld_rows,
  "\\bottomrule",
  "\\end{tabular}",
  "\\end{subtable}"
)

# -----
# Export
# -----

writeLines(

```

```

    latex_output,
    con = tex_file,
    useBytes = TRUE
  )

  message(
    "LaTeX subtables saved to: ",
    normalizePath(tex_file, mustWork = FALSE)
  )

  invisible(latex_output)
}

```

```

[63]: export_posthoc_subtables(
  posthoc = result__DOU$posthoc,
  cld = result__DOU$cld,
  tex_file = "dou_posthoc_subtables.tex"
)

```

LaTeX subtables saved to: /home/judith/Schreibtisch/angew. Informatik - system engineering/Study_DrawingAttention/dou_posthoc_subtables.tex

```
[ ]:
```

7 For a specific property of tasks, is there a difference in TTU/DOU across the groups?

```

[64]: cat ("H: Across tasks with property ..., there is no overall difference in TTU/
  ↪DOU between participant groups.")

```

H: Across tasks with property ..., there is no overall difference in TTU/DOU between participant groups.

```

[65]: filter_by_property <- function(
  data,
  property_col,
  property_value
) {

  if (!property_col %in% names(data)) {
    stop("Column not found: ", property_col)
  }

  data[
    vapply(
      data[[property_col]],

```

```

    function(x) property_value %in% x,
    logical(1)
  ),
]
}

```

```

[66]: interpret_group_and_interaction <- function(
  report,
  task_col = "task_id",
  group_col = "group"
) {

  group_result <- report %>%
    dplyr::filter(effect == group_col)

  interaction_result <- report %>%
    dplyr::filter(
      grepl(task_col, effect, fixed = TRUE) &
      grepl(group_col, effect, fixed = TRUE)
    )

  if (nrow(group_result) == 0) {
    warning("No group effect found in report.")
    return(NULL)
  }

  if (nrow(interaction_result) == 0) {
    warning("No task × group interaction found in report.")
    return(NULL)
  }

  # Wichtig: p-Werte sicher in einzelne numerische Werte umwandeln
  group_p <- as.numeric(unlist(group_result$p_value))[1]
  interaction_p <- as.numeric(unlist(interaction_result$p_value))[1]

  group_significant <- !is.na(group_p) && group_p < alpha
  interaction_significant <- !is.na(interaction_p) &&
    interaction_p < alpha

  cat("\n\n\nInterpretation:\n")

  if (!group_significant && !interaction_significant) {

    interpretation <- "Not significant."

    followup <- ""
  }
}

```

```

} else if (group_significant && !interaction_significant) {

  interpretation <- "Significant effect of participant group."

  followup <- paste0(
    "global pairwise group post-hoc tests with Holm correction"
  )

} else if (!group_significant && interaction_significant) {

  interpretation <- "Task-dependent group differences."

  followup <- paste0(
    "See task-specific group comparisons. ",
    "Do not create one global compact letter display."
  )

} else {

  interpretation <- paste0(
    # "Significant group effects, but group differences are task-dependent."
    "***-> task-abhängig, aber keine signifikanten Gruppenunterschiede**"
  )

  followup <- paste0(
    "See task-specific group comparisons. No global compact letter display_
↳possible"
  )
}

cat(interpretation, "\n")
cat("Recommended follow-up: ", followup, "\n", sep = "")

invisible(
  list(
    group_p = group_p,
    interaction_p = interaction_p,
    group_significant = group_significant,
    interaction_significant = interaction_significant,
    interpretation = interpretation,
    followup = followup# TODO follow-up kursiv
  )
)
}

```

```

analyse_property <- function(
  data,
  property_col = "structural_aspects",
  property_value,
  outcome = "TTU",
  task_col = "task_id",
  group_col = "group",
  participant_col = "participant"
) {

  cat("\n")
  cat(strrep("=", 75), "\n")
  cat("PROPERTY ANALYSIS\tfor ", property_value, " with outcome = ", outcome, "\n")
  cat(strrep("=", 75), "\n")

  # 1. Tasks mit dieser Property auswählen
  property_data <- filter_by_property(
    data = data,
    property_col = property_col,
    property_value = property_value
  )

  # 2. Enthaltene Tasks ermitteln
  included_tasks <- property_data %>%
    dplyr::distinct(.data[[task_col]]) %>%
    dplyr::arrange(.data[[task_col]]) %>%
    dplyr::pull(.data[[task_col]])

  cat(
    "Included tasks (", length(included_tasks), "): ",
    paste(included_tasks, collapse = ", "),
    "\n",
    sep = ""
  )

  if (nrow(property_data) == 0) {
    warning(
      "No data found for property '", property_value,
      "' in column '", property_col, "'. "
    )
    return(NULL)
  }

  # Mindestens zwei Tasks nötig für task_id * group
  if (length(included_tasks) < 2) {
    warning(

```

```

    "Skipping Brunner-Langer analysis for property '", property_value,
    "': only one task is included. "
  )
  return(list(
    property = property_value,
    outcome = outcome,
    included_tasks = included_tasks,
    data = property_data,
    fit = NULL,
    report = NULL
  ))
}

# 3. Faktoren vorbereiten
property_data <- property_data %>%
  dplyr::mutate(
    "{participant_col}" := factor(.data[[participant_col]]),
    "{group_col}" := factor(.data[[group_col]]),
    "{task_col}" := factor(
      .data[[task_col]],
      levels = sort(unique(.data[[task_col]]))
    )
  )

# 4. Dynamische Formel erzeugen, z. B. TTU ~ task_id * group
test_formula <- as.formula(
  paste(outcome, "~", task_col, "*", group_col)
)

# 5. Brunner-Langer-Test
fit <- tryCatch(
  nparLD::nparLD(
    formula = test_formula,
    data = property_data,
    subject = participant_col
  ),
  error = function(e) {
    warning(
      "nparLD failed for property '", property_value,
      "' and outcome '", outcome, "': ", e$message
    )
    NULL
  }
)

if (is.null(fit)) {
  return(list(

```

```

    property = property_value,
    outcome = outcome,
    included_tasks = included_tasks,
    data = property_data,
    fit = NULL,
    report = NULL
  ))
}

# 6. ATS-Ergebnis über deine vorhandene Funktion aufbereiten
report <- report_ats(
  fit = fit,
  outcome = outcome,
  within = task_col,
  between = group_col
)

cat("\nATS results:\n")

print(
  report %>%
    dplyr::filter(
      effect == group_col |
      (
        grepl(task_col, effect, fixed = TRUE) &
        grepl(group_col, effect, fixed = TRUE)
      )
    ) %>%
    dplyr::select(
      effect,
      ANOVA_Type_Statistic,
      degrees_of_freedom,
      p_value,
      significant
    )
)

interpretation <- interpret_group_and_interaction(
  report = report,
  task_col = task_col,
  group_col = group_col
)

# Alles für spätere Verwendung zurückgeben
list(
  property_column = property_col,
  property = property_value,

```

```

    outcome = outcome,
    included_tasks = included_tasks,
    data = property_data,
    fit = fit,
    report = report
  )
}

```

```

[67]: analyse_property_both_outcomes <- function(
  data,
  property_value,
  property_col = "structural_aspects",
  outcomes = c("TTU", "DOU")
) {

  results <- list()

  for (outcome in outcomes) {

    cat("\n", strrep("=", 80), "\n", sep = "")
    cat(
      "Property: ", property_value,
      " | Outcome: ", outcome,
      "\n",
      sep = ""
    )
    cat(strrep("=", 80), "\n", sep = "")

    results[[outcome]] <- analyse_property(
      data = data,
      property_col = property_col,
      property_value = property_value,
      outcome = outcome
    )
  }

  invisible(results)
}
# INFO: results in:
# return_value$TTU
# return_value$DOU

```

```

[68]: pairwise_property_nparld <- function(
  property_result,
  task_col = "task_id",
  group_col = "group",
  participant_col = "participant"

```

```

) {

  property_data <- property_result$data
  outcome <- property_result$outcome

  groups <- levels(
    droplevels(
      factor(property_data[[group_col]])
    )
  )

  if (length(groups) < 2) {
    stop("At least two groups are required.")
  }

  group_pairs <- combn(groups, 2, simplify = FALSE)

  results <- lapply(group_pairs, function(pair) {

    group_1 <- pair[1]
    group_2 <- pair[2]

    pair_data <- property_data %>%
      dplyr::filter(
        .data[[group_col]] %in% pair
      ) %>%
      dplyr::mutate(
        "{participant_col}" := factor(.data[[participant_col]]),
        "{group_col}" := factor(.data[[group_col]]),
        "{task_col}" := factor(.data[[task_col]])
      )

    test_formula <- as.formula(
      paste(outcome, "~", task_col, "*", group_col)
    )

    # Pairwise Brunner-Langer mixed-design analysis
    fit_pair <- nparLD::nparLD(
      formula = test_formula,
      data = pair_data,
      subject = participant_col
    )

    # Pairwise ATS report
    pair_report <- report_ats(
      fit = fit_pair,
      outcome = outcome,

```

```

    within = task_col,
    between = group_col
  )

  # Extract only the between-group effect
  group_result <- pair_report %>%
    dplyr::filter(effect == group_col)

  if (nrow(group_result) != 1) {
    stop(
      "Could not extract exactly one group effect for comparison: ",
      group_1, " vs. ", group_2
    )
  }

  # One result row per group pair.
  # RTE is stored as the original vector from fit_pair$effects$RTE.
  test_row <- data.frame(
    outcome = outcome,
    group1 = group_1,
    group2 = group_2,
    ANOVA_Type_Statistic = as.numeric(
      unlist(group_result$ANOVA_Type_Statistic)
    )[1],
    degrees_of_freedom = as.numeric(
      unlist(group_result$degrees_of_freedom)
    )[1],
    p_value = as.numeric(
      unlist(group_result$p_value)
    )[1],
    row.names = NULL,
    check.names = FALSE
  )

  test_row$RTE <- list(fit_pair$effects$RTE)

  test_row
})

tests <- dplyr::bind_rows(results) %>%
  dplyr::mutate(
    p_holm = p.adjust(p_value, method = "holm"),
    significant = p_holm < alpha,
    conclusion = ifelse(
      significant,
      "Significant after Holm correction",
      "Not significant after Holm correction"
    )
  )

```

```

    )
  )

  list(
    tests = tests
  )
}

```

[69]: *# wenn immer noch significant -> CLD and meidan-trend*

```

cld_from_pairwise_nparld <- function(
  posthoc_results,
  data,
  outcome,
  group_col = "group"
) {

  # CLD aus den Holm-korrigierten paarweisen nparLD-Tests
  pair_significant <- posthoc_results$p_holm < alpha

  names(pair_significant) <- paste(
    posthoc_results$group1,
    posthoc_results$group2,
    sep = "-"
  )

  letters <- multcompView::multcompLetters(
    pair_significant
  )$Letters

  cld <- data.frame(
    group = names(letters),
    compact_letter = unname(letters),
    row.names = NULL
  )

  # Median je Gruppe über alle in `data` enthaltenen Property-Tasks
  medians <- data %>%
    dplyr::filter(
      !is.na(.data[[outcome]]),
      is.finite(.data[[outcome]])
    ) %>%
    dplyr::group_by(group = .data[[group_col]]) %>%
    dplyr::summarise(
      n = dplyr::n(),
      mean = mean(.data[[outcome]]),
      median = median(.data[[outcome]]),

```

```

    q1 = quantile(.data[[outcome]], 0.25),
    q3 = quantile(.data[[outcome]], 0.75),
    .groups = "drop"
  )

  # Median und CLD verbinden; Gruppen nach Median sortieren
  medians %>%
    dplyr::left_join(cld, by = "group") %>%
    dplyr::arrange(median)
}

```

```

[70]: property_results_to_dataframe <- function(
  property_results,
  existing_data = NULL
) {

  new_results <- list()

  for (outcome_name in names(property_results)) {

    current_result <- property_results[[outcome_name]]

    if (
      is.null(current_result) ||
      is.null(current_result$report)
    ) {
      next
    }

    current_report <- current_result$report

    new_results[[outcome_name]] <- data.frame(
      property_value = rep(
        as.character(current_result$property),
        nrow(current_report)
      ),
      outcome = rep(
        as.character(current_result$outcome),
        nrow(current_report)
      ),
      effect = as.character(current_report$effect),
      p_value = as.numeric(
        unlist(current_report$p_value)
      ),
      stringsAsFactors = FALSE,
      row.names = NULL
    )
  }
}

```

```

}

new_results <- dplyr::bind_rows(new_results)

if (nrow(new_results) == 0) {
  warning("No valid results were found.")

  if (is.null(existing_data)) {
    return(
      data.frame(
        property_value = character(),
        outcome = character(),
        effect = character(),
        p_value = numeric()
      )
    )
  }

  return(existing_data)
}

# If no previous data frame exists, return the new results.
if (is.null(existing_data)) {
  return(new_results)
}

required_columns <- c(
  "property_value",
  "outcome",
  "effect",
  "p_value"
)

missing_columns <- setdiff(
  required_columns,
  names(existing_data)
)

if (length(missing_columns) > 0) {
  stop(
    "'existing_data' is missing column(s): ",
    paste(missing_columns, collapse = ", ")
  )
}

# Append rather than replace.
dplyr::bind_rows(

```

```

    existing_data,
    new_results
  )
}

```

```

[71]: # alle vergebenen task properties:
all_structural_aspects <- sort(
  unique(
    unlist(dat$structural_aspects)
  )
)

all_structural_aspects

```

1. 'BACK' 2. 'BATCH' 3. 'CELL' 4. 'COMP' 5. 'COND' 6. 'CROSS' 7. 'FORWARD' 8. 'FUNC'
9. 'LIST' 10. 'LIT' 11. 'LOOK' 12. 'OFF' 13. 'ON' 14. 'RANGE' 15. 'VAL'

7.0.1 COMP

```

[72]: x = analyse_property_both_outcomes(data = dat, property_value="COMP")

property_results_df <- property_results_to_dataframe(x)

```

```

=====
Property: COMP | Outcome: TTU
=====

```

```

=====
PROPERTY ANALYSIS          for COMP with outcome = TTU
=====

```

Included tasks (11): 1, 2, 3, 4, 7, 8, 9, 11, 12, 13, 15

ATS results:

	effect	ANOVA_Type_Statistic	degrees_of_freedom	p_value	significant
1	group	1.0510744	1.824183	0.3445260	FALSE
2	group:task_id	0.9257079	7.907112	0.4928112	FALSE

Interpretation:

Not significant.

Recommended follow-up:

```

=====
Property: COMP | Outcome: DOU
=====

```

```
=====
PROPERTY ANALYSIS          for COMP  with outcome =  DOU
=====
```

Included tasks (11): 1, 2, 3, 4, 7, 8, 9, 11, 12, 13, 15

ATS results:

	effect	ANOVA_Type_Statistic	degrees_of_freedom	p_value	
1	group	2.307771	1.723237	0.1075507375	
2	group:task_id	3.878630	7.179544	0.0002704798	
	significant				
1	FALSE				
2	TRUE				

Interpretation:

Task-dependent group differences.

Recommended follow-up: See task-specific group comparisons. Do not create one global compact letter display.

7.0.2 COND

```
[73]: x = analyse_property_both_outcomes(data = dat, property_value="COND")

property_results_df <- property_results_to_dataframe(
  property_results = x,
  existing_data = property_results_df
)
```

```
=====
Property: COND | Outcome: TTU
=====
```

```
=====
PROPERTY ANALYSIS          for COND  with outcome =  TTU
=====
```

Included tasks (4): 10, 15, 16, 17

ATS results:

	effect	ANOVA_Type_Statistic	degrees_of_freedom	p_value	significant
1	group	0.5152722	1.657489	0.5631618	FALSE
2	group:task_id	1.5086207	3.868450	0.1983693	FALSE

Interpretation:
Not significant.
Recommended follow-up:

```
=====
Property: COND | Outcome: DOU
=====
```

```
=====
PROPERTY ANALYSIS          for COND with outcome = DOU
=====
```

Included tasks (4): 10, 15, 16, 17

ATS results:

	effect	ANOVA_Type_Statistic	degrees_of_freedom	p_value	significant
1	group	3.266873	1.708035	0.04582343	TRUE
2	group:task_id	2.723752	4.536427	0.02213397	TRUE

Interpretation:
-> task-abhängig, aber keine signifikanten Gruppenunterschiede
Recommended follow-up: See task-specific group comparisons. No global compact letter display possible

```
[74]: # posthoc_comp_dou <- pairwise_property_nparld(
#       property_result = x$DOU
# )
# posthoc_comp_dou
```

```
[75]: # cld_comp_dou <- cld_from_pairwise_nparld(
#       posthoc_results = posthoc_comp_dou,
#       data = x$DOU$data,
#       outcome = "DOU"
# )
# cld_comp_dou
```

7.0.3 LOOK

```
[76]: x = analyse_property_both_outcomes(data = dat, property_value="LOOK")

property_results_df <- property_results_to_dataframe(
  property_results = x,
  existing_data = property_results_df
)
```

```
=====
Property: LOOK | Outcome: TTU
=====
```

```
=====
PROPERTY ANALYSIS      for LOOK with outcome = TTU
=====
```

Included tasks (3): 14, 15, 17

ATS results:

	effect	ANOVA_Type_Statistic	degrees_of_freedom	p_value	significant
1	group	0.7309042	1.538883	0.4479721	FALSE
2	group:task_id	2.1118378	2.804757	0.1008229	FALSE

Interpretation:

Not significant.

Recommended follow-up:

```
=====
Property: LOOK | Outcome: DOU
=====
```

```
=====
PROPERTY ANALYSIS      for LOOK with outcome = DOU
=====
```

Included tasks (3): 14, 15, 17

ATS results:

	effect	ANOVA_Type_Statistic	degrees_of_freedom	p_value	significant
1	group	5.186325	1.785170	0.007556946	TRUE
2	group:task_id	3.668919	3.070401	0.011069706	TRUE

Interpretation:

-> task-abhängig, aber keine signifikanten Gruppenunterschiede

Recommended follow-up: See task-specific group comparisons. No global compact letter display possible

7.1 Operand Types

7.1.1 CELL

```
[77]: x = analyse_property_both_outcomes(data = dat, property_value="CELL")
```

```
property_results_df <- property_results_to_dataframe(  
  property_results = x,  
  existing_data = property_results_df  
)
```

```
=====  
Property: CELL | Outcome: TTU  
=====
```

```
=====  
PROPERTY ANALYSIS      for CELL with outcome = TTU  
=====
```

```
Included tasks (11): 1, 3, 4, 8, 9, 10, 11, 12, 13, 14, 15
```

ATS results:

	effect	ANOVA_Type_Statistic	degrees_of_freedom	p_value	significant
1	group	0.9916576	1.930962	0.3686399	FALSE
2	group:task_id	0.8669931	8.586697	0.5498900	FALSE

Interpretation:

Not significant.

Recommended follow-up:

```
=====  
Property: CELL | Outcome: DOU  
=====
```

```
=====  
PROPERTY ANALYSIS      for CELL with outcome = DOU  
=====
```

```
Included tasks (11): 1, 3, 4, 8, 9, 10, 11, 12, 13, 14, 15
```

ATS results:

	effect	ANOVA_Type_Statistic	degrees_of_freedom	p_value	significant
1	group	5.824479	1.741050	0.004554492	TRUE
2	group:task_id	2.882925	7.054085	0.005065089	TRUE

Interpretation:

****-> task-abhängig, aber keine signifikanten Gruppenunterschiede****

Recommended follow-up: See task-specific group comparisons. No global compact letter display possible

7.1.2 RANGE

```
[78]: x = analyse_property_both_outcomes(data = dat, property_value="CELL")
```

```
property_results_df <- property_results_to_dataframe(  
  property_results = x,  
  existing_data = property_results_df  
)
```

```
=====
```

```
Property: CELL | Outcome: TTU
```

```
=====
```

```
=====
```

```
PROPERTY ANALYSIS          for CELL with outcome = TTU
```

```
=====
```

```
Included tasks (11): 1, 3, 4, 8, 9, 10, 11, 12, 13, 14, 15
```

ATS results:

	effect	ANOVA_Type_Statistic	degrees_of_freedom	p_value	significant
1	group	0.9916576	1.930962	0.3686399	FALSE
2	group:task_id	0.8669931	8.586697	0.5498900	FALSE

Interpretation:

Not significant.

Recommended follow-up:

```
=====
```

```
Property: CELL | Outcome: DOU
```

```
=====
```

```
=====
```

```
PROPERTY ANALYSIS          for CELL with outcome = DOU
```

```
=====
```

```
Included tasks (11): 1, 3, 4, 8, 9, 10, 11, 12, 13, 14, 15
```

ATS results:

	effect	ANOVA_Type_Statistic	degrees_of_freedom	p_value	significant
--	--------	----------------------	--------------------	---------	-------------

1	group	5.824479	1.741050	0.004554492	TRUE
2	group:task_id	2.882925	7.054085	0.005065089	TRUE

Interpretation:

****-> task-abhängig, aber keine signifikanten Gruppenunterschiede****

Recommended follow-up: See task-specific group comparisons. No global compact letter display possible

7.1.3 LIT

```
[79]: x = analyse_property_both_outcomes(data = dat, property_value="LIT")
```

```
property_results_df <- property_results_to_dataframe(
  property_results = x,
  existing_data = property_results_df
)
```

```
=====
Property: LIT | Outcome: TTU
=====
```

```
=====
PROPERTY ANALYSIS      for LIT with outcome = TTU
=====
```

Included tasks (5): 3, 8, 10, 15, 16

ATS results:

	effect	ANOVA_Type_Statistic	degrees_of_freedom	p_value	significant
1	group	0.9631453	1.835717	0.3754502	FALSE
2	group:task_id	1.3376085	4.945307	0.2453627	FALSE

Interpretation:

Not significant.

Recommended follow-up:

```
=====
Property: LIT | Outcome: DOU
=====
```

```
=====
PROPERTY ANALYSIS      for LIT with outcome = DOU
=====
```

```
=====
Included tasks (5): 3, 8, 10, 15, 16
```

ATS results:

	effect	ANOVA_Type_Statistic	degrees_of_freedom	p_value	significant
1	group	6.827789	1.853183	0.001475000	TRUE
2	group:task_id	4.376270	4.545313	0.000878805	TRUE

Interpretation:

****-> task-abhängig, aber keine signifikanten Gruppenunterschiede****

Recommended follow-up: See task-specific group comparisons. No global compact letter display possible

7.1.4 FUNC

```
[80]: x = analyse_property_both_outcomes(data = dat, property_value="FUNC")

property_results_df <- property_results_to_dataframe(
  property_results = x,
  existing_data = property_results_df
)
```

```
=====
Property: FUNC | Outcome: TTU
=====
```

```
=====
PROPERTY ANALYSIS      for  FUNC  with outcome =  TTU
=====
```

Included tasks (4): 5, 6, 7, 15

ATS results:

	effect	ANOVA_Type_Statistic	degrees_of_freedom	p_value	significant
1	group	0.5642298	1.577210	0.5285035	FALSE
2	group:task_id	1.4393225	4.288117	0.2146810	FALSE

Interpretation:

Not significant.

Recommended follow-up:

Property: FUNC | Outcome: DOU

PROPERTY ANALYSIS for FUNC with outcome = DOU

Included tasks (4): 5, 6, 7, 15

ATS results:

	effect	ANOVA_Type_Statistic	degrees_of_freedom	p_value	significant
1	group	0.2902663	1.837120	0.7292653812	
2	group:task_id	7.0620262	2.794395	0.0001505919	
1					FALSE
2					TRUE

Interpretation:

Task-dependent group differences.

Recommended follow-up: See task-specific group comparisons. Do not create one global compact letter display.

7.2 RESULT TYPE

7.2.1 VAL

```
[81]: x = analyse_property_both_outcomes(data = dat, property_value="VAL")
```

```
property_results_df <- property_results_to_dataframe(  
  property_results = x,  
  existing_data = property_results_df  
)
```

Property: VAL | Outcome: TTU

PROPERTY ANALYSIS for VAL with outcome = TTU

Included tasks (14): 1, 2, 3, 4, 5, 6, 7, 8, 10, 11, 12, 13, 14, 15

ATS results:

	effect	ANOVA_Type_Statistic	degrees_of_freedom	p_value	significant
1	group	1.045736	1.766365	0.3444414	FALSE
2	group:task_id	1.013764	9.112606	0.4262340	FALSE

Interpretation:
 Not significant.
 Recommended follow-up:

```
=====
Property: VAL | Outcome: DOU
=====
```

```
=====
PROPERTY ANALYSIS          for VAL with outcome = DOU
=====
```

Included tasks (14): 1, 2, 3, 4, 5, 6, 7, 8, 10, 11, 12, 13, 14, 15

ATS results:

	effect	ANOVA_Type_Statistic	degrees_of_freedom	p_value
1	group	1.456973	1.677938	0.2339554432
2	group:task_id	3.445509	7.823263	0.0006336115
	significant			
1	FALSE			
2	TRUE			

Interpretation:
 Task-dependent group differences.
 Recommended follow-up: See task-specific group comparisons. Do not create one global compact letter display.

7.2.2 BATCH

```
[82]: x = analyse_property_both_outcomes(data = dat, property_value="BATCH")

property_results_df <- property_results_to_dataframe(
  property_results = x,
  existing_data = property_results_df
)
```

```
=====
Property: BATCH | Outcome: TTU
=====
=====
```

```

PROPERTY ANALYSIS          for BATCH with outcome = TTU
=====
Included tasks (1): 9

Warning message in analyse_property(data = data, property_col = property_col,
property_value = property_value, :
"Skipping Brunner-Langer analysis for property 'BATCH': only one task is
included. "

=====
Property: BATCH | Outcome: DOU
=====

=====
PROPERTY ANALYSIS          for BATCH with outcome = DOU
=====
Included tasks (1): 9

Warning message in analyse_property(data = data, property_col = property_col,
property_value = property_value, :
"Skipping Brunner-Langer analysis for property 'BATCH': only one task is
included. "
Warning message in property_results_to_dataframe(property_results = x,
existing_data = property_results_df):
"No valid results were found."

```

7.2.3 LIST

```

[83]: x = analyse_property_both_outcomes(data = dat, property_value="LIST")

property_results_df <- property_results_to_dataframe(
  property_results = x,
  existing_data = property_results_df
)

```

```

=====
Property: LIST | Outcome: TTU
=====

=====
PROPERTY ANALYSIS          for LIST with outcome = TTU
=====
Included tasks (2): 16, 17

ATS results:
      effect ANOVA_Type_Statistic degrees_of_freedom  p_value significant
1      group           1.7622234             1.758465 0.1760768      FALSE
2 group:task_id         0.9211423             1.949084 0.3959629      FALSE

```

Interpretation:
Not significant.
Recommended follow-up:

```
=====
Property: LIST | Outcome: DOU
=====
```

```
=====
PROPERTY ANALYSIS      for LIST with outcome = DOU
=====
```

Included tasks (2): 16, 17

ATS results:

	effect	ANOVA_Type_Statistic	degrees_of_freedom	p_value	significant
1	group	0.8410042	1.910954	0.4267054	FALSE
2	group:task_id	0.2270273	1.958696	0.7923385	FALSE

Interpretation:
Not significant.
Recommended follow-up:

7.3 Ref. direction

7.3.1 BACK

```
[84]: x = analyse_property_both_outcomes(data = dat, property_value="BACK")

property_results_df <- property_results_to_dataframe(
  property_results = x,
  existing_data = property_results_df
)
```

```
=====
Property: BACK | Outcome: TTU
=====
```

```
=====
PROPERTY ANALYSIS      for BACK with outcome = TTU
=====
```

Included tasks (13): 1, 2, 3, 5, 6, 7, 8, 9, 10, 11, 12, 13, 16

ATS results:

	effect	ANOVA_Type_Statistic	degrees_of_freedom	p_value	significant
1	group	1.2609504	1.716372	0.2804070	FALSE
2	group:task_id	0.9395204	9.369622	0.4912869	FALSE

Interpretation:

Not significant.

Recommended follow-up:

=====
Property: BACK | Outcome: DOU
=====

=====
PROPERTY ANALYSIS for BACK with outcome = DOU
=====

Included tasks (13): 1, 2, 3, 5, 6, 7, 8, 9, 10, 11, 12, 13, 16

ATS results:

	effect	ANOVA_Type_Statistic	degrees_of_freedom	p_value	significant
1	group	1.586046	1.792191	0.2070266	FALSE
2	group:task_id	1.588499	8.294430	0.1192102	FALSE

Interpretation:

Not significant.

Recommended follow-up:

7.3.2 FORW

```
[85]: x = analyse_property_both_outcomes(data = dat, property_value="FORWARD")

property_results_df <- property_results_to_dataframe(
  property_results = x,
  existing_data = property_results_df
)
```

=====
Property: FORWARD | Outcome: TTU
=====

```
=====
PROPERTY ANALYSIS          for FORWARD with outcome = TTU
=====
```

Included tasks (6): 4, 12, 13, 14, 15, 17

ATS results:

	effect	ANOVA_Type_Statistic	degrees_of_freedom	p_value	significant
1	group	1.269133	1.828967	0.2795788	FALSE
2	group:task_id	1.598630	5.263016	0.1528881	FALSE

Interpretation:

Not significant.

Recommended follow-up:

```
=====
Property: FORWARD | Outcome: DOU
=====
```

```
=====
PROPERTY ANALYSIS          for FORWARD with outcome = DOU
=====
```

Included tasks (6): 4, 12, 13, 14, 15, 17

ATS results:

	effect	ANOVA_Type_Statistic	degrees_of_freedom	p_value	significant
1	group	6.767758	1.763929	0.001878619	TRUE
2	group:task_id	3.254789	4.208226	0.009850964	TRUE

Interpretation:

****-> task-abhängig, aber keine signifikanten Gruppenunterschiede****

Recommended follow-up: See task-specific group comparisons. No global compact letter display possible

7.4 Ref. dispersion

7.4.1 ON

```
[86]: x = analyse_property_both_outcomes(data = dat, property_value="ON")

property_results_df <- property_results_to_dataframe(
  property_results = x,
  existing_data = property_results_df
```

)

```
=====
Property: ON | Outcome: TTU
=====
```

```
=====
PROPERTY ANALYSIS      for ON with outcome = TTU
=====
```

```
Included tasks (12): 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 15, 16
```

ATS results:

	effect	ANOVA_Type_Statistic	degrees_of_freedom	p_value	significant
1	group	2.1322701	1.794535	0.1241491	FALSE
2	group:task_id	0.8296337	8.634744	0.5842637	FALSE

Interpretation:

Not significant.

Recommended follow-up:

```
=====
Property: ON | Outcome: DOU
=====
```

```
=====
PROPERTY ANALYSIS      for ON with outcome = DOU
=====
```

```
Included tasks (12): 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 15, 16
```

ATS results:

	effect	ANOVA_Type_Statistic	degrees_of_freedom	p_value	significant
1	group	1.279206	1.764763	0.276245480	FALSE
2	group:task_id	2.947423	8.183968	0.002468212	TRUE

Interpretation:

Task-dependent group differences.

Recommended follow-up: See task-specific group comparisons. Do not create one global compact letter display.

7.4.2 OFF

```
[87]: x = analyse_property_both_outcomes(data = dat, property_value="OFF")

property_results_df <- property_results_to_dataframe(
  property_results = x,
  existing_data = property_results_df
)
```

```
=====
Property: OFF | Outcome: TTU
=====
```

```
=====
PROPERTY ANALYSIS          for OFF with outcome = TTU
=====
Included tasks (2): 11, 13
```

ATS results:

	effect	ANOVA_Type_Statistic	degrees_of_freedom	p_value	significant
1	group	0.9162489	1.736500	0.3881978	FALSE
2	group:task_id	0.3050469	1.826349	0.7170709	FALSE

Interpretation:
Not significant.
Recommended follow-up:

```
=====
Property: OFF | Outcome: DOU
=====
```

```
=====
PROPERTY ANALYSIS          for OFF with outcome = DOU
=====
Included tasks (2): 11, 13
```

ATS results:

	effect	ANOVA_Type_Statistic	degrees_of_freedom	p_value	significant
1	group	0.5	1.6	0.5651424	FALSE
2	group:task_id	0.5	1.6	0.5651424	FALSE

Interpretation:
 Not significant.
 Recommended follow-up:

7.4.3 CROSS

```
[88]: x = analyse_property_both_outcomes(data = dat, property_value="CROSS")

property_results_df <- property_results_to_dataframe(
  property_results = x,
  existing_data = property_results_df
)
```

```
=====
Property: CROSS | Outcome: TTU
=====
```

```
=====
PROPERTY ANALYSIS      for CROSS with outcome = TTU
=====
Included tasks (5): 12, 13, 14, 15, 17
```

ATS results:

	effect	ANOVA_Type_Statistic	degrees_of_freedom	p_value	significant
1	group	0.8341749	1.769039	0.4216645	FALSE
2	group:task_id	1.8401934	4.969732	0.1017788	FALSE

Interpretation:
 Not significant.
 Recommended follow-up:

```
=====
Property: CROSS | Outcome: DOU
=====
```

```
=====
PROPERTY ANALYSIS      for CROSS with outcome = DOU
=====
Included tasks (5): 12, 13, 14, 15, 17
```

ATS results:

	effect	ANOVA_Type_Statistic	degrees_of_freedom	p_value	significant
1	group	6.695223	1.774662	0.001961318	TRUE
2	group:task_id	3.069244	4.133623	0.014327610	TRUE

Interpretation:

****-> task-abhängig, aber keine signifikanten Gruppenunterschiede****

Recommended follow-up: See task-specific group comparisons. No global compact letter display possible

```
[89]: export_property_results_table <- function(
  data,
  tex_file = "property_results.tex",
  task_col = "task_id",
  group_col = "group"
) {

  # -----
  # Checks
  # -----

  if (!is.data.frame(data)) {
    stop("'data' must be a data frame.")
  }

  required_columns <- c(
    "property_value",
    "outcome",
    "effect",
    "p_value"
  )

  missing_columns <- setdiff(
    required_columns,
    names(data)
  )

  if (length(missing_columns) > 0) {
    stop(
      "'data' is missing column(s): ",
      paste(missing_columns, collapse = ", ")
    )
  }

  # Use global alpha
  if (!exists("alpha", inherits = TRUE)) {
    stop("Global variable 'alpha' was not found.")
  }
}
```

```

alpha_value <- get("alpha", inherits = TRUE)

if (
  length(alpha_value) != 1 ||
  !is.numeric(alpha_value) ||
  !is.finite(alpha_value) ||
  alpha_value <= 0 ||
  alpha_value >= 1
) {
  stop("Global variable 'alpha' must be one number between 0 and 1.")
}

# -----
# Prepare data
# -----

table_data <- data[
  !is.na(data$property_value) &
  !is.na(data$outcome) &
  !is.na(data$effect),
  ,
  drop = FALSE
]

if (nrow(table_data) == 0) {
  stop("No valid results are available.")
}

table_data$property_value <- as.character(
  table_data$property_value
)

table_data$outcome <- toupper(
  trimws(as.character(table_data$outcome))
)

table_data$effect <- trimws(
  as.character(table_data$effect)
)

table_data$p_value <- suppressWarnings(
  as.numeric(as.character(table_data$p_value))
)

# Keep only DOU and TTU
table_data <- table_data[

```

```

    table_data$outcome %in% c("DOU", "TTU"),
    ,
    drop = FALSE
]

if (nrow(table_data) == 0) {
  stop("No DOU or TTU results were found.")
}

# -----
# Classify effects
# -----

classify_effect <- function(effect) {

  has_task <- grepl(
    task_col,
    effect,
    fixed = TRUE
  )

  has_group <- grepl(
    group_col,
    effect,
    fixed = TRUE
  )

  has_interaction_separator <- grepl(
    ":",
    effect,
    fixed = TRUE
  )

  if (
    has_task &&
    has_group &&
    has_interaction_separator
  ) {
    return("interaction")
  }

  if (identical(effect, group_col)) {
    return("group")
  }

  if (identical(effect, task_col)) {
    return("task")
  }

```

```

}

NA_character_
}

table_data$effect_type <- vapply(
  table_data$effect,
  classify_effect,
  character(1)
)

# Remove effects other than group, task, and interaction
table_data <- table_data[
  !is.na(table_data$effect_type),
  ,
  drop = FALSE
]

if (nrow(table_data) == 0) {
  stop(
    "No group, task, or interaction effects were found."
  )
}

# -----
# Check for duplicated results
# -----

result_keys <- paste(
  table_data$property_value,
  table_data$outcome,
  table_data$effect_type,
  sep = "\r"
)

duplicated_keys <- unique(
  result_keys[
    duplicated(result_keys) |
    duplicated(result_keys, fromLast = TRUE)
  ]
)

if (length(duplicated_keys) > 0) {

  duplicate_rows <- table_data[
    result_keys %in% duplicated_keys,
    c(

```

```

      "property_value",
      "outcome",
      "effect",
      "p_value"
    ),
    drop = FALSE
  ]

  print(duplicate_rows)

  stop(
    "Duplicate results were found for at least one ",
    "property × outcome × effect combination. ",
    "Remove duplicated rows before exporting."
  )
}

# Preserve the order in which properties first occur
property_values <- unique(
  table_data$property_value
)

# -----
# LaTeX helpers
# -----

latex_escape <- function(x) {

  x <- as.character(x)

  vapply(
    x,
    function(value) {

      if (is.na(value)) {
        return("")
      }

      characters <- strsplit(
        value,
        "",
        fixed = TRUE
      )[[1]]

      replacements <- c(
        "&" = "\\&",
        "%" = "\\%",

```

```

    "$" = "\\$",
    "#" = "\\#",
    "_" = "\\_",
    "{" = "\\{",
    "}" = "\\}",
    "~" = "\\textasciitilde{}",
    "^" = "\\textasciicircum{}"
  )

  paste0(
    vapply(
      characters,
      function(character) {

        if (character %in% names(replacements)) {
          replacements[[character]]
        } else {
          character
        }
      },
      character(1)
    ),
    collapse = ""
  )
},
character(1)
)
}

# Format p-values with exactly six decimal places.
# Significant values are underlined.
# Values <= 0 are reported as < 1e-6.
format_p_value <- function(value) {

  value <- suppressWarnings(
    as.numeric(as.character(value))
  )

  if (
    length(value) == 0 ||
    is.na(value[1])
  ) {
    return("")
  }

  value <- value[1]

```

```

if (!is.finite(value)) {
  return(latex_escape(as.character(value)))
}

# nparLD may store extremely small p-values as zero.
if (value <= 0) {
  return(
    "\\underline{<$ \\num{1e-6}}}"
  )
}

formatted_value <- paste0(
  "\\num{" ,
  sprintf("%.6f", value),
  "}"
)

if (value < alpha_value) {
  formatted_value <- paste0(
    "\\underline{" ,
    formatted_value,
    "}"
  )
}

formatted_value
}

# -----
# Extract one p-value for a given property, outcome, and effect
# -----

get_p_value <- function(
  property,
  outcome,
  effect_type
) {

  selected_value <- table_data$p_value[
    table_data$property_value == property &
    table_data$outcome == outcome &
    table_data$effect_type == effect_type
  ]

  if (length(selected_value) == 0) {
    return("")
  }
}

```

```

    format_p_value(selected_value[1])
  }

# -----
# Build wide table
# -----

wide_table <- data.frame(
  property = latex_escape(property_values),

  dou_group = vapply(
    property_values,
    get_p_value,
    character(1),
    outcome = "DOU",
    effect_type = "group"
  ),

  dou_task = vapply(
    property_values,
    get_p_value,
    character(1),
    outcome = "DOU",
    effect_type = "task"
  ),

  dou_interaction = vapply(
    property_values,
    get_p_value,
    character(1),
    outcome = "DOU",
    effect_type = "interaction"
  ),

  ttu_group = vapply(
    property_values,
    get_p_value,
    character(1),
    outcome = "TTU",
    effect_type = "group"
  ),

  ttu_task = vapply(
    property_values,
    get_p_value,
    character(1),

```

```

    outcome = "TTU",
    effect_type = "task"
  ),

  ttu_interaction = vapply(
    property_values,
    get_p_value,
    character(1),
    outcome = "TTU",
    effect_type = "interaction"
  ),

  stringsAsFactors = FALSE,
  check.names = FALSE
)

# -----
# Construct table rows
# -----

table_rows <- vapply(
  seq_len(nrow(wide_table)),
  function(i) {
    paste0(
      paste(
        as.character(wide_table[i, ]),
        collapse = " & "
      ),
      " \\\\"
    )
  },
  character(1)
)

# -----
# Construct tabular environment
# -----

latex_output <- c(
  paste0(
    "% Significance threshold: p < ",
    format(
      alpha_value,
      scientific = FALSE,
      trim = TRUE
    )
  )
)

```

```

),
"% Significant p-values are underlined.",
"% Stored p-values <= 0 are displayed as < 1e-6.",
"",
"\\begin{tabular}{lrrrrrr}",
"\\toprule",
paste0(
  "Structural Aspect & ",
  "\\multicolumn{3}{c}{\\dou } & ",
  "\\multicolumn{3}{c}{\\ttu } \\\\"
),
"\\cmidrule(lr){2-4} \\cmidrule(lr){5-7}",
paste0(
  " & Group & Task & Group $\\times$ Task",
  " & Group & Task & Group $\\times$ Task \\\\"
),
"\\midrule",
table_rows,
"\\bottomrule",
"\\end{tabular}"
)

# -----
# Export
# -----

writeLines(
  latex_output,
  con = tex_file,
  useBytes = TRUE
)

message(
  "LaTeX tabular saved to: ",
  normalizePath(tex_file, mustWork = FALSE)
)

invisible(latex_output)
}

```

```

[90]: property_results_df <- property_results_df %>%
  dplyr::distinct(
    property_value,
    outcome,
    effect,
    p_value,
    .keep_all = TRUE
  )

```

```
)  
  
property_results_df  
  
export_property_results_table(  
    data = property_results_df,  
    tex_file = "structural_aspects_total.tex"  
)
```

property_value <chr>	outcome <chr>	effect <chr>	p_value <dbl>
COMP	TTU	group	3.445260e-01
COMP	TTU	task_id	0.000000e+00
COMP	TTU	group:task_id	4.928112e-01
COMP	DOU	group	1.075507e-01
COMP	DOU	task_id	3.330669e-16
COMP	DOU	group:task_id	2.704798e-04
COND	TTU	group	5.631618e-01
COND	TTU	task_id	1.634090e-06
COND	TTU	group:task_id	1.983693e-01
COND	DOU	group	4.582343e-02
COND	DOU	task_id	2.726359e-02
COND	DOU	group:task_id	2.213397e-02
LOOK	TTU	group	4.479721e-01
LOOK	TTU	task_id	6.440078e-04
LOOK	TTU	group:task_id	1.008229e-01
LOOK	DOU	group	7.556946e-03
LOOK	DOU	task_id	1.006895e-01
LOOK	DOU	group:task_id	1.106971e-02
CELL	TTU	group	3.686399e-01
CELL	TTU	task_id	0.000000e+00
CELL	TTU	group:task_id	5.498900e-01
CELL	DOU	group	4.554492e-03
CELL	DOU	task_id	2.665383e-07
CELL	DOU	group:task_id	5.065089e-03
LIT	TTU	group	3.754502e-01
LIT	TTU	task_id	0.000000e+00
LIT	TTU	group:task_id	2.453627e-01
LIT	DOU	group	1.475000e-03
LIT	DOU	task_id	1.444480e-06
LIT	DOU	group:task_id	8.788050e-04
BACK	TTU	group	2.804070e-01
BACK	TTU	task_id	0.000000e+00
BACK	TTU	group:task_id	4.912869e-01
BACK	DOU	group	2.070266e-01
BACK	DOU	task_id	2.220446e-15
BACK	DOU	group:task_id	1.192102e-01
FORWARD	TTU	group	2.795788e-01
FORWARD	TTU	task_id	1.036948e-13
FORWARD	TTU	group:task_id	1.528881e-01
FORWARD	DOU	group	1.878619e-03
FORWARD	DOU	task_id	7.001198e-05
FORWARD	DOU	group:task_id	9.850964e-03
ON	TTU	group	1.241491e-01
ON	TTU	task_id	0.000000e+00
ON	TTU	group:task_id	5.842637e-01
ON	DOU	group	2.762455e-01
ON	DOU	task_id	1.488698e-12
ON	DOU	group:task_id	2.468212e-03
OFF	TTU	group	3.881978e-01
OFF	TTU	task_id	4.127881e-04

A data.frame: 78 × 4

LaTeX tabular saved to: /home/judith/Schreibtisch/angew. Informatik - system engineering/Study_DrawingAttention/structural_aspects_total.tex

==> Es gibt keine signifikanten Einflüsse der Teilnehmergruppen auf die Task-Aspekte.

Aber: Bauchgefühl, es könnte durch den andersartigen Task 15 bedingt sein -> nehmen wir den doch einmal heraus

```
[91]: dat_without_15 <- dat %>%
      dplyr::filter(task_id != 15)

[92]: x = analyse_property_both_outcomes(data = dat_without_15, property_value="COMP")

      property_results_df_without_15 <-
      ↪property_results_to_dataframe(property_results = x)
```

```
=====
Property: COMP | Outcome: TTU
=====
```

```
=====
PROPERTY ANALYSIS          for COMP with outcome = TTU
=====
```

Included tasks (10): 1, 2, 3, 4, 7, 8, 9, 11, 12, 13

ATS results:

	effect	ANOVA_Type_Statistic	degrees_of_freedom	p_value	significant
1	group	1.041110	1.781883	0.3464732	FALSE
2	group:task_id	0.967605	7.766135	0.4577987	FALSE

Interpretation:

Not significant.

Recommended follow-up:

```
=====
Property: COMP | Outcome: DOU
=====
```

```
=====
PROPERTY ANALYSIS          for COMP with outcome = DOU
=====
```

Included tasks (10): 1, 2, 3, 4, 7, 8, 9, 11, 12, 13

ATS results:

	effect	ANOVA_Type_Statistic	degrees_of_freedom	p_value	significant
1	group	0.5252903	1.663062	0.55826501	FALSE
2	group:task_id	1.9725014	6.518629	0.05975499	FALSE

Interpretation:

Not significant.

Recommended follow-up:

```
[93]: x = analyse_property_both_outcomes(data = dat_without_15, property_value="COND")

property_results_df_without_15 <- property_results_to_dataframe(
  property_results = x,
  existing_data = property_results_df_without_15
)
```

```
=====
Property: COND | Outcome: TTU
=====
```

```
=====
PROPERTY ANALYSIS      for COND with outcome = TTU
=====
```

```
Included tasks (3): 10, 16, 17
```

ATS results:

	effect	ANOVA_Type_Statistic	degrees_of_freedom	p_value	significant
1	group	0.5936131	1.711856	0.52703460	FALSE
2	group:task_id	2.1639669	2.899079	0.09225467	FALSE

Interpretation:

Not significant.

Recommended follow-up:

```
=====
Property: COND | Outcome: DOU
=====
```

```
=====
PROPERTY ANALYSIS      for COND with outcome = DOU
=====
```

Included tasks (3): 10, 16, 17

ATS results:

	effect	ANOVA_Type_Statistic	degrees_of_freedom	p_value	significant
1	group	1.3980730	1.741629	0.2470413	FALSE
2	group:task_id	0.1652619	3.405087	0.9373745	FALSE

Interpretation:

Not significant.

Recommended follow-up:

```
[94]: x = analyse_property_both_outcomes(data = dat_without_15, property_value="LOOK")

property_results_df_without_15 <- property_results_to_dataframe(
  property_results = x,
  existing_data = property_results_df_without_15
)
```

=====
Property: LOOK | Outcome: TTU
=====

=====
PROPERTY ANALYSIS for LOOK with outcome = TTU
=====

Included tasks (2): 14, 17

ATS results:

	effect	ANOVA_Type_Statistic	degrees_of_freedom	p_value	significant
1	group	0.7939903	1.679022	0.43239654	FALSE
2	group:task_id	2.6327791	1.761423	0.07900059	FALSE

Interpretation:

Not significant.

Recommended follow-up:

=====
Property: LOOK | Outcome: DOU
=====

PROPERTY ANALYSIS for LOOK with outcome = DOU

=====

Included tasks (2): 14, 17

ATS results:

	effect	ANOVA_Type_Statistic	degrees_of_freedom	p_value	significant
1	group	1.108812	1.812274	0.3256316	FALSE
2	group:task_id	1.134296	1.969982	0.3210802	FALSE

Interpretation:

Not significant.

Recommended follow-up:

```
[95]: x = analyse_property_both_outcomes(data = dat_without_15, property_value="CELL")

property_results_df_without_15 <- property_results_to_dataframe(
  property_results = x,
  existing_data = property_results_df_without_15
)
```

=====

Property: CELL | Outcome: TTU

=====

=====

PROPERTY ANALYSIS for CELL with outcome = TTU

=====

Included tasks (10): 1, 3, 4, 8, 9, 10, 11, 12, 13, 14

ATS results:

	effect	ANOVA_Type_Statistic	degrees_of_freedom	p_value	significant
1	group	0.9819804	1.941140	0.3725348	FALSE
2	group:task_id	0.8408402	8.492839	0.5723805	FALSE

Interpretation:

Not significant.

Recommended follow-up:

=====

Property: CELL | Outcome: DOU

=====

```
=====
PROPERTY ANALYSIS          for CELL with outcome = DOU
=====
Included tasks (10): 1, 3, 4, 8, 9, 10, 11, 12, 13, 14
```

```
ATS results:
      effect ANOVA_Type_Statistic degrees_of_freedom    p_value significant
1      group                2.823285                1.599038 0.07153166      FALSE
2 group:task_id                1.600057                6.574672 0.13523876      FALSE
```

```
Interpretation:
Not significant.
Recommended follow-up:
```

```
[96]: # property_results_df_without_15
```

```
[97]: posthoc_comp_dou <- pairwise_property_nparld(
      property_result = x$DOU
    )
posthoc_comp_dou
```

	outcome <chr>	group1 <chr>	group2 <chr>	ANOVA_7 <dbl>
\$tests = A data.frame: 3 × 10	DOU	Dynamic sketch construction	Formula construction	3.4402470
	DOU	Dynamic sketch construction	Static sketch construction	7.1465513
	DOU	Formula construction	Static sketch construction	0.1301751

```
[98]: cld_comp_dou <- cld_from_pairwise_nparld(
      posthoc_results = posthoc_comp_dou,
      data = x$DOU$data,
      outcome = "DOU"
    )
cld_comp_dou
```

	group <chr>	n <int>	mean <dbl>	median <dbl>	q1 <dbl>	q3 <dbl>	compact_letter <chr>
A tibble: 3 × 7	Dynamic sketch construction	70	0.9823980	1	1	1	NA
	Formula construction	70	0.8999150	1	1	1	NA
	Static sketch construction	70	0.9483333	1	1	1	NA

```
[ ]:
```

```
[99]: x = analyse_property_both_outcomes(data = dat_without_15,
    ↪property_value="RANGE")
```

```
property_results_df_without_15 <- property_results_to_dataframe(
  property_results = x,
  existing_data = property_results_df_without_15
)
```

```
=====
Property: RANGE | Outcome: TTU
=====
```

```
=====
PROPERTY ANALYSIS      for RANGE with outcome = TTU
=====
```

```
Included tasks (6): 2, 5, 6, 7, 16, 17
```

ATS results:

	effect	ANOVA_Type_Statistic	degrees_of_freedom	p_value	significant
1	group	1.938893	1.544791	0.1543753	FALSE
2	group:task_id	1.185531	5.607475	0.3117210	FALSE

Interpretation:

Not significant.

Recommended follow-up:

```
=====
Property: RANGE | Outcome: DOU
=====
```

```
=====
PROPERTY ANALYSIS      for RANGE with outcome = DOU
=====
```

```
Included tasks (6): 2, 5, 6, 7, 16, 17
```

ATS results:

	effect	ANOVA_Type_Statistic	degrees_of_freedom	p_value	significant
1	group	1.5097144	1.933615	0.2214963	FALSE
2	group:task_id	0.9875856	5.829743	0.4303479	FALSE

Interpretation:

Not significant.

Recommended follow-up:

```
[100]: x = analyse_property_both_outcomes(data = dat_without_15, property_value="LIT")

property_results_df_without_15 <- property_results_to_dataframe(
  property_results = x,
  existing_data = property_results_df_without_15
)
```

```
=====
Property: LIT | Outcome: TTU
=====
```

```
=====
PROPERTY ANALYSIS      for LIT with outcome = TTU
=====
```

```
Included tasks (4): 3, 8, 10, 16
```

ATS results:

	effect	ANOVA_Type_Statistic	degrees_of_freedom	p_value	significant
1	group	1.066103	1.765129	0.3378107	FALSE
2	group:task_id	1.301062	4.068344	0.2665418	FALSE

Interpretation:

Not significant.

Recommended follow-up:

```
=====
Property: LIT | Outcome: DOU
=====
```

```
=====
PROPERTY ANALYSIS      for LIT with outcome = DOU
=====
```

```
Included tasks (4): 3, 8, 10, 16
```

ATS results:

	effect	ANOVA_Type_Statistic	degrees_of_freedom	p_value	significant
1	group	7.162848	1.989338	0.000793627	TRUE
2	group:task_id	1.693120	3.562392	0.155974947	FALSE

Interpretation:

Significant effect of participant group.

Recommended follow-up: global pairwise group post-hoc tests with Holm correction

```
[101]: posthoc_comp_dou <- pairwise_property_nparld(
  property_result = x$DOU
)
posthoc_comp_dou
```

	outcome <chr>	group1 <chr>	group2 <chr>	ANOVA_7 <dbl>
\$tests = A data.frame: 3 × 10	DOU	Dynamic sketch construction	Formula construction	0.8200265
	DOU	Dynamic sketch construction	Static sketch construction	14.9960530
	DOU	Formula construction	Static sketch construction	5.6865906

```
[102]: cld_comp_dou <- cld_from_pairwise_nparld(
  posthoc_results = posthoc_comp_dou,
  data = x$DOU$data,
  outcome = "DOU"
)
cld_comp_dou
```

	group <chr>	n <int>	mean <dbl>	median <dbl>	q1 <dbl>	q3 <dbl>	compact_letter <chr>
A tibble: 3 × 7	Static sketch construction	28	0.8514031	0.875	0.75000	1	NA
	Dynamic sketch construction	28	0.9451531	1.000	0.87500	1	NA
	Formula construction	28	0.8920918	1.000	0.85625	1	NA

7.4.4 FUNC

```
[103]: x = analyse_property_both_outcomes(data = dat_without_15, property_value="FUNC")

property_results_df_without_15 <- property_results_to_dataframe(
  property_results = x,
  existing_data = property_results_df_without_15
)
```

```
=====
Property: FUNC | Outcome: TTU
=====
```

```
=====
PROPERTY ANALYSIS      for FUNC with outcome = TTU
=====
Included tasks (3): 5, 6, 7
```

ATS results:

	effect	ANOVA_Type_Statistic	degrees_of_freedom	p_value	significant
1	group	0.5332564	1.519795	0.5380372	FALSE
2	group:task_id	1.8118587	3.168444	0.1391496	FALSE

Interpretation:
Not significant.
Recommended follow-up:

=====
Property: FUNC | Outcome: DOU
=====

=====
PROPERTY ANALYSIS for FUNC with outcome = DOU
=====

Included tasks (3): 5, 6, 7

ATS results:

	effect	ANOVA_Type_Statistic	degrees_of_freedom	p_value	significant
1	group	2.3139034	1.958612	0.1000564	FALSE
2	group:task_id	0.7813657	2.500076	0.4833289	FALSE

Interpretation:
Not significant.
Recommended follow-up:

```
[104]: x = analyse_property_both_outcomes(data = dat_without_15, property_value="VAL")

property_results_df_without_15 <- property_results_to_dataframe(
  property_results = x,
  existing_data = property_results_df_without_15
)
```

=====
Property: VAL | Outcome: TTU
=====

=====
PROPERTY ANALYSIS for VAL with outcome = TTU
=====

Included tasks (13): 1, 2, 3, 4, 5, 6, 7, 8, 10, 11, 12, 13, 14

ATS results:

	effect	ANOVA_Type_Statistic	degrees_of_freedom	p_value	significant
--	--------	----------------------	--------------------	---------	-------------

1	group	1.053178	1.740316	0.3411697	FALSE
2	group:task_id	0.999728	9.070238	0.4377445	FALSE

Interpretation:
 Not significant.
 Recommended follow-up:

=====

Property: VAL | Outcome: DOU

=====

=====

PROPERTY ANALYSIS for VAL with outcome = DOU

=====

Included tasks (13): 1, 2, 3, 4, 5, 6, 7, 8, 10, 11, 12, 13, 14

ATS results:

	effect	ANOVA_Type_Statistic	degrees_of_freedom	p_value	significant
1	group	1.023087	1.645271	0.34741384	FALSE
2	group:task_id	2.132688	7.785356	0.03092806	TRUE

Interpretation:
 Task-dependent group differences.
 Recommended follow-up: See task-specific group comparisons. Do not create one global compact letter display.

```
[105]: x = analyse_property_both_outcomes(data = dat_without_15, property_value="LIST")

property_results_df_without_15 <- property_results_to_dataframe(
  property_results = x,
  existing_data = property_results_df_without_15
)
```

=====

Property: LIST | Outcome: TTU

=====

=====

PROPERTY ANALYSIS for LIST with outcome = TTU

=====

Included tasks (2): 16, 17

ATS results:

	effect	ANOVA_Type_Statistic	degrees_of_freedom	p_value	significant
1	group	1.7622234	1.758465	0.1760768	FALSE
2	group:task_id	0.9211423	1.949084	0.3959629	FALSE

Interpretation:

Not significant.

Recommended follow-up:

=====
Property: LIST | Outcome: DOU
=====

=====
PROPERTY ANALYSIS for LIST with outcome = DOU
=====

Included tasks (2): 16, 17

ATS results:

	effect	ANOVA_Type_Statistic	degrees_of_freedom	p_value	significant
1	group	0.8410042	1.910954	0.4267054	FALSE
2	group:task_id	0.2270273	1.958696	0.7923385	FALSE

Interpretation:

Not significant.

Recommended follow-up:

```
[106]: x = analyse_property_both_outcomes(data = dat_without_15, property_value="BACK")

property_results_df_without_15 <- property_results_to_dataframe(
  property_results = x,
  existing_data = property_results_df_without_15
)
```

=====
Property: BACK | Outcome: TTU
=====

=====
PROPERTY ANALYSIS for BACK with outcome = TTU
=====

```
=====
Included tasks (13): 1, 2, 3, 5, 6, 7, 8, 9, 10, 11, 12, 13, 16
```

ATS results:

	effect	ANOVA_Type_Statistic	degrees_of_freedom	p_value	significant
1	group	1.2609504	1.716372	0.2804070	FALSE
2	group:task_id	0.9395204	9.369622	0.4912869	FALSE

Interpretation:

Not significant.

Recommended follow-up:

```
=====
Property: BACK | Outcome: DOU
=====
```

```
=====
PROPERTY ANALYSIS      for BACK with outcome = DOU
=====
```

```
Included tasks (13): 1, 2, 3, 5, 6, 7, 8, 9, 10, 11, 12, 13, 16
```

ATS results:

	effect	ANOVA_Type_Statistic	degrees_of_freedom	p_value	significant
1	group	1.586046	1.792191	0.2070266	FALSE
2	group:task_id	1.588499	8.294430	0.1192102	FALSE

Interpretation:

Not significant.

Recommended follow-up:

```
[107]: x = analyse_property_both_outcomes(data = dat_without_15,
      ↪property_value="FORWARD")

property_results_df_without_15 <- property_results_to_dataframe(
  property_results = x,
  existing_data = property_results_df_without_15
)
```

```
=====
Property: FORWARD | Outcome: TTU
=====
```

```
=====
PROPERTY ANALYSIS          for FORWARD with outcome = TTU
=====
```

Included tasks (5): 4, 12, 13, 14, 17

ATS results:

	effect	ANOVA_Type_Statistic	degrees_of_freedom	p_value	significant
1	group	1.344756	1.940203	0.2604702	FALSE
2	group:task_id	1.553265	4.649617	0.1744672	FALSE

Interpretation:

Not significant.

Recommended follow-up:

```
=====
Property: FORWARD | Outcome: DOU
=====
```

```
=====
PROPERTY ANALYSIS          for FORWARD with outcome = DOU
=====
```

Included tasks (5): 4, 12, 13, 14, 17

ATS results:

	effect	ANOVA_Type_Statistic	degrees_of_freedom	p_value	significant
1	group	1.8609005	1.864983	0.1584561	FALSE
2	group:task_id	0.7067204	3.728255	0.5775076	FALSE

Interpretation:

Not significant.

Recommended follow-up:

```
[108]: x = analyse_property_both_outcomes(data = dat_without_15, property_value="ON")

property_results_df_without_15 <- property_results_to_dataframe(
  property_results = x,
  existing_data = property_results_df_without_15
)
```

Property: ON | Outcome: TTU

PROPERTY ANALYSIS for ON with outcome = TTU

Included tasks (11): 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 16

ATS results:

	effect	ANOVA_Type_Statistic	degrees_of_freedom	p_value	significant
1	group	2.1684863	1.757000	0.1210779	FALSE
2	group:task_id	0.8045947	8.421156	0.6043171	FALSE

Interpretation:

Not significant.

Recommended follow-up:

Property: ON | Outcome: DOU

PROPERTY ANALYSIS for ON with outcome = DOU

Included tasks (11): 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 16

ATS results:

	effect	ANOVA_Type_Statistic	degrees_of_freedom	p_value	significant
1	group	1.490456	1.790959	0.2265169	FALSE
2	group:task_id	1.666233	8.079225	0.1001616	FALSE

Interpretation:

Not significant.

Recommended follow-up:

```
[109]: x = analyse_property_both_outcomes(data = dat_without_15, property_value="OFF")

property_results_df_without_15 <- property_results_to_dataframe(
  property_results = x,
  existing_data = property_results_df_without_15
)
```

```
=====
Property: OFF | Outcome: TTU
=====
```

```
=====
PROPERTY ANALYSIS      for OFF with outcome = TTU
=====
```

```
Included tasks (2): 11, 13
```

```
ATS results:
```

	effect	ANOVA_Type_Statistic	degrees_of_freedom	p_value	significant
1	group	0.9162489	1.736500	0.3881978	FALSE
2	group:task_id	0.3050469	1.826349	0.7170709	FALSE

```
Interpretation:
```

```
Not significant.
```

```
Recommended follow-up:
```

```
=====
Property: OFF | Outcome: DOU
=====
```

```
=====
PROPERTY ANALYSIS      for OFF with outcome = DOU
=====
```

```
Included tasks (2): 11, 13
```

```
ATS results:
```

	effect	ANOVA_Type_Statistic	degrees_of_freedom	p_value	significant
1	group	0.5	1.6	0.5651424	FALSE
2	group:task_id	0.5	1.6	0.5651424	FALSE

```
Interpretation:
```

```
Not significant.
```

```
Recommended follow-up:
```

```
[110]: x = analyse_property_both_outcomes(data = dat_without_15,
      ↪property_value="CROSS")

property_results_df_without_15 <- property_results_to_dataframe(
```

```

property_results = x,
existing_data = property_results_df_without_15
)

```

```

=====
Property: CROSS | Outcome: TTU
=====

```

```

=====
PROPERTY ANALYSIS          for CROSS with outcome = TTU
=====

```

Included tasks (4): 12, 13, 14, 17

ATS results:

	effect	ANOVA_Type_Statistic	degrees_of_freedom	p_value	significant
1	group	0.860731	1.915065	0.4187018	FALSE
2	group:task_id	1.792482	4.219196	0.1233303	FALSE

Interpretation:

Not significant.

Recommended follow-up:

```

=====
Property: CROSS | Outcome: DOU
=====

```

```

=====
PROPERTY ANALYSIS          for CROSS with outcome = DOU
=====

```

Included tasks (4): 12, 13, 14, 17

ATS results:

	effect	ANOVA_Type_Statistic	degrees_of_freedom	p_value	significant
1	group	1.8625341	1.863119	0.1582484	FALSE
2	group:task_id	0.6608663	3.603269	0.6033941	FALSE

Interpretation:

Not significant.

Recommended follow-up:

```
[111]: # property_results_df_without_15
```

```
[112]: property_results_df_without_15 <- property_results_df_without_15 %>%  
  dplyr::distinct(  
    property_value,  
    outcome,  
    effect,  
    p_value,  
    .keep_all = TRUE  
  )  
  
property_results_df_without_15  
  
export_property_results_table(  
  data = property_results_df_without_15,  
  tex_file = "structural_aspects_without_15.tex"  
)
```

	property_value <chr>	outcome <chr>	effect <chr>	p_value <dbl>
	COMP	TTU	group	3.464732e-01
	COMP	TTU	task_id	0.000000e+00
	COMP	TTU	group:task_id	4.577987e-01
	COMP	DOU	group	5.582650e-01
	COMP	DOU	task_id	1.265654e-14
	COMP	DOU	group:task_id	5.975499e-02
	COND	TTU	group	5.270346e-01
	COND	TTU	task_id	2.312506e-01
	COND	TTU	group:task_id	9.225467e-02
	COND	DOU	group	2.470413e-01
	COND	DOU	task_id	3.947218e-02
	COND	DOU	group:task_id	9.373745e-01
	LOOK	TTU	group	4.323965e-01
	LOOK	TTU	task_id	5.620266e-01
	LOOK	TTU	group:task_id	7.900059e-02
	LOOK	DOU	group	3.256316e-01
	LOOK	DOU	task_id	1.917314e-01
	LOOK	DOU	group:task_id	3.210802e-01
	CELL	TTU	group	3.725348e-01
	CELL	TTU	task_id	3.219514e-11
	CELL	TTU	group:task_id	5.723805e-01
	CELL	DOU	group	7.153166e-02
	CELL	DOU	task_id	4.054493e-06
	CELL	DOU	group:task_id	1.352388e-01
	RANGE	TTU	group	1.543753e-01
	RANGE	TTU	task_id	0.000000e+00
	RANGE	TTU	group:task_id	3.117210e-01
	RANGE	DOU	group	2.214963e-01
	RANGE	DOU	task_id	3.913824e-08
A data.frame: 84 × 4	RANGE	DOU	group:task_id	4.303479e-01
	BACK	TTU	group	2.804070e-01
	BACK	TTU	task_id	0.000000e+00
	BACK	TTU	group:task_id	4.912869e-01
	BACK	DOU	group	2.070266e-01
	BACK	DOU	task_id	2.220446e-15
	BACK	DOU	group:task_id	1.192102e-01
	FORWARD	TTU	group	2.604702e-01
	FORWARD	TTU	task_id	1.634454e-06
	FORWARD	TTU	group:task_id	1.744672e-01
	FORWARD	DOU	group	1.584561e-01
	FORWARD	DOU	task_id	5.069838e-03
	FORWARD	DOU	group:task_id	5.775076e-01
	ON	TTU	group	1.210779e-01
	ON	TTU	task_id	0.000000e+00
	ON	TTU	group:task_id	6.043171e-01
	ON	DOU	group	2.265169e-01
	ON	DOU	task_id	1.734612e-12
	ON	DOU	group:task_id	1.001616e-01
	OFF	TTU	group	3.881978e-01
	OFF	TTU	task_id	4.127881e-04

LaTeX tabular saved to: /home/judith/Schreibtisch/angew. Informatik - system engineering/Study_DrawingAttention/structural_aspects_without_15.tex

[]:

[]:

[]:

8 CONCLUSION

[113]: *# latex export of some result tables?*

[]:

[]:

[]:

[]:

[]:

[]:

[]:

[]:

[]:

[]:

[]:

[]: