

```

import Database from "better-sqlite3";
import { drizzle } from "drizzle-orm/better-sqlite3";
import fs from "node:fs";
import path from "node:path";
import * as schema from "./schema";

export const dbPath = (process.env.DATABASE_URL ?? "file:./data/keystone.db").replace(
  "file:", fs.mkdirSync(path.dirname(dbPath), { recursive: true })
);

export const sqlite = new Database(dbPath);
sqlite.pragma("journal_mode = WAL");
sqlite.pragma("foreign_keys = ON");

// Tables are created on first boot, so there is no separate migration step.
sqlite.exec(`
CREATE TABLE IF NOT EXISTS user (id text PRIMARY KEY, name text NOT NULL, email text NOT NULL);
CREATE TABLE IF NOT EXISTS session (id text PRIMARY KEY, expiresAt date NOT NULL);
CREATE TABLE IF NOT EXISTS account (id text PRIMARY KEY, accountId text NOT NULL);
CREATE TABLE IF NOT EXISTS verification (id text PRIMARY KEY, identifier text NOT NULL);
CREATE TABLE IF NOT EXISTS subscriptions (user_id text PRIMARY KEY, stripe_custom_id text NOT NULL);
CREATE TABLE IF NOT EXISTS stripe_events (id text PRIMARY KEY, created_at integer NOT NULL);
CREATE TABLE IF NOT EXISTS hot_leads (id integer PRIMARY KEY AUTOINCREMENT, user_id text NOT NULL);
CREATE TABLE IF NOT EXISTS prospects (id integer PRIMARY KEY AUTOINCREMENT, user_id text NOT NULL);
CREATE TABLE IF NOT EXISTS ai_usage (user_id text NOT NULL, day text NOT NULL, n integer NOT NULL);
CREATE TABLE IF NOT EXISTS leads (id integer PRIMARY KEY AUTOINCREMENT, name text NOT NULL);
`);

export const db = drizzle(sqlite, { schema });

```