Intermittent rate coding without short-term plasticity

Abstract

Working memory is thought to rely either on persistent spiking activity, sustained by slow NMDA receptor currents, or on activity-silent synaptic traces. Recent prefrontal recordings showed that the remembered item can be decoded only intermittently on single trials, with Off periods in which decoding falls to chance. These Off periods have been taken as evidence that memories are carried by short-term synaptic plasticity when spiking activity fails to hold them. Here we show that intermittent decoding is also expected from a conventional attractor network with fixed synapses. When a shared input, such as fluctuating attention, briefly drops, the network falls silent and decoding fails. However, NMDA receptor currents, which decay over 150 ms as measured in cortical neurons, bridge the silence and the memory is reinstated when the attentional input returns. Fitted to the recordings, this model reproduces the number and duration of On and Off states while retaining the memory. In the data, we found that Off states are more frequent when fewer or less selective neurons are decoded, so their frequency partly reflects how well the recorded sample reads out the memory. Without refitting, the model predicts this dependence out of distribution for decoded populations it was never fitted to. Intermittent decoding is therefore compatible with persistent activity and does not, on its own, require activity-silent mechanisms.

Introduction

Two main mechanisms have been proposed to hold information in working memory. In persistent-activity models, recurrent excitation keeps a cue-selective population firing through the delay, and slow NMDA receptor currents make this activity stable (Amit and Brunel, 1997; Wang, 1999, 2001; Compte et al., 2000). In activity-silent models, the memory is instead stored in short-term synaptic facilitation and needs no ongoing spikes (Mongillo et al., 2008; Stokes, 2015).

Panichello et al. (2024) found that decoding from prefrontal populations is intermittent on single trials. It alternates between On states, when the cue can be read out, and Off states, when it cannot. They concluded that persistent activity is not sufficient and that synaptic changes carry the memory through Off states. Here, we propose that intermittent decoding does not require short-term plasticity and is instead consistent with the NMDA account. In our model, the memory is held as attractor activity, and a common input, which we interpret as a fluctuating attentional signal, briefly drops and silences the network. Slow NMDA currents carry the memory across each silence, so the cued population resumes firing when the input returns. We read out the model with the same decoding and On/Off criteria as Panichello et al. (2024) and fit it to the On/Off statistics of the recordings. The model reproduces the number and length of On and Off states while keeping the memory in 98% of trials, so Off states do not erase the memory. In the recordings, Off states are more frequent when fewer or less selective neurons are decoded, so their frequency partly reflects how well the recorded sample reads out the memory. Without refitting, the model predicts this dependence out of distribution for decoded populations it was never fitted to. Intermittent decoding is therefore compatible with persistent activity sustained by NMDA currents, without short-term plasticity.




Figure 1: Input dips create On and Off states, and NMDA carries the memory. **a**, Example trial. Top: rates of the cued (black) and uncued (grey) pools, relative to the maximum rate, and their NMDA gating (dotted); grey shading marks the cue. Middle: common input (attention signal), constant for the first 1,000 ms after the cue and with dips afterwards. The dip-free first second is shown for illustration only; in all other simulated trials, dips occur throughout the delay. Bottom: decoding z score, with On (red) and Off (cyan) states. Dashed lines: On threshold ($z = 1.96$) and Off threshold ($z = 0.84$), as in Panichello et al. (2024). **b**, Length distributions of Off (top) and On (bottom) states in the model.

Results

Input dips produce Off states and NMDA carries the memory across them

The model has two memory pools, cued and uncued, with NMDA self-excitation and shared inhibition (Methods). After the cue, the cued pool stays active. With brief dips in the common input, which we interpret as fluctuations of an attention signal, both pools fall silent and decoding drops to chance (Fig. 1a, after 1,000 ms). With a constant common input, decoding stays On for the whole delay (Fig. 1a, first second after the cue). We show this case for illustration only; all other simulated trials, including those used for fitting, have dips throughout the delay. During each dip, the NMDA gating of the cued pool decays with a time constant of 150 ms but stays higher than that of the uncued pool. This value lies within the measured decay times of NMDA receptor currents, which are slowest for receptors containing the GluN2B (NR2B) subunit (Vicini et al., 1998), and GluN2B-containing NMDA receptors are required for persistent firing in primate prefrontal cortex (Wang et al., 2013). When the input returns, lagging feed-forward inhibition gives both pools a brief kick, and the pool with more NMDA gating wins the competition. Off states therefore do not erase the memory: NMDA gating carries it across each silence, and the memory is still correct at the end of the delay in 98% of trials.

To compare the model with the data, we turned its activity into a decoding z score: the difference between the cued and uncued pool rates in 100 ms windows, multiplied by a gain (c) and added to noise (η) with the statistics measured in the data (Methods). Importantly, the gain was not fitted to the On/Off statistics. Instead, it was calibrated on a single quantity measured in the data, the typical z value when decoding is high, which we call the decoding strength (Methods). On and Off states (red and cyan in Fig. 1a) are then labelled with the same thresholds as in Panichello et al. (2024) (red and cyan dashed lines in Fig. 1a). Read out this way, the model alternates between On and Off states (Fig. 1a, bottom). Both length distributions peak near 100 ms and have long tails (Fig. 1b), qualitatively like those in the recordings (Panichello et al., 2024); we compare them quantitatively in the next section.




Figure 2: The model predicts how On/Off statistics change with the decoded population. Decoders using the most cue-selective neurons (top 5, 20, 50) are On more often and Off less often than decoders using the same numbers of random neurons (rand 5, 20, 50). Black circles: data, mean ± 95% CI (2 SEM) over 25 sessions. Grey dots: single sessions. Cyan and red circles: model, Off and On statistics. The model was fitted to all neurons only (grey bar); the other six decoded populations are predictions obtained by changing only the read-out gain and noise.

On/Off statistics depend on which neurons are decoded

So far we considered decoders that use all recorded neurons. We found, however, that On/Off statistics depend strongly on which neurons the decoder uses, which we call the decoded population (Fig. 2, black circles). Decoders using the most cue-selective neurons spend much more of the delay On, and less Off, than decoders using the same numbers of randomly chosen neurons, which also show more Off states per trial. The decoded populations differ mainly in decoding strength, which is much higher for the most selective neurons. How often a memory appears Off therefore depends partly on how well the recorded neurons read it out. This matters for interpreting Off states as evidence for activity-silent memory: a decoder trained on a limited sample of neurons can fall to chance while the memory is still present in the activity of other, unrecorded neurons. The measured fraction of Off states is therefore an upper bound on, not a measure of, how often the memory leaves spiking activity.

A model fitted to all neurons predicts this dependence

Can our model explain this dependence? If Off states come from shared dips in network activity, the same dynamics, read out with a higher or lower decoding strength, should reproduce the change across decoded populations. To test this, we fitted seven parameters of the dynamics only to the decoder using all neurons in 25 sessions (Methods). The model matches the data in Off states per trial (3.1 vs 3.3), Off median length (110 vs 112 ms), On states per trial (1.9 vs 2.1) and On median length (140 vs 134 ms) (Fig. 2, grey band). We then kept the dynamics fixed and, for each of the six other decoded populations, changed only the read-out without fitting any parameters: its gain was calibrated on that population's decoding strength, and its noise on that population's pre-cue z (Methods). Without any refitting, the model predicts quantitatively the

shift between selective and random neurons.

Methods

Rate model

Two excitatory memory pools $X \in \{\text{cued}, \text{uncued}\}$ have rates r_X and NMDA gating s_X. They share an inhibitory population r_I and a feed-forward inhibition q that follows the common input $m(t)$ with a lag:

$$\tau_r \frac{dr_X}{dt} = -r_X + \Phi\big(w_s s_X + w_a r_X - w_I r_I + I_0\, m(t) - w_{ff}\, q + \text{cue}_X + \sigma\xi_X\big), \tag{1}$$

$$\tau_N \frac{ds_X}{dt} = -s_X + \beta\, r_X(1 - s_X), \tag{2}$$

$$\tau_I \frac{dr_I}{dt} = -r_I + w_{EI}\,(r_{\text{cued}} + r_{\text{uncued}})\,, \tag{3}$$

$$\tau_{ff} \frac{dq}{dt} = -q + m(t). \tag{4}$$

$\Phi(x) = r_{\max}/(1 + \exp(-(x-1)/\kappa))$, and ξ_X are independent Ornstein–Uhlenbeck noises ($\tau_\xi =$ 10 ms). Fixed parameters: $r_{\max} = 150$, $\kappa = 0.06$, $w_a = 0.0141$, $\beta = 0.02$, $w_I = 0.04$, $w_{EI} = 0.5$, $w_{ff} = 0.8$, $I_0 = 1.496$; $\tau_r = 10$ ms, $\tau_I = 1$ ms, $\tau_{ff} = 15$ ms. The cue is a 50 ms input of amplitude 1 to the cued pool, after 300 ms of baseline, followed by a 1,600 ms delay. Equations were integrated with Euler steps of 0.1 ms. The memory was scored correct when, in the last 100 ms, the NMDA gating of the cued pool exceeded the uncued pool's by more than 0.05.

The common input $m(t)$ is 1 except during dips, where it drops to $1-\delta$ with 10 ms ramps. Dip lengths are gamma-distributed (mean μ_d, shape k), and the gaps between dips are exponential with mean $1/\lambda_d$.

Decoding read-out, On/Off labelling and statistics

The decoder z score was modelled as $z(t) = c\,\Delta r(t) + \eta(t)$, where Δr is the cued minus uncued rate in 100 ms windows stepped by 10 ms. The noise η has unit variance, the autocorrelation of overlapping windows, and a slow per-trial offset whose variance share was measured from the pre-cue z of the data (0.35 for all neurons, 0.09 for the most selective neurons, 0.11 for random neurons). The gain c was not fitted: for each decoded population, it was chosen so that the upper mean of a two-component Gaussian mixture of delay z values matched the data's. We call this upper mean the decoding strength. States were labelled as in Panichello et al. (2024). On states are runs of $z > 1.96$ whose summed z exceeds the 95th percentile of the same quantity in pure noise. Off states are runs of at least 5 points (50 ms) with $z < 0.84$. States were counted from 0 to 1,400 ms after cue onset, and fractions of the delay spent On or Off from 500 to 1,400 ms. Model statistics were computed from 2,112 simulated trials (792 per evaluation during fitting). Data statistics are means over the 25 sessions; for random neurons, the 10 draws were first averaged within each session.

Data

We reanalysed the recordings of Panichello et al. (2024): 25 sessions, correct trials only, all cue locations (13,190 trials; 329 units per session on average). For each time bin, an L2-regularised logistic decoder ($\lambda = 10{,}000$) was evaluated with approximate leave-one-out and z-scored against 30 shuffled label sets per cue pair. Decoded populations were all neurons, the k most cue-selective neurons (ranked by split-half ANOVA), and k randomly chosen neurons (10 draws, averaged within sessions), with $k = 5$, 20 and 50.

Fitting

Seven parameters were fitted with CMA-ES to the decoder using all neurons only: τ_N, w_s, λ_d, μ_d, k, δ and σ. The loss combined the squared scaled errors of six statistics (On and Off states per trial, mean lengths and fractions of the delay), the squared Hellinger distance between model and data length distributions (states ≥ 40 ms), and a penalty when the memory was correct in fewer than 98% of trials. Best fit: $\tau_N = 150$ ms, $w_s = 1.30$, $\lambda_d = 10.2$/s, $\mu_d = 90$ ms, $k = 8.7$, $\delta = 0.60$, $\sigma = 0.006$. τ_N and w_s ended at the bounds of the search (50–150 ms and 1.30–1.70).

Code: `paper_model/` on the `paper-model` branch of the `gamma_bursts-` repository.

References

Daniel J. Amit and Nicolas Brunel. Model of global spontaneous activity and local structured activity during delay periods in the cerebral cortex. *Cerebral Cortex*, 7:237–252, 1997.

Albert Compte, Nicolas Brunel, Patricia S. Goldman-Rakic, and Xiao-Jing Wang. Synaptic mechanisms and network dynamics underlying spatial working memory in a cortical network model. *Cerebral Cortex*, 10:910–923, 2000.

Gianluigi Mongillo, Omri Barak, and Misha Tsodyks. Synaptic theory of working memory. *Science*, 319:1543–1546, 2008.

Matthew F. Panichello et al. Intermittent rate coding and cue-specific ensembles support working memory. *Nature*, 636:422–429, 2024.

Mark G. Stokes. 'activity-silent' working memory in prefrontal cortex: a dynamic coding framework. *Trends in Cognitive Sciences*, 19:394–405, 2015.

Stefano Vicini et al. Functional and pharmacological differences between recombinant N-methyl-D-aspartate receptors. *Journal of Neurophysiology*, 79:555–566, 1998.

Min Wang et al. NMDA receptors subserve persistent neuronal firing during working memory in dorsolateral prefrontal cortex. *Neuron*, 77:736–749, 2013.

Xiao-Jing Wang. Synaptic basis of cortical persistent activity: the importance of NMDA receptors to working memory. *Journal of Neuroscience*, 19:9587–9603, 1999.

Xiao-Jing Wang. Synaptic reverberation underlying mnemonic persistent activity. *Trends in Neurosciences*, 24:455–463, 2001.