Automating Pen and Ink Landscape Renderings

Jim Mower
Geography and Planning
University at Albany
NYSGIS State Agency Advisory Group Meeting
Summer 2006

Classic Block Diagrams


- Block diagrams represent
 - Landscape views in perspective
 - Underlying bedrock geology
- They employ
 - Large scale views
 - Pen and ink renderings

Armin Lobeck

- Lobeck wrote a wonderful book on block diagrams and other perspective landscape illustrations
 - Lobeck, A.K (1958) "Block diagrams and other graphic methods used in geology and geography."
 Emerson-Trussell Book Co., Amherst, MA.
- It contains drawing instructions and many examples

Purpose of My Project

- Automate pen & ink rendering techniques
- Generate views from DEMs using expert systems approach
- Several interesting problems arise...



Easy Problems to Solve

Geometry

- Using Direct3D, render surface using only "ridge lines" and hachures
- Hachures are implemented as the line of steepest descent through a triangular surface facet
- Ridges are implemented as boundary lines between visible and invisible facets relative to the viewpoint

Rendered Lines

Ridge


Viewpoint

Rendered
Ridge


Visible facets

Invisible facets

Hachure



Easy Problems Solved! But...



How Do You Eliminate Crud?

- Controlling hachure and ridge density automatically
 - A generalization problem
 - At a given rendered thickness, hachures should never touch one another
 - Both ridges and hachures should not be drawn for purely geometric reasons
 - Must define significance for both types of renderings

Defining Significance

- Slope criteria
 - Only show a ridge line if the angle of the intersecting facets is greater than a minimum value
 - Only draw a hachure if its plane exceeds a minimum slope and is beyond a minimum distance from the VP

Other Significance Criteria

- Only show a ridge line if it coincides with a hydrological ridge
 - A drainage basin boundary
 - Might be too restrictive
 - Escarpments are not necessarily drainage basin boundaries
- Detect 2D line proximity after rendering
 - Create buffers around hachures, check for intersection, delete lowest slope

Significance Criteria (cont.)

- Adaptive surface resampling
 - The input DEM is a TIN with variable resampling with distance from the VP
 - Resampling is currently performed from a densely sampled DEM in a separate program
 - Could perform resampling on the fly in this program

Lots of Things To Do

- But that's the fun part!
- Questions?