Deployment

Run less, and fail safely when something does run

Node selection Build exactly the slice of the DAG a change actually touches

`dbt build --select "+fct_orders"`	+ upstream
`dbt build --select "fct_orders+"`	+ downstream
`dbt build --select "@fct_orders"`	+ up, down, and their up
`dbt build --select tag:finance`	By tag
`selectors.yml`	Reusable, not copy-pasted strings

Retry and clone Don't rebuild what already succeeded or exists elsewhere

`dbt retry`	Rerun only what failed
`dbt clone --select state:modified+`	Clone changed nodes
`dbt build --select state:modified+`	Build only what changed

dbt Jobs Each job type exists for a different reason — dbt platform

`Deploy`	Schedule/API -> prod
`CI`	PR commit -> ephemeral schema
`Merge`	Merge -> prod
`dbt State`	Every run, skip/clone/build
`24h run limit`	Same cap, every job type

CI jobs in detail Built to stay cheap no matter the project size — dbt platform

`Ephemeral per-PR schema`	Torn down after
`Runs execute in parallel`	Team velocity
`Smart cancellation`	Newer commit cancels the old run
`SQL linting`	Starter plan and above

Platform API Trigger and manage runs from outside the UI — dbt platform

```
curl -H "Authorization: Token $TOKEN" \
  -X POST ".../jobs/<id>/run/"
```

`Admin API v2 (legacy) / v3 (current)`	Download artifacts, run jobs
`Terraform provider`	Calls the same endpoints

Pre/post-hooks SQL that runs around a build, nobody has to remember

```
{{ config(
    post_hook="grant select on {{ this }} to bi_role"
) }}
```

`Runs on models, seeds, snapshots`	Not sources

dbt State Rebuilds only what actually changed — dbt platform

`dbt build --manage-state`	Starts a free trial
`dbt state explain`	v2: why skip/clone/build
`dbt-state explain`	v1 (hyphenated)
`config: {state: {lag_tolerance: ...}}`	Per-model freshness window

dbt Checks Project-quality rules, enforced before a model compiles

```
select unique_id from {{ info_schema('models') }}
where description = ''
```

`dbt check`	Runs all checks
`config: {severity: warn}`	Default is error
`dbt build --skip-checks`	Bypass, on purpose

CI/CD with GitHub Actions The self-hosted version of the same CI discipline

```
run: >
  dbt build --select "state:modified+"
  --defer --state ./prod-artifacts
env:
  SF_PASSWORD: ${{ secrets.SF_PASSWORD }}
```