# C1 — Contact / Coupe — FR

INTRADOS > EXTRADOS | 41 positions | 5 EDM | 09/11/2026

### 1. C1 : INTRADOS vers EXTRADOS

41 positions, matrice 8x8, 3 485 lois, cinq EDM. La cartographie bleue garde les valeurs et la calibration originales : reference 3 mm = 50 % FSH. Les axes sont le parcours acoustique et le numero du tir.

### 2. Glissement et contact

Le pied graphique 25x25 mm suit la peau du maillage de la racine. Les 401 poses intermediaires sont calculees par intersection avec cette surface. Le contact affiche est distinct du point O UT : ce dernier est une origine acoustique virtuelle de la simulation source et reste inchange. L acquisition suivante est affichee apres l arrivee a sa position.

### 3. Coupe cotee et faisceaux

Le bouton Coupe cotee montre l intersection du plan local avec les triangles reels de la racine, a echelle uniforme. Les directions sources sont projetees dans ce plan ; la direction nominale appartient au plan. La coupe montre seulement les indications du tir courant, et les echantillons proches du plan. Cela evite de projeter artificiellement des indications eloignees sur la coupe.

### 4. Tache UT et vue 3D

La tache utilise les echantillons UT sources du tir courant dans une porte de visualisation de +/-8 mm autour du parcours nominal vers la cible. La coupe conserve les points a moins de 3 mm du plan. Ce filtrage d affichage ne modifie pas la detection. Le bouton 3D montre le pied sur la peau et les 85 directions. Le nuage global reste accessible.

### 5. Resultats conserves

Les onglets donnent acces aux indications, TFM, voxel et rapport. Au dernier tir, les cinq EDM de reference sont identifiees. Les autres candidats restent consultables : cinq correspondances ne signifient pas zero faux positif. Les dimensions d images TFM/voxel ne sont pas automatiquement des dimensions physiques de fissure.

### 6. Etude du slot et limites

Le dossier ETUDE_SLOT_C1 contient 401 positions/normales, une polyligne STEP/DXF et 41 coupes DXF. La polyligne est discretisee. Le pied adapte est une representation geometrique : il ne qualifie ni le profil physique du sabot, ni les 55 degres, ni le couplage ou les collisions. Definir guidage, rayon de suiveur et jeux avant fabrication. La mecanique de rupture reste a completer.

# C1 — Contact / Coupe — EN

INTRADOS > EXTRADOS | 41 positions | 5 EDM | 09/11/2026

### 1. C1: INTRADOS to EXTRADOS

41 positions, 8x8 matrix, 3,485 laws, five EDMs. The blue cartography retains original values and calibration: 3 mm reference = 50% FSH. Axes show sound path and shot number.

### 2. Sliding and contact

The graphic 25x25 mm foot follows the central-root mesh skin. All 401 intermediate poses are intersected with that surface. Displayed contact is separate from UT O, the virtual acoustic origin used by the source simulation, which remains unchanged. The next acquisition is displayed after arrival at its position.

### 3. Dimensioned section and beams

Dimensioned section intersects the local plane with actual root triangles, at equal scale. Original-law directions are projected into this plane; the nominal direction belongs to the plane. Only current-shot indications and near-plane samples appear in the section. This avoids projecting remote indications onto an unrelated section.

### 4. UT spot and 3D view

The spot uses source UT samples from the current shot, within a display gate of +/-8 mm around nominal sound path to the target. The section retains samples within 3 mm of its plane. This display filtering does not alter detection. The 3D button shows the foot on the skin and all 85 directions. The global cloud remains available.

### 5. Preserved results

Tabs open indications, TFM, voxel and report. At the last shot, five reference EDMs are identified. Other candidates remain available: five matches do not mean zero false positives. TFM/voxel image extents are not automatically physical crack dimensions.

### 6. Slot study and limits

ETUDE_SLOT_C1 contains 401 positions/normals, a STEP/DXF polyline and 41 DXF sections. The polyline is discretized. The adapted foot is a geometric representation: it does not qualify the physical wedge profile, 55-degree incidence, coupling or collisions. Define guidance, follower radius and clearances before manufacture. Fracture mechanics is pending.