C1 — Contact / Coupe — FR

INTRADOS > EXTRADOS | 41 positions | 5 EDM | 09/11/2026

1. C1 : INTRADOS vers EXTRADOS

41 positions, matrice 8x8, 3 485 lois, cinq EDM. La cartographie bleue garde les valeurs et la calibration originales : reference 3 mm = 50 % FSH. Les axes sont le parcours acoustique et le numero du tir.

2. Glissement et contact

Reference nominale27,6mm depuis coin superieur intrados. Recalage rigide par pose pour reconstruire PA, elements, champ et indications ensemble ; matrices sources conservees, pas une nouvelle validation physique. Le pied graphique25x25mm suit la peau du maillage de la racine. Le repere du support est transporte sans retournement selon les normales ; de petits retours locaux du trajet ne le font plus pivoter. Le mouvement est continu, avec une nouvelle intersection peau/trajectoire a chaque image. Les 401 reperes exportes sont conserves. Le contact affiche est distinct du point O UT : ce dernier est une origine acoustique virtuelle de la simulation source et reste inchange. Les 41 acquisitions se mettent a jour au passage des positions, sans arret impose.

3. Coupe cotee et faisceaux

Le plan de coupe est vertical et contient le tir nominal. Les contours viennent des triangles reels, a echelle uniforme. Les directions sources sont projetees dans ce plan ; la direction nominale appartient au plan. La coupe montre seulement les indications du tir courant, et les echantillons proches du plan. Une indication hors plan porte la mention proj. La premiere gorge est visible dans la coupe courante, sans profil decale.

4. Volume coherent calcule

64 elements et 85 lois sources calculent le gain coherent 3D, max sur les lois successives (pas une emission simultanee). Surfaces -6/-12 dB, reference fixe G=1 ; pas une pression calibree ni %FSH. Coupes sectorielle/skew du meme volume. Pas spatial 2 a 2,47 mm. Le volume est celui du dernier tir acquis ; entre tirs, il est transporte avec le PA, sans nouveau calcul. Les detections sont cumulees. La retrodiffusion Green/Kirchhoff/Born/GTD complete reste a raccorder.

5. Resultats conserves

Les onglets donnent acces aux indications, TFM, voxel et rapport. Au dernier tir, les cinq EDM de reference sont identifiees. Les autres candidats restent consultables : cinq correspondances ne signifient pas zero faux positif. Les dimensions d images TFM/voxel ne sont pas automatiquement des dimensions physiques de fissure.

6. Etude du slot et limites

Le dossier ETUDE_SLOT_C1 contient 401 positions/normales, une polyligne STEP/DXF et 41 coupes DXF. La polyligne est discretisee. Le pied adapte est une representation geometrique : il ne qualifie ni le profil physique du sabot, ni les 55 degres, ni le couplage ou les collisions. Definir guidage, rayon de suiveur et jeux avant fabrication. La mecanique de rupture reste a completer.

C1 — Contact / Coupe — EN

INTRADOS > EXTRADOS | 41 positions | 5 EDM | 09/11/2026

1. C1: INTRADOS to EXTRADOS

41 positions, 8x8 matrix, 3,485 laws, five EDMs. The blue cartography retains original values and calibration: 3 mm reference = 50% FSH. Axes show sound path and shot number.

2. Sliding and contact

Nominal27.6mm upper intrados platform-corner reference. Proper rigid pose registration reconstructs PA, elements, field and indications together; source matrices retained, not a new physical validation. The graphic25x25mm foot follows the central-root mesh skin. The support frame follows the normals without flipping when small local path reversals occur. Movement is continuous, with a new skin intersection each animation frame. The 401 exported study points are retained. Displayed contact is separate from UT O, the virtual acoustic origin used by the source simulation, which remains unchanged. The 41 acquisitions update on crossing their positions, without an imposed dwell.

3. Dimensioned section and beams

The section is vertical and contains the nominal beam. Contours come from actual root triangles, at equal scale. Original-law directions are projected into this plane; the nominal direction belongs to the plane. Only current-shot indications and near-plane samples appear in the section. Off-plane indications are marked proj. The first groove appears in the current section without an offset profile.

4. Computed coherent volume

64 elements and 85 original laws compute 3D coherent gain, maximized over sequential laws (not simultaneous firing). Surfaces -6/-12 dB, fixed G=1 reference; neither calibrated pressure nor %FSH. Sectorial/skew slices show the same volume. Grid spacing 2 to 2.47 mm. The volume belongs to the last acquired shot; between shots it is transported with the PA without a new field calculation. Detections are cumulative. Full Green/Kirchhoff/Born/GTD backscatter remains to be linked.

5. Preserved results

Tabs open indications, TFM, voxel and report. At the last shot, five reference EDMs are identified. Other candidates remain available: five matches do not mean zero false positives. TFM/voxel image extents are not automatically physical crack dimensions.

6. Slot study and limits

ETUDE_SLOT_C1 contains 401 positions/normals, a STEP/DXF polyline and 41 DXF sections. The polyline is discretized. The adapted foot is a geometric representation: it does not qualify the physical wedge profile, 55-degree incidence, coupling or collisions. Define guidance, follower radius and clearances before manufacture. Fracture mechanics is pending.